

Assignment – 11

Subqueries.

Name: Shivam Dolase

PRN: 240840320100

- 1) Write a query that uses a subquery to obtain all orders for the customer named Cisneros. Assume you do not know his customer number (cnum).

```
mysql> select Onum,amt,Odate from Orders where Snum=(Select Snum from customers where Cname='Cisneros');
```

```
mysql> select Onum,amt,Odate from Orders where Snum=(Select Snum
from customers where Cname='Cisneros');
+-----+-----+-----+
| Onum | amt   | Odate   |
+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 |
| 3006 | 1098.16 | 1990-10-03 |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> select O.Onum,O.amt,O.Odate,C.Cname from Orders as O Inner join Customers as C On O.Snum=C.Snum where C.Cname='Cisneros';
```

```
mysql> select O.Onum,O.amt,O.Odate,C.Cname from Orders as O Inner
join Customers as C On O.Snum=C.Snum where C.Cname='Cisneros';
+-----+-----+-----+-----+
| Onum | amt   | Odate   | Cname   |
+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | Cisneros |
| 3006 | 1098.16 | 1990-10-03 | Cisneros |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

- 2) Write a query that produces the names and ratings of all customers who have above-average orders.

```
mysql> select C.Cname,C.rating from customers as C Inner Join Orders as O on C.Cnum=O.Cnum where O.amt>(select avg(amt) from orders);
```

```
mysql> select C.Cname,C.rating from customers as C Inner Join Orders as O on C.Cnum=O.Cnum where O.amt>(select avg(amt) from orders);
```

Cname	rating
Liu	200
Clemens	100
Clemens	100

3 rows in set (0.01 sec)

3) Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the amount of the largest order in the table.

```
mysql> select Snum,Sum(amt) from Orders group by snum Having Sum(amt)>(Select max(amt) from Orders);
```

```
mysql> select Snum,Sum(amt) from Orders group by snum Having Sum(amt)>(Select max(amt) from Orders);
```

Snum	Sum(amt)
1001	15382.07

1 row in set (0.00 sec)