

Premium Armored Speaker Cable – Bhujang 8CH6SQMM

Product Description

High-performance armored multi-core speaker cable engineered for professional AV, defense installations, auditoriums, and long-distance high-power transmission. Designed with XLPE M9 insulation, stainless steel strip armoring, and 10 AWG high-strand copper conductors.

Technical Specifications

Conductor Configuration: 8 × 10 AWG + 1 × Ground
Conductor Material: High-strand tin copper
Insulation Type: XLPE, Grade M9 (high-temperature cross-linked polyethylene)
Inner Jacket: High-density Aluminum
Armor Type: Stainless Steel (SS) strip armoring, corrosion-proof
Outer Sheath: UV-stabilized black PVC outdoor rated



Electrical Characteristics

Rated Voltage: 1000 V
Conductor DC Resistance: $\leq 0.26 \Omega/\text{km}$
Insulation Resistance: $\geq 10 \text{ G}\Omega/\text{km}$ @ 80°C
Capacitance: Optimized for long-distance, low-loss AV systems

Mechanical & Environmental Performance

Operating Temperature Range: -30°C to +100°C
Installation Temperature: -20°C to +90°C
Pull Strength: Heavy-duty armored
Crush Resistance: >1500 N
Outdoor Suitability: Sunlight, moisture, and fungus resistant

Compliance & Standards

- XLPE M9 insulation classification
- IEC 60332-3 flame and safety compliance
- CE compliant
- ERDA Type-Tested for electrical, environmental, and aging performance

- CPRI Certified for XLPE M9 & SS Strip Armoring
- UL 1277 / UL 44 with stainless steel armoring.
- RoHS 2 compliant.
- ISO 9001
- ISO 45001
- ISO 20000
- ISO 27001
- GMP Compliant Manufacturing

Dimensions & Packaging

Outer Diameter: 29MM

Standard Reel Length: 1000 m / 1500 m

Markings: Sequential meter marking on outer jacket for accuracy