SHEIN 16x16 PARKING TILES

Heavy-Duty Vitrified Outdoor Collection

- AURELIAN INTERNATIONAL EXPORT CATALOGUE
- Manufactured in Morbi, Gujarat, India
- Standard Export Dimension: 400x400 mm (16x16 inch)
- Thickness: 12 mm / 16 mm High Compressive Density
- Surface: Anti-Skid Textured Punch / Heavy Load Bearing
- Water Absorption: < 0.05% (Impermeable BIa Group)

TECHNICAL SPECIFICATIONS & LOAD TEST

ISO 13006 & EN 14411 Group BIa Compliance

- Compressive Strength: > 2800 N/mm² (Vehicular Grade)
- Breaking Strength: > 6500 N
- Mohs Surface Hardness: Scale 7 - 8
- Slip Resistance Rating: R11 / R12 Wet & Dry Ramp Test
- Thermal Shock Resistance: Fully Resistant (15°C to 145°C)
- Frost Resistance: 100 Freeze-Thaw Cycles (ASTM C1026)
- Chemical & Stain Resistance: Class A Acid / Alkali Resistant

EXPORT PACKING & CONTAINER SPECIFICATIONS

Standard 20-Foot Full Container Load (FCL)

- Tiles Per Corrugated Box: 5 Pieces (0.80 sq. meters)
- Average Box Weight: Approx. 18.5 kg
- Pallet Type: ISPM-15 Heat-Treated & Fumigated Hardwood Pallets
- Boxes Per Pallet: 64 Boxes per Euro-style Pallet
- Total Pallets in 20ft FCL: 22 Heavy Pallets
- Total Surface Area in 20ft FCL: Approx. 1,126.4 sq. meters
- Total Gross Weight: Approx. 26.5 Metric Tons

COMMERCIAL TERMS & QUALITY CERTIFICATION

Aurelian International Global Logistics Desk

- Pre-Shipment Inspection: SGS / Bureau Veritas / TUV Rheinland
- Payment Terms: Irrevocable Confirmed L/C at Sight / TT Advance
- Incoterms Available: FOB Mundra / CIF / CFR Global Sea Ports
- Lead Time to Loading Port: 10-14 Business Days from Production
- Contact Export Desk: +91 70966 70655
- Official Email: exports@aurelianinternational.com