

# SQL ASSIGNMENT 1

## Problem Statements :

1. Design the complete database + schema + tables for the diagram shown above using appropriate data type for every column along with any constraints (checks + PK) mentioned in the task description and load the below data into the requisite tables.



### -- NEW DATABASE CREATED

```
CREATE DATABASE BIKESTORES;  
USE DATABASE BIKESTORES;
```

### -- NEW SCHEMA CREATED

```
CREATE OR REPLACE SCHEMA PRODUCTION;  
CREATE OR REPLACE SCHEMA SALES;
```

### -- TABLE CREATION IN SALES SCHEMA

```
CREATE OR REPLACE TABLE SALES.STORES  
(  
  STORE_ID INT IDENTITY(1,1) ,  
  STORE_NAME VARCHAR(25),  
  PHONE VARCHAR(25),  
  EMAIL VARCHAR(30),  
  STREET VARCHAR(30),  
  CITY VARCHAR(15),  
  STATE VARCHAR(5),  
  ZIP_CODE INT ,  
  PRIMARY KEY (STORE_ID)  
);
```

```
CREATE OR REPLACE TABLE SALES.STAFFS  
(  
  STAFF_ID INT,  
  FIRST_NAME VARCHAR(15),  
  LAST_NAME VARCHAR(15),  
  EMAIL VARCHAR(50) ,  
  PHONE VARCHAR(20) ,  
  ACTIVE TINYINT,  
  STORE_ID INT ,  
  MANAGER_ID INT,  
  PRIMARY KEY (STAFF_ID)  
);
```

CREATE OR REPLACE TABLE SALES.CUSTOMERS

```
(  
  CUSTOMER_ID INT IDENTITY(1,1),  
  FIRST_NAME VARCHAR(15),  
  LAST_NAME VARCHAR(15),  
  PHONE VARCHAR(20),  
  EMAIL VARCHAR(50),  
  STREET VARCHAR(50),  
  CITY VARCHAR(50),  
  STATE CHAR(10),  
  ZIP_CODE INT,  
  PRIMARY KEY(CUSTOMER_ID)  
);
```

CREATE OR REPLACE TABLE SALES.ORDERS

```
(  
  ORDER_ID INT,  
  CUSTOMER_ID INT,  
  ORDER_STATUS INT,  
  ORDER_DATE VARCHAR(10),  
  REQUIRED_DATE VARCHAR(10),  
  SHIPPED_DATE VARCHAR(10),  
  STORE_ID INT,  
  STAFF_ID INT,  
  PRIMARY KEY(ORDER_ID)  
);
```

CREATE OR REPLACE TABLE SALES.ORDER\_ITEMS

```
(  
  ORDER_ID INT,  
  ITEM_ID INT,  
  PRODUCT_ID INT,  
  QUANTITY INT,  
  LIST_PRICE DECIMAL(10,2),  
  DISCOUNT DECIMAL(4,2),  
  PRIMARY KEY(ORDER_ID,ITEM_ID)  
);
```

**-- TABLE CREATION IN PRODUCTION SCHEMA**

CREATE OR REPLACE TABLE PRODUCTION.CATEGORIES

```
(  
  CATEGORY_ID INT,  
  CATEGORY_NAME VARCHAR(50),  
  PRIMARY KEY(CATEGORY_ID)  
);
```

CREATE OR REPLACE TABLE PRODUCTION.BRANDS

```
(  
  BRAND_ID INT,  
  BRAND_NAME VARCHAR(50),  
  PRIMARY KEY(BRAND_ID)  
);
```


CREATE OR REPLACE TABLE PRODUCTION.PRODUCTS

```
(  
  PRODUCT_ID INT,  
  PRODUCT_NAME VARCHAR(100),  
  BRAND_ID INT,  
  CATEGORY_ID INT,  
  MODEL_YEAR INT,  
  LIST_PRICE DECIMAL(10,2),  
  PRIMARY KEY(PRODUCT_ID)BIKESTORESBIKESTORES.PRODUCTIONBIKESTORES.SALES  
);
```

CREATE OR REPLACE TABLE PRODUCTION.STOCKS

```
(  
  STORE_ID INT,  
  PRODUCT_ID INT,  
  QUANTITY INT,  
  PRIMARY KEY(STORE_ID, PRODUCT_ID)  
);
```

## FINAL OUTPUT IS:



**2. Once the table has got created , there is a requirement of FOREIGN KEY implementation coming into picture where one needs to add(ALTER TABLE COMMAND) below foreign key on the table mentioned pointing to another table (READ ABOUT FOREIGN KEY) as :**

**-- SALES.STAFFS (STORE\_ID) -> SALES.STORES(STORIED)**

```
ALTER TABLE SALES.STAFFS
ADD FOREIGN KEY(STORE_ID) REFERENCES SALES.STORES(STORE_ID);
```

**-- SALES.STAFFS (MANAGER\_ID) -> SALES.STAFFS (STAFF\_ID)**

```
ALTER TABLE SALES.STAFFS
ADD FOREIGN KEY(MANAGER_ID) REFERENCES SALES.STAFFS(STAFF_ID);
```

**-- PRODUCTION.PRODUCTS (CATEGORY\_ID) -> PRODUCTION.CATEGORIES (CATEGORY\_ID)**

```
ALTER TABLE PRODUCTION.PRODUCTS
ADD FOREIGN KEY(CATEGORY_ID) REFERENCES PRODUCTION.CATEGORIES(CATEGORY_ID);
```

**-- PRODUCTION.PRODUCTS(BRAND\_ID) -> PRODUCTION.BRANDS (BRAND\_ID)**

```
ALTER TABLE PRODUCTION.PRODUCTS
ADD FOREIGN KEY(BRAND_ID) REFERENCES PRODUCTION.BRANDS(BRAND_ID);
```

**-- SALES.ORDERS (CUSTOMER\_ID) -> SALES.CUSTOMERS (CUSTOMER\_ID)**

```
ALTER TABLE SALES.ORDERS
ADD FOREIGN KEY(CUSTOMER_ID) REFERENCES SALES.CUSTOMERS(CUSTOMER_ID);
```

**-- SALES.ORDERS(STORE\_ID) -> SALES.STORES (STORE\_ID)**

```
ALTER TABLE SALES.ORDERS
ADD FOREIGN KEY(STORE_ID) REFERENCES SALES.STORES(STORE_ID);
```

**-- SALES.ORDERS (STAFF\_ID) -> SALES.STAFFS (STAFF\_ID)**

```
ALTER TABLE SALES.ORDERS
ADD FOREIGN KEY(STAFF_ID) REFERENCES SALES.STAFFS(STAFF_ID);
```

**-- SALES.ORDER\_ITEMS(ORDER\_ID) -> SALES.ORDERS (ORDER\_ID)**

```
ALTER TABLE SALES.ORDER_ITEMS
ADD FOREIGN KEY(ORDER_ID) REFERENCES SALES.ORDERS(ORDER_ID);
```

-- SALES.ORDER\_ITEMS (PRODUCT\_ID) -> PRODUCTION.PRODUCTS (PRODUCT\_ID)

ALTER TABLE SALES.ORDER\_ITEMS

ADD FOREIGN KEY(PRODUCT\_ID) REFERENCES PRODUCTION.PRODUCTS(PRODUCT\_ID);

-- PRODUCTION.STOCKS (STORE\_ID) -> SALES.STORES (STORE\_ID)

ALTER TABLE PRODUCTION.STOCKS

ADD FOREIGN KEY(STORE\_ID) REFERENCES SALES.STORES(STORE\_ID);

-- PRODUCTION.STOCKS (PRODUCT\_ID) -> PRODUCTION.PRODUCTS (PRODUCT\_ID)

ALTER TABLE PRODUCTION.STOCKS

ADD FOREIGN KEY(PRODUCT\_ID) REFERENCES PRODUCTION.PRODUCTS(PRODUCT\_ID);

### 3. Does any of the table has missing or NULL value ? If yes which are those and what are their counts ?

Sales.Customer - Column(PHONE) is having NULL values.

```
180
181 -- Sales.Customer - Column(PHONE) is having NULL values.
182 | SELECT COUNT(*) AS TOT_NULL_VALUES FROM SALES.CUSTOMERS WHERE PHONE IS NULL;
183
```

Results Chart

	TOT_NULL_VALUES
1	1,267

Sales.Orders - Column(SHIPPED\_DATE) is having NULL values.

```
184 -- Sales.Orders - Column(SHIPPED_DATE) is having NULL values.
185 | SELECT COUNT(*) AS TOT_NULL_VALUES from SALES.ORDERS WHERE SHIPPED_DATE is NULL;
186
187
```

Results Chart

	TOT_NULL_VALUES
1	170

**4. Does the datasets has any DUPLICATE(identical rows) ? If yes – can you just keep the first record and remove all rest if its possible without using any JOINS or WINDOW function.**

```
SELECT COUNT(*) AS TOT_ROWS FROM SALES.CUSTOMERS; -- 1445
```

```
SELECT COUNT(DISTINCT FIRST_NAME, LAST_NAME, PHONE, EMAIL, STREET, CITY, STATE, ZIP_CODE) AS  
TOT_DISTINCT_ROWS  
FROM SALES.CUSTOMERS; --1445
```

```
SELECT COUNT(*) AS TOT_ROWS FROM SALES.ORDERS; -- 1615
```

```
SELECT COUNT(DISTINCT ORDER_ID, CUSTOMER_ID, ORDER_STATUS, ORDER_DATE, REQUIRED_DATE, SHIPPED_DATE,  
STORE_ID,STAFF_ID) AS TOT_DISTINCT_ROWS  
FROM SALES.ORDERS; -- 1615
```

```
SELECT COUNT(*) AS TOT_ROWS FROM SALES.ORDER_ITEMS; -- 4722
```

```
SELECT COUNT(DISTINCT ORDER_ID, ITEM_ID, PRODUCT_ID, QUANTITY, LIST_PRICE,DISCOUNT) AS TOT_DISTINCT_ROWS  
FROM SALES.ORDER_ITEMS; -- 4722
```

```
SELECT COUNT(*) AS TOT_ROWS FROM SALES.STAFFS; -- 10
```

```
SELECT COUNT(DISTINCT STAFF_ID, FIRST_NAME, LAST_NAME, EMAIL, PHONE, ACTIVE, STORE_ID, MANAGER_ID) AS  
TOT_DISTINCT_ROWS  
FROM SALES.STAFFS; -- 10
```

```
SELECT COUNT(*) AS TOT_ROWS FROM SALES.STORES; -- 3
```

```
SELECT COUNT(DISTINCT STORE_NAME, PHONE, EMAIL, STREET, CITY, STATE, ZIP_CODE) AS TOT_DISTINCT_ROWS  
FROM SALES.STORES; -- 3
```

```
SELECT COUNT(*) AS TOT_ROWS FROM PRODUCTION.BRANDS; -- 9
```

```
SELECT COUNT(DISTINCT BRAND_ID,BRAND_NAME) AS TOT_DISTINCT_ROWS  
FROM PRODUCTION.BRANDS; -- 9
```

```
SELECT COUNT(*) AS TOT_ROWS FROM PRODUCTION.CATEGORIES; -- 7
```

```
SELECT COUNT(DISTINCT CATEGORY_ID,CATEGORY_NAME) AS TOT_DISTINCT_ROWS  
FROM PRODUCTION.CATEGORIES; -- 7
```

```
SELECT COUNT(*) AS TOT_ROWS FROM PRODUCTION.PRODUCTS; -- 321
```

```
SELECT COUNT(DISTINCT PRODUCT_ID, PRODUCT_NAME, BRAND_ID, CATEGORY_ID, MODEL_YEAR, LIST_PRICE) AS  
TOT_DISTINCT_ROWS  
FROM PRODUCTION.PRODUCTS; -- 321
```

```
SELECT COUNT(*) AS TOT_ROWS FROM PRODUCTION.STOCKS; -- 939
```

```
SELECT COUNT(DISTINCT STORE_ID, PRODUCT_ID, QUANTITY) AS TOT_DISTINCT_ROWS  
FROM PRODUCTION.STOCKS; -- 939
```

**Therefore, this dataset has no Duplicate (Identical Rows).**

5. How many unique tables are present in each schema and under each table how many records are having ? (Write SQL Script for the same – I don't need answer like 3/5/4 etc)

```
230 SELECT TABLE_SCHEMA, TABLE_NAME, ROW_COUNT
231 FROM INFORMATION_SCHEMA.TABLES
232 ORDER BY 1 DESC;
233
```

Results Chart

	TABLE_SCHEMA	TABLE_NAME	ROW_COUNT
1	SALES	ORDERS	1,615
2	SALES	STAFFS	10
3	SALES	STORES	3
4	SALES	CUSTOMERS	1,445
5	SALES	ORDER_ITEMS	4,722
6	PRODUCTION	BRANDS	9
7	PRODUCTION	STOCKS	939
8	PRODUCTION	PRODUCTS	321
9	PRODUCTION	CATEGORIES	7
10	INFORMATION_SCHEMA	TABLES	null
11	INFORMATION_SCHEMA	USAGE_PRIVILEGES	null
12	INFORMATION_SCHEMA	REPLICATION_GROUPS	null
13	INFORMATION_SCHEMA	PROCEDURES	null
14	INFORMATION_SCHEMA	CLASS_INSTANCES	null
15	INFORMATION_SCHEMA	CLASSES	null
16	INFORMATION_SCHEMA	CLASS_INSTANCE_FUNCTIONS	null
17	INFORMATION_SCHEMA	PACKAGES	null
18	INFORMATION_SCHEMA	REPLICATION_DATABASES	null
19	INFORMATION_SCHEMA	FILE_FORMATS	null
20	INFORMATION_SCHEMA	APPLICABLE_ROLES	null



## 6. How many total serving customer BikeStore has ?

```
237 | SELECT COUNT(DISTINCT CUSTOMER_ID) AS TOT_SERVING_CUST FROM SALES.ORDERS ;  
238 |  
239 |
```

Results Chart

	TOT_SERVING_CUST
1	1,445

## 7. How many total orders are there ?

```
239 |  
240 | -- 7. How many total orders are there ?  
241 |  
242 | SELECT COUNT(DISTINCT ORDER_ID) AS TOT_ORDERS FROM SALES.ORDERS;  
243 |  
244 |
```

Results Chart

	TOT_ORDERS
1	1,615

## 8. Which store has the highest number of sales ?

```
244
245      -- 8. Which store has the highest number of sales ?
246
247      SELECT STORE_ID,
248             COUNT(ORDER_ID) AS Highest_Sales
249      FROM SALES.ORDERS
250      GROUP BY 1
251      ORDER BY 2 DESC
252      LIMIT 1;
253
254
```

Results Chart

	STORE_ID	HIGHEST_SALES
1	2	1,093

## 9. Which month the sales was highest and for which store ?

```
254
255      -- 9. Which month the sales was highest and for which store ?
256
257      SELECT SUBSTR(ORDER_DATE,6,2) AS Month_No,
258             ORDERS.STORE_ID,
259             ROUND(SUM(QUANTITY*LIST_PRICE*(1-DISCOUNT)),2) AS TOT_SALES
260      FROM BIKESTORES.SALES.ORDER_ITEMS, BIKESTORES.SALES.ORDERS
261      GROUP BY 1,2
262      ORDER BY 3 DESC
263      LIMIT 1;
264
265
```

Results Chart

	MONTH_NO	STORE_ID	TOT_SALES
1	03	2	1,022,652,502.16

## 10. How many orders each customer has placed (give me top 10 customers)

```
266 -- 10. How many orders each customer has placed (give me top 10 customers)
267
268 SELECT CUSTOMER_ID,
269 COUNT(DISTINCT ORDER_ID) AS TOT_ORDERS
270 FROM BIKESTORES.SALES.ORDERS
271 GROUP BY 1
272 ORDER BY 2 DESC
273 LIMIT 10;
```

Results Chart

	CUSTOMER_ID	TOT_ORDERS
1	32	3
2	8	3
3	7	3
4	31	3
5	66	3
6	9	3
7	50	3
8	5	3
9	43	3
10	24	3

## 11. Which are the TOP 3 selling product ?

```
275
276 -- 11. Which are the TOP 3 selling product ?
277
278 SELECT PRODUCT_ID,
279 ROUND(SUM(QUANTITY*LIST_PRICE*(1-DISCOUNT)),2) AS TOT_SALES
280 FROM BIKESTORES.SALES.ORDER_ITEMS
281 GROUP BY 1
282 ORDER BY 2 DESC
283 LIMIT 3;
284
285
```

Results Chart

	PRODUCT_ID	TOT_SALES
1	7	555,558.61
2	9	389248.70
3	4	368,472.73

## 12. Which was the first and last order placed by the customer who has placed maximum number of orders ?

```
286
287 -- 12. Which was the first and last order placed by the customer who has placed maximum number of orders ?
288
289 SELECT CUSTOMER_ID,
290 MIN(ORDER_ID) AS First_Order,
291 MAX(ORDER_ID) as Last_Order
292 FROM BIKESTORES.SALES.ORDERS
293 GROUP BY 1
294 ORDER BY COUNT(ORDER_ID) DESC
295 LIMIT 1;
296
```

Results Chart

	CUSTOMER_ID	FIRST_ORDER	LAST_ORDER
1	7	104	1,604

### 13. For every customer , which is the cheapest product and the costliest product which the customer has bought.

BIKESTORES.SALES ▾ Settings ▾

```

297
298 -- 13. For every customer , which is the cheapest product and the costliest product which the customer has bought.
299
300     SELECT Cheap.CUSTOMER_ID, Cheapest_Product, Costliest_Product
301     FROM
302     (
303         SELECT CUSTOMER_ID, PRODUCT_NAME AS Cheapest_Product
304         FROM
305         (
306             SELECT CUSTOMER_ID, PRODUCT_NAME,
307             DENSE_RANK() OVER (PARTITION BY CUSTOMER_ID ORDER BY OT.LIST_PRICE ASC) AS PRICE_RANK
308             FROM BIKESTORES.SALES.ORDERS O
309             INNER JOIN BIKESTORES.SALES.ORDER_ITEMS OT
310             ON O.ORDER_ID = OT.ORDER_ID
311             INNER JOIN BIKESTORES.PRODUCTION.PRODUCTS P
312             ON OT.PRODUCT_ID = P.PRODUCT_ID
313             ORDER BY 1,3
314         )
315         WHERE PRICE_RANK = 1
316     ) Cheap
317
318     INNER JOIN
319
320     (
321         SELECT CUSTOMER_ID, PRODUCT_NAME AS Costliest_Product
322         FROM
323         (
324             SELECT CUSTOMER_ID, PRODUCT_NAME,
325             DENSE_RANK() OVER (PARTITION BY CUSTOMER_ID ORDER BY OT.LIST_PRICE DESC) AS PRICE_RANK
326             FROM BIKESTORES.SALES.ORDERS O
327             INNER JOIN BIKESTORES.SALES.ORDER_ITEMS OT
328             ON O.ORDER_ID = OT.ORDER_ID
329             INNER JOIN BIKESTORES.PRODUCTION.PRODUCTS P
330             ON OT.PRODUCT_ID = P.PRODUCT_ID
331             ORDER BY 1,3
332         )
333         WHERE PRICE_RANK = 1
334     ) Costly
335     ON Cheap.CUSTOMER_ID = Costly.CUSTOMER_ID;
336

```

↳ Results ↗ Chart

	CUSTOMER_ID	CHEAPEST_PRODUCT	COSTLIEST_PRODUCT
1	1	"Electra Girl's Hawaii 1 (16-inch) - 2015/2016"	"Trek Domane SL Frameset - 2018"
2	2	"Sun Bicycles Lil Bolt Type-R - 2017"	"Trek Domane SLR 6 Disc - 2017"
3	3	"Trek Precaliber 12 Boy's - 2018"	"Trek Silque SLR 7 Women's - 2017"
4	4	"Strider Strider 20 Sport - 2018"	"Trek Slash 8 27.5 - 2016"

#### 14. Which product has orders more than 200 ?

There is no product who has more than 200 orders

```
341      -- 14. Which product has orders more than 200 ?
342
343      SELECT PRODUCT_ID, COUNT(DISTINCT ORDER_ID) AS TOT_ORDERS
344      FROM BIKESTORES.SALES.ORDER_ITEMS
345      GROUP BY 1
346      HAVING TOT_ORDERS > 200
347      ORDER BY 2 DESC;
348
```

Results Chart

PRODUCT_ID	TOT_ORDERS
------------	------------

Query produced no results

#### 15. Add a column TOTAL\_PRICE with appropriate data type into the sales.order\_items.

```
-- 15. Add a column TOTAL_PRICE with appropriate data type into the sales.order_items
```

```
ALTER TABLE BIKESTORES.SALES.ORDER_ITEMS
ADD COLUMN TOTAL_PRICE DECIMAL(11,2);
```

#### 16. Calculate TOTAL\_PRICE = quantity \* list price and Update the value for all rows in the sales.order\_items table.

```
-- 16. Calculate TOTAL_PRICE = quantity * list price and Update the value for all rows in the sales.order_items table.
```

```
UPDATE BIKESTORES.SALES.ORDER_ITEMS
SET TOTAL_PRICE = ROUND(QUANTITY * LIST_PRICE,2);
```

### 17. What is the value of the TOTAL\_PRICE paid for all the sales.order\_items ?

```
362      -- 17. What is the value of the TOTAL_PRICE paid for all the sales.order_items ?
363
364      SELECT SUM(TOTAL_PRICE) AS TOT_PRICE_PAID FROM BIKESTORES.SALES.ORDER_ITEMS;
365
```

↳ Results  Chart

	TOT_PRICE_PAID
1	8578988.88

\*\*\*\*\* **THANK YOU** \*\*\*\*\*