

## Experiment 8 :

- **Original Inserted Values:**

1. hotel\_post

|   | post_id | title                    | price | location    |
|---|---------|--------------------------|-------|-------------|
| ▶ | 1       | Luxury Beachfront Resort | 250   | Miami Beach |
|   | 2       | Mountain Retreat         | 180   | Denver      |
|   | 3       | City Center Hotel        | 150   | New York    |
|   | 4       | Countryside Inn          | 120   | Austin      |
|   | 5       | Lakeside Lodge           | 220   | Lake Tahoe  |
|   | 6       | Desert Oasis             | 200   | Phoenix     |
|   | 7       | Downtown Skyline Hotel   | 170   | Chicago     |
|   | 8       | Tropical Paradise Resort | 300   | Hawaii      |
| * | NULL    | NULL                     | NULL  | NULL        |

- **Stored Function: Count Hotels in a Location**

```
1  DELIMITER //
```

```
2
```

```
3  • CREATE FUNCTION count_hotels_by_location(input_location VARCHAR(50))
```

```
4  RETURNS INT
```

```
5  DETERMINISTIC
```

```
6  BEGIN
```

```
7      DECLARE total_hotels INT;
```

```
8
```

```
9      SELECT COUNT(*) INTO total_hotels
```

```
10     FROM hotel_post
```

```
11     WHERE location = input_location;
```

```
12
```

```
13     RETURN total_hotels;
```

```
14 END //
```

```
15
```

```
16 DELIMITER ;
```

```
18 • SELECT count_hotels_by_location('Miami Beach');
```

|                                         |   |              |         |                    |
|-----------------------------------------|---|--------------|---------|--------------------|
| Result Grid                             |   | Filter Rows: | Export: | Wrap Cell Content: |
| count_hotels_by_location('Miami Beach') |   |              |         |                    |
| ▶                                       | 1 |              |         |                    |

- **Procedure without Parameter**

```
1  DELIMITER //
```

```
2
```

```
3  • CREATE PROCEDURE get_expensive_hotels()
```

```
4  BEGIN
```

```
5      SELECT *
```

```
6      FROM hotel_post
```

```
7      WHERE price > 200;
```

```
8  END //
```

```
9
```

```
10 DELIMITER ;
```

```
12 • CALL get_expensive_hotels();
```

| Result Grid | Filter Rows:             | Export: | Wrap Cell Content: |
|-------------|--------------------------|---------|--------------------|
| post_id     | title                    | price   | location           |
| 1           | Luxury Beachfront Resort | 250     | Miami Beach        |
| 5           | Lakeside Lodge           | 220     | Lake Tahoe         |
| 8           | Tropical Paradise Resort | 300     | Hawaii             |

- **Procedure with IN Parameter**

```
1  DELIMITER //
```

```
2
```

```
3  • CREATE PROCEDURE get_hotels_by_location(IN input_location VARCHAR(50))
```

```
4  BEGIN
```

```
5      SELECT *
```

```
6      FROM hotel_post
```

```
7      WHERE location = input_location;
```

```
8  END //
```

```
9
```

```
10 DELIMITER ;
```

```
12 • CALL get_hotels_by_location('Denver');
```

| Result Grid | Filter Rows:     | Export: | Wrap Cell Content: |
|-------------|------------------|---------|--------------------|
| post_id     | title            | price   | location           |
| 2           | Mountain Retreat | 180     | Denver             |

## • Procedure with OUT Parameter

```
1 DELIMITER //
```

```
2
```

```
3 • CREATE PROCEDURE get_total_hotels(OUT total_count INT)
```

```
4 BEGIN
```

```
5     SELECT COUNT(*) INTO total_count
```

```
6     FROM hotel_post;
```

```
7 END //
```

```
8
```

```
9 DELIMITER ;
```

```
10 • CALL get_total_hotels(@count);
```

```
11 • SELECT @count;
```

|             |        |              |         |                    |
|-------------|--------|--------------|---------|--------------------|
| Result Grid |        | Filter Rows: | Export: | Wrap Cell Content: |
|             | @count |              |         |                    |
| ▶           | 8      |              |         |                    |