

Backend algo8 task

By Shivam Singha <shivamsingha@live.com (mailto:shivamsingha@live.com)>

github.com/shivamsingha (https://github.com/shivamsingha)

GET /

localhost:3000

Returns JSON containing CSRF-Token which is to be used in other requests.

Example Request

```
GET / HTTP/1.1
Host: localhost:3000
```

POST /login

localhost:3000/login

Allows users to login.

JSON body with following params:

| Name | Type | Description |
|------------|--------|---|
| emailphone | string | Either email or phone of user used to login |
| password | string | Password of user |

Responds with JSON

| Name | Type | Description |
|-------|--------|-------------|
| token | string | JWT Token |

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

BODY raw

```
{
  "emailphone": "some@gmail.com",
  "password": "qqqqQQQQ1"
}
```

Example Request

localhost:3000/login

POST /login HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

```
{
  "emailphone": "some@gmail.com",
  "password": "qqqqQQQQ1"
}
```

Example Response

200 OK

Body Headers (16)

```
{
  "token": "eyJlbmMiOiJBMTI4Q0JDLUhTMjU2IiwiaWwiYXNjaioiUEJFUzItSFMyNTYrQTEyOEtXIiwicDjIjoyNzYxLCJwMi"
}
```

POST /register

localhost:3000/register

Used to register a new account. This also sends an verification email.

JSON body with following params:

| Name | Type | Description |
|----------|--------|---|
| email | string | Email of user |
| phone | string | Phone no. of user |
| password | string | Password of user. Min 8 characters long, min 4 lowercase, min 4 uppercase, min 1 number |

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

BODY raw

```
{
  "email": "some3@gmail.com",
  "phone": "+919876343212",
  "password": "qqqqQQQQ1"
}
```

Example Request

/register

POST /register HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

```
{
  "email": "some4@gmail.com",
  "phone": "+919876543212",
  "password": "qqqqQQQQ1"
}
```

GET /verify/:userId/:code

```
localhost:3000/verify/:userId/:code
```

This link is send to the email of the newly registered user. Code is a randomly generated string stored in database which could be used to verify only the user that generated it. Also the code is deleted after one use.

PATH VARIABLES

userId

26
User ID

code

8a102bf1cc073d502c9442626248f015aabcf5375c0f9350f4e6db990d02b007
Verification Code

Example Request /verify/:userId/:code

GET /verify/26/8a102bf1cc073d502c9442626248f015aabcf5375c0f9350f4e6db990d02b007 HTTP/1.1
Host: localhost:3000

GET /item

localhost:3000/item

Returns a list of all items

Example Request /item

GET /item HTTP/1.1
Host: localhost:3000

Example Response 200 OK

Body Headers (16)

```
[
  {
    "id": 2,
    "desc": null,
    "title": "another",
    "price": 10,
    "noOfRatings": 0,
    "totalScore": 0
  },
  {
```

[View More](#)

GET /item/:itemId

localhost:3000/item/:itemId

Returns details of the item with itemId

PATH VARIABLES

itemId

1

Item ID

Example Request

/item/:itemId

```
GET /item/1 HTTP/1.1
Host: localhost:3000
```

Example Response

200 OK

Body Headers (16)

```
{
  "title": "test",
  "desc": null,
  "price": 12,
  "noOfRatings": 1,
  "totalScore": 5
}
```

POST /user/addToCart/:itemId

localhost:3000/user/addToCart/:itemId

Add item with itemId to cart.

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

PATH VARIABLES

itemId

1

Item ID

Example Request

/user/addToCart/:itemId

POST /user/addToCart/1 HTTP/1.1

Host: localhost:3000

CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

Example Response

200 OK

Body Headers (16)

```
{
  "profile": {
    "cart": [
      {
        "id": 2,
        "title": "another",
        "stock": 1,
        "price": 10,
        "desc": null,
        "images": []
      }
    ]
  }
}
```

[View More](#)

POST /user/rateItem/:itemId

localhost:3000/user/rateItem/:itemId

Give a rating to item with itemId

JSON with following params

| Name | Type | Description |
|--------|------|--------------------------------|
| rating | Int | Rating of the product out of 5 |

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

PATH VARIABLES

itemId

1

Item ID

BODY raw

```
{
  "rating": 5
}
```

Example Request

/user/rateItem/:itemId

```
POST /user/rateItem/1 HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps
```

```
{
  "rating": 5
}
```

POST /user/checkout

localhost:3000/user/checkout

Checkout all the items in cart, create an order and prompt for payment.

| Name | Type | Description |
|------------|--------|--------------------------------|
| couponCode | string | Enter coupon code for discount |

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

Example Request

/user/checkout

POST /user/checkout HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

POST /user/editProfile

localhost:3000/user/editProfile

Edit profile of user

JSON body with following params

| Name | Type | Description |
|---------|--------|-------------------|
| name | string | Full name of user |
| address | string | Address of user |

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

BODY raw

```
{
  "name": "Shivam Singha",
  "address": "India"
}
```

POST /user/editProfile HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

```
{
  "name": "Shivam Singha",
  "address": "India"
}
```

Example Response 200 OK

Body Headers (16)

```
{
  "profile": {
    "id": 1,
    "name": "Shivam Singha",
    "address": "India",
    "Picture": null,
    "userId": 23
  }
}
```

POST /user/payment/:orderId

localhost:3000/user/payment/:orderId

Make payment for given orderId. This verifies the payment status with the payment gateway.

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

PATH VARIABLES

orderId

1

Order ID

Example Request

/user/payment/:orderId

POST /user/payment/1 HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

GET /admin/saleReport

localhost:3000/admin/saleReport

Return a full report of sales.

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

Example Request

/admin/saleReport

GET /admin/saleReport HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

GET /admin/userLoginReport

localhost:3000/admin/userLoginReport

Returns a log of user logins.

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

Example Request

/admin/userLoginReport

GET /admin/userLoginReport HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

Example Response

200 OK

Body Headers (16)

```
[
  {
    "id": 1,
    "loginTime": "2020-12-18T17:30:51.803Z",
    "userId": 23
  }
]
```

GET /admin/itemStockReport

localhost:3000/admin/itemStockReport

Returns a report of available stocks of items.

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

Example Request

/admin/itemStockReport

GET /admin/itemStockReport HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

Example Response

200 OK

Body Headers (16)

[
 {
 "id": 2,
 "title": "another",
 "stock": 1
 },
 {
 "id": 1,
 "title": "test",
 "stock": 1

[View More](#)

POST /admin/addNewItem

localhost:3000/admin/addNewItem

Allows admins to add new item and it's details.

JSON body with following params:

| Name | Type | Description |
|-------|--------|-----------------------|
| title | string | Title of item |
| desc | string | Description of item |
| price | float | Price of item |
| stock | Int | No. of items in stock |

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

BODY raw

```
{
  "title": "new product",
  "desc": "Amazing item",
  "price": 300,
  "stock": 10
}
```

Example Request

/admin/addNewItem

POST /admin/addNewItem HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps

```
{
  "title": "new product",
  "desc": "Amazing item",
  "price": 300,
  "stock": 10
}
```

Example Response

200 OK

Body Headers (16)

```
{
  "id": 3,
  "title": "new product",
  "stock": 10,
  "price": 300,
  "desc": "Amazing item",
  "images": [],
  "noOfRatings": 0,
  "totalScore": 0,
  "orderId": null.
```

[View More](#)

POST /admin/editItem

localhost:3000/admin/editItem

Allows admins to edit item details.

JSON body with following params:

| Name | Type | Description |
|-------|--------|-----------------------|
| title | string | Title of item |
| desc | string | Description of item |
| price | float | Price of item |
| stock | Int | No. of items in stock |

AUTHORIZATION

Bearer Token

Token

<token>

HEADERS

CSRF-Token

vXqxFzy1-tc7D3rxSZRr2FwPulHsa0Lzprps

BODY raw

```
{
  "id": 3,
  "title": "changed name product",
  "desc": "Midrange item",
  "price": 250,
  "stock": 15
}
```

Example Request

/admin/editItem

```
POST /admin/editItem HTTP/1.1
Host: localhost:3000
CSRF-Token: vXqxFzy1-tc7D3rxSZRr2FwPuIHsa0Lzprps
```

```
{
  "id": 3,
  "title": "changed name product",
  "desc": "Midrange item",
  "price": 250,
  "stock": 15
}
```

[View More](#)

Example Response

200 OK

Body Headers (16)

```
{
  "id": 3,
  "title": "changed name product",
  "stock": 15,
  "price": 250,
  "desc": "Midrange item",
  "images": [],
  "noOfRatings": 0,
  "totalScore": 0,
  "orderId": null.
}
```

[View More](#)