

Simulate REAL Outage Pressure

These labs reflect **production-like failures** without step-by-step.

LAB 1: Pod Running but Application Down

Setup: Deploy a pod that runs, but the port is wrong, or the service is misconfigured.

Expected Debug Areas:

- service → endpoints
 - container ports
 - readiness probe
 - network reachability
- 

LAB 2: Random DNS Failures Inside Pods

Setup: Temporarily modify the coredns config or use the wrong DNS config.

Expected Debug Areas:

- DNS caching
 - /etc/resolv.conf
 - cluster DNS service IP
 - network policies
-

LAB 3: Node Goes ReadOnly / Disk Full

Setup: Fill the node disk via large files.

Expected Debug Areas:

- `df -h`
 - `dmesg`
 - kubelet node status
 - eviction logic
-

LAB 4: Deployment Not Updating

Setup: Use an incorrect image tag or a lack of permissions.

Expected Debug Areas:

- rollout status
 - `imagePullErrors`
 - repo access
 - events
-

LAB 5: Basic GitOps Simulation (Very Light)

Setup:

- Have a Deployment locally with a different version
- Apply the GitOps manifest with another version
- Introduce mismatch

Expected Debug Areas:

- diff between applied and running state
- version drift
- events
- logs

