Practical 9:

Aim: system has RAM which can store four pages simultaneously to satisfy page requests. Write a Program to calculate percentage page hit and page fault if the system uses Optimal page replacement technique for the page references entered by the user i.e. 1, 2, 3, 4, 1, 2, 5, 1, 2, 3, 4, 5 (No of Frames=3).

Code:

```
~
  GNU nano 8.7
#include <stdio.h>

int main() {
    int pages[] = {1,2,3,4,1,2,5,1,2,3,4,5};
    int frame[3], n=12, frames=3;
    int i,j,k,hit=0,fault=0,pos,far;

    for(i=0;i<frames;i++)
        frame[i] = -1;

    for(i=0;i<n;i++) {
        int found = 0;

        for(j=0;j<frames;j++) {
            if(frame[j] == pages[i]) {
                hit++;
                found = 1;
                break;
            }
        }

        if(!found) {
            fault++;

            for(j=0;j<frames;j++) {
                if(frame[j] == -1) {
                    frame[j] = pages[i];
                    found = 1;
                    break;
                }
            }

            if(!found) {
                far = -1;
                pos = -1;

                for(j=0;j<frames;j++) {
                    int next = -1;

                    for(k=i+1;k<n;k++) {
                        if(frame[j] == pages[k]) {
                            next = k;
                            break;
                        }
^G Help          ^O Write Out     ^F Where Is      ^K Cut           ^T Execute
^X Exit          ^R Read File     ^\ Replace       ^U Paste         ^J Justify
```

```
                    }

                    if(next == -1) {
                        pos = j;
                        break;
                    }

                    if(next > far) {
                        far = next;
                        pos = j;
                    }
                }

                frame[pos] = pages[i];
            }
        }
    }

    printf("Hits = %d\nFaults = %d\n", hit, fault);
    printf("Hit %% = %.2f\nFault %% = %.2f\n",(float)hit/n*100,(float)fault/n*100);

    return 0;
}

^G Help        ^O Write Out   ^F Where Is    ^K Cut         ^T Execute     ^C L
^X Exit        ^R Read File   ^\ Replace     ^U Paste       ^J Justify     ^/ G
```

Output :

```
~

hp@DESKTOP-CA6S8T8 MSYS ~
$ nano optimal.c

hp@DESKTOP-CA6S8T8 MSYS ~
$ gcc optimal.c -o optimal

hp@DESKTOP-CA6S8T8 MSYS ~
$ ./optimal
Hits = 5
Faults = 7
Hit % = 41.67
Fault % = 58.33

hp@DESKTOP-CA6S8T8 MSYS ~
$
```