1QUES. Turn Off Lights

hackerearth.com/problem/algorithm/turn-off-lights-be46dc6c/?source=list_view

PRACTICE COMPETE JOBS LEADERBOARD

All Tracks > Problem

Turn Off Lights

1970 77% 30 ★★★★★8 votes Share

Details Submissions Discussion Similar Problems Editorial

Problem

There are n bulbs arranged in a row. The state of the bulbs is represented by a binary string *bulbs* of length n, the 0 at i^{th} position in the string represents the bulb is OFF and 1 represents the bulb is ON, where $0 \leq i < n$. You have to switch OFF all the bulbs by performing following operation atmost k times. The operation is defined as:-

- Choose any index i in the string *bulb* and turn OFF all the lights having indexes i to $\min(n-1, i+l-1)$ (inclusive), where l is a pre defined number, greater than zero and fixed for all the operations.

The task is to find the smallest value of l greater than zero, such that you can turn OFF all the bulbs in atmost k operations.

Input format

Enter your code or Upload your code as file. Save C++14 (g++ 10.3.0)

```cpp
#include <iostream>
using namespace std;

int main() {
    int n, m;
    cin >> n >> m;

    string bulbs;
    cin >> bulbs;

    for(int k = 1; k <= n; k++) {

        int operations = 0;

        for(int i = 0; i < n; ) {
            if(bulbs[i] == '1') {
```

Temps to drop Next Tuesday Search ENG IN 10:19 04-04-2026

hackerearth.com/practice/algorithms/string-algorithm/string-searching/practice-problems/algorithm/turn-off-lights-be46dc6c/

PRACTICE COMPETE JOBS LEADERBOARD

All Tracks > Algorithms > String Algorithms > String Searching > Problem

Turn Off Lights

2722 81% 30 ★★★★★8 votes String Algorithms, Algorithms, String Searching Share

Details Submissions Discussion Similar Problems Editorial

Problem

There are n bulbs arranged in a row. The state of the bulbs is represented by a binary string *bulbs* of length n, the 0 at i^{th} position in the string represents the bulb is OFF and 1 represents the bulb is ON, where $0 \leq i < n$. You have to switch OFF all the bulbs by performing following operation atmost k times. The operation is defined as:-

- Choose any index i in the string *bulb* and turn OFF all the lights having indexes i to $\min(n-1, i+l-1)$ (inclusive), where l is a pre defined number, greater than zero and fixed for all the operations.

The task is to find the smallest value of l greater than zero, such that you can turn OFF all the bulbs in atmost k operations.

Input format

Submission ID: 127547521

RESULT: Accepted Refer judge environment

Score	Time (sec)	Memory (KiB)	Language
0	0.55526	2356	C++14

Input	Result	Time (sec)	Memory (KiB)	Score	Your output	Correct output	Diff
Input #1	Accepted	0.009377	2	10			
Input #2	Accepted	0.009635	2	10			
Input #3	Accepted	0.025594	916	10			