Sioyek Documentation

Contents

1 Commands **10**

1.1 add_annot_to_highlight 10
1.2 add_bookmark 10
1.3 add_freetext_bookmark 10
1.4 add_highlight 10
1.5 add_highlight_with_current_type 10
1.6 add_keybind 10
1.7 add_marked_bookmark 11
1.8 add_marked_data, remove_marked_data, export_marked_data, undo_marked_data, goto_random_page 11
1.9 change_highlight 11
1.10 clear_current_page_drawings, clear_current_document_drawings 11
1.11 clear_scratchpad 11
1.12 close_overview 11
1.13 close_window 11
1.14 command 11
1.15 command_palette 11
1.16 control_menu 11
1.17 copy 13
1.18 copy_drawings_from_scratchpad 13
1.19 copy_link 13
1.20 copy_screenshot_to_clipboard 13
1.21 copy_screenshot_to_scratchpad 13
1.22 copy_window_size_config 13
1.23 create_fulltext_index_for_current_document 13
1.24 create_visible_portal 13
1.25 delete_current_file_from_server 13
1.26 delete_freehand_drawings 13
1.27 delete_highlight_under_cursor 13
1.28 delete_portal, delete_bookmark, delete_highlight 14
1.29 delete_visible_bookmark 14
1.30 donate 14
1.31 download_paper_with_url, download_clipboard_url 14

1.32 download_link 14
1.33 download_overview_paper, download_overview_paper_no_prompt 14
1.34 download_paper_under_cursor 14
1.35 download_paper_with_name 14
1.36 download_unsynced_files 14
1.37 edit_portal 15
1.38 edit_selected_bookmark 15
1.39 edit_selected_highlight 15
1.40 edit_visible_bookmark 15
1.41 embed_annotations 15
1.42 enter_password 15
1.43 enter_visual_mark_mode 15
1.44 escape 15
1.45 execute, execute_shell_command 15
1.46 execute_macro 16
1.47 exit_ruler_mode, close_visual_mark 16
1.48 export 16
1.49 external_search 16
1.50 extract_table, extract_table_with_prompt 16
1.51 fit_epub_to_window 17
1.52 fit_to_page_width_ratio 17
1.53 fit_to_page_width, fit_to_page_height, fit_to_page_width_smart, fit_to_page_height_smart, fit_to_page_smart 17
1.54 focus_text 17
1.55 force_download_annotations 17
1.56 framebuffer_screenshot 17
1.57 generic_delete 17
1.58 generic_select 17
1.59 get_annotations_json 18
1.60 get_config_no_dialog 18
1.61 get_config_value 18
1.62 get_mode_string 18
1.63 get_overview_paper_name 19
1.64 get_paper_name 19
1.65 get_state_json 19
1.66 goto_beginning, goto_end 20
1.67 goto_bookmark, goto_bookmark_g 20
1.68 goto_definition 20
1.69 goto_highlight, goto_highlight_g 20
1.70 goto_left, goto_right, goto_left_smart, goto_right_smart 20
1.71 goto_mark 20
1.72 goto_next_highlight, goto_prev_highlight 20
1.73 goto_next_highlight_of_type, goto_prev_highlight_of_type 20
1.74 goto_overview 20
1.75 goto_page_with_label 21
1.76 goto_page_with_page_number 21

1.77 goto_portal 21
1.78 goto_portal_list 21
1.79 goto_selected_text 21
1.80 goto_tab 21
1.81 goto_toc 21
1.82 goto_top_of_page, goto_bottom_of_page 21
1.83 goto_window 21
1.84 import 21
1.85 import_annotations 21
1.86 import_local_database, import_shared_database 22
1.87 increase_freetext_font_size, decrease_freetext_font_size 22
1.88 keyboard_overview 22
1.89 keyboard_select 22
1.90 keyboard_select_line 22
1.91 keyboard_smart_jump 22
1.92 keys 22
1.93 keys_user 22
1.94 keys_user_all 22
1.95 load_annotations_file, import_annotations_file_sync_deleted 23
1.96 load_scratchpad 23
1.97 login 23
1.98 login_using_access_token 23
1.99 logout 23
1.100 maximize 23
1.101 move_left, move_right, move_down, move_up 23
1.102 move_left_in_overview, move_right_in_overview 23
1.103 move_ruler_up, move_ruler_down, move_visual_mark_up, move_visual_mark_down 23
1.104 move_ruler_to_next_block, move_ruler_to_prev_block . . 23
1.105 move_ruler_next, move_ruler_prev, move_visual_mark_next, move_visual_mark_prev 24
1.106 move_window, set_window_rect 24
1.107 new_window 24
1.108 next_overview, previous_overview 24
1.109 next_chapter, prev_chapter 24
1.110 next_item, previous_item 24
1.111 next_page, previous_page 24
1.112 next_state, prev_state 24
1.113 noop 24
1.114 open_containing_folder 25
1.115 open_document 25
1.116 open_document_embedded 25
1.117 open_document_embedded_from_current_path 25
1.118 open_external_text_editor 25
1.119 open_last_document 25
1.120 open_link 25

1.121 open_local_database_containing_folder, open_shared_database_containing_folder 25
1.122 open_prev_doc 25
1.123 open_server_only_file 25
1.124 overview_definition 26
1.125 overview_link 26
1.126 overview_next_item, overview_prev_item 26
1.127 overview_to_portal 26
1.128 overview_to_ruler_portal, goto_ruler_portal 26
1.129 overview_under_cursor 26
1.130 portal 26
1.131 portal_to_definition 26
1.132 portal_to_link 26
1.133 portal_to_overview 27
1.134 prefs 27
1.135 prefs_user 27
1.136 prefs_user_all 27
1.137 quit 27
1.138 regex_search 27
1.139 reload 27
1.140 reload_config 27
1.141 reload_no_flicker 27
1.142 rename 28
1.143 resume_to_server 28
1.144 resync_document 28
1.145 rotate_clockwise, rotate_counterclockwise 28
1.146 ruler_under_cursor, visual_mark_under_cursor 28
1.147 ruler_under_selected_point 28
1.148 save_scratchpad 28
1.149 scan_new_files 28
1.150 screenshot 28
1.151 screen_down, screen_up 28
1.152 search, chapter_search 28
1.153 search_all_indexed_documents 29
1.154 select_current_search_match 29
1.155 select_freehand_drawings 29
1.156 select_rect 29
1.157 select_ruler_text 29
1.158 semantic_search 29
1.159 semantic_search_extractive 29
1.160 set_freehand_alpha 29
1.161 set_freehand_thickness 30
1.162 set_freehand_type 30
1.163 set_mark 30
1.164 set_page_offset 30
1.165 set_select_highlight_type 30
1.166 set_status_string, clear_status_string 30

1.167 set_view_state 30
1.168 show_context_menu 31
1.169 show_custom_context_menu 31
1.170 show_custom_options 31
1.171 show_text_prompt 31
1.172 show_touch_draw_controls 31
1.173 show_touch_highlight_type_select 31
1.174 show_touch_main_menu 31
1.175 show_touch_page_select 32
1.176 show_touch_settings_menu 32
1.177 smart_jump_under_cursor 32
1.178 move_down_smooth, move_up_smooth 32
1.179 start_mobile_text_selection_at_point 32
1.180 start_reading, stop_reading 32
1.181 start_reading_high_quality 32
1.182 synchronize 32
1.183 synctex_forward_search 32
1.184 synctex_under_cursor 33
1.185 synctex_under_ruler 33
1.186 sync_current_file_location 33
1.187 test_command, export_config_names, open_selected_url, toggle_smooth_scroll_mode, export_python_api, print_undocumented_commands, print_non_default_configs, export_default_config_file, unregister_url_handler, toggle_one_window, register_url_handler, export_command_names, goto_begining, send_symbol, open_all_docs, print_undocumented_configs, toggle_show_last_command, move_selected_bookmark, type_text 33
1.188 toggle_text_mark, move_text_mark_forward, move_text_mark_backward, move_text_mark_forward_word, move_text_mark_backward_word, move_text_mark_down, move_text_mark_up 33
1.189 toggle_custom_color 33
1.190 toggle_dark_mode 33
1.191 toggle_drawing_mask 34
1.192 toggle_fastread 34
1.193 toggle_freehand_drawing_mode 34
1.194 toggle_fullscreen 34
1.195 toggle_highlight_links 34
1.196 toggle_horizontal_scroll_lock 34
1.197 toggle_line_select_cursor 34
1.198 toggle_mouse_drag_mode 34
1.199 toggle_pdf_annotations 34
1.200 toggle_pen_drawing_mode 34
1.201 toggle_presentation_mode, turn_on_presentation_mode . . 34
1.202 toggle_reading 35
1.203 toggle_rect_hints 35
1.204 toggle_ruler_scroll_mode, toggle_visual_scroll 35

1.205 toggle_scratchpad_mode 35
1.206 toggle_scrollbar 35
1.207 toggle_select_highlight 35
1.208 toggle_statusbar 35
1.209 toggle_synctex, turn_on_synctex 35
1.210 toggle_titlebar 35
1.211 toggle_two_page_mode 35
1.212 toggle_typing_mode 36
1.213 toggle_window_configuration 36
1.214 turn_on_all_drawings, turn_off_all_drawings 36
1.215 undo_drawing 36
1.216 upload_current_file 36
1.217 wait 36
1.218 wait_for_renders_to_finish, wait_for_search_to_finish, wait_for_indexing_to_finish, wait_for_downloads_to_finish 36
1.219 write_annotations_file 36
1.220 zoom_in, zoom_out, zoom_in_cursor, zoom_out_cursor . . 36
1.221 zoom_in_overview, zoom_out_overview 37

2 Configs 37
2.1 adjust_annotation_colors_for_dark_mode 37
2.2 align_link_dst_to_top 37
2.3 allow_horizontal_drag_when_document_is_small 37
2.4 allow_main_view_scroll_while_in_overview 37
2.5 annotations_directory 37
2.6 autocenter_ruler 37
2.7 automatically_download_matching_paper_name 37
2.8 automatically_index_documents_for_fulltext_search . . . 38
2.9 automatically_update_checksum_when_document_is_changed 38
2.10 automatically_upload_portal_destination_for_synced_documents 38
2.11 auto_login_on_startup 38
2.12 auto_rename_downloaded_papers 38
2.13 background_bookmarks_pixel_budget 38
2.14 background_color, custom_color_mode_empty_background_color, dark_mode_background_color 38
2.15 case_sensitive_search 38
2.16 check_for_updates_on_startup 38
2.17 shift_click_command, control_click_command, command_click_command, hold_middle_click_command, tablet_pen_click_command, tablet_pen_double_click_command, right_click_command, middle_click_command, shift_middle_click_command, control_middle_click_command, command_middle_click_command, alt_middle_click_command, shift_right_click_command, control_right_click_command, command_right_click_command, alt_click_command, alt_right_click_command 39
2.18 collapsed_toc 39

2.19 context_menu_items, context_menu_items_for_links, context_menu_items_for_selected_text, context_menu_items_for_highlights, context_menu_items_for_bookmarks, context_menu_items_for_overview 39
2.20 create_table_of_contents_if_not_exists 39
2.21 custom_text_color, custom_background_color 39
2.22 dark_mode_contrast 39
2.23 default_open_file_path 39
2.24 documentation_font_size 40
2.25 document_location_mismatch_strategy 40
2.26 dont_center_if_synctex_rect_is_visible 40
2.27 epub_css 40
2.28 epub_width, epub_height, epub_font_size 40
2.29 exact_highlight_select 40
2.30 external_text_editor_command 40
2.31 extract_table_prompt 40
2.32 fill_textbar_with_selected_text 41
2.33 fit_to_page_width_ratio 41
2.34 flat_toc 41
2.35 font_size 41
2.36 freetext_bookmark_color 41
2.37 freetext_bookmark_font_size 41
2.38 fuzzy_searching 41
2.39 gamma 41
2.40 hide_overlapping_link_labels 41
2.41 highlight_color_[a-z] 41
2.42 highlight_links 42
2.43 highlight_middle_click 42
2.44 hover_overview 42
2.45 ignore_scroll_events 42
2.46 ignore_whitespace_in_presentation_mode 42
2.47 incremental_search 42
2.48 initial_snapped_dragging 42
2.49 inverse_search_command 42
2.50 inverted_horizontal_scrolling 42
2.51 invert_selected_text 43
2.52 keyboard_point_selection 43
2.53 keyboard_select_background_color, keyboard_select_text_color, keyboard_selected_tag_background_color, keyboard_selected_tag_text_color 43
2.54 keyboard_select_font_size 43
2.55 linear_filter 43
2.56 link_highlight_color 43
2.57 max_created_toc_size 43
2.58 menu_matched_search_highlight 43
2.59 menu_screen_width_ratio, menu_screen_height_ratio . . . 43
2.60 middle_click_search_engine, shift_middle_click_search_engine 43
2.61 move_screen_ratio 44

2.62 numeric_tags 44
2.63 num_cached_pages 44
2.64 num_prerendered_next_slides, num_prerendered_prev_slides 44
2.65 num_two_page_columns 44
2.66 overview_reference_highlight_color 44
2.67 page_separator_width, page_separator_color 44
2.68 page_space_x, page_space_y 44
2.69 papers_folder_path 44
2.70 paper_download_should_create_portal 45
2.71 paper_download_should_detect_paper_name 45
2.72 prerendered_page_count 45
2.73 prerender_next_page_presentation 45
2.74 preserve_image_colors_in_dark_mode, inverted_preserved_image_colors 45
2.75 question_bookmark_background_color, question_bookmark_text_color 45
2.76 real_page_separation 45
2.77 reload_interval_miliseconds 45
2.78 render_freetext_borders 46
2.79 render_pdf_annotations 46
2.80 resize_command 46
2.81 right_click_context_menu 46
2.82 ruler_auto_move_threshold_distance 46
2.83 ruler_color 46
2.84 ruler_display_mode 46
2.85 ruler_marker_color 46
2.86 ruler_next_page_end_pos, ruler_next_page_begin_pos . . 47
2.87 ruler_padding, ruler_x_padding 47
2.88 ruler_pixel_width 47
2.89 ruler_slit_color 47
2.90 save_externally_edited_text_on_focus 47
2.91 scrollview_sensitivity 47
2.92 search_highlight_color 47
2.93 search_url_[a-z] 47
2.94 server_and_local_document_mismatch_threshold 48
2.95 shared_database_path 48
2.96 should_highlight_unselected_search 48
2.97 should_launch_new_window 48
2.98 should_load_tutorial_when_no_other_file 48
2.99 should_warn_about_user_key_override 48
2.100 show_most_recent_commands_first 48
2.101 show_reference_overview_highlights 48
2.102 single_click_selects_words 49
2.103 sliced_rendering 49
2.104 smartcase_search 49
2.105 smooth_move_max_velocity 49
2.106 sort_bookmarks_by_location 49
2.107 startup_commands 49

2.108 status_bar_color, status_bar_text_color 49
2.109 status_bar_font_size 49
2.110 status_bar_format, right_status_bar_format, status_*_command 50
2.111 status_custom_message_[a-d] 51
2.112 status_font 51
2.113 strike_line_width 51
2.114 super_fast_search 51
2.115 synctex_highlght_timeout 51
2.116 synctex_highlight_color 51
2.117 synctex_highlight_timeout 52
2.118 table_extract_behaviour 52
2.119 tag_font_face 52
2.120 text_highlight_color 52
2.121 toc_jump_align_top 52
2.122 touchpad_sensitivity 52
2.123 touch_mode 52
2.124 back_rect_tap_command, back_rect_hold_command, forward_rect_tap_command, forward_rect_hold_command, middle_left_rect_tap_command, middle_left_rect_hold_command, middle_right_rect_tap_command, middle_right_rect_hold_command, ruler_next_tap_command, ruler_next_hold_command, ruler_prev_tap_command, ruler_prev_hold_command 53
2.125 tts_rate 53
2.126 ui_font 53
2.127 portrait_back_ui_rect, portrait_forward_ui_rect, landscape_back_ui_rect, landscape_forward_ui_rect, portrait_visual_mark_next, portrait_visual_mark_prev, landscape_visual_mark_next, landscape_visual_mark_prev, landscape_middle_right_rect, portrait_middle_right_rect, landscape_middle_left_rect, portrait_middle_left_rect 53
2.128 ui_text_color, ui_background_color, ui_selected_text_color, ui_selected_background_color 53
2.129 unselected_search_highlight_color 53
2.130 use_ruler_to_highlight_synctex_line 53
2.131 use_system_theme, use_custom_color_as_dark_system_theme 54
2.132 vertical_move_amount, horizontal_move_amount 54
2.133 wheel_zoom_in_cursor 54
2.134 main_window_size, helper_window_size, main_window_move, helper_window_move, single_main_window_size, single_main_window_move, overview_size, overview_offset 54
2.135 zoom_inc_factor 54

1 Commands

1.1 `add_annot_to_highlight`

Alows the user to select a highlight to add annotations to using the keyboard.

1.2 `add_bookmark`

Add an invisible bookmark in the current location. You can later search the bookmarks using the `goto_bookmark` command.

1.3 `add_freetext_bookmark`

Add a freetext bookmark in the selected rectangle. Freetext bookmarks are visible in the document. You can change the display style of the bookmark using the following prefixes:

- if the bookmark text starts with `#` followed by a symbol, it will draw a box with the symbol's color (the same color as the highlighs of the symbol).
- if the bookmark text starts with `#markdown`, the rest of the bookmark will be rendered as markdown
- if the bookmark text starts with `#latex`, the rest of the bookmark will be rendered as latex
- if the bookmarks text starts with `?`, it will be interpreted as a question to be asked from the current document (using a large language model). The response will be displayed in the bookmark (this feature is only available to pro users).

1.4 `add_highlight`

Highlight the selected text. Requires a symbol which specifies the color of the highlighted text. For example executing `add_highlight` followed by pressing `a` will create a highlight with color `highlight_color_a`. You can configure the highlight color of all highlights in your config files. The highlights can later be searched using `goto_highlight`.

1.5 `add_highlight_with_current_type`

Highlight the selected text with the current highlight type as set by `set_select_highlight_type`.

1.6 `add_keybind`

Dynamically add a new keybinding.

1.7 add_marked_bookmark

Add a marked bookmark in the selected location. Marked bookmarks are visible in the document using a small icon. You can later search the bookmarks using the `goto_bookmark` command.

1.8 add_marked_data, remove_marked_data, export_marked_data, undo_marked_data, goto_random_page

1.9 change_highlight

Alows the user to change highlight type using keyboard. The user first enters the label of the highlight they want to change, then they enter the label of the new highlight type they want to change it to.

1.10 clear_current_page_drawings, clear_current_document_drawings

Clear all freehand drawings in the current page/document.

1.11 clear_scratchpad

Clear the scratchpad.

1.12 close_overview

Close the overview window.

1.13 close_window

Close the current sioyek window (doesn't close the application if there are more than one window open).

1.14 command

Open a searchable list of all commands.

1.15 command_palette

Show a command palette with human-readable command names.

1.16 control_menu

Used to control ui menus using keyboard or scripts. Takes the desired action as an input string which can be one of the following:

Action	Description
`down`	Move down in menu
`up`	move up in menu
`page_down`	move to the next page in menu
`page_up`	move to the previous page in menu
`menu_begin`	move to the first item in menu
`menu_end`	move to the last item in menu
`select`	select the highlighted item
`get`	get the value of selected item (mainly used in scripting)
`cursor_backward`	move the text cursor one character backward
`cursor_forward`	move the text cursor one character forward
`select_backward`	select text one character backward
`select_forward`	select text one character forward
`move_word_backward`	move the text cursor one word backward
`move_word_forward`	move the text cursor one word forward
`select_word_backward`	select the previous word
`select_word_forward`	select the next word
`move_to_end`	move to the end of text input
`move_to_begin`	move to the start of text input
`select_to_end`	select to the end of text input
`select_to_begin`	select to the start of text input
`select_all`	select all of the text input
`delete_to_end`	delete text from cursor location to the end of the input
`delete_to_begin`	delete text from the start of the input to the cursor
`delete_next_word`	delete the next word after cursor
`delete_prev_word`	delete the previous word before cursor
`delete_next_char`	delete the character after cursor
`delete_prev_char`	delete the character before cursor
`next_suggestion`	show the next autocomplete suggestion
`prev_suggestion`	show the previous autocomplete suggestion

For example, suppose you want to use `<C-j>` and `<C-k>` keybinds to move up and down in a menu. You can add the following to your `keys_user.config`:

```
control_menu('down') <C-j>
control_menu('up') <C-k>
```

1.17 `copy`

Copy the selected text to clipboard.

1.18 `copy_drawings_from_scratchpad`

Copy drawings in the selected rectangle from the scratchpad to the main document.

1.19 `copy_link`

Displays a symbol next to each visible link and copies the URL of selected link.

1.20 `copy_screenshot_to_clipboard`

Copy a screenshot of selected rectangle to the clipboard.

1.21 `copy_screenshot_to_scratchpad`

Copy a screenshot of the document to the scratchpad (for example can be used to copy an image of an equation to the scratchpad).

1.22 `copy_window_size_config`

1.23 `create_fulltext_index_for_current_document`

Add the current document to the fulltext search indexed. All indexed documents can later be searched using `search_all_indexed_documents`.

1.24 `create_visible_portal`

Creates a portal with the selected window point as source. The source will be visible on the document. The destination of the portal can later be set using the `portal` command. An overview to the destination of the portal can be opened by right clicking on the portal icon.

1.25 `delete_current_file_from_server`

Delete current file from sioyek servers.

1.26 `delete_freehand_drawings`

Delete the freehand drawings in the selected rectangle.

1.27 `delete_highlight_under_cursor`

Delete the highlight under mouse cursor.

1.28 `delete_portal, delete_bookmark, delete_highlight`

Delete the selected portal/bookmark/highlight. If no item is selected then we delete the closest portal/bookmark/highlight to the current location.

1.29 `delete_visible_bookmark`

Delete a visible bookmark on the screen using keyboard by specifying the label of the bookmark.

1.30 `donate`

Make a donation to support the development of sioyek.

1.31 `download_paper_with_url, download_clipboard_url`

Download and open a paper from an input URL (`download_paper_with_url`) or the URL in clipboard (`download_clipboard_url`).

1.32 `download_link`

Download a paper by selecting its link using the keyboard.

1.33 `download_overview_paper, download_overview_paper_no_prompt`

Downloads the paper currently shown in overview window. The `download_overview_paper` command first displays the automatically detected paper title and asks for confirmation. The `download_overview_paper_no_prompt` command downloads the paper without asking for confirmation.

1.34 `download_paper_under_cursor`

Download the paper under mouse cursor. This can be the actual name of the paper (either in the document itself or the overview window) or a reference to the paper (e.g. executing `download_paper_under_cursor` while cursor is on a reference like `[12]` will download the paper referenced by `[12]`).

1.35 `download_paper_with_name`

Download a paper given its name as input.

1.36 `download_unsynced_files`

Download all files on sioyek server that are not available locally.

1.37 `edit_portal`

Edit the destination of the portal with the closest source. When `edit_portal` is executed, sioyek jumps to the destination of the portal, now we can move around the destination and when we are done, we execute `prev_state` which updates the destination with the current location and brings us back to the source of the portal.

1.38 `edit_selected_bookmark`

Edits the selected bookmark (a bookmark can be selected by clicking on it).

1.39 `edit_selected_highlight`

Edits the annotation of selected highlight (highlights can be selected by clicking on them).

1.40 `edit_visible_bookmark`

Edit a visible bookmark on the screen using keyboard by specifying the label of the bookmark.

1.41 `embed_annotations`

Embeds the sioyek annotations into the document as native PDF annotations. This is useful when sharing the file with others who do not have sioyek installed.

1.42 `enter_password`

Enter the password for password-protected PDF files.

1.43 `enter_visual_mark_mode`

1.44 `escape`

Simulates pressing escape.

1.45 `execute, execute_shell_command`

Executes the given shell command. The following substrings will be expanded in the command:

- `%{file_path}` will expand to the full path of current file.
- `%{file_name}` will expand to current file name.
- `%{selected_text}` will expand to the current selected text.
- `%{selection_begin_document}` and `%{selection_end_document}` will expand to the document location of the begin and end of current text selection. The format is `page x y`.

- `%{page_number}` will expand to the current page number.
- `%{command_text}` will ask the user for a text input and expand to the input.
- `%{mouse_pos_window}` will expand to the mouse position in the window. The format is `x y`.
- `%{mouse_pos_document}` will expand to the mouse position in the document. The format is `page x y`.
- `%{paper_name}` will expand to the current file's automatically detected paper/document title
- `%{sioyek_path}` will expand to the path of sioyek executable
- `%{local_database}` will expand to the path the local database file
- `%{shared_database}` will expand to the path the shared database file
- `%{selected_rect}` will expand to the selected rectangle in the document. The format is `page x1 y1 x2 y2`.
- `%{zoom_level}` will expand to the current zoom level.
- `%{offset_x}` and `%{offset_y}` will expand to the current absolute offsets
- `%{offset_x_document}` and `%{offset_y_document}` will expand to the current document offsets
- `%{line_text}`: if we are in ruler mode will expand to the text of current ruler line

1.46 `execute_macro`

Execute the given sioyek commands string. This is mainly used for scripting and it is probably not directly useful for end-users.

1.47 `exit_ruler_mode, close_visual_mark`

Exit ruler mode.

1.48 `export`

Export annotation data into a json file.

1.49 `external_search`

Search the selected text using the configured external search engine. This is a symbol command, and each symbol could be configured for a different search engine. For example in the default configuration `g` searches in google and `s` searches in google scholar. If no text is selected, we search the title of the current document instead (e.g. in the default configuration, to search the current paper in google scholar you can press `ss` when no text is selected).

1.50 `extract_table, extract_table_with_prompt`

Extract the contents of selected table. The `extract_table_with_prompt` command asks the user for a natural language prompt and extracts the table according

to that (for example you can say something like this: “extract the contents of this table into a latex table”).

1.51 fit_epub_to_window

Fit an epub document exactly to the window dimensions.

1.52 fit_to_page_width_ratio

Fit to current document to a ratio of screen configured using `fit_to_page_width_ratio`. This is useful for users with very wide screens.

1.53 fit_to_page_width, fit_to_page_height, fit_to_page_width_smart, fit_to_page_height_smart, fit_to_page_smart

Fits the document to page width/height. The smart variants try to ignore the white page margins while fitting. `fit_to_page_smart` command fits the document to the minimum of width and height, ignoring the white margins.

1.54 focus_text

Create the ruler under the line with the given text.

1.55 force_download_annotations

Download all unsynced annotations from the server. This is usually performed automatically but can be manually triggered with this command.

1.56 framebuffer_screenshot

Take a screenshot from sioyek framebuffer (ignoring other widgets) and save it to the given path. This is mainly used for testing purposes.

1.57 generic_delete

Allows the user to delete annotations using keyboard. The user enters the label of the annotation they want to delete.

1.58 generic_select

Allows the user to select annotations using keyboard. The user enters the label of the annotation they want to delete.

1.59 get_annotations_json

the current document's annotations as a json string.

Example:

```
from sioyek import Sioyek
import json
s = Sioyek('')
annotations = json.loads(s.get_annotations_json())
print(annotations)
```

1.60 get_config_no_dialog

commands: get_config_value

Returns the current value of given config without displaying anything to the user. This is mainly useful for scripting.

Example:

```
from sioyek import sioyek
s = sioyek.Sioyek('')
print(s.get_config_no_dialog('highlight_color_a')) # 'color3 0.94 0.64 1\n'
```

1.61 get_config_value

commands: get_config_no_dialog

demo_code:

```
s = sioyek.Sioyek('', launch_if_not_exists=True, launch_args=LAUNCH_ARGS)
s.goto_page_with_page_number(1)
start_recording(RECORDING_FILE_NAME)
show_run_command(s, 'get_config_value')
type_words(s, "highlight_color_a")
time.sleep(3)
end_recording()
```

Displays the vlue of the given config string to the user.

1.62 get_mode_string

the string for current mode. See @concept(mode) for more information.

Example:

```
from sioyek import Sioyek
s = Sioyek('')
print(s.get_mode_string()) # 'RXHQEDPOSFMT'
```

1.63 get_overview_paper_name

the title of the paper in current overview window. This is useful for scripting and probably not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = Sioyek('')
paper_name = s.get_overview_paper_name()
s.set_status_string(f'Current overview paper name is: {paper_name}')
```

1.64 get_paper_name

the title of the current document. This is useful for scripting and probably not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = Sioyek('')
paper_name = s.get_paper_name()
s.set_status_string(f'Current document name is: {paper_name}')
```

1.65 get_state_json

a json string containing the current state of the application. The state is a list of json objects for each sioyek window. Each object contains the following fields:

- `document_checksum`: MD5 checksum of the document
- `document_path`: Path to the document
- `loaded_documents`: List of the paths of loaded documents
- `page_number`: Current page number
- `searching`: Whether the application is currently searching
- `selected_text`: The currently selected text
- `window_height`: Height of the window
- `window_width`: Width of the window
- `window_id`: The id of the window
- `x_offset` and `y_offset`: Current position in document
- `x_offset_in_page` and `y_offset_in_page`: Current position in page
- `zoom_level`: Current zoom level

Example:

```
from sioyek import sioyek
import json

s = sioyek.Sioyek('')
state = json.loads(s.get_state_json())
print(state['page_number'])
```

1.66 goto_beginning, goto_end

Move to the beginning/end of the document.

1.67 goto_bookmark, goto_bookmark_g

`goto_bookmark` opens a searchable list of current document's bookmarks. `goto_bookmark_g` opens a searchable list of all documents' bookmarks.

1.68 goto_definition

Go to the the definition of the first symbol in the highlighted line using the @link(ruler_mode, "ruler").

1.69 goto_highlight, goto_highlight_g

Open a searchable list of all highlights in the current document. You can limit the search to highlights of a certain type by prefixing the query by the type of the highlight followed by a space. For example `j {query}` searches for `{query}` only in highlights of type j. `goto_highlight_g` opens a searchable list of all documents' highlights.

1.70 goto_left, goto_right, goto_left_smart, goto_right_smart

Move to the left/right side of the document. The `_smart` variants ignore the white page margins.

1.71 goto_mark

Goto a mark previously set by `set_mark`. See `set_mark` for more details.

1.72 goto_next_highlight, goto_prev_highlight

Jump to the next/previous highlight in the current document.

1.73 goto_next_highlight_of_type, goto_prev_highlight_of_type

Jump to the next/previous highlight with the current highlight type (as set by `set_select_highlight_type`)

1.74 goto_overview

Jump to the location of current overview.

1.75 goto_page_with_label

commands: goto_page_with_page_number

Prompts the user for a page label and jumps to that page. The label can be different from the page number in some documents (e.g. some documents have some pages labeled as “i”, “ii”, “iii”, etc.).

1.76 goto_page_with_page_number

commands: goto_page_with_label

Prompts the user for a page number and jumps to that page.

1.77 goto_portal

Go to the destination of the portal with the closest source.

1.78 goto_portal_list

ist of portals in the current

1.79 goto_selected_text

Jump to the location of selected text.

1.80 goto_tab

list of tabs.

1.81 goto_toc

Open the table of contents.

1.82 goto_top_of_page, goto_bottom_of_page

Go to the top/bottom of the current page.

1.83 goto_window

Open a searchable list of current sioyek windows.

1.84 import

Import annotation data from an exported json file using `export`.

1.85 import_annotations

Imports the native PDF annotations into sioyek annotations.

1.86 import_local_database, import_shared_database

Import the data from `local.db` or `shared.db` file.

1.87 increase_freetext_font_size, decrease_freetext_font_size

Increase/decrease the font size of the freetext bookmark being edited.

1.88 keyboard_overview

Displays a tag next to each word in the document, opens an overview to the selected tag's word (this works even for documents that don't have links, otherwise `overview_link` would be used).

1.89 keyboard_select

Displays a tag next to each word in the document, selects the text corresponding to the entered begin and end tag (separated by a space).

1.90 keyboard_select_line

Select a line using keyboard. Show a label next to each visible line and create a ruler under that line when a label corresponding to that line is entered.

1.91 keyboard_smart_jump

Displays a tag next to each word in the document, jumps to the selected tag's word (this works even for documents that don't have links, otherwise `overview_link` would be used).

1.92 keys

Opens the default `keys.config` file.

1.93 keys_user

Opens the default `keys_user.config` file.

1.94 keys_user_all

Shows a list of all considered `keys_user.config` files, sorted by priority. All of these files are applied but the files with higher priority override the lower-priority files if they contain the same setting.

1.95 `load_annotations_file, import_annotations_file_sync_deleted`

Load the annotations from the file created using `write_annotations_file`. The `load_annotations_file` doesn't delete anything from the current file but the `import_annotations_file_sync_deleted` will overwrite the current annotations with the annotations in the file and delete any annotations that are not in the file.

1.96 `load_scratchpad`

Load a previously saved scratchpad state. This state should have been previously saved using `save_scratchpad`.

1.97 `login`

Login into your sioyek account.

1.98 `login_using_access_token`

Login to sioyek servers using previously obtained access token.

1.99 `logout`

Logout from your sioyek account.

1.100 `maximize`

Maximize the sioyek window.

1.101 `move_left, move_right, move_down, move_up`

Basic movement in the current document.

1.102 `move_left_in_overview, move_right_in_overview`

Move left and right in the overview (you can use the normal up and down movement commands to move up and down).

1.103 `move_ruler_up, move_ruler_down, move_visual_mark_up, move_visual_mark_down`

Move the ruler up or down.

1.104 `move_ruler_to_next_block, move_ruler_to_prev_block`

Move the ruler to previous/next text block.

1.105 move_ruler_next, move_ruler_prev, move_visual_mark_next, move_visual_mark_prev

Move the ruler such that more content is visible. This is the same as `move_ruler_down` `move_ruler_up` commands when the ruler is entirely visible, but when part of the ruler is offscreen (e.g. in mobile devices with a small screen) this command moves such that the obscured part of the ruler becomes visible and only moves to the next line when the entire line has been viewed. A red marked highlights the leftmost part of the next ruler position, so when you reach the red mark you can run `move_ruler_next` and continue reading from the left side of the screen.

1.106 move_window, set_window_rect

1.107 new_window

Create a new sioyek window.

1.108 next_overview, previous_overview

Go to the next/prevoius possible overview desitnation. For example, when executing `overview_definition` there might be more than one possible target. This command will jump to the next/previous target.

1.109 next_chapter, prev_chapter

Go to the next/previous chapter in table of contents.

1.110 next_item, previous_item

Go to the next/previous search result.

1.111 next_page, previous_page

Move to the next/previous page.

1.112 next_state, prev_state

Move forward/backward in history. Note that this history works even across files (i.e. if you go to a different file you can return to the previous file by executing `prev_state` or go back forward to the new file by executing `next_state`.)

1.113 noop

Do nothing (for example can be used to unbind default keybindings, by binding them to `noop` instead).

1.114 open_containing_folder

Open the folder containing the current file in file explorer.

1.115 open_document

Open the operating system's file explorer to select a document to open.

1.116 open_document_embedded

Opens an embedded file browser in sioyek (unlike open_document which uses the operating system's file browser).

1.117 open_document_embedded_from_current_path

Opens an embedded file browser in sioyek rooted at the current opened file's directory with the current file being selected.

1.118 open_external_text_editor

Open an external text editor to edit the current text input. For example you can open an external editor to edit bookmarks or highlight annotations. The external editor can be configured using `external_text_editor_command`, the corresponding text input will be updated in sioyek whenever the file is saved.

1.119 open_last_document

Opens the last document that was opened in the current sioyek window.

1.120 open_link

Displays a symbol next to each visible link and jumps when user enters the link symbol.

1.121 open_local_database_containing_folder, open_shared_database_containin

Open the folder containing the local/shared database file.

1.122 open_prev_doc

Shows a list of previously opened documents.

1.123 open_server_only_file

Open a list of files that the user has previously uploaded on sioyek servers but are not available on the current device.

1.124 `overview_definition`

Open an overview to the definition of the first symbol in the highlighted line using the @link(ruler_mode, "ruler").

1.125 `overview_link`

Displays a symbol next to each visible link and opens an overview to link destination when user enters the link symbol.

1.126 `overview_next_item, overview_prev_item`

Open an overview to the next/previous search result.

1.127 `overview_to_portal`

Open an overview to the closest portal.

1.128 `overview_to_ruler_portal, goto_ruler_portal`

Open an overview/Jump to the portal on current ruler line.

1.129 `overview_under_cursor`

Open the overview window to the location of reference under mouse cursor. This works even when the document doesn't have links.

1.130 `portal`

Creates a new pending portal with the current location as source. If we already have a pending-portal, create the portal with the current location as the destination. As an example use-case you can create a portal from a part of text describing an equation or table to the equation/table itself, the contents of the destination portal can be viewed in a separate window using `toggle_window_configuration` or an overview to see the contents of the portal in the same window using `overview_to_portal`.

1.131 `portal_to_definition`

Create a portal to the definition of the first symbol in the highlighted line using the @link(ruler_mode, "ruler").

1.132 `portal_to_link`

Displays a symbol next to each visible link and creates a portal from the current location to the selected link's location.

1.133 `portal_to_overview`

Create a portal from the current location to the overview location.

1.134 `prefs`

Opens the default `prefs.config` file.

1.135 `prefs_user`

Opens the default `prefs_user.config` file.

1.136 `prefs_user_all`

Shows a list of all considered `prefs_user.config` files, sorted by priority. All of these files are applied but the files with higher priority override the lower-priority files if they contain the same setting.

1.137 `quit`

Quits sioyek (closes all windows).

1.138 `regex_search`

Search the contents of current document using regular expressions. You can navigate the results the same way you would with `search` results.

1.139 `reload`

Reload all of the current file's data. This can be useful for situations where the file has been modified outside of sioyek, although sioyek will try to automatically reload the file if it detects changes on rare occasions it might fail to do so, in such situations you can use this command to manually reload the file.

1.140 `reload_config`

Reloads the config files. Sioyek automatically reloads the config files when they are changed but in rare situations when it doesn't do so automatically (e.g. due to a permission issue), you can manually reload them using this command.

1.141 `reload_no_flicker`

This is similar to the `reload` with the difference that here we don't immediately delete the previous renders (which causes the screen to flicker before the new document is rendered).

1.142 rename

Rename the current file. Sioyek tries to fill the default value to an automatically detected title.

1.143 resume_to_server

Resume the current file location to the last location in sioyek servers.

1.144 resync_document

Re-sync current document's annotations with sioyek servers. This command is usually performed automatically but can be manually triggered with this command.

1.145 rotate_clockwise, rotate_counterclockwise

Rotate the document.

1.146 ruler_under_cursor, visual_mark_under_cursor

Create a ruler under the line under mouse cursor.

1.147 ruler_under_selected_point

1.148 save_scratchpad

Save the current scratchpad state to a file. This file can be loaded later using `load_scratchpad`.

1.149 scan_new_files

1.150 screenshot

Take a screenshot from sioyek window and save it to the given path. This is mainly used for testing purposes.

1.151 screen_down, screen_up

Move one screen up or down. The amount of movement can be configured using `move_screen_ratio`.

1.152 search, chapter_search

Search the contents of current document. You can use `next_item` and `previous_item` to navigate search results. You can optionally specify a page range using the following syntax: `<begin_page,end_page>query`. The

`chapter_search` command automatically fills the page range with the current chapter's page range.

1.153 search_all_indexed_documents

Perform a fulltext search in all documents indexed by `create_fulltext_index_for_current_document` or `automatically_index_documents_for_fulltext_search`.

1.154 select_current_search_match

Selects the current highlighted search result.

1.155 select_freehand_drawings

Select the freehand drawings in the selected rectangle. The selected drawings can be moved by dragging the selection rectangle.

1.156 select_rect

1.157 select_ruler_text

Select the current line highlighted by ruler, you can use the up and down movement commands to move the selection and `toggle_line_select_cursor` to toggle between begin and end of the selection. Exit the selection mode by pressing escape.

1.158 semantic_search

Performs a semantic search on the current document. This method produces a relatively lower quality result but costs a lot less than `semantic_search_extractive`.

Explanation of how this method works for more technical users: This method simply splits the document into paragraph-sized chunks and embeds each chunk using an embedding model. Then it finds the chunks with most similarity to the query.

1.159 semantic_search_extractive

Performs a semantic search on the current document. This method produces a relatively higher quality result than `semantic_search` but is more expensive.

1.160 set_freehand_alpha

commands: toggle_freehand_drawing_mode toggle_pen_drawing_mode set_freehand_type

Set the alpha transparency of freehand drawings.

1.161 set_freehand_thickness

commands: toggle_freehand_drawing_mode toggle_pen_drawing_mode

Set the thickness of freehand drawings. The initial thickness value is 1.

1.162 set_freehand_type

commands: toggle_freehand_drawing_mode toggle_pen_drawing_mode

Set the color symbol of freehand drawings. This is a symbol command which takes a single character as input. The color of drawing with symbol `s` will be the same color as highlights with symbol `s`.

1.163 set_mark

Set a mark in the current location so we can return to it later using the `goto_mark` command. After executing `set_mark` command, sioyek will wait for you to press a symbol, which can be a lowercase or uppercase letter. Lowercase marks are local to the current file but uppercase marks are global. If you press a symbol that is already used as a mark, the previous mark will be overwritten. You can later return to the mark by executing `goto_mark` command with the same symbol.

1.164 set_page_offset

1.165 set_select_highlight_type

Set the default highlight type. This is mainly used with `toggle_select_highlight` and `add_highlight_with_current_type`.

1.166 set_status_string, clear_status_string

Set the message in sioyek status bar. This message will be displayed until it is cleared using `clear_status_string`. This is mainly useful for scripts and plugins to display messages to the user.

1.167 set_view_state

view state to the state described by the given input text. The text format is : `{offset_x} {offset_y} {zoom_level} {push_state}`. For example: `0 1000 3 1` means we want to move to location (0, 1000) in the document with `zoom_level=3` and we want to push the previous state into history stack.

This command in mainly useful for scripting and it is probably not directly useful for end-users.

1.168 show_context_menu

Show a context menu below the mouse cursor. The commands shown in the menu can be configured using the following configs (depending on the object under mouse cursor):

- `context_menu_items`
- `context_menu_items_for_links`
- `context_menu_items_for_selected_text`
- `context_menu_items_for_highlights`
- `context_menu_items_for_bookmarks`
- `context_menu_items_for_overview`

1.169 show_custom_context_menu

1.170 show_custom_options

|-separated list of options, displays the options to the user and returns the result. This is used for scripting and is not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = sioyek.Sioyek('')
result = s.show_custom_options('one|two|three')
s.set_status_string(f'You chose {result}')
```

1.171 show_text_prompt

a text prompt to the user and returns the entered text. This is used for scripting and is not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = sioyek.Sioyek('')
result = s.show_text_prompt('Enter a string:')
s.set_status_string(f'You entered {result}')
```

1.172 show_touch_draw_controls

Show the freehand drawing menu for touch devices.

1.173 show_touch_highlight_type_select

Show the highlight type selector for touch devices.

1.174 show_touch_main_menu

Show the main menu for touch devices.

1.175 `show_touch_page_select`

Show the page selector for touch devices.

1.176 `show_touch_settings_menu`

Show the settings menu for touch devices.

1.177 `smart_jump_under_cursor`

Go to the location of reference under mouse cursor. This works even when the document doesn't have links.

1.178 `move_down_smooth, move_up_smooth`

Basic movement in the current document. Holding these commands results in a smooth continuous movement in the document unlike `move_down` and `move_up`.

1.179 `start_mobile_text_selection_at_point`

1.180 `start_reading, stop_reading`

Start reading from the current line highlighted by ruler using the local text to speech engine.

1.181 `start_reading_high_quality`

Start reading from the current line highlighted by ruler using the sioyek servers' high quality neural text to speech engine.

1.182 `synchronize`

Synchronize a desynchronized file with the server. On rare occasions files might become desynchronized where sioyek can not automatically decide whether to upload annotations to sioyek servers or not. For example suppose you have two copies of the same file on two different devices and with different annotations, and then you upload one of them to sioyek servers. When the other file is opened on the other device, sioyek will not automatically decide to upload the annotations to the server (because the user might not want that, e.g. perhaps those annotations are very sensitive data that you do not want uploaded). In such situations the other file is in desynchronized state and you can use this command to synchronize it with the server. This command will upload the annotations to the server if they are not already there.

1.183 `synctex_forward_search`

Given a latex file path and line number, performs a forward search to the corresponding location in the PDF document.

1.184 synctex_under_cursor

Perform a synctex search under mouse cursor (this works regardless of whether we are in synctex mode or not). The search command is configured using `inverse_search_command`.

1.185 synctex_under_ruler

Perform a synctex search to the location of the line highlighted by ruler.

1.186 sync_current_file_location

Upload the current file location to sioyek servers (can later be resumed on other devices with @(resume_to_server) command). This command is usually performed automatically (only on files that have been uploaded to sioyek servers) but can be manually triggered with this command.

1.187 test_command, export_config_names, open_selected_url, toggle_smooth_scroll_mode, export_python_api, print_undocumented_commands, print_non_default_configs, export_default_config_file, unregister_url_handler, toggle_one_window, register_url_handler, export_command_names, goto_begining, send_symbol, open_all_docs, print_undocumented_configs, toggle_show_last_command, move_selected_bookmark, type_text

1.188 toggle_text_mark, move_text_mark_forward, move_text_mark_backward, move_text_mark_forward_word, move_text_mark_backward_word, move_text_mark_down, move_text_mark_up

These commands are used to manipulate the text selection using keyboard. `move_{forward/backward}` commands move the cursor one character forward/backward and `move_{forward/backward}_word` commands move the cursor one word forward/backward, and `move_{down/up}` commands move the cursor one line down/up. `toggle_text_mark` toggles the position of cursor between the start and end of text selection.

1.189 toggle_custom_color

Toggle between light and custom color schemes. The background and text color of custom color scheme can be configured using `custom_text_color` and `custom_background_color`.

1.190 toggle_dark_mode

Toggle between light and dark color schemes.

1.191 `toggle_drawing_mask`

This is a symbol command which given a symbol `s`, toggles the visibility of freehand drawings with type `s`.

1.192 `toggle_fastread`

1.193 `toggle_freehand_drawing_mode`

Toggle freehand drawing mode. In this mode you can use the mouse to draw on the document.

1.194 `toggle_fullscreen`

Toggle fullscreen mode.

1.195 `toggle_highlight_links`

Highlight the PDF links.

1.196 `toggle_horizontal_scroll_lock`

Locks horizontal scrolling. This is useful for touchpad or touch devices when you want to always keep the document centered in the screen.

1.197 `toggle_line_select_cursor`

Toggle between begin and end of line text selection by `select_ruler_text`.

1.198 `toggle_mouse_drag_mode`

Toggle mouse drag mode. When enabled, you can drag the mouse to move the document (instead of text selection).

1.199 `toggle_pdf_annotations`

Toggles the visibility of PDF annotations (these are different from sioyek annotations, the PDF annotations are embedded in the PDF file itself).

1.200 `toggle_pen_drawing_mode`

Toggle pen drawing mode. In this mode you can use the stylus to draw on the document.

1.201 `toggle_presentation_mode, turn_on_presentation_mode`

Toggle/turn on presentation mode, in this mode we fit each slide to the entire page and movement commands move to the next/previous slide.

1.202 `toggle_reading`

1.203 `toggle_rect_hints`

Shows the locations of touch mode shortcut rectangles and the commands that they perform.

1.204 `toggle_ruler_scroll_mode, toggle_visual_scroll`

Toggles ruler scroll mode. In this mode mouse wheel moves the ruler instead of scrolling the document.

1.205 `toggle_scratchpad_mode`

Opens a scratchpad, you can use this scratchpad to draw or do calculations (this is mainly useful for touch/stylus devices).

1.206 `toggle_scrollbar`

Toggle the scrollbar.

1.207 `toggle_select_highlight`

Toggle select highlight mode. In this mode all selected text will automatically be highlighted with the type set using `set_select_highlight_type`.

1.208 `toggle_statusbar`

Toggle the statusbar.

1.209 `toggle_synctex, turn_on_synctex`

Toggle/turn on synctex mode. In this mode, right clicking on the PDF file performs an inverse search from the corresponding location in the source latex file (using the configured `inverse_search_command`).

1.210 `toggle_titlebar`

Toggle the titlebar of the sioyek window.

1.211 `toggle_two_page_mode`

Toggles between two-page mode and single-page mode.

1.212 toggle_typing_mode

1.213 toggle_window_configuration

Toggle helper window. The helper window displays the portal destination of the closest portal source to current location.

1.214 turn_on_all_drawings, turn_off_all_drawings

Turn all drawings on/off.

1.215 undo_drawing

Undo the last drawn freehand drawing.

1.216 upload_current_file

Upload the current file into sioyek servers.

1.217 wait

Wait for the given duration (in miliseconds). This is mainly used for testing purposes.

1.218 wait_for_renders_to_finish, wait_for_search_to_finish, wait_for_indexing_to_finish, wait_for_downloads_to_finish

Wait for all pending renders/searches/indexing to finish. This is mainly used for testing and scripting (for example we may want to wait for renders to finish before we compare a screenshot to the saved screenshot).

1.219 write_annotations_file

Write the annotations of current file into an annotations file next to the current file. The annotations file will have the same name as the current file with a `sioyek.annotations` extension. This is useful when you want to share the annotations with others or move them to another computer.

Alternatively you can set the `annotations_directory` config to a directory path and the annotations file will be written there instead of next to the current file.

1.220 zoom_in, zoom_out, zoom_in_cursor, zoom_out_cursor

Zoom in/out in the current document. The `zoom_in_cursor` and `zoom_out_cursor` commands zoom in/out around the cursor position while the `zoom_in` and `zoom_out` commands zoom in/out around the center of the screen.

1.221 zoom_in_overview, zoom_out_overview

Zoom in/out in the overview window.

2 Configs

2.1 adjust_annotation_colors_for_dark_mode

Automatically adjust annotation colors to be more appropriate in dark mode.

2.2 align_link_dst_to_top

Normally when jumping to links, we align the middle of the screen with the link destination. If this option is set we align the top of the screen instead.

2.3 allow_horizontal_drag_when_document_is_small

Normally when the document is smaller than screen width, we center in the screen and disallow horizontal mouse dragging to keep the document centered. If this option is set, then we allow the document to be dragged even when it is smaller than the screen width.

2.4 allow_main_view_scroll_while_in_overview

Allow the main document to be scrolled when overview is opened (otherwise we use scrolling outside the overview while the overview window is opened to move between possible overview targets).

2.5 annotations_directory

Normally sioyek keeps some annotations files next to the pdf files (e.g. the freehand drawings file). If you don't want this you can specify the `annotations_directory` and then sioyek keeps the annotations files in that directory.

2.6 autocenter_ruler

Always center the document on the ruler when moving the ruler.

2.7 automatically_download_matching_paper_name

If this config is not set, when downloading papers, we search the paper name and show the user a list of matching papers and download it when the user selects one of the options. If this option is set and one of the found paper matches the query title exactly, we no longer show the user a list and automatically download the matching paper.

2.8 automatically_index_documents_for_fulltext_search

Automatically index opened documents for fulltext search.

2.9 automatically_update_checksum_when_document_is_changed

When the document is changed (e.g. a latex document being edited) automatically update the checksum.

2.10 automatically_upload_portal_destination_for_synced_documents

When uploading a document to sioyek servers, also upload the portal destinations for portals in that document.

2.11 auto_login_on_startup

Automatically login to sioyek servers on startup (if previous credentials are available).

2.12 auto_rename_downloaded_papers

If set, sioyek renames the downloaded papers to an automatically determined file name (e.g. instead of a cryptic name like `23434.234.pdf` it will be renamed to something like `some_paper_title.pdf`).

2.13 background_bookmarks_pixel_budget

Maximum number of pixels allocated to cached freetext bookmarks.

2.14 background_color, custom_color_mode_empty_background_color, dark_mode_background_color

The empty background color in light/dark/custom color modes.

2.15 case_sensitive_search

If set, we match the search queries in a case-sensitive manner.

2.16 check_for_updates_on_startup

Check for software updates when sioyek starts.

2.17 shift_click_command, control_click_command, command_click_command, hold_middle_click_command, tablet_pen_click_command, tablet_pen_double_click_command, right_click_command, middle_click_command, shift_middle_click_command, control_middle_click_command, command_middle_click_command, alt_middle_click_command, shift_right_click_command, control_right_click_command, command_right_click_command, alt_click_command, alt_right_click_command

@concept(macro) commands to run when the corresponding button is clicked (while possibly holding modifier keys). Example:

```
alt_click_command toggle_dark_mode;toggle_scrollbar;set_status_string('hi there')
```

2.18 collapsed_toc

Open the table of contents in collapsed state by default.

2.19 context_menu_items, context_menu_items_for_links, context_menu_items_for_selected_text, context_menu_items_for_highlights context_menu_items_for_bookmarks, context_menu_items_for_overview

Items in context menu to show when `show_context_menu` is executed and the cursor is on the object specific to the option (`context_menu_items` is for the case where no special object is under the cursor).

If `right_click_context_menu` is set, you can open this all these menus (except for `context_menu_items`) by right-clicking on objects in the page.

2.20 create_table_of_contents_if_not_exists

If the document doesn't have a table of contents, try to automatically generate one (this is a heuristic and doesn't work perfectly all the time).

2.21 custom_text_color, custom_background_color

Text and background colors in custom color mode.

2.22 dark_mode_contrast

The color contrast in dark mode.

2.23 default_open_file_path

The default root path when opening files.

2.24 `documentation_font_size`

Font size of documentation.

2.25 `document_location_mismatch_strategy`

Specifies what to do when there is a mistmatch between a local document and the last location uploaded to sioyek servers. Possible values are:

- `local`: remain in the local position
- `server`: move to the server position
- `ask`: prompt the user to choose a position
- `show_button`: show a resume button in sioyek statusbar

2.26 `dont_center_if_synctex_rect_is_visible`

When performing a synctex search, if the target is already visible on the screen we don't move the document to center on the target.

2.27 `epub_css`

CSS to apply to epub documents.

2.28 `epub_width, epub_height, epub_font_size`

Configure the appearance of epub documents.

2.29 `exact_highlight_select`

When adding the selected highlight, add the exact highlighted text (otherwise we highlight an entire word event when a part of it is selected).

2.30 `external_text_editor_command`

The command line program to use when running `open_external_text_editor` command. In this config, `%{file}` expands to the file that should be opened. For example:

```
external_text_editor_command nvim "%{file}"
```

2.31 `extract_table_prompt`

The plain english prompt to use when extracting table data using a large language model with `extract_table` command.

Example:

```
extract_table_prompt Extract the table in this image into a markdown table. Take your time a
```

2.32 `fill_textbar_with_selected_text`

When opening the textbar (e.g. when executing `search` or any other command that requires text input) automatically fill the input with the selected text.

2.33 `fit_to_page_width_ratio`

The screen width ratio when using `fit_to_page_width_ratio` command.

2.34 `flat_toc`

Show the table of contents as a flat list instead of a hierarchial tree. This can improve the performance on documents with extremely large table of contents.

2.35 `font_size`

The font size for UI menus.

2.36 `freetext_bookmark_color`

Text color to use when adding new freetext bookmarks.

2.37 `freetext_bookmark_font_size`

Font size to use when adding new freetext bookmarks.

2.38 `fuzzy_searching`

(Deprecated) Whether we should employ fuzzy searching in menus. As we are using a fuzzy algorithm by default in more and more menus this option is becoming less relevant as time goes on.

2.39 `gamma`

The gamma value, each pixel value `p` will be replace with `p^gamma`. Higher gamma values make fonts look thicker and lower gamma values make them look thinner.

2.40 `hide_overlapping_link_labels`

When highlighting links in a document with overlapping links, show the label only for one of the overlapping links (avoids clutter in some malformed documents).

2.41 `highlight_color_[a-z]`

Specifies the color for each of highlight types.

2.42 highlight_links

Whether we should highlight PDF links.

2.43 highlight_middle_click

If set, middle clicking on selected text highlights it with the current highlight type.

2.44 hover_overview

Open the overview page when mouse cursor hovers over a link (I don't recommend using this config because it might not work well with other sioyek features, just right click on the link to create the overview).

2.45 ignore_scroll_events

Ignore scroll events (e.g. useful to avoid moving in presentation mode when accidentally touching the touchpad).

2.46 ignore_whitespace_in_presentation_mode

Ignore whitespace when fitting pages to screen in presentation mode.

2.47 incremental_search

If this is set, then we perform searches as user is typing the search query.

2.48 initial_snapped_dragging

If set, when dragging the document (e.g. in touch mode) we ignore very small horizontal scrolls because when the user is trying to scroll vertically they probably will also do some horizontal scrollling inadvertently. So we start the dragging in a "snapped" state (meaning we are snapped to the original horizontal position) and only unspan when the user moves horizontally past a threshold.

2.49 inverse_search_command

The command line program to open the corresponding file when peforming a synctex inverse search. `%1` will expand to the path of TeX file and `%2` will exapnd to the line number.

For example here is how to configure it for vscode on windows:

```
inverse_search_command      "C:\path\to\Code.exe" -r -g "%1":%2
```

2.50 inverted_horizontal_scrolling

Invert the horizontal scrolling when using touchpad.

2.51 invert_selected_text

Invert the selected text to highlight it.

2.52 keyboard_point_selection

If set, when executing commands that require a point on the screen to be selected, we show a list of labels on the screen and allow the user to select the point by typing the label using keyboard.

2.53 keyboard_select_background_color, keyboard_select_text_color, keyboard_selected_tag_background_color, keyboard_selected_tag_text_col

The color of the tags displayed for keyboard commands.

2.54 keyboard_select_font_size

The font size of the tags displayed for keyboard commands.

2.55 linear_filter

Perform linear texture filtering instead of nearest neighbor (should not be necessary unless you use non-interger render scales).

2.56 link_highlight_color

Highlight color to use when highlighting links.

2.57 max_created_toc_size

The maximum size of automatically generated table of contents.

2.58 menu_matched_search_highlight

The CSS style used to highlight matched search results in menus.

2.59 menu_screen_width_ratio, menu_screen_height_ratio

The ratio of screen width/height to use for menus.

2.60 middle_click_search_engine, shift_middle_click_search_engine

When middle clicking on a paper name, we will search for it in the engine (as configured in `search_url_[a-z]`) set here.

For example:

```
search_url_s https://scholar.google.com/scholar?q=
middle_click_search_engine s
```

means that we will search the paper name in google scholar when user middle clicks on a paper name.

2.61 move_screen_ratio

The ratio of screen height to move when executing `screen_down` and `screen_up`.

2.62 numeric_tags

When performing `keyboard_` commands that require a point to be selected, we associate a tag with each possible target. If this option is set, the tags only use numerical values instead of alphabetical values.

2.63 num_cached_pages

Total number of cached rendered pages. Higher values may reduce flickering and power consumption (because pages have to be re-rendered less) at the cost of increased memory usage.

2.64 num_prerendered_next_slides, num_prerendered_prev_slides

Number of next/previous pages to prerender in presentation mode.

2.65 num_two_page_columns

Changes the number of page columns in "two" page mode.

2.66 overview_reference_highlight_color

Highlight color to use when highlighting the automatically detected overview paper name.

2.67 page_separator_width, page_separator_color

Color and size of separator between pages.

2.68 page_space_x, page_space_y

Spacing between pages in two page mode.

2.69 papers_folder_path

Path of the directory where downloaded papers should move to.

2.70 paper_download_should_create_portal

When downloading papers, create a portal from the source document to the downloaded document. Otherwise (if this config is 0) we open the downloaded document in a new window.

2.71 paper_download_should_detect_paper_name

When downloading papers, create a portal from the source document to the downloaded document. Otherwise (if this config is 0) we open the downloaded document in a new window.

2.72 prerendered_page_count

Number of pages to pre-render.

2.73 prerender_next_page_presentation

Prerender the next page in presentation mode (avoids flickering when moving to the next slide).

2.74 preserve_image_colors_in_dark_mode, inverted_preserved_image_colors

Preserve original image colors in dark mode and custom color mode. If `inverted_preserved_image_colors` is set, then we invert the original image colors in custom color mode.

2.75 question_bookmark_background_color, question_bookmark_text_color

The background and text color of question bookmarks (the bookmarks starting with `?`, see `add_freetext_bookmark` for more information).

2.76 real_page_separation

The page separator configured using `page_separator_width` doesn't actually separate the pages, it is simply a box drawn to distinguish the pages. If `real_page_separation` is set, then we actually move the pages to separate them (technically it is less efficient than the other method which is why it is not the default but it shouldn't matter in most cases). Also note that when this option is set, the distance between pages is not configured with `page_separator_width` rather it uses `page_space_y`.

2.77 reload_interval_miliseconds

We check the document for changes (e.g. a latex document might be changed from external sources) every `reload_interval_miliseconds`.

2.78 `render_freetext_borders`

Render the borders around freetext bookmarks.

2.79 `render_pdf_annotations`

If set to 0, we don't render PDF annotations (by PDF annotations I mean the native PDF annotations embedded in the PDF file and not the sioyek annotations).

2.80 `resize_command`

@concept(macro) commands to run when sioyek window is resized. Example:

```
resize_command fit_to_page_width_smart
```

2.81 `right_click_context_menu`

Show a context menu when user right clicks on annotations/overview. The commands displayed in this context menu can be configured using @conf(context_menu_items*) commands.

2.82 `ruler_auto_move_threshold_distance`

In touch mode, you are able to move the ruler by pressing on the move down rect and then moving the cursor, each time the cursor moves `ruler_auto_move_threshold_distance` we move to the next line.

2.83 `ruler_color`

Ruler color.

2.84 `ruler_display_mode`

Specifies how the ruler should be rendered. The possible values are:

- `box`: draw a box around selected line
- `slit`: draw a shadow on everything except the selected line
- `underline`: draw a line under the selected line
- `highlight_below`: highlight the entire screen area below the line

2.85 `ruler_marker_color`

The ruler marker color to highlight the next left side of the screen when using `move_ruler_next`.

2.86 ruler_next_page_end_pos, ruler_next_page_begin_pos

`ruler_next_page_end_pos` determines when we should move to the next page when using the ruler and when we do so, `ruler_next_page_begin_pos` determines where the new location of the ruler should be in the screen.

`ruler_next_page_begin_pos` is relative to the center of the screen and `ruler_next_page_end_pos` is relative to the bottom of the screen. For example, `ruler_next_page_begin_pos`=1 means we move one unit (each unit is half screen height) up from the middle of the screen which means we move to the top of the screen when moving to the next page.

2.87 ruler_padding, ruler_x_padding

Ruler padding when using `slit` ruler display mode.

2.88 ruler_pixel_width

Ruler thickness when `ruler_display_mode` is set to `underline`.

2.89 ruler_slit_color

Ruler color when `ruler_display_mode` is set to `slit`.

2.90 save_externally_edited_text_on_focus

If this option is set, when editing text using `open_external_text_editor` command, we accept the externally edited text when the sioyek window gains focus again (otherwise the user has to manually press enter to accept the input).

2.91 scrollview_sensitivity

The relative sensitivity when scrolling the overview window.

2.92 search_highlight_color

Highligh color of search matches.

2.93 search_url_[a-z]

Search url for `external_search` command. After executing external search, the user can enter the symbol corresponding to the configured search engine to perform the search using that engine.

For example if we have the following in `prefs_user.config`:

```
search_url_g https://www.google.com/search?q=
search_url_s https://scholar.google.com/scholar?q=
```

Then executing `external_search` followed by `s` will search google and if it is followed by `s` it will search google scholar.

2.94 server_and_local_document_mismatch_threshold

When the location of server and document do not match (for example when the user has moved the document to another location in another device) if the distance is greater than this threshold a resume button will be displayed in the statusbar which allows the user to resume to the server location.

2.95 shared_database_path

Path of shared database to use, if not set we use the default path.

2.96 should_highlight_unselected_search

Whether we should highlight the found search results that are not the current search result.

2.97 should_launch_new_window

When opening a new file from command line, use a new sioyek window if one already exists.

2.98 should_load_tutorial_when_no_other_file

When there is no other file to open (e.g. due to sioyek being opened for the first time) show the sioyek tutorial.

2.99 should_warn_about_user_key_override

Print a warning message in console when a key override is detected in `keys_user.config`.

2.100 show_most_recent_commands_first

When opening the command menu show the most recent commands executed in the current session first.

2.101 show_reference_overview_highlights

Highlight the reference paper name in overview window (this is the automatically detected paper name which will be downloaded with `download_overview_paper` command).

2.102 `single_click_selects_words`

Normally when selecting text using mouse, we select individual characters, unless the user has double clicked to initiate the selection, in which case we select entire words instead of individual characters.

If `single_click_selects_words` is set, then we select words even when user uses single-click to initiate text selection.

2.103 `sliced_rendering`

Normally we render entire pages as a whole. This can cause problems on high zoom levels on low-memory devices becasue a huge chunk of memory with the correct size might not be available. If `sliced_rendering` is set, instead of rendering pages as a whole, we slice the pages into multiple strips and render each strip.

2.104 `smartcase_search`

If set, we match the search queries in a case-insensitive manner if all the characters in the query is lowercase and otherwise we perform a case-sensitive search.

2.105 `smooth_move_max_velocity`

The speed of `move_*_smooth` commands.

2.106 `sort_bookmarks_by_location`

Sort bookmarks by location (instead of creation date).

2.107 `startup_commands`

@concept(macro) commands to run then sioyek starts up. For example:

```
startup_commands toggle_dark_mode;toggle_scrollbar;set_status_string(hi there)
```

Will set the color scheme to dark mode and enable scrollbar and show a message in sioyek statusbar when sioyek starts up.

2.108 `status_bar_color, status_bar_text_color`

Text and background colors of statusbar.

2.109 `status_bar_font_size`

Font size of the status bar.

2.110 status_bar_format, right_status_bar_format, status_*_command

The items and format to show in the statusbar. The default value is:

```
[ %{current_page} / %{num_pages} ]%{chapter_name}%{search_results}%{search_progress}%{link_s
```

The `right_status_bar_format` is similar, but determines what to display on right-aligned statusbar.

Here is what each of the `%{}` variables expand to: - `%{current_page}` expands to the current page number - `%{current_page_label}` expands to the the label of the current page (might be different from `current_page` for example some documents have pages labeled with roman numerals, e.g. XII) - `%{num_pages}` expands to the total number of pages in current document - `%{chapter_name}` expands to the name of current chapter - `%{document_name}` expands to the file name of current document - `%{auto_name}` expands to automatically detected document name - `%{search_results}` expands to the search results (if there is a search active) - `%{search_progress}` expands to the current search progress (if there is one in progress) - `%{link_status}` specifies whether we are linking (that is the source of a `portal` has been set and we are waiting for the destination) - `%{waiting_for_symbol}` specifies if a command is expecting a symbol to be entered - `%{indexing}` specifies if the current document is currently being indexed - `%{preview_index}` if there are more than one possible overviews available for the overview window, this option shows how many there are and what is the current index - `%{synctex}` displays if we are in synctex mode (`toggle_synctex`) - `%{drag}` displays if we are in mouse drag mode (`toggle_mouse_drag_mode`) - `%{presentation}` displays if we are in presentation mode (`toggle_presentation_mode`) - `%{visual_scroll}` displays if we are in ruler scorll mode (`toggle_ruler_scroll_mode`) - `%{locked_scroll}` displays if we have locked horizontal scrolling (`toggle_horizontal_scroll_lock`) - `%{highlight}` displays information about the current highlight state (`set_select_highlight_type`) - `%{freehand_drawing}` displays if we are in freehand drawing mode (`toggle_freehand_drawing_mode`) - `%{rect_select}` displays if a command requires a rectangle to be selected - `%{point_select}` displays if a command requires a point to be selected - `%{custom_message}` user message that can be set using `set_status_string` - `%{download}` displays if we are currently downloading a paper - `%{download_button}` a button that displays when the current overview is a reference to a paper, clickin on this button downloads the paper - `%{closest_bookmark}` displays the closest bookmark to current location - `%{closest_portal}` displays the closest portal to the current location - `%{selected_highlight}` displays the comment of the selected highlight - `%{mode_string}` displays the current mode string (this can be useful when defining @concept(macro)s) - `%{network_status}` displays the current network status - `%{tts_status}` displays the current text to speech status - `%{tts_rate}` displays the current text to speech speed - `%{custom_message_a}` to `%{custom_message_d}` expands to a custom message

which can be set using `status_custom_message_[a-d]`

Note that clicking on many of these items performs a relevant command. For example clicking on the text expanded from `${current_page}` shows a page-selection widget or clicking on `%{chapter_name}` opens the table of contents. The exact command executed when some part of the statusbar is clicked can be configured using `status_*_command` config options where `*` can be any of the options described above. For example if we have the following in the `prefs_user.config` file:

```
status_num_pages_command toggle_dark_mode
```

then clicking on the number of pages in the statusbar toggles dark mode.

2.111 status_custom_message_[a-d]

Show custom messages which can be shown in statusbar if `%{custom_message_a}` to `%{custom_message_d}` is added to `status_bar_format`. When the message is clicked, the command configured in `status_custom_message_[a-d]_command` will be run.

2.112 status_font

Font face to use for menus.

2.113 strike_line_width

The strike width when adding strike highlights (highlights with type `_`).

2.114 super_fast_search

If set, we index the document so that searches can be performed instantaneously. Some other sioyek features work only if this option is enabled so I recommend to keep it enabled (the extra memory requirement due to this option being enabled is extremely small).

2.115 synctex_highlght_timeout

Highlight color to use when highlighting synctex search results. This only applies when `use_ruler_to_highlight_synctex_line` is set to 0, otherwise we use the ruler to highlight the line.

2.116 synctex_highlight_color

Highlight color to use when highlighting synctex search results. This only applies when `use_ruler_to_highlight_synctex_line` is set to 0, otherwise we use the ruler to highlight the line.

2.117 `synctex_highlight_timeout`

Duration (in seconds) to highlight the synctex line. If the duration is -1, the highlight will stay indefinitely.

2.118 `table_extract_behaviour`

What to do with extracted table. The possible values are: - `bookmark`: Create a freetext bookmark with the extracted table - `copy`: Copy the extracted table into clipboard

2.119 `tag_font_face`

Font face to use for keyboard tags.

2.120 `text_highlight_color`

The highlight color of selected text (e.g. when user selects text using mouse or using commands like `keyboard_select`).

2.121 `toc_jump_align_top`

When jumping to a table of contents entry, align the top of the screen with the target location (instead of center of the screen).

2.122 `touchpad_sensitivity`

Relative scrolling sensitivity when using touchpad or mouse wheel, this is a multiplier that modifies `vertical_move_amount` so the overal move amount when using touchpad or mouse wheel is `touchpad_sensitivity * vertical_move_amount`.

2.123 `touch_mode`

This config is suitable for touch devices, if set, many behaviours of sioyek change to better support touch devices. For exmaple dragging on the screen moves the document instead of selecting text and menus are now optimized for touch devices.

2.124 back_rect_tap_command, back_rect_hold_command, forward_rect_tap_command, forward_rect_hold_command, middle_left_rect_tap_command, middle_left_rect_hold_command, middle_right_rect_tap_command, middle_right_rect_hold_command, ruler_next_tap_command, ruler_next_hold_command, ruler_prev_tap_command, ruler_prev_hold_command

@concept(macro) commands to run when the corresponding rectangle is tapped or held (only works in touch mode). You can view the location of these rectangles by executing executing `toggle_rect_hints`.

2.125 tts_rate

The text to speech speaking speed when using text to speech commands.

2.126 ui_font

Font face to use for menus.

2.127 portrait_back_ui_rect, portrait_forward_ui_rect, landscape_back_ui_rect, landscape_forward_ui_rect, portrait_visual_mark_next, portrait_visual_mark_prev, landscape_visual_mark_next, landscape_visual_mark_prev, landscape_middle_right_rect, portrait_middle_right_rect, landscape_middle_left_rect, portrait_middle_left_rect

Configures the rectangles in touch mode. If the user taps on these rectangles, we execute the corresponding command as configured in `touch_rect_commands`.

2.128 ui_text_color, ui_background_color, ui_selected_text_color, ui_selected_background_color

Text and background colors of ui menus.

2.129 unselected_search_highlight_color

The highlight color to highlight unselected search matches when `should_highlight_unselected_search` is set.

2.130 use_ruler_to_highlight_synctex_line

Use the ruler to highlight the synctex search result (instead of highlighting it with a color).

2.131 `use_system_theme, use_custom_color_as_dark_system_theme`

Try to use system theme for light/dark modes (might not work in some operating systems). If `use_custom_color_as_dark_system_theme` is set, then we use the custom color mode instead of dark mode when system theme is set to dark.

2.132 `vertical_move_amount, horizontal_move_amount`

The amount to move when executing movement commands (including mouse wheel).

2.133 `wheel_zoom_in_cursor`

When performing zoom using control+mouse wheel, zoom on the mouse cursor instead of the center of the screen.

2.134 `main_window_size, helper_window_size, main_window_move, helper_window_move, single_main_window_size, single_main_window_move, overview_size, overview_offset`

Default size and offset of sioyek windows. the `single_*` is used when only the main sioyek window is visible (no helper window) otherwise we use the other values.

2.135 `zoom_inc_factor`

The amount to multiply/divide the zoom level when executing zoom commands. For example, if the current zoom level is 2 and `zoom_inc_factor` is 1.5, then after executing `zoom_in`, the zoom level will be `2 * 1.5 = 3`.