Sioyek Documentation

Contents

1 Commands **10**

1.1 add_annot_to_highlight 10
1.2 add_bookmark 11
1.3 add_freetext_bookmark, add_freetext_bookmark_auto . . . 11
1.4 add_highlight 12
1.5 add_highlight_with_current_type 13
1.6 add_keybind 13
1.7 add_marked_bookmark 13
1.8 add_marked_data, remove_marked_data, export_marked_data, undo_marked_data, goto_random_page 13
1.9 cancel_all_downloads 13
1.10 change_highlight 14
1.11 citers 14
1.12 clear_current_page_drawings, clear_current_document_drawings 14
1.13 clear_scratchpad 14
1.14 close_overview 14
1.15 close_window 15
1.16 command 15
1.17 command_palette 15
1.18 control_menu 15
1.19 convert_to_latex 16
1.20 copy 17
1.21 copy_drawings_from_scratchpad 17
1.22 copy_link 17
1.23 copy_screenshot_to_clipboard 17
1.24 copy_screenshot_to_scratchpad 17
1.25 copy_window_size_config 17
1.26 create_fulltext_index_for_current_document 17
1.27 create_visible_portal 18
1.28 delete_all_pdf_annotations, delete_intersecting_pdf_annotations 18
1.29 delete_current_file_from_server 18
1.30 delete_document_from_fulltext_search_index 18

1.31 delete_freehand_drawings 18
1.32 delete_highlight_under_cursor 19
1.33 delete_portal, delete_bookmark, delete_highlight 19
1.34 delete_visible_bookmark 19
1.35 documentation_search 19
1.36 donate 19
1.37 download_paper_with_url, download_clipboard_url 19
1.38 download_link 20
1.39 download_overview_paper, download_overview_paper_no_prompt 20
1.40 download_paper_under_cursor 20
1.41 download_paper_with_name 20
1.42 download_unsynced_files 21
1.43 edit_portal 21
1.44 edit_selected_bookmark 21
1.45 edit_selected_highlight 21
1.46 edit_visible_bookmark 21
1.47 embed_annotations 22
1.48 embed_selected_annotation 22
1.49 enter_password 22
1.50 enter_visual_mark_mode 22
1.51 escape 22
1.52 execute, execute_shell_command 22
1.53 execute_macro 23
1.54 exit_ruler_mode, close_visual_mark 23
1.55 export 23
1.56 external_search 23
1.57 extract_table, extract_table_with_prompt 24
1.58 find_references 24
1.59 fit_epub_to_window 24
1.60 fit_to_overview_width 24
1.61 fit_to_page_width_ratio 24
1.62 fit_to_page_width, fit_to_page_height,
fit_to_page_width_smart, fit_to_page_height_smart,
fit_to_page_smart 25
1.63 focus_text 25
1.64 force_download_annotations 25
1.65 framebuffer_screenshot 25
1.66 fulltext_search_current_document 25
1.67 fuzzy_search 25
1.68 generic_delete 26
1.69 generic_select 26
1.70 get_annotations_json 26
1.71 get_config_no_dialog 26
1.72 get_config_value 27
1.73 get_mode_string 27
1.74 get_overview_paper_name 27

1.75 get_paper_name 27
1.76 get_state_json 27
1.77 goto_beginning, goto_end 28
1.78 goto_bookmark, goto_bookmark_g 28
1.79 goto_definition 28
1.80 goto_highlight, goto_highlight_g 29
1.81 goto_left, goto_right, goto_left_smart, goto_right_smart 29
1.82 goto_mark 29
1.83 goto_next_highlight, goto_prev_highlight 29
1.84 goto_next_highlight_of_type, goto_prev_highlight_of_type 29
1.85 goto_overview 30
1.86 goto_page_with_label 30
1.87 goto_page_with_page_number 30
1.88 goto_portal 30
1.89 goto_portal_list 30
1.90 goto_selected_text 30
1.91 goto_tab 30
1.92 goto_toc 31
1.93 goto_top_of_page, goto_bottom_of_page 31
1.94 goto_window 31
1.95 import 31
1.96 import_annotations 31
1.97 import_local_database, import_shared_database 31
1.98 increase_freetext_font_size, decrease_freetext_font_size 31
1.99 increase_tts_rate, decrease_tts_rate 32
1.100 keyboard_overview 32
1.101 keyboard_select 32
1.102 keyboard_select_line 32
1.103 keyboard_smart_jump 33
1.104 keys 33
1.105 keys_user 33
1.106 keys_user_all 33
1.107 load_annotations_file, import_annotations_file_sync_deleted 33
1.108 load_scratchpad 34
1.109 login 34
1.110 login_using_access_token 34
1.111 logout 34
1.112 maximize 34
1.113 move_left, move_right, move_down, move_up 34
1.114 move_left_in_overview, move_right_in_overview 35
1.115 move_ruler_up, move_ruler_down, move_visual_mark_up, move_visual_mark_down 35
1.116 move_ruler_to_next_block, move_ruler_to_prev_block . . 35

1.117 move_ruler_next, move_ruler_prev, move_visual_mark_next, move_visual_mark_prev 35
1.118 move_window, set_window_rect 36
1.119 new_window 36
1.120 next_overview, previous_overview 36
1.121 next_chapter, prev_chapter 36
1.122 next_item, previous_item 36
1.123 next_page, previous_page 36
1.124 next_state, prev_state 36
1.125 noop 37
1.126 open_containing_folder 37
1.127 open_document 37
1.128 open_document_embedded 37
1.129 open_document_embedded_from_current_path 37
1.130 open_external_text_editor 37
1.131 open_last_document 38
1.132 open_link 38
1.133 open_local_database_containing_folder, open_shared_database_containing_folder 38
1.134 open_prev_doc 38
1.135 open_server_only_file 38
1.136 overview_definition 38
1.137 overview_link 38
1.138 overview_next_item, overview_prev_item 39
1.139 overview_to_portal 39
1.140 overview_to_ruler_portal, goto_ruler_portal 39
1.141 overview_under_cursor 39
1.142 pin_overview_as_portal 39
1.143 portal 40
1.144 portal_to_definition 40
1.145 portal_to_link 40
1.146 portal_to_overview 40
1.147 prefs 41
1.148 prefs_user 41
1.149 prefs_user_all 41
1.150 quit 41
1.151 regex_search 41
1.152 reload 42
1.153 reload_config 42
1.154 reload_no_flicker 42
1.155 rename 42
1.156 resume_to_server 42
1.157 resync_document 43
1.158 rotate_clockwise, rotate_counterclockwise 43
1.159 ruler_under_cursor, visual_mark_under_cursor 43
1.160 ruler_under_selected_point 43

1.161 save_scratchpad 43
1.162 scan_new_files 43
1.163 screenshot 43
1.164 screen_down, screen_up 44
1.165 scroll_selected_bookmark_down,
scroll_selected_bookmark_up 44
1.166 search, chapter_search 44
1.167 search_all_indexed_documents 44
1.168 select_current_search_match 44
1.169 select_freehand_drawings 45
1.170 select_rect 45
1.171 select_ruler_text 45
1.172 semantic_search 45
1.173 semantic_search_extractive 45
1.174 set_freehand_alpha 46
1.175 set_freehand_thickness 46
1.176 set_freehand_type 46
1.177 set_mark 46
1.178 set_page_offset 47
1.179 set_select_highlight_type 47
1.180 set_status_string, clear_status_string 47
1.181 set_view_state 47
1.182 show_context_menu 47
1.183 show_custom_context_menu 48
1.184 show_custom_options 48
1.185 show_text_prompt 48
1.186 show_touch_draw_controls 48
1.187 show_touch_highlight_type_select 48
1.188 show_touch_main_menu 49
1.189 show_touch_page_select 49
1.190 show_touch_settings_menu 49
1.191 show_touch_ui_for_config 49
1.192 smart_jump_under_cursor 49
1.193 move_down_smooth, move_up_smooth 49
1.194 start_mobile_text_selection_at_point 50
1.195 start_reading, stop_reading 50
1.196 start_reading_high_quality 50
1.197 synchronize 50
1.198 synctex_forward_search 50
1.199 synctex_under_cursor 51
1.200 synctex_under_ruler 51
1.201 sync_current_file_location 51

1.202 test_command, export_config_names, open_selected_url, toggle_smooth_scroll_mode, export_python_api, print_undocumented_commands, print_non_default_configs, export_default_config_file, unregister_url_handler, toggle_one_window, register_url_handler, export_command_names, goto_begining, send_symbol, open_all_docs, print_undocumented_configs, toggle_show_last_command, move_selected_bookmark, type_text 51
1.203 toggle_text_mark, move_text_mark_forward, move_text_mark_backward, move_text_mark_forward_word, move_text_mark_backward_word, move_text_mark_down, move_text_mark_up 51
1.204 toggle_custom_color 52
1.205 toggle_dark_mode 52
1.206 toggle_drawing_mask 52
1.207 toggle_fastread 53
1.208 toggle_freehand_drawing_mode 53
1.209 toggle_fullscreen 53
1.210 toggle_highlight_links 53
1.211 toggle_horizontal_scroll_lock 53
1.212 toggle_line_select_cursor 53
1.213 toggle_menu_collapse 53
1.214 toggle_mouse_drag_mode 53
1.215 toggle_pdf_annotations 54
1.216 toggle_pen_drawing_mode 54
1.217 toggle_presentation_mode, turn_on_presentation_mode . . 54
1.218 toggle_reading 54
1.219 toggle_rect_hints 54
1.220 toggle_ruler_scroll_mode, toggle_visual_scroll 54
1.221 toggle_scratchpad_mode 54
1.222 toggle_scrollbar 55
1.223 toggle_select_highlight 55
1.224 toggle_statusbar 55
1.225 toggle_synctex, turn_on_synctex 55
1.226 toggle_titlebar 55
1.227 toggle_two_page_mode 55
1.228 toggle_typing_mode 55
1.229 toggle_window_configuration 55
1.230 turn_on_all_drawings, turn_off_all_drawings 56
1.231 undo_delete 56
1.232 undo_drawing 56
1.233 upload_current_file 56
1.234 wait 56

1.235 wait_for_renders_to_finish, wait_for_search_to_finish, wait_for_indexing_to_finish, wait_for_downloads_to_finish 57
1.236 write_annotations_file 57
1.237 zoom_in, zoom_out, zoom_in_cursor, zoom_out_cursor . . 57
1.238 zoom_in_overview, zoom_out_overview 57

2 Configs **58**
2.1 [bool] adjust_annotation_colors_for_dark_mode 58
2.2 [bool] align_link_dest_to_top 58
2.3 [bool] allow_horizontal_drag_when_document_is_small . . 58
2.4 [bool] allow_main_view_scroll_while_in_overview 58
2.5 [string] annotations_directory 58
2.6 [bool] autocenter_ruler 59
2.7 [bool] automatically_download_matching_paper_name . . . 59
2.8 [bool] automatically_index_documents_for_fulltext_search 59
2.9 [bool] automatically_update_checksum_when_document_is_changed 59
2.10 [bool] automatically_upload_portal_destination_for_synced_documents 59
2.11 [bool] auto_login_on_startup 59
2.12 [bool] auto_rename_downloaded_papers 60
2.13 [int] background_bookmarks_pixel_budget 60
2.14 [color3] background_color, custom_color_mode_empty_background_color, dark_mode_background_color 60
2.15 [bool] case_sensitive_search 60
2.16 [bool] check_for_updates_on_startup 60
2.17 [string] shift_click_command, control_click_command, command_click_command, hold_middle_click_command, tablet_pen_click_command, tablet_pen_double_click_command, right_click_command, middle_click_command, shift_middle_click_command, control_middle_click_command, command_middle_click_command, alt_middle_click_command, shift_right_click_command, control_right_click_command, command_right_click_command, alt_click_command, alt_right_click_command 61
2.18 [bool] collapsed_toc 61
2.19 [string] context_menu_items, context_menu_items_for_links, context_menu_items_for_selected_text, context_menu_items_for_highlights, context_menu_items_for_bookmarks, context_menu_items_for_overview 61
2.20 [bool] create_table_of_contents_if_not_exists 62
2.21 [color3] custom_text_color, custom_background_color . . 62
2.22 [float] dark_mode_contrast 62

2.23 [string] default_open_file_path 62
2.24 [int] documentation_font_size 62
2.25 [string] document_location_mismatch_strategy 62
2.26 [bool] dont_center_if_synctex_rect_is_visible 63
2.27 [string] epub_css 63
2.28 [int] epub_width, epub_height, epub_font_size 63
2.29 [bool] exact_highlight_select 63
2.30 [string] external_text_editor_command 63
2.31 [string] extract_table_prompt 63
2.32 [bool] fill_textbar_with_selected_text 64
2.33 [float] fit_to_page_width_ratio 64
2.34 [bool] flat_toc 64
2.35 [int] font_size 64
2.36 [color3] freetext_bookmark_color 64
2.37 [int] freetext_bookmark_font_size 65
2.38 [bool] fuzzy_searching 65
2.39 [float] gamma 65
2.40 [bool] hide_overlapping_link_labels 65
2.41 [color3] highlight_color_[a-z] 65
2.42 [bool] highlight_links 66
2.43 [bool] highlight_middle_click 66
2.44 [bool] hover_overview 66
2.45 [bool] ignore_scroll_events 66
2.46 [bool] ignore_whitespace_in_presentation_mode 66
2.47 [bool] incremental_search 66
2.48 [bool] initial_snapped_dragging 66
2.49 [string] inverse_search_command 67
2.50 [bool] inverted_horizontal_scrolling 67
2.51 [bool] invert_selected_text 67
2.52 [bool] keyboard_point_selection 67
2.53 [color4] keyboard_select_background_color, keyboard_select_text_color, keyboard_selected_tag_background_color, keyboard_selected_tag_text_color 67
2.54 [int] keyboard_select_font_size 68
2.55 [bool] linear_filter 68
2.56 [color3] link_highlight_color 68
2.57 [int] max_created_toc_size 68
2.58 [string] menu_matched_search_highlight 68
2.59 [float] menu_screen_width_ratio, menu_screen_height_ratio 68
2.60 [symbol] middle_click_search_engine, shift_middle_click_search_engine 69
2.61 [float] move_screen_ratio 69
2.62 [bool] numeric_tags 69
2.63 [int] num_cached_pages 69

2.64 [int] num_prerendered_next_slides, num_prerendered_prev_slides 70
2.65 [int] num_two_page_columns 70
2.66 [color3] overview_reference_highlight_color 70
2.67 [int/color3] page_separator_width, page_separator_color 70
2.68 [int] page_space_x, page_space_y 70
2.69 [string] papers_folder_path 70
2.70 [bool] paper_download_should_create_portal 71
2.71 [int] prerendered_page_count 71
2.72 [bool] prerender_next_page_presentation 71
2.73 [bool] preserve_image_colors_in_dark_mode, inverted_preserved_image_colors 71
2.74 [color4/color3] question_bookmark_background_color, question_bookmark_text_color 71
2.75 [bool] real_page_separation 72
2.76 [int] reload_interval_miliseconds 72
2.77 [bool] render_freetext_borders 72
2.78 [bool] render_pdf_annotations 72
2.79 [string] resize_command 72
2.80 [bool] right_click_context_menu 72
2.81 [int] ruler_auto_move_threshold_distance 73
2.82 [color3] ruler_color 73
2.83 [string] ruler_display_mode 73
2.84 [color3] ruler_marker_color 73
2.85 [float] ruler_next_page_end_pos, ruler_next_page_begin_pos 74
2.86 [int] ruler_padding, ruler_x_padding 74
2.87 [int] ruler_pixel_width 74
2.88 [color4] ruler_slit_color 74
2.89 [bool] save_externally_edited_text_on_focus 75
2.90 [float] scrollview_sensitivity 75
2.91 [color3] search_highlight_color 75
2.92 [string] search_url_[a-z] 75
2.93 [float] server_and_local_document_mismatch_threshold . 76
2.94 [string] shared_database_path 76
2.95 [bool] should_highlight_unselected_search 76
2.96 [bool] should_launch_new_window 76
2.97 [bool] should_load_tutorial_when_no_other_file 76
2.98 [bool] should_warn_about_user_key_override 76
2.99 [bool] show_most_recent_commands_first 77
2.100 [bool] show_reference_overview_highlights 77
2.101 [bool] single_click_selects_words 77
2.102 [bool] sliced_rendering 77
2.103 [bool] smartcase_search 77
2.104 [float] smooth_move_max_velocity 77
2.105 [bool] sort_bookmarks_by_location 78

2.106 [string] startup_commands 78
2.107 [color3] status_bar_color, status_bar_text_color 78
2.108 [int] status_bar_font_size 78
2.109 [string] status_bar_format, right_status_bar_format, status_*_command 78
2.110 [string] status_custom_message_[a-d], status_custom_message_[a-d]_command 80
2.111 [string] status_font 80
2.112 [int] strike_line_width 80
2.113 [bool] super_fast_search 80
2.114 [color3] synctex_highlight_color 81
2.115 [float] synctex_highlight_timeout 81
2.116 [string] table_extract_behaviour 81
2.117 [string] tag_font_face 82
2.118 [color3] text_highlight_color 82
2.119 [bool] toc_jump_align_top 82
2.120 [float] touchpad_sensitivity 82
2.121 [bool] touch_mode 82
2.122 [string] back_rect_tap_command, back_rect_hold_command, forward_rect_tap_command, forward_rect_hold_command, middle_left_rect_tap_command, middle_left_rect_hold_command, middle_right_rect_tap_command, middle_right_rect_hold_command, ruler_next_tap_command, ruler_next_hold_command, ruler_prev_tap_command, ruler_prev_hold_command 83
2.123 [float] tts_rate 83
2.124 [string] ui_font 83
2.125 [rect] portrait_back_ui_rect, portrait_forward_ui_rect, landscape_back_ui_rect, landscape_forward_ui_rect, portrait_visual_mark_next, portrait_visual_mark_prev, landscape_visual_mark_next, landscape_visual_mark_prev, landscape_middle_right_rect, portrait_middle_right_rect, landscape_middle_left_rect, portrait_middle_left_rect 83
2.126 [color3] ui_text_color, ui_background_color, ui_selected_text_color, ui_selected_background_color . 84
2.127 [color3] unselected_search_highlight_color 84
2.128 [bool] use_ruler_to_highlight_synctex_line 84
2.129 [bool] use_system_theme, use_custom_color_as_dark_system_theme 84
2.130 [float] vertical_move_amount, horizontal_move_amount . 84
2.131 [bool] wheel_zoom_in_cursor 85
2.132 [int] main_window_size, helper_window_size, main_window_move, helper_window_move, single_main_window_size, single_main_window_move, overview_size, overview_offset 85

2.133 [bool] zoom_inc_factor 85

1 Commands

1.1 add_annot_to_highlight

Allows the user to select a highlight to add annotations to using the keyboard. A label is displayed next to each visible highlight, and the user can press the corresponding key to select the highlight. Then a text box will appear where the user can type the annotation.

Related Commands

add_highlight, change_highlight, delete_highlight, generic_delete

1.2 add_bookmark

Add an invisible bookmark in the current location. You can later search the bookmarks using the goto_bookmark command.

Related Commands

add_freetext_bookmark, add_marked_bookmark, goto_bookmark, goto_bookmark_g

1.3 add_freetext_bookmark, add_freetext_bookmark_auto

Add a freetext bookmark in the selected rectangle. The add_freetext_bookmark prompts the user to select the rectangle while the add_freetext_bookmark_auto command doesn't ask for a rectangle, instead it automatically detects possible large empty spaces in the current screen and asks the user to pick one of those. Freetext bookmarks are visible in the document. You can change the display style of the bookmark using the following prefixes:

- If the bookmark text starts with # followed by a symbol, it will draw a box with the symbol's color (the same color as the highlighs of the symbol).
- If the bookmark text starts with #markdown, the rest of the bookmark will be rendered as markdown
- If the bookmark text starts with #latex, the rest of the bookmark will be rendered as latex
- You can change the border/background/text color of the bookmark by adding the corresponding symbol prefix after the # or #markdown or #latex prefix. For example, #rgb this is bookmark text will create a bookmark with a red border and green background and blue text.

Similarly you can edit the colors of a markdown bookmark like this: `#markdownrgb this is **markdown** bookmark text`.

- If the bookmarks text starts with `?`, it will be interpreted as a question to be asked from the current document (using a large language model). The response will be displayed in the bookmark (this feature is only available to pro users).
- If the bookmark text starts with `#shell` followed by a shell command, then sioyek will run the shell command and fill the bookmark with the output of the shell command. The following variables will be expanded in the shell command:
  - `%{text}` will expand to the text of the bookmark after the `#shell` line (following the newline character). For example, `#shell ping %{text}\ngoogle.com` will run `ping google.com` and display the output in the bookmark. Obviously, this is not useful when running the `#shell` bookmark directly but it is useful when defining predefined shell commands using `new_shell_bookmark_command???`.
  - `%{document_text_file}` expands to the path of a temporary file containing the current document's text.
  - `%{current_page_begin_index}` expands to the index of the first character of the current page in the document text file.
  - `%{current_page_end_index}` expands to the index of the last character of the current page in the document text file.
  - `%{bookmark_image_file}` expands to the path of a temporary file containing the image of the document section where the bookmark is located.
  - `%{selected_text}` expands to the text of the selected text in the document.
- If the bookmark text starts with `@cmd` where `cmd` is a command previously defined using `new_shell_bookmark_command???`, then sioyek will run the command and fill the bookmark with the output of the command.

Related Commands

`add_marked_bookmark`, `add_bookmark`, `delete_bookmark`, `edit_visible_bookmark`, `edit_selected_bookmark`, `generic_delete`, `generic_select`

Related Configs

`new_shell_bookmark_command???`

1.4 add_highlight

Highlight the selected text. Requires a symbol which specifies the color of the highlighted text. For example executing `add_highlight` followed by pressing `a` will create a highlight with color `highlight_color_a???`. You can configure

the highlight color of all highlights in your config files. The highlights can later be searched using `goto_highlight`.

Related Commands

`goto_highlight`, `goto_highlight_g`, `add_highlight_with_current_type`, `goto_next_highlight`, `goto_next_highlight_of_type`, `delete_highlight`, `change_highlight`, `edit_selected_highlight`, `generic_delete`, `generic_select`

Related Configs

`highlight_color_[a-z]`

1.5 add_highlight_with_current_type

Highlight the selected text with the current highlight type as set by `set_select_highlight_type`.

Related Commands

`add_highlight`, `set_select_highlight_type`

1.6 add_keybind

Dynamically add a new keybinding using the same syntax as a line in `keys.config` file.

1.7 add_marked_bookmark

Add a marked bookmark in the selected location. Marked bookmarks are visible in the document with a small icon. You can later search the bookmarks using the `goto_bookmark` command.

Related Commands

`add_freetext_bookmark`, `add_bookmark`, `goto_bookmark`, `goto_bookmark_g`, `edit_visible_bookmark`, `edit_selected_bookmark`, `delete_bookmark`, `generic_select`, `generic_delete`

1.8 add_marked_data, remove_marked_data, export_marked_data, undo_marked_data, goto_random_page

1.9 cancel_all_downloads

Cancel all pending downloads.

Related Commands
download_link, download_overview_paper

1.10 change_highlight

Alows the user to change highlight type using keyboard. The user first enters the label of the highlight they want to change, then they enter the label of the new highlight type they want to change it to.

Related Commands
add_highlight, add_annot_to_highlight

1.11 citers

Show citers of the current paper.

Related Commands
external_search

1.12 clear_current_page_drawings, clear_current_document_drawings

Clear all freehand drawings in the current page/document.

Related Commands
toggle_freehand_drawing_mode, toggle_pen_drawing_mode

1.13 clear_scratchpad

Clear the scratchpad.

Related Commands
toggle_scratchpad_mode

1.14 `close_overview`

Close the overview window.

Related Commands

`overview_under_cursor`, `overview_definition`, `overview_to_portal`, `overview_to_ruler_portal`

1.15 `close_window`

Close the current sioyek window (doesn't close the application if there are more than one window open).

Related Commands

`new_window`, `quit`

1.16 `command`

Open a searchable list of all commands. Appending or prepending a `?` to the search query will open the documentation for the selected command. If the query starts with `=` it will show a list of `setconfig` commands which are used to dynamically set configurations, changes made using `setconfig` are not permenant. If you want to permenantly set a config, you can enter `+=` which will search for `setsaveconfig` commands which persistantly set configurations. Alternatively if you want to save the current value of a configuration you can enter `+` which will search the `saveconfig` commands which saves the current value of the selected configuration. If the query starts with `!` it will show a list of `toggleconfig` commands which are used to toggle the value of boolean configurations.

Related Commands

`command_palette`

1.17 `command_palette`

Show a command palette with human-readable command names.

Related Commands

`command`

1.18 `control_menu`

Used to control ui menus using keyboard or scripts. Takes the desired action as an input string which can be one of the following:

Action	Description
`down`	Move down in menu
`up`	move up in menu
`page_down`	move to the next page in menu
`page_up`	move to the previous page in menu
`menu_begin`	move to the first item in menu
`menu_end`	move to the last item in menu
`select`	select the highlighted item
`get`	get the value of selected item (mainly used in scripting)
`cursor_backward`	move the text cursor one character backward
`cursor_forward`	move the text cursor one character forward
`select_backward`	select text one character backward
`select_forward`	select text one character forward
`move_word_backward`	move the text cursor one word backward
`move_word_forward`	move the text cursor one word forward
`select_word_backward`	select the previous word
`select_word_forward`	select the next word
`move_to_end`	move to the end of text input
`move_to_begin`	move to the start of text input
`select_to_end`	select to the end of text input
`select_to_begin`	select to the start of text input
`select_all`	select all of the text input
`delete_to_end`	delete text from cursor location to the end of the input
`delete_to_begin`	delete text from the start of the input to the cursor
`delete_next_word`	delete the next word after cursor
`delete_prev_word`	delete the previous word before cursor
`delete_next_char`	delete the character after cursor
`delete_prev_char`	delete the character before cursor
`next_suggestion`	show the next autocomplete suggestion
`prev_suggestion`	show the previous autocomplete suggestion

For example, suppose you want to use `<C-j>` and `<C-k>` keybinds to move up and down in a menu. You can add the following to your `keys_user.config`:

```
control_menu('down') <C-j>
control_menu('up') <C-k>
```

1.19 convert_to_latex

Convert the image of the selected rectangle to LaTeX code.

1.20 copy

Copy the selected text to clipboard.

1.21 copy_drawings_from_scratchpad

Copy drawings in the selected rectangle from the scratchpad to the main document.

Related Commands
`toggle_scratchpad_mode`, `copy_screenshot_to_scratchpad`

1.22 copy_link

Displays a symbol next to each visible link and copies the URL of selected link.

Related Commands
`open_link`

1.23 copy_screenshot_to_clipboard

Copy a screenshot of the selected rectangle to the clipboard.

1.24 copy_screenshot_to_scratchpad

Copy a screenshot of the document to the scratchpad (for example can be used to copy an image of an equation to the scratchpad).

Related Commands
`toggle_scratchpad_mode`, `copy_drawings_from_scratchpad`

1.25 copy_window_size_config

1.26 create_fulltext_index_for_current_document

Add the current document to the fulltext search indexed. All indexed documents can later be searched using `search_all_indexed_documents`.

Related Commands
`search_all_indexed_documents`

1.27 create_visible_portal

Creates a portal with the selected window point as source. The source will be visible on the document. The destination of the portal can later be set using the `portal` command. An overview to the destination of the portal can be opened by right clicking on the portal icon.

Related Commands
`portal`, `overview_to_portal`, `goto_portal`, `edit_portal`, `delete_portal`, `generic_delete`, `generic_select`

1.28 delete_all_pdf_annotations, delete_intersecting_pdf_annotations

Delete all of the built-in PDF annotations (this is different from sioyek annotations, here we mean the PDF annotations created in other PDF viewers or using sioyek's embed_annotations). The `delete_intersecting_pdf_annotations` command can be used to delete only the annotations that intersect with the selected rectangle.

Related Commands
`embed_annotations`, `import_annotations`, `generic_delete`

1.29 delete_current_file_from_server

Delete current file from sioyek servers.

Related Commands
`upload_current_file`

1.30 delete_document_from_fulltext_search_index

Delete the current document from the fulltext search index.

Related Commands

`create_fulltext_index_for_current_document`

Related Configs

`automatically_index_documents_for_fulltext_search`

1.31 delete_freehand_drawings

Delete the freehand drawings in the selected rectangle.

Related Commands

`select_freehand_drawings`, `toggle_freehand_drawing_mode`, `toggle_pen_drawing_mode`

1.32 delete_highlight_under_cursor

Delete the highlight under mouse cursor.

Related Commands

`add_highlight`, `delete_highlight`, `generic_delete`

1.33 delete_portal, delete_bookmark, delete_highlight

Delete the selected portal/bookmark/highlight. If no item is selected then we delete the closest portal/bookmark/highlight to the current location.

Related Commands

`generic_delete`

1.34 delete_visible_bookmark

Delete a visible bookmark on the screen using keyboard by specifying the label of the bookmark.

Related Commands

`add_marked_bookmark`, `add_freetext_bookmark`, `edit_visible_bookmark`, `generic_delete`

1.35 `documentation_search`

Search the sioyek documentation.

1.36 `donate`

Make a donation to support the development of sioyek.

1.37 `download_paper_with_url, download_clipboard_url`

Download and open a paper from an input URL (`download_paper_with_url`) or the URL in clipboard (`download_clipboard_url`).

1.38 `download_link`

Download a paper by selecting its link using the keyboard.

Related Commands

`open_link`, `download_overview_paper`

1.39 `download_overview_paper, download_overview_paper_no_prompt`

Downloads the paper currently shown in overview window. The `download_overview_paper` command first displays the automatically detected paper title and asks for confirmation. The `download_overview_paper_no_prompt` command downloads the paper without asking for confirmation.

Related Commands

`overview_definition`, `download_link`, `download_paper_under_cursor`

Related Configs

`papers_folder_path`, `paper_download_should_create_portal`

1.40 `download_paper_under_cursor`

Download the paper under mouse cursor. This can be the actual name of the paper (either in the document itself or the overview window) or a reference to the paper (e.g. executing `download_paper_under_cursor` while cursor is on a reference like `[12]` will download the paper referenced by `[12]`).

Related Commands

`download_link`

Related Configs

`papers_folder_path`, `paper_download_should_create_portal`

1.41 download_paper_with_name

Download a paper given its name as input.

Related Commands

`download_paper_under_cursor`

1.42 download_unsynced_files

Download all files on sioyek server that are not available locally.

1.43 edit_portal

Edit the destination of the portal with the closest source. When `edit_portal` is executed, sioyek jumps to the destination of the portal, now we can move around the destination and when we are done, we execute `prev_state` which updates the destination with the current location and brings us back to the source of the portal.

Related Commands

`portal`, `overview_to_portal`

1.44 edit_selected_bookmark

Edits the selected bookmark (a bookmark can be selected by clicking on it).

Related Commands

`add_bookmark`, `add_freetext_bookmark`, `add_marked_bookmark`, `generic_select`

1.45 edit_selected_highlight

Edits the annotation of selected highlight (highlights can be selected by clicking on them).

Related Commands

`add_highlight`, `generic_select`

1.46 edit_visible_bookmark

Edit a visible bookmark on the screen using keyboard by specifying the label of the bookmark.

Related Commands

`add_marked_bookmark`, `add_freetext_bookmark`, `delete_visible_bookmark`

1.47 embed_annotations

Embeds the sioyek annotations into the document as native PDF annotations. This is useful when sharing the file with others who do not have sioyek installed.

Related Commands

`import_annotations`

1.48 embed_selected_annotation

Embed the selected sioyek annotation into an embedded PDF annotation that can be viewed in other PDF viewers.

Related Commands

`embed_annotations`, `delete_all_pdf_annotations`, `delete_intersecting_pdf_annotations`

1.49 enter_password

Enter the password for password-protected PDF files.

1.50 enter_visual_mark_mode

1.51 escape

Simulates pressing escape (e.g. unselects text, exits ruler mode, etc.).

1.52 execute, execute_shell_command

Executes the given shell command. The following substrings will be expanded in the command:

- %{file_path} will expand to the full path of current file.
- %{file_name} will expand to current file name.
- %{selected_text} will expand to the current selected text.
- %{selection_begin_document} and %{selection_end_document} will expand to the document location of the begin and end of current text selection. The format is page x y.
- %{page_number} will expand to the current page number.
- %{command_text} will ask the user for a text input and expand to the input.
- %{mouse_pos_window} will expand to the mouse position in the window. The format is x y.
- %{mouse_pos_document} will expand to the mouse position in the document. The format is page x y.
- %{paper_name} will expand to the current file's automatically detected paper/document title
- %{sioyek_path} will expand to the path of sioyek executable
- %{local_database} will expand to the path the local database file
- %{shared_database} will expand to the path the shared database file
- %{selected_rect} will expand to the selected rectangle in the document. The format is page x1 y1 x2 y2.
- %{zoom_level} will expand to the current zoom level.
- %{offset_x} and %{offset_y} will expand to the current absolute offsets
- %{offset_x_document} and %{offset_y_document} will expand to the current document offsets
- %{line_text}: if we are in ruler mode will expand to the text of current ruler line

1.53 execute_macro

Execute the given sioyek commands string. This is mainly used for scripting and it is probably not directly useful for end-users.

1.54 exit_ruler_mode, close_visual_mark

Exit ruler mode.

Related Commands
ruler_under_cursor, keyboard_select_line

1.55 export

Export annotation data into a JSON file.

Related Commands
`import`

1.56 `external_search`

Search the selected text using the configured external search engine. This is a symbol command, and each symbol could be configured for a different search engine using `search_url_[a-z]???`. For example in the default configuration `g` searches in google and `s` searches in google scholar. If no text is selected, we search the title of the current document instead (e.g. in the default configuration, to search the current paper in google scholar you can press `ss` when no text is selected).

Related Configs
`search_url_[a-z]`

1.57 `extract_table, extract_table_with_prompt`

Extract the contents of selected table. The `extract_table_with_prompt` command asks the user for a natural language prompt and extracts the table according to that (for example you can say something like this: "extract the contents of this table into a latex table").

1.58 `find_references`

If a piece of text is selected, this command will search for PDF links that point to a location in the span of the selected text. Otherwise this command will allow you to select a PDF link visible in the current screen and finds other PDF links with the same destination. This is useful e.g. to find all references to a specific paper in a document.

1.59 `fit_epub_to_window`

Fit an epub document exactly to the window dimensions.

1.60 `fit_to_overview_width`

Fit the overview page such that it fills the width of the screen.

Related Commands
`overview_definition`, `overview_to_portal`

1.61 fit_to_page_width_ratio

Fit to current document to a ratio of screen configured using `fit_to_page_width_ratio`. This is useful for users with very wide screens.

Related Commands

`fit_to_page_width`

Related Configs

`fit_to_page_width_ratio`

1.62 fit_to_page_width, fit_to_page_height, fit_to_page_width_smart, fit_to_page_height_smart, fit_to_page_smart

Fits the document to page width/height. The smart variants try to ignore the white page margins while fitting. `fit_to_page_smart` command fits the document to the minimum of width and height, ignoring the white margins.

1.63 focus_text

Create the ruler under the line with the given text.

1.64 force_download_annotations

Download all unsynced annotations from the server. This is usually performed automatically but can be manually triggered with this command.

1.65 framebuffer_screenshot

Take a screenshot from sioyek framebuffer (ignoring other widgets) and save it to the given path. This is mainly used for testing purposes.

1.66 fulltext_search_current_document

Perform a fulltext search in the current document. The document must be indexed for fulltext search. To index the current document, use `create_fulltext_index_for_current_document`. To automatically index all documents, set `automatically_index_documents_for_fulltext_search` to `1`.

Related Commands

`create_fulltext_index_for_current_document`

Related Configs

`automatically_index_documents_for_fulltext_search`

1.67 fuzzy_search

Perform a fuzzy search in the current document. The search string doesn't have to match the text exactly. We try to find the closest matches.

Related Commands

`search`, `regex_search`

1.68 generic_delete

Allows the user to delete annotations using keyboard. The user enters the label of the annotation they want to delete.

Related Commands

`generic_select`

1.69 generic_select

Allows the user to select annotations using keyboard. The user enters the label of the annotation they want to select.

Related Commands

`generic_delete`

1.70 get_annotations_json

Returns the current document's annotations as a json string.

Example:

```
from sioyek import Sioyek
import json
s = Sioyek('')
annotations = json.loads(s.get_annotations_json())
print(annotations)
```

1.71 get_config_no_dialog

Returns the current value of given config without displaying anything to the user. This is mainly useful for scripting.

Example:

```
from sioyek import sioyek
s = sioyek.Sioyek('')
print(s.get_config_no_dialog('highlight_color_a')) # 'color3 0.94 0.64 1\n'
```

Related Commands
get_config_value

1.72 get_config_value

Displays the value of the given config string to the user.

Related Commands
get_config_no_dialog

1.73 get_mode_string

Returns the string for current mode. See @concept(mode) for more information.

Example:

```
from sioyek import Sioyek
s = Sioyek('')
print(s.get_mode_string()) # 'RXHQEDPOSFMT'
```

1.74 get_overview_paper_name

Returns the title of the paper in current overview window. This is useful for scripting and probably not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = Sioyek('')
paper_name = s.get_overview_paper_name()
s.set_status_string(f'Current overview paper name is: {paper_name}')
```

1.75 get_paper_name

Returns the title of the current document. This is useful for scripting and probably not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = Sioyek('')
```

```
paper_name = s.get_paper_name()
s.set_status_string(f'Current document name is: {paper_name}')
```

1.76 get_state_json

Returns a json string containing the current state of the application. The state is a list of json objects for each sioyek window. Each object contains the following fields:

- `document_checksum`: MD5 checksum of the document
- `document_path`: Path to the document
- `loaded_documents`: List of the paths of loaded documents
- `page_number`: Current page number
- `searching`: Whether the application is currently searching
- `selected_text`: The currently selected text
- `window_height`: Height of the window
- `window_width`: Width of the window
- `window_id`: The id of the window
- `x_offset` and `y_offset`: Current position in document
- `x_offset_in_page` and `y_offset_in_page`: Current position in page
- `zoom_level`: Current zoom level

Example:

```
from sioyek import sioyek
import json

s = sioyek.Sioyek('')
state = json.loads(s.get_state_json())
print(state['page_number'])
```

1.77 goto_beginning, goto_end

Move to the beginning/end of the document. If the repeat count of the command is `n!=0` then we jump to page `n` (vim style).

1.78 goto_bookmark, goto_bookmark_g

`goto_bookmark` opens a searchable list of current document's bookmarks. `goto_bookmark_g` opens a searchable list of all documents' bookmarks.

Related Commands
`add_bookmark`, `add_marked_bookmark`, `add_freetext_bookmark`

1.79 goto_definition

Go to the the definition of the first symbol in the highlighted line using the @concept(ruler).

Related Commands
overview_definition, portal_to_definition, visual_mark_under_cursor

1.80 goto_highlight, goto_highlight_g

Open a searchable list of all highlights in the current document. You can limit the search to highlights of a certain type by prefixing the query by the type of the highlight followed by a space. For example `j {query}` searches for `{query}` only in highlights of type j. `goto_highlight_g` opens a searchable list of all documents' highlights.

Related Commands
add_highlight

1.81 goto_left, goto_right, goto_left_smart, goto_right_smart

Move to the left/right side of the document. The `_smart` variants ignore the white page margins.

Related Commands
move_left, move_right

1.82 goto_mark

Goto a mark previously set by `set_mark`. See `set_mark` for more details.

Related Commands
set_mark

1.83 goto_next_highlight, goto_prev_highlight

Jump to the next/previous highlight in the current document.

Related Commands

`add_highlight`, `add_highlight_with_current_type`

1.84 goto_next_highlight_of_type, goto_prev_highlight_of_type

Jump to the next/previous highlight with the current highlight type (as set by `set_select_highlight_type`).

Related Commands

`add_highlight`, `add_highlight_with_current_type`

1.85 goto_overview

Jump to the location of current overview.

Related Commands

`overview_definition`

1.86 goto_page_with_label

Prompts the user for a page label and jumps to that page. The label can be different from the page number in some documents (e.g. some documents have some pages labeled as “i”, “ii”, “iii”, etc.).

Related Commands

`goto_page_with_page_number`

1.87 goto_page_with_page_number

Prompts the user for a page number and jumps to that page.

Related Commands

`goto_page_with_label`, `goto_beginning`

1.88 goto_portal

Go to the destination of the portal with the closest source.

Related Commands

`portal`, `overview_to_portal`

1.89 goto_portal_list

Open a list of portals in the current document.

1.90 goto_selected_text

Jump to the location of selected text.

1.91 goto_tab

Opens a searchable list of tabs.

1.92 goto_toc

Open the table of contents.

Related Configs

`collapsed_toc`, `create_table_of_contents_if_not_exists`, `max_created_table_of_contents_size`???

1.93 goto_top_of_page, goto_bottom_of_page

Go to the top/bottom of the current page.

1.94 goto_window

Open a searchable list of current sioyek windows.

Related Commands

`close_window`, `new_window`

1.95 import

Import annotation data from an exported json file using `export`.

Related Commands

`export`

1.96 import_annotations

Imports the native PDF annotations into sioyek annotations.

Related Commands
`import_annotations`

1.97 `import_local_database, import_shared_database`

Import the data from `local.db` or `shared.db` file.

1.98 `increase_freetext_font_size, decrease_freetext_font_size`

Increase/decrease the font size of the freetext bookmark being edited.

Related Commands
`add_freetext_bookmark`

1.99 `increase_tts_rate, decrease_tts_rate`

Increase/decrease the rate of the text-to-speech (TTS) engine by `tts_rate_increment`???.

Related Commands
`start_reading`, `stop_reading`

Related Configs
`tts_rate_increment`???

1.100 `keyboard_overview`

Displays a tag next to each word in the document, opens an overview to the selected tag's word (this works even for documents that don't have links, otherwise `overview_link` would be used).

Related Commands
`keyboard_select_line`, `keyboard_overview`, `keyboard_smart_jump`

1.101 `keyboard_select`

Displays a tag next to each word in the document, selects the text corresponding to the entered begin and end tag (separated by a space). If only a single tag is entered, then we just select that word.

Related Commands
keyboard_select_line, keyboard_overview, keyboard_smart_jump

1.102 keyboard_select_line

Select a line using keyboard. Show a label next to each visible line and create a ruler under that line when a label corresponding to that line is entered.

Related Commands
ruler_under_cursor

1.103 keyboard_smart_jump

Displays a tag next to each word in the document, jumps to the selected tag's word (this works even for documents that don't have links, otherwise overview_link would be used).

Related Commands
keyboard_select_line, keyboard_overview, keyboard_smart_jump

1.104 keys

Opens the default keys.config file.

Related Commands
keys_user, keys_user_all, prefs, prefs_user, prefs_user_all

1.105 keys_user

Opens the default keys_user.config file.

Related Commands
keys, keys_user_all, prefs, prefs_user, prefs_user_all

1.106 keys_user_all

Shows a list of all considered keys_user.config files, sorted by priority. All of these files are applied but the files with higher priority override the lower-priority files if they contain the same setting.

Related Commands
keys_user

1.107 load_annotations_file, import_annotations_file_sync_deleted

Load the annotations from the file created using `write_annotations_file`. The `load_annotations_file` doesn't delete anything from the current file but the `import_annotations_file_sync_deleted` will overwrite the current annotations with the annotations in the file and delete any annotations that are not in the file.

Related Commands
write_annotations_file

1.108 load_scratchpad

Load a previously saved scratchpad state. This state should have been previously saved using `save_scratchpad`.

Related Commands
toggle_scratchpad_mode, save_scratchpad

1.109 login

Login into your sioyek account.

Related Commands
logout

1.110 login_using_access_token

Login to sioyek servers using previously obtained access token.

Related Commands
login, logout

1.111 logout

Logout from your sioyek account.

Related Commands

`login`

1.112 maximize

Maximize the sioyek window.

Related Commands

`toggle_fullscreen`

1.113 move_left, move_right, move_down, move_up

Basic movement in the current document.

Related Commands

`move_down_smooth`, `move_up_smooth`, `screen_down`, `screen_up`

1.114 move_left_in_overview, move_right_in_overview

Move left and right in the overview (you can use the normal up and down movement commands to move up and down).

Related Commands

`overview_definition`

1.115 move_ruler_up, move_ruler_down, move_visual_mark_up, move_visual_mark_down

Move the ruler up or down.

Related Commands

`keyboard_select_line`

1.116 move_ruler_to_next_block, move_ruler_to_prev_block

Move the ruler to previous/next text block.

Related Commands

`keyboard_select_line`, `move_ruler_up`, `move_ruler_down`

1.117 move_ruler_next, move_ruler_prev, move_visual_mark_next, move_visual_mark_prev

Move the ruler such that more content is visible. This is the same as `move_ruler_down` `move_ruler_up` commands when the ruler is entirely visible, but when part of the ruler is offscreen (e.g. in mobile devices with a small screen) this command moves such that the obscured part of the ruler becomes visible and only moves to the next line when the entire line has been viewed. A red mark highlights the leftmost part of the next ruler position, so when you reach the red mark you can run `move_ruler_next` and continue reading from the left side of the screen.

Related Commands
`keyboard_select_line`, `move_ruler_up`, `move_ruler_down`

1.118 move_window, set_window_rect

1.119 new_window

Create a new sioyek window.

Related Commands
`close_window`, `goto_window`

1.120 next_overview, previous_overview

Go to the next/prevoius possible overview desitnation. For example, when executing `overview_definition` there might be more than one possible target. This command will jump to the next/previous target.

Related Commands
`overview_definition`

1.121 next_chapter, prev_chapter

Go to the next/previous chapter in table of contents.

1.122 next_item, previous_item

Go to the next/previous search result.

Related Commands
`search`, `regex_search`

1.123 `next_page, previous_page`

Move to the next/previous page.

Related Commands
`goto_page_with_page_number`, `goto_page_with_label`

1.124 `next_state, prev_state`

Move forward/backward in history. Note that this history works even across files (i.e. if you go to a different file you can return to the previous file by executing `prev_state` or go back forward to the new file by executing `next_state`.)

1.125 `noop`

Do nothing (for example can be used to unbind default keybindings, by binding them to `noop` instead).

1.126 `open_containing_folder`

Open the folder containing the current file in file explorer.

1.127 `open_document`

Open the operating system's file explorer to select a document to open.

Related Commands
`open_prev_doc`, `open_document_embedded`, `open_document_embedded_from_current_path`

1.128 `open_document_embedded`

Opens an embedded file browser in sioyek (unlike `open_document` which uses the operating system's file browser).

Related Commands
`open_document`, `open_document_embedded_from_current_path`

1.129 `open_document_embedded_from_current_path`

Opens an embedded file browser in sioyek rooted at the current opened file's directory with the current file being selected.

Related Commands

`open_document`, `open_document_embedded`

1.130 open_external_text_editor

Open an external text editor to edit the current text input. For example you can open an external editor to edit bookmarks or highlight annotations. The external editor can be configured using `external_text_editor_command`, the corresponding text input will be updated in sioyek whenever the file is saved.

Related Configs

`external_text_editor_command`

1.131 open_last_document

Opens the last document that was opened in the current sioyek window.

1.132 open_link

Opens PDF links using keyboard. Displays a symbol next to each visible link and jumps when user enters the link symbol.

Related Commands

`overview_link`

1.133 open_local_database_containing_folder, open_shared_database_containing_folder

Open the folder containing the local/shared database file.

1.134 open_prev_doc

Shows a searchable list of previously opened documents.

Related Commands

`open_document`, `open_document_embedded`, `open_document_embedded_from_current_path`

1.135 open_server_only_file

Open a list of files that the user has previously uploaded on sioyek servers but are not available on the current device.

1.136 `overview_definition`

Open an overview to the definition of the first symbol in the highlighted line using the @concept(ruler).

Related Commands

`goto_definition`, `portal_to_definition`, `visual_mark_under_cursor`, `next_overview`, `previous_overview`

1.137 `overview_link`

Create an overview to a PDF link using keyboard. Displays a symbol next to each visible link and opens an overview to link destination when user enters the link symbol.

Related Commands

`open_link`

1.138 `overview_next_item, overview_prev_item`

Open an overview to the next/previous search result.

Related Commands

`search`, `regex_search`

1.139 `overview_to_portal`

Open an overview to the closest portal.

Related Commands

`portal`, `create_visible_portal`

1.140 `overview_to_ruler_portal, goto_ruler_portal`

Open an overview/Jump to the portal on current ruler line.

Related Commands

`create_visible_portal`, `download_link`, `download_overview_paper`, `download_overview_paper_no_prompt`

1.141 `overview_under_cursor`

Open the overview window to the location of reference under mouse cursor. This works even when the document doesn't have links.

Related Commands
`close_overview`, `overview_definition`

1.142 `pin_overview_as_portal`

Create a "pinned portal" from the current overview. Pinned portals appear as part of the page, you can think of them as an overview that is embedded in a specific part of the page. For example you can pin a figure to the right side of a page describing the figure.

Related Commands
`portal`, `overview_definition`, `overview_to_portal`

1.143 `portal`

Creates a new pending portal with the current location as source. If we already have a pending-portal, create the portal with the current location as the destination. As an example use-case you can create a portal from a part of text describing an equation or table to the equation/table itself, the contents of the destination portal can be viewed in a separate window using `toggle_window_configuration` or an overview to see the contents of the portal in the same window using `overview_to_portal`.

If this command is executed while an @concept(overview) is visible, then it creates a "pinned portal" from the current location to the overview. Pinned portals are portals that are displayed in a box like overviews so their destination content is always visible.

Related Commands
`overview_to_portal`, `toggle_window_configuration`

1.144 `portal_to_definition`

Create a portal to the definition of the first symbol in the highlighted line using the @concept(ruler).

Related Commands

`goto_definition`, `overview_definition`, `visual_mark_under_cursor`

1.145 portal_to_link

Displays a symbol next to each visible link and creates a portal from the current location to the selected link's location.

Related Commands

`open_link`, `overview_to_portal`

1.146 portal_to_overview

Create a portal from the current location to the overview location.

Related Commands

`overview_definition`

1.147 prefs

Opens the default `prefs.config` file.

Related Commands

`keys`, `keys_user`, `keys_user_all`, `prefs_user`, `prefs_user_all`

1.148 prefs_user

Opens the default `prefs_user.config` file.

Related Commands

`keys`, `keys_user`, `keys_user_all`, `prefs`, `prefs_user_all`

1.149 prefs_user_all

Shows a list of all considered `prefs_user.config` files, sorted by priority. All of these files are applied but the files with higher priority override the lower-priority files if they contain the same setting.

Related Commands

`prefs_user`

1.150 `quit`

Quits sioyek (closes all windows).

Related Commands

`close_window`

1.151 `regex_search`

Search the contents of current document using regular expressions. You can navigate the results the same way you would with `search` results.

Related Commands

`search`, `next_item`, `previous_item`, `overview_next_item`, `overview_prev_item`

1.152 `reload`

Reload all of the current file's data. This can be useful for situations where the file has been modified outside of sioyek, although sioyek will try to automatically reload the file if it detects changes on rare occasions it might fail to do so, in such situations you can use this command to manually reload the file.

Related Commands

`reload_no_flicker`

1.153 `reload_config`

Reloads the config files. Sioyek automatically reloads the config files when they are changed but in rare situations when it doesn't do so automatically (e.g. due to a permission issue), you can manually reload them using this command.

Related Commands

`prefs_user`, `keys_user`

1.154 reload_no_flicker

This is similar to the `reload` with the difference that here we don't immediately delete the previous renders (which causes the screen to flicker before the new document is rendered).

Related Commands
`reload`

1.155 rename

Rename the current file. Sioyek tries to fill the default value to an automatically detected title.

1.156 resume_to_server

Resume the current file location to the last location in sioyek servers.

Related Commands
`sync_current_file_location`

Related Configs
`document_location_mismatch_strategy`

1.157 resync_document

Re-sync current document's annotations with sioyek servers. This command is usually performed automatically but can be manually triggered with this command.

1.158 rotate_clockwise, rotate_counterclockwise

Rotate the document.

1.159 ruler_under_cursor, visual_mark_under_cursor

Create a ruler under the line under mouse cursor.

Related Commands
`move_ruler_down`, `move_ruler_up`, `overview_definition`

1.160 ruler_under_selected_point

1.161 save_scratchpad

Save the current scratchpad state to a file. This file can be loaded later using `load_scratchpad`.

Related Commands

toggle_scratchpad???, `load_scratchpad`

1.162 scan_new_files

1.163 screenshot

Take a screenshot from sioyek window and save it to the given path. This is mainly used for testing purposes.

1.164 screen_down, screen_up

Move one screen up or down. The amount of movement can be configured using `move_screen_ratio`.

1.165 scroll_selected_bookmark_down, scroll_selected_bookmark_up

Scroll the contents of a freetext bookmark up or down.

Related Commands

`add_freetext_bookmark`

1.166 search, chapter_search

Search the contents of current document. You can use `next_item` and `previous_item` to navigate search results. You can optionally specify a page range using the following syntax: `<begin_page,end_page>query`. The `chapter_search` command automatically fills the page range with the current chapter's page range.

Related Commands

`regex_search`, `next_item`, `previous_item`, `overview_next_item`, `overview_prev_item`

1.167 search_all_indexed_documents

Perform a fulltext search in all documents indexed by `create_fulltext_index_for_current_document` or `automatically_index_documents_for_fulltext_search`.

Related Commands

`create_fulltext_index_for_current_document`

1.168 select_current_search_match

Selects the current highlighted search result.

Related Commands

`search`, `regex_search`

1.169 select_freehand_drawings

Select the freehand drawings in the selected rectangle. The selected drawings can be moved by dragging the selection rectangle.

Related Commands

`delete_freehand_drawings`, `toggle_freehand_drawing_mode`, `toggle_pen_drawing_mode`

1.170 select_rect

1.171 select_ruler_text

Select the current line highlighted by ruler, you can use the up and down movement commands to move the selection and `toggle_line_select_cursor` to toggle between begin and end of the selection. Exit the selection mode by pressing escape (this is similar to vim's visual line mode).

Related Commands

`visual_mark_under_cursor`, `focus_text`, `toggle_line_select_cursor`, `move_ruler_to_next_block`, `move_ruler_to_prev_block`

1.172 semantic_search

Performs a semantic search on the current document. This method produces a relatively lower quality result but costs a lot less than

`semantic_search_extractive`.

Explanation of how this method works for more technical users: This method simply splits the document into paragraph-sized chunks and embeds each chunk using an embedding model. Then it finds the chunks with most similarity to the query.

Related Commands

`semantic_search_extractive`

1.173 `semantic_search_extractive`

Performs a semantic search on the current document. This method produces a relatively higher quality result than `semantic_search` but is more expensive.

Related Commands

`semantic_search`

1.174 `set_freehand_alpha`

Set the alpha transparency of freehand drawings.

Related Commands

`toggle_freehand_drawing_mode`, `toggle_pen_drawing_mode`, `set_freehand_type`

1.175 `set_freehand_thickness`

Set the thickness of freehand drawings. The initial thickness value is 1.

Related Commands

`toggle_freehand_drawing_mode`, `toggle_pen_drawing_mode`

1.176 `set_freehand_type`

Set the color symbol of freehand drawings. This is a symbol command which takes a single character as input. The color of drawing with symbol `s` will be the same color as highlights with symbol `s`.

Related Commands

`toggle_freehand_drawing_mode`, `toggle_pen_drawing_mode`

Related Configs

`highlight_color_[a-z]`

1.177 set_mark

Set a mark in the current location so we can return to it later using the `goto_mark` command. After executing `set_mark` command, sioyek will wait for you to press a symbol, which can be a lowercase or uppercase letter. Lowercase marks are local to the current file but uppercase marks are global. If you press a symbol that is already used as a mark, the previous mark will be overwritten. You can later return to the mark by executing `goto_mark` command with the same symbol. All marks are persistant, meaning they are saved when sioyek closes is reopened.

Related Commands

`goto_mark`

1.178 set_page_offset

1.179 set_select_highlight_type

Set the default highlight type. This is mainly used with `toggle_select_highlight` and `add_highlight_with_current_type`.

Related Commands

`toggle_select_highlight`

1.180 set_status_string, clear_status_string

Set the message in sioyek status bar. This message will be displayed until it is cleared using `clear_status_string`. This is mainly useful for scripts and plugins to display messages to the user.

1.181 set_view_state

view state to the state described by the given input text. The text format is : `{offset_x} {offset_y} {zoom_level} {push_state}`. For example: `0 1000 3 1` means we want to move to location (0, 1000) in the document with `zoom_level=3` and we want to push the previous state into history stack.

This command in mainly useful for scripting and it is probably not directly useful for end-users.

1.182 show_context_menu

Show a context menu below the mouse cursor. The commands shown in the menu can be configured using the following configs (depending on the object under mouse cursor):

- `context_menu_items`
- `context_menu_items_for_links`
- `context_menu_items_for_selected_text`
- `context_menu_items_for_highlights`
- `context_menu_items_for_bookmarks`
- `context_menu_items_for_overview`

Related Configs

`context_menu_items`, `context_menu_items_for_links`, `context_menu_items_for_selected_text`, `context_menu_items_for_highlights`, `context_menu_items_for_bookmarks`, `context_menu_items_for_overview`

1.183 show_custom_context_menu

1.184 show_custom_options

Given a |-separated list of options, displays the options to the user and returns the result. This is used for scripting and is not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = sioyek.Sioyek('')
result = s.show_custom_options('one|two|three')
s.set_status_string(f'You chose {result}')
```

1.185 show_text_prompt

Displays a text prompt to the user and returns the entered text. This is used for scripting and is not directly useful for end-users.

Example:

```
from sioyek import Sioyek
s = sioyek.Sioyek('')
result = s.show_text_prompt('Enter a string:')
s.set_status_string(f'You entered {result}')
```

1.186 show_touch_draw_controls

Show the freehand drawing menu for touch devices.

Related Commands
show_touch_main_menu

1.187 show_touch_highlight_type_select

Show the highlight type selector for touch devices.

Related Commands
add_highlight_with_current_type, set_select_highlight_type

1.188 show_touch_main_menu

Show the main menu for touch devices.

Related Commands
show_touch_settings_menu, show_touch_page_select

1.189 show_touch_page_select

Show the page selector for touch devices.

Related Commands
show_touch_settings_menu, show_touch_main_menu

1.190 show_touch_settings_menu

Show the settings menu for touch devices.

Related Commands
show_touch_main_menu, show_touch_page_select

1.191 show_touch_ui_for_config

Show the touch UI to configure the given configuration.

1.192 smart_jump_under_cursor

Go to the location of reference under mouse cursor. This works even when the document doesn't have links.

Related Commands
keyboard_smart_jump

1.193 move_down_smooth, move_up_smooth

Basic movement in the current document. Holding these commands results in a smooth continuous movement in the document unlike `move_down` and `move_up`.

Related Commands
move_down, move_up

1.194 start_mobile_text_selection_at_point

1.195 start_reading, stop_reading

Start reading from the current line highlighted by @concept(ruler) using the local text to speech engine.

1.196 start_reading_high_quality

Start reading from the current line highlighted by @concept(ruler) using the sioyek servers' high quality neural text to speech engine.

Related Commands
stop_reading

1.197 synchronize

Synchronize a desynchronized file with the server. On rare occasions files might become desynchronized where sioyek can not automatically decide whether to upload annotations to sioyek servers or not. For example suppose you have two copies of the same file on two different devices and with different annotations, and then you upload one of them to sioyek servers. When the other file is opened on the other device, sioyek will not automatically decide to upload the annotations to the server (because the user might not want that, e.g. perhaps those annotations are very sensitive data that you do not want uploaded). In such situations the other file is in desynchronized state and you can use this command to synchronize it with the server. This command will upload the annotations to the server if they are not already there.

1.198 synctex_forward_search

Given a latex file path and line number, performs a forward search to the corresponding location in the PDF document.

Related Commands
synctex_under_ruler, toggle_synctex, synctex_under_cursor

1.199 synctex_under_cursor

Perform a synctex search under mouse cursor (this works regardless of whether we are in synctex mode or not). The search command is configured using inverse_search_command.

Related Commands
toggle_synctex, synctex_under_ruler

1.200 synctex_under_ruler

Perform a synctex search to the location of the line highlighted by ruler.

1.201 sync_current_file_location

Upload the current file location to sioyek servers (can later be resumed on other devices with resume_to_server command). This command is usually performed automatically (only on files that have been uploaded to sioyek servers) but can be manually triggered with this command.

Related Commands
resume_to_server

1.202 test_command, export_config_names, open_selected_url, toggle_smooth_scroll_mode, export_python_api, print_undocumented_commands, print_non_default_configs, export_default_config_file, unregister_url_handler, toggle_one_window, register_url_handler, export_command_names, goto_begining, send_symbol, open_all_docs, print_undocumented_configs, toggle_show_last_command, move_selected_bookmark, type_text

1.203 toggle_text_mark, move_text_mark_forward, move_text_mark_backward, move_text_mark_forward_word, move_text_mark_backward_word, move_text_mark_down, move_text_mark_up

These commands are used to manipulate the text selection using keyboard. `move_{forward/backward}` commands move the cursor one character forward/backward and `move_{forward/backward}_word` commands move the cursor one word forward/backward, and `move_{down/up}` commands move the cursor one line down/up. `toggle_text_mark` toggles the position of cursor between the start and end of text selection.

Related Commands

`keyboard_select`, `select_ruler_text`

1.204 toggle_custom_color

Toggle between light and custom color schemes. The background and text color of custom color scheme can be configured using `custom_text_color` and `custom_background_color`.

All color configs in sioyek can be specialized for custom color mode by adding the `CUSTOM_` prefix. For example, if we want to adjust the `text_highlight_color` for custom color mode only, we could set `CUSTOM_text_highlight_color`.

Related Configs

`custom_text_color`, `custom_background_color`, `custom_color_mode_empty_background_color`

1.205 toggle_dark_mode

Toggle between light and dark color schemes.

All color configs in sioyek can be specialized for dark mode by adding the `DARK_` prefix. For example, if we want to adjust the `text_highlight_color` for dark mode only, we could set `DARK_text_highlight_color`.

Related Configs

`dark_mode_contrast`, `dark_mode_background_color`

1.206 toggle_drawing_mask

This is a symbol command which given a symbol `s`, toggles the visibility of freehand drawings with type `s`.

Related Commands

`toggle_freehand_drawing_mode`, `toggle_pen_drawing_mode`, `set_freehand_type`, `turn_on_all_drawings`, `turn_off_all_drawings`

1.207 toggle_fastread

1.208 toggle_freehand_drawing_mode

Toggle freehand drawing mode. In this mode you can use the mouse to draw on the document.

Related Commands

`set_freehand_thickness`, `set_freehand_type`, `toggle_pen_drawing_mode`

1.209 toggle_fullscreen

Toggle fullscreen mode.

Related Commands

`toggle_statusbar`, `toggle_scrollbar`

1.210 toggle_highlight_links

Highlight the PDF links.

1.211 toggle_horizontal_scroll_lock

Locks horizontal scrolling. This is useful for touchpad or touch devices when you want to always keep the document centered in the screen and accidental

horizontal scrolling is undesirable.

1.212 toggle_line_select_cursor

Toggle between begin and end of line text selection by `select_ruler_text`.

Related Commands
`select_ruler_text`

1.213 toggle_menu_collapse

Collapse/expand items in table of contents menu.

1.214 toggle_mouse_drag_mode

Toggle mouse drag mode. When enabled, you can drag the mouse to move the document (instead of text selection).

1.215 toggle_pdf_annotations

Toggles the visibility of PDF annotations (these are different from sioyek annotations, the PDF annotations are embedded in the PDF file itself).

1.216 toggle_pen_drawing_mode

Toggle pen drawing mode. In this mode you can use the stylus to draw on the document.

Related Commands
`set_freehand_thickness`, `set_freehand_type`, `toggle_freehand_drawing_mode`

1.217 toggle_presentation_mode, turn_on_presentation_mode

Toggle/turn on presentation mode, in this mode we fit each slide to the entire page and movement commands move to the next/previous slide.

1.218 toggle_reading

1.219 toggle_rect_hints

Shows the locations of touch mode shortcut rectangles and the commands that they perform.

1.220 `toggle_ruler_scroll_mode, toggle_visual_scroll`

Toggles ruler scroll mode. In this mode mouse wheel moves the ruler instead of scrolling the document.

Related Commands
`keyboard_select_line`, `ruler_under_cursor`

1.221 `toggle_scratchpad_mode`

Opens a scratchpad, you can use this scratchpad to draw or do calculations (this is mainly useful for touch/stylus devices).

Related Commands
`save_scratchpad`, `load_scratchpad`, `copy_drawings_from_scratchpad`, `copy_screenshot_to_scratchpad`

1.222 `toggle_scrollbar`

Toggle the scrollbar.

1.223 `toggle_select_highlight`

Toggle select highlight mode. In this mode all selected text will automatically be highlighted with the type set using `set_select_highlight_type`.

Related Commands
`add_highlight`, `set_select_highlight_type`

1.224 `toggle_statusbar`

Toggle the statusbar.

1.225 `toggle_synctex, turn_on_synctex`

Toggle/turn on synctex mode. In this mode, right clicking on the PDF file performs an inverse search from the corresponding location in the source latex file (using the configured `inverse_search_command`).

Related Configs
`inverse_search_command`

1.226 toggle_titlebar

Toggle the titlebar of the sioyek window.

1.227 toggle_two_page_mode

Toggles between two-page mode and single-page mode.

Related Configs
num_two_page_columns

1.228 toggle_typing_mode

1.229 toggle_window_configuration

Toggle helper window. The helper window displays the portal destination of the closest portal source to current location.

Related Commands
portal

1.230 turn_on_all_drawings, turn_off_all_drawings

Turn all drawings on/off.

Related Commands
toggle_freehand_drawing_mode, toggle_pen_drawing_mode, set_freehand_type, toggle_drawing_mask

1.231 undo_delete

Undo the last annotation delete operation.

Related Commands
generic_delete

1.232 undo_drawing

Undo the last drawn freehand drawing.

Related Commands
toggle_freehand_drawing_mode, toggle_pen_drawing_mode

1.233 upload_current_file

Upload the current file into sioyek servers.

Related Commands
delete_current_file_from_server

1.234 wait

Wait for the given duration (in miliseconds). This is mainly used for testing purposes.

1.235 wait_for_renders_to_finish, wait_for_search_to_finish, wait_for_indexing_to_finish, wait_for_downloads_to_finish

Wait for all pending renders/searches/indexing to finish. This is mainly used for testing and scripting (for example we may want to wait for renders to finish before we compare a screenshot to the saved screenshot).

1.236 write_annotations_file

Write the annotations of current file into an annotations file next to the current file. The annotations file will have the same name as the current file with a `sioyek.annotations` extension. This is useful when you want to share the annotations with others or move them to another computer.

Alternatively you can set the `annotations_directory` config to a directory path and the annotations file will be written there instead of next to the current file.

Related Commands
load_annotations_file

Related Configs
annotations_directory

1.237 zoom_in, zoom_out, zoom_in_cursor, zoom_out_cursor

Zoom in/out in the current document. The `zoom_in_cursor` and `zoom_out_cursor` commands zoom in/out around the cursor position while the `zoom_in` and `zoom_out` commands zoom in/out around the center of the screen.

Related Commands

zoom_in_overview, zoom_out_overview, fit_to_page_width

Related Configs

zoom_inc_factor, wheel_zoom_on_cursor???, scroll_zoom_inc_factor???

1.238 zoom_in_overview, zoom_out_overview

Zoom in/out in the overview window.

Related Commands

zoom_in, zoom_out

2 Configs

2.1 [bool] adjust_annotation_colors_for_dark_mode

Automatically adjust annotation colors to be more appropriate in dark/custom color modes.

Related Commands

add_highlight, add_freetext_bookmark

2.2 [bool] align_link_dest_to_top

Normally when jumping to links, we align the middle of the screen with the link destination. If this option is set we align the top of the screen instead.

2.3 [bool] allow_horizontal_drag_when_document_is_small

Normally when the document is smaller than screen width, we center in the screen and disallow horizontal mouse dragging to keep the document centered. If this option is set, then we allow the document to be dragged even when it is smaller than the screen width.

2.4 [bool] allow_main_view_scroll_while_in_overview

Allow the main document to be scrolled when overview is opened (otherwise we use scrolling outside the overview while the overview window is opened to move between possible overview targets).

2.5 [string] annotations_directory

Normally sioyek keeps some annotations files next to the pdf files (e.g. the freehand drawings file). If you don't want this you can specify the `annotations_directory` and then sioyek keeps the annotations files in that directory.

Related Commands
`toggle_freehand_drawing_mode`, `write_annotations_file`

2.6 [bool] autocenter_ruler

Always center the document on the ruler when moving the ruler.

Related Commands
`ruler_under_cursor`, `toggle_ruler_scroll_mode`

2.7 [bool] automatically_download_matching_paper_name

If this config is not set, when downloading papers, we search the paper name and show the user a list of matching papers and download it when the user selects one of the options. If this option is set and one of the found paper matches the query title exactly, we no longer show the user a list and automatically download the matching paper.

Related Commands
`download_link`, `download_overview_paper`

2.8 [bool] automatically_index_documents_for_fulltext_search

Automatically index opened documents for fulltext search.

Related Commands
`create_fulltext_index_for_current_document`, `search_all_indexed_documents`

2.9 [bool] automatically_update_checksum_when_document_is_changed

When the document is changed (e.g. a latex document being edited) automatically update the checksum.

2.10 [bool] automatically_upload_portal_destination_for_synced_documents

When uploading a document to sioyek servers, also upload the portal destinations for portals in that document.

2.11 [bool] auto_login_on_startup

Automatically login to sioyek servers on startup (if previous credentials are available).

2.12 [bool] auto_rename_downloaded_papers

If set, sioyek renames the downloaded papers to an automatically determined file name (e.g. instead of a cryptic name like `23434.234.pdf` it will be renamed to something like `some_paper_title.pdf`).

Related Commands

`download_link`, `download_overview_paper`

2.13 [int] background_bookmarks_pixel_budget

Maximum number of pixels allocated to cached freetext bookmarks.

2.14 [color3] background_color, custom_color_mode_empty_background_color, dark_mode_background_color

The empty background color in light/dark/custom color modes.

2.15 [bool] case_sensitive_search

If set, we match the search queries in a case-sensitive manner.

Related Commands

`search`

Related Configs

`smartcase_search`

2.16 [bool] check_for_updates_on_startup

Check for software updates when sioyek starts.

2.17 [string] shift_click_command, control_click_command, command_click_command, hold_middle_click_command, tablet_pen_click_command, tablet_pen_double_click_command, right_click_command, middle_click_command, shift_middle_click_command, control_middle_click_command, command_middle_click_command, alt_middle_click_command, shift_right_click_command, control_right_click_command, command_right_click_command, alt_click_command, alt_right_click_command

@concept(macro) commands to run when the corresponding button is clicked (while possibly holding modifier keys). Example:

```
alt_click_command toggle_dark_mode;toggle_scrollbar;set_status_string('hi there')
```

2.18 [bool] collapsed_toc

Open the table of contents in collapsed state by default.

Related Commands
goto_toc

2.19 [string] context_menu_items, context_menu_items_for_links, context_menu_items_for_selected_text, context_menu_items_for_highlights, context_menu_items_for_bookmarks, context_menu_items_for_overview

Items in context menu to show when `show_context_menu` is executed and the cursor is on the object specific to the option (`context_menu_items` is for the case where no special object is under the cursor).

If `right_click_context_menu` is set, you can open this all these menus (except for `context_menu_items`) by right-clicking on objects in the page.

Related Commands
show_context_menu

Related Configs
right_click_context_menu

2.20 [bool] create_table_of_contents_if_not_exists

If the document doesn't have a table of contents, try to automatically generate one (this is a heuristic and doesn't work perfectly all the time).

Related Commands
goto_toc

2.21 [color3] custom_text_color, custom_background_color

Text and background colors in custom color mode.

Related Commands
toggle_custom_color

2.22 [float] dark_mode_contrast

The color contrast in dark mode.

Related Commands
toggle_dark_mode

2.23 [string] default_open_file_path

The default root path when opening files.

2.24 [int] documentation_font_size

Font size of documentation, when viewing the embedded documentation widget.

2.25 [string] document_location_mismatch_strategy

Specifies what to do when there is a mistmatch between a local document and the last location uploaded to sioyek servers. Possible values are:

- `local`: remain in the local position
- `server`: move to the server position
- `ask`: prompt the user to choose a position
- `show_button`: show a resume button in sioyek statusbar

Related Commands
resume_to_server

2.26 [bool] dont_center_if_synctex_rect_is_visible

When performing a synctex search, if the target is already visible on the screen we don't move the document to center on the target.

Related Commands
toggle_synctex

Related Configs
synctex_highlight_timeout, synctex_highlight_color

2.27 [string] epub_css

CSS to apply to epub documents.

2.28 [int] epub_width, epub_height, epub_font_size

Configure the appearance of epub documents.

2.29 [bool] exact_highlight_select

When adding the selected highlight, add the exact highlighted text (otherwise we highlight an entire word event when a part of it is selected).

Related Commands
add_highlight

2.30 [string] external_text_editor_command

The command line program to use when running `open_external_text_editor` command. In this config, `%{file}` expands to the file that should be opened. For example:

```
external_text_editor_command nvim "%{file}"
```

Related Commands
open_external_text_editor

2.31 [string] extract_table_prompt

The plain english prompt to use when extracting table data using a large language model with `extract_table` command.

Example:

`extract_table_prompt` Extract the table in this image into a markdown table. Take your time a

Related Commands
`extract_table`

2.32 [bool] fill_textbar_with_selected_text

When opening the textbar (e.g. when executing `search` or any other command that requires text input) automatically fill the input with the selected text.

Related Commands
`search`

2.33 [float] fit_to_page_width_ratio

The screen width ratio when using `fit_to_page_width_ratio` command.

Related Commands
`fit_to_page_width_ratio`

2.34 [bool] flat_toc

Show the table of contents as a flat list instead of a hierarchial tree. This can improve the performance on documents with extremely large table of contents.

Related Commands
`goto_toc`

2.35 [int] font_size

The font size for UI menus.

Related Configs
`status_bar_font_size`

2.36 [color3] freetext_bookmark_color

Text color to use when adding new freetext bookmarks.

Related Commands
`add_freetext_bookmark`

Related Configs

`freetext_bookmark_font_size`

2.37 [int] freetext_bookmark_font_size

Font size to use when adding new freetext bookmarks.

Related Commands

`add_freetext_bookmark`

Related Configs

`freetext_bookmark_color`

2.38 [bool] fuzzy_searching

(Deprecated) Whether we should employ fuzzy searching in menus. As we are using a fuzzy algorithm by default in more and more menus this option is becoming less relevant as time goes on.

2.39 [float] gamma

The gamma value, each pixel value `p` will be replace with `p^gamma`. Higher gamma values make fonts look thicker and lower gamma values make them look thinner.

2.40 [bool] hide_overlapping_link_labels

When highlighting links in a document with overlapping links, show the label only for one of the overlapping links (avoids clutter in some malformed documents).

Related Commands

`open_link`

2.41 [color3] highlight_color_[a-z]

Specifies the color for each of highlight types. For example `highlight_color_r` specifies the color of highlights with symbol `r`.

Related Commands

`add_highlight`

2.42 [bool] highlight_links

Whether we should highlight PDF links.

2.43 [bool] highlight_middle_click

If set, middle clicking on selected text highlights it with the current highlight type.

Related Commands
`add_highlight`, `add_highlight_with_current_type`, `set_select_highlight_type`

2.44 [bool] hover_overview

Open the overview page when mouse cursor hovers over a link (I don't recommend using this config because it might not work well with other sioyek features, just right click on the link to create the overview).

2.45 [bool] ignore_scroll_events

Ignore scroll events (e.g. useful to avoid moving in presentation mode when accidentally touching the touchpad).

2.46 [bool] ignore_whitespace_in_presentation_mode

Ignore whitespace when fitting pages to screen in presentation mode.

Related Commands
`toggle_presentation_mode`

2.47 [bool] incremental_search

If this is set, then we perform searches as user is typing the search query.

Related Commands
`search`

2.48 [bool] initial_snapped_dragging

If set, when dragging the document (e.g. in touch mode) we ignore very small horizontal scrolls because when the user is trying to scroll vertically they probably will also do some horizontal scrollling inadvertently. So we start the dragging in

a “snapped” state (meaning we are snapped to the original horizontal position) and only unspan when the user moves horizontally past a threshold.

2.49 [string] inverse_search_command

The command line program to open the corresponding file when peforming a synctex inverse search. `%1` will expand to the path of TeX file and `%2` will exapnd to the line number.

For example here is how to configure it for vscode on windows:

```
inverse_search_command      "C:\path\to\Code.exe" -r -g "%1":%2
```

Related Commands

`toggle_synctex`, `synctex_under_cursor`, `synctex_under_ruler`

2.50 [bool] inverted_horizontal_scrolling

Invert the horizontal scrolling when using touchpad.

2.51 [bool] invert_selected_text

Invert the selected text to highlight it.

2.52 [bool] keyboard_point_selection

If set, when executing commands that require a point on the screen to be selected, we show a list of labels on the screen and allow the user to select the point by typing the label using keyboard.

2.53 [color4] keyboard_select_background_color, keyboard_select_text_color, keyboard_selected_tag_background_color, keyboard_selected_tag_text_color

The color of the tags displayed for keyboard commands.

Related Commands

`open_link`, `keyboard_select`

Related Configs

`tag_font_face`, `keyboard_point_selection`, `keyboard_select_font_size`

2.54 [int] keyboard_select_font_size

The font size of the tags displayed for keyboard commands.

Related Commands
open_link, keyboard_select

Related Configs
tag_font_face, keyboard_point_selection

2.55 [bool] linear_filter

Perform linear texture filtering instead of nearest neighbor (should not be necessary unless you use non-interger render scales).

2.56 [color3] link_highlight_color

Highlight color to use when highlighting links.

Related Commands
open_link, toggle_highlight_links

2.57 [int] max_created_toc_size

The maximum size of automatically generated table of contents.

Related Configs
create_table_of_contents_if_not_exists

2.58 [string] menu_matched_search_highlight

The CSS style used to highlight matched search results in menus.

2.59 [float] menu_screen_width_ratio, menu_screen_height_ratio

The ratio of screen width/height to use for menus.

Related Commands
command, open_prev_doc, goto_highlight, goto_bookmark

2.60 [symbol] middle_click_search_engine, shift_middle_click_search_engine

When middle clicking on a paper name, we will search for it in the engine (as configured in search_url_[a-z]???) set here.

For example:

```
search_url_s https://scholar.google.com/scholar?q=
middle_click_search_engine s
```

means that we will search the paper name in google scholar when user middle clicks on a paper name.

Related Commands

external_search

Related Configs

search_url_[a-z]

2.61 [float] move_screen_ratio

The ratio of screen height to move when executing screen_down and screen_up.

Related Commands

screen_down, screen_up

2.62 [bool] numeric_tags

When performing keyboard_ commands that require a point to be selected, we associate a tag with each possible target. If this option is set, the tags only use numerical values instead of alphabetical values.

Related Commands

keyboard_select

2.63 [int] num_cached_pages

Total number of cached rendered pages. Higher values may reduce flickering and power consumption (because pages have to be re-rendered less) at the cost of increased memory usage.

2.64 [int] num_prerendered_next_slides, num_prerendered_prev_slides

Number of next/previous pages to prerender in presentation mode.

Related Commands
toggle_presentation_mode

Related Configs
prerender_next_page_presentation

2.65 [int] num_two_page_columns

Changes the number of page columns in "two" page mode.

Related Commands
toggle_two_page_mode

2.66 [color3] overview_reference_highlight_color

Highlight color to use when highlighting the automatically detected overview paper name.

Related Commands
overview_definition, download_overview_paper

2.67 [int/color3] page_separator_width, page_separator_color

Color and size of separator between pages.

2.68 [int] page_space_x, page_space_y

Spacing between pages in two page mode.

Related Commands
toggle_two_page_mode

2.69 [string] papers_folder_path

Path of the directory where downloaded papers should move to.

Related Commands

`download_clipboard_url`, `download_overview_paper`, `download_paper_with_url`, `download_paper_with_name`, `download_paper_under_cursor`

2.70 [bool] paper_download_should_create_portal

When downloading papers, create a portal from the source document to the downloaded document. Otherwise (if this config is 0) we open the downloaded document in a new window.

Related Commands

`download_link`, `download_overview_paper`

2.71 [int] prerendered_page_count

Number of pages to pre-render.

2.72 [bool] prerender_next_page_presentation

Prerender the next page in presentation mode (avoids flickering when moving to the next slide).

Related Commands

`toggle_presentation_mode`

2.73 [bool] preserve_image_colors_in_dark_mode, inverted_preserved_image_colors

Preserve original image colors in dark mode and custom color mode. If `inverted_preserved_image_colors` is set, then we invert the original image colors in custom color mode.

Related Commands

`toggle_dark_mode`, `toggle_custom_color`

2.74 [color4/color3] question_bookmark_background_color, question_bookmark_text_color

The background and text color of question bookmarks (the bookmarks starting with `?`, see `add_freetext_bookmark` for more information).

2.75 [bool] real_page_separation

The page separator configured using `page_separator_width` doesn't actually separate the pages, it is simply a box drawn to distinguish the pages. If `real_page_separation` is set, then we actually move the pages to separate them (technically it is less efficient than the other method which is why it is not the default but it shouldn't matter in most cases). Also note that when this option is set, the distance between pages is not configured with `page_separator_width` rather it uses `page_space_y`.

Related Configs
`page_separator_width`

2.76 [int] reload_interval_miliseconds

We check the document for changes (e.g. a latex document might be changed from external sources) every `reload_interval_miliseconds`.

2.77 [bool] render_freetext_borders

Render the borders around freetext bookmarks.

Related Commands
`add_freetext_bookmark`

2.78 [bool] render_pdf_annotations

If set to 0, we don't render PDF annotations (by PDF annotations I mean the native PDF annotations embedded in the PDF file and not the sioyek annotations).

Related Commands
`toggle_pdf_annotations`

2.79 [string] resize_command

@concept(macro) commands to run when sioyek window is resized. Example:

```
resize_command fit_to_page_width_smart
```

2.80 [bool] right_click_context_menu

Show a context menu when user right clicks on annotations/overview. The commands displayed in this context menu can be configured using

`context_menu_items` commands.

Related Commands
`show_context_menu`

Related Configs
`context_menu_items`

2.81 [int] ruler_auto_move_threshold_distance

In touch mode, you are able to move the ruler by pressing on the move down rect and then moving the cursor, each time the cursor moves `ruler_auto_move_threshold_distance` we move to the next line.

2.82 [color3] ruler_color

Ruler color.

Related Commands
`keyboard_select_line`

2.83 [string] ruler_display_mode

Specifies how the ruler should be rendered. The possible values are:

- `box`: draw a box around selected line
- `slit`: draw a shadow on everything except the selected line
- `underline`: draw a line under the selected line
- `highlight_below`: highlight the entire screen area below the line
- `highlight`: highlights the ruler line

Related Commands
`ruler_under_cursor`

2.84 [color3] ruler_marker_color

The ruler marker color to highlight the next left side of the screen when using `move_ruler_next`.

Related Commands
`keyboard_select_line`, `move_ruler_next`, `move_ruler_prev`

2.85 [float] ruler_next_page_end_pos, ruler_next_page_begin_pos

`ruler_next_page_end_pos` determines when we should move to the next page when using the ruler and when we do so, `ruler_next_page_begin_pos` determines where the new location of the ruler should be in the screen.

`ruler_next_page_begin_pos` is relative to the center of the screen and `ruler_next_page_end_pos` is relative to the bottom of the screen. For example, `ruler_next_page_begin_pos`=1 means we move one unit (each unit is half screen height) up from the middle of the screen which means we move to the top of the screen when moving to the next page.

Related Commands

`move_ruler_down`, `move_ruler_up`, `toggle_ruler_scroll_mode`

2.86 [int] ruler_padding, ruler_x_padding

Ruler padding when using `slit` ruler display mode.

Related Commands

`keyboard_select_line`

Related Configs

`ruler_display_mode`

2.87 [int] ruler_pixel_width

Ruler thickness when `ruler_display_mode` is set to `underline`.

Related Commands

`ruler_under_cursor`, `focus_text`

Related Configs

`ruler_display_mode`

2.88 [color4] ruler_slit_color

Ruler color when `ruler_display_mode` is set to `slit`.

Related Commands

keyboard_select_line, ruler_under_cursor

Related Configs

ruler_display_mode

2.89 [bool] save_externally_edited_text_on_focus

If this option is set, when editing text using open_external_text_editor command, we accept the externally edited text when the sioyek window gains focus again (otherwise the user has to manually press enter to accept the input).

Related Commands

open_external_text_editor

2.90 [float] scrollview_sensitivity

The relative sensitivity when scrolling the overview window.

Related Commands

overview_definition

2.91 [color3] search_highlight_color

Highligh color of search matches.

Related Commands

search, regex_search, semantic_search, semantic_search_extractive

2.92 [string] search_url_[a-z]

Search url for external_search command. After executing external search, the user can enter the symbol corresponding to the configured search engine to perform the search using that engine.

For example if we have the following in prefs_user.config:

```
search_url_g https://www.google.com/search?q=
search_url_s https://scholar.google.com/scholar?q=
```

Then executing `external_search` followed by `s` will search google and if it is followed by `s` it will search google scholar.

2.93 [float] server_and_local_document_mismatch_threshold

When the location of server and document do not match (for example when the user has moved the document to another location in another device) if the distance is greater than this threshold a resume button will be displayed in the statusbar which allows the user to resume to the server location.

Related Commands
resume_to_server

2.94 [string] shared_database_path

Path of shared database to use, if not set we use the default path.

2.95 [bool] should_highlight_unselected_search

Whether we should highlight the found search results that are not the current search result.

Related Commands
search

Related Configs
unselected_search_highlight_color

2.96 [bool] should_launch_new_window

When opening a new file from command line, use a new sioyek window if one already exists.

2.97 [bool] should_load_tutorial_when_no_other_file

When there is no other file to open (e.g. due to sioyek being opened for the first time) show the sioyek tutorial.

2.98 [bool] should_warn_about_user_key_override

Print a warning message in console when a key override is detected in `keys_user.config`.

2.99 [bool] show_most_recent_commands_first

When opening the command menu show the most recent commands executed in the current session first.

Related Commands
command

2.100 [bool] show_reference_overview_highlights

Highlight the reference paper name in overview window (this is the automatically detected paper name which will be downloaded with `download_overview_paper` command).

Related Commands
overview_link, overview_definition

2.101 [bool] single_click_selects_words

Normally when selecting text using mouse, we select individual characters, unless the user has double clicked to initiate the selection, in which case we select entire words instead of individual characters.

If `single_click_selects_words` is set, then we select words even when user uses single-click to initiate text selection.

2.102 [bool] sliced_rendering

Normally we render entire pages as a whole. This can cause problems on high zoom levels on low-memory devices becasue a huge chunk of memory with the correct size might not be available. If `sliced_rendering` is set, instead of rendering pages as a whole, we slice the pages into multiple strips and render each strip.

2.103 [bool] smartcase_search

If set, we match the search queries in a case-insensitive manner if all the characters in the query is lowercase and otherwise we perform a case-sensitive search.

Related Commands
search

2.104 [float] smooth_move_max_velocity

The speed of `move_*_smooth` commands.

Related Commands

`move_down_smooth`, `move_up_smooth`

2.105 [bool] sort_bookmarks_by_location

Sort bookmarks by location (instead of creation date).

Related Commands

`goto_bookmark`

2.106 [string] startup_commands

@concept(macro) commands to run then sioyek starts up. For example:

```
startup_commands toggle_dark_mode;toggle_scrollbar;set_status_string(hi there)
```

Will set the color scheme to dark mode and enable scrollbar and show a message in sioyek statusbar when sioyek starts up.

2.107 [color3] status_bar_color, status_bar_text_color

Text and background colors of statusbar.

Related Commands

`toggle_statusbar`

2.108 [int] status_bar_font_size

Font size of the status bar.

2.109 [string] status_bar_format, right_status_bar_format, status_*_command

The items and format to show in the statusbar. The default value is:

```
[ %{current_page} / %{num_pages} ]%{chapter_name}%{search_results}%{search_progress}
%{link_status}%{waiting_for_symbol}%{indexing}%{preview_index}%{synctex}%{drag}
%{presentation}%{visual_scroll}%{locked_scroll}%{highlight}%{freehand_drawing}
%{rect_select}%{custom_message}%{download}%{download_button}%{network_status}
%{tts_status}%{tts_rate}
```

The `right_status_bar_format` is similar, but determines what to display on right-aligned statusbar.

Here is what each of the `%{}` variables expand to:

- `%{current_page}` expands to the current page number
- `%{current_page_label}` expands to the the label of the current page (might be different from `current_page` for example some documents have pages labeled with roman numerals, e.g. XII)
- `%{num_pages}` expands to the total number of pages in current document
- `%{chapter_name}` expands to the name of current chapter
- `%{document_name}` expands to the file name of current document
- `%{auto_name}` expands to automatically detected document name
- `%{search_results}` expands to the search results (if there is a search active)
- `%{search_progress}` expands to the current search progress (if there is one in progress)
- `%{link_status}` specifies whether we are linking (that is the source of a `portal` has been set and we are waiting for the destination)
- `%{waiting_for_symbol}` specifies if a command is expecting a symbol to be entered
- `%{indexing}` specifies if the current document is currently being indexed
- `%{preview_index}` if there are more than one possible overviews available for the overview window, this option shows how many there are and what is the current index
- `%{synctex}` displays if we are in synctex mode (`toggle_synctex`)
- `%{drag}` displays if we are in mouse drag mode (`toggle_mouse_drag_mode`)
- `%{presentation}` displays if we are in presentation mode (`toggle_presentation_mode`)
- `%{visual_scroll}` displays if we are in ruler scorll mode (`toggle_ruler_scroll_mode`)
- `%{locked_scroll}` displays if we have locked horizontal scrolling (`toggle_horizontal_scroll_lock`)
- `%{highlight}` displays information about the current highlight state (`set_select_highlight_type`)
- `%{freehand_drawing}` displays if we are in freehand drawing mode (`toggle_freehand_drawing_mode`)
- `%{rect_select}` displays if a command requires a rectangle to be selected
- `%{point_select}` displays if a command requires a point to be selected
- `%{custom_message}` user message that can be set using `set_status_string`
- `%{download}` displays if we are currently downloading a paper
- `%{download_button}` a button that displays when the current overview is a reference to a paper, clickin on this button downloads the paper
- `%{closest_bookmark}` displays the closest bookmark to current location
- `%{closest_portal}` displays the closest portal to the current location
- `%{selected_highlight}` displays the comment of the selected highlight
- `%{mode_string}` displays the current mode string (this can be useful when defining @concept(macro)s)
- `%{network_status}` displays the current network status

- %{tts_status} displays the current text to speech status
- %{tts_rate} displays the current text to speech speed
- %{custom_message_a} to %{custom_message_d} expands to a custom message which can be set using status_custom_message_[a-d]???

Note that clicking on many of these items performs a relevant command. For example clicking on the text expanded from ${current_page} shows a page-selection widget or clicking on %{chapter_name} opens the table of contents. The exact command executed when some part of the statusbar is clicked can be configured using status_*_command config options where * can be any of the options described above. For example if we have the following in the prefs_user.config file:

```
status_num_pages_command toggle_dark_mode
```

then clicking on the number of pages in the statusbar toggles dark mode.

2.110 [string] status_custom_message_[a-d], status_custom_message_[a-d]_command

Show custom messages which can be shown in statusbar if %{custom_message_a} to %{custom_message_d} is added to status_bar_format. When the message is clicked, the command configured in status_custom_message_[a-d]_command??? will be run.

Related Configs

status_bar_format, right_status_bar_format, status_custom_message_[a-d]_command

2.111 [string] status_font

Font face to use for menus.

2.112 [int] strike_line_width

The strike width when adding strike highlights (highlights with type _).

Related Commands

add_highlight

2.113 [bool] super_fast_search

If set, we index the document so that searches can be performed instantaneously. Some other sioyek features work only if this option is enabled so I recommend to

keep it enabled (the extra memory requirement due to this option being enabled is extremely small).

Related Commands

`search`, `regex_search`

2.114 [color3] synctex_highlight_color

Highlight color to use when highlighting synctex search results. This only applies when `use_ruler_to_highlight_synctex_line` is set to 0, otherwise we use the ruler to highlight the line.

Related Commands

`synctex_under_cursor`, `synctex_under_ruler`, `toggle_synctex`

Related Configs

`use_ruler_to_highlight_synctex_line`, `synctex_highlight_timeout`, `synctex_highlight_timeout`

2.115 [float] synctex_highlight_timeout

Duration (in seconds) to highlight the synctex line. If the duration is -1, the highlight will stay indefinitely.

Related Commands

`synctex_under_cursor`, `synctex_under_ruler`, `toggle_synctex`

Related Configs

`synctex_highlight_color`

2.116 [string] table_extract_behaviour

What to do with extracted table. The possible values are:

- `bookmark`: Create a freetext bookmark with the extracted table
- `copy`: Copy the extracted table into clipboard

Related Commands

`extract_table`

2.117 [string] tag_font_face

Font face to use for keyboard tags.

Related Commands
open_link, keyboard_select

2.118 [color3] text_highlight_color

The highlight color of selected text (e.g. when user selects text using mouse or using commands like keyboard_select).

Related Commands
keyboard_select

2.119 [bool] toc_jump_align_top

When jumping to a table of contents entry, align the top of the screen with the target location (instead of center of the screen).

2.120 [float] touchpad_sensitivity

Relative scrolling sensitivity when using touchpad or mouse wheel, this is a multiplier that modifies vertical_move_amount so the overal move amount when using touchpad or mouse wheel is touchpad_sensitivity * vertical_move_amount.

Related Commands
move_down, move_up, move_left, move_right

Related Configs
vertical_move_amount, horizontal_move_amount

2.121 [bool] touch_mode

This config is suitable for touch devices, if set, many behaviours of sioyek change to better support touch devices. For exmaple dragging on the screen moves the document instead of selecting text and menus are now optimized for touch devices.

2.122 [string] back_rect_tap_command, back_rect_hold_command, forward_rect_tap_command, forward_rect_hold_command, middle_left_rect_tap_command, middle_left_rect_hold_command, middle_right_rect_tap_command, middle_right_rect_hold_command, ruler_next_tap_command, ruler_next_hold_command, ruler_prev_tap_command, ruler_prev_hold_command

@concept(macro) commands to run when the corresponding rectangle is tapped or held (only works in touch mode). You can view the location of these rectangles by executing executing `toggle_rect_hints`.

2.123 [float] tts_rate

The text to speech speaking speed when using text to speech commands.

Related Commands
`start_reading`, `start_reading_high_quality`

2.124 [string] ui_font

Font face to use for menus.

2.125 [rect] portrait_back_ui_rect, portrait_forward_ui_rect, landscape_back_ui_rect, landscape_forward_ui_rect, portrait_visual_mark_next, portrait_visual_mark_prev, landscape_visual_mark_next, landscape_visual_mark_prev, landscape_middle_right_rect, portrait_middle_right_rect, landscape_middle_left_rect, portrait_middle_left_rect

Configures the rectangles in touch mode. If the user taps on these rectangles, we execute the corresponding command as configured in `touch_rect_commands???`.

Related Configs
`touch_rect_commands`

2.126 [color3] ui_text_color, ui_background_color, ui_selected_text_color, ui_selected_background_color

Text and background colors of ui menus.

2.127 [color3] unselected_search_highlight_color

The highlight color to highlight unselected search matches when `should_highlight_unselected_search` is set.

Related Commands

`search`, `regex_search`, `semantic_search`, `semantic_search_extractive`

Related Configs

`should_highlight_unselected_search`

2.128 [bool] use_ruler_to_highlight_synctex_line

Use the ruler to highlight the synctex search result (instead of highlighting it with a color).

Related Commands

`toggle_synctex`

2.129 [bool] use_system_theme, use_custom_color_as_dark_system_theme

Try to use system theme for light/dark modes (might not work in some operating systems). If `use_custom_color_as_dark_system_theme` is set, then we use the custom color mode instead of dark mode when system theme is set to dark.

2.130 [float] vertical_move_amount, horizontal_move_amount

The amount to move when executing movement commands (including mouse wheel).

Related Commands

`move_down`, `move_up`, `move_left`, `move_right`, `move_ruler_down`, `move_ruler_up`

Related Configs
`touchpad_sensitivity`

2.131 [bool] wheel_zoom_in_cursor

When performing zoom using control+mouse wheel, zoom on the mouse cursor instead of the center of the screen.

2.132 [int] main_window_size, helper_window_size, main_window_move, helper_window_move, single_main_window_size, single_main_window_move, overview_size, overview_offset

Default size and offset of sioyek windows. the `single_*` is used when only the main sioyek window is visible (no helper window) otherwise we use the other values.

2.133 [bool] zoom_inc_factor

The amount to multiply/divide the zoom level when executing zoom commands. For example, if the current zoom level is 2 and `zoom_inc_factor` is 1.5, then after executing `zoom_in`, the zoom level will be `2 * 1.5 = 3`.

Related Commands
`zoom_in`, `zoom_out`, `zoom_in_cursor`, `zoom_out_cursor`