

## AI LAB 10

### 1BM21CS203

Create a knowledgebase consisting of first order logic statements and prove the given query using forward reasoning.

```
import re

def isVariable(x):
    return len(x) == 1 and x.islower() and x.isalpha()

def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return matches

def getPredicates(string):
    expr = '([a-z~]+\)\([^&]+\)'
    return re.findall(expr, string)

class Fact:
    def __init__(self, expression):
        self.expression = expression
        predicate, params = self.splitExpression(expression)
        self.predicate = predicate
        self.params = params
        self.result = any(self.getConstants())

    def splitExpression(self, expression):
        predicate = getPredicates(expression)[0]
        params = getAttributes(expression)[0].strip('()').split(',')
        return [predicate, params]

    def getResult(self):
        return self.result

    def getConstants(self):
        return [None if isVariable(c) else c for c in self.params]

    def getVariables(self):
        return [v if isVariable(v) else None for v in self.params]

    def substitute(self, constants):
        c = constants.copy()
        f = f"{self.predicate}({''.join([constants.pop(0) if
isVariable(p) else p for p in self.params])})"
        return Fact(f)
```

```

class Implication:
    def __init__(self, expression):
        self.expression = expression
        l = expression.split('=>')
        self.lhs = [Fact(f) for f in l[0].split('&')]
        self.rhs = Fact(l[1])

    def evaluate(self, facts):
        constants = {}
        new_lhs = []
        for fact in facts:
            for val in self.lhs:
                if val.predicate == fact.predicate:
                    for i, v in enumerate(val.getVariables()):
                        if v:
                            constants[v] = fact.getConstants()[i]
                            new_lhs.append(fact)
            predicate, attributes = getPredicates(self.rhs.expression)[0],
str(getAttributes(self.rhs.expression)[0])
            for key in constants:
                if constants[key]:
                    attributes = attributes.replace(key, constants[key])
            expr = f'{predicate}{attributes}'
            return Fact(expr) if len(new_lhs) and all([f.getResult() for f
in new_lhs]) else None

class KB:
    def __init__(self):
        self.facts = set()
        self.implications = set()

    def tell(self, e):
        if '=>' in e:
            self.implications.add(Implication(e))
        else:
            self.facts.add(Fact(e))
        for i in self.implications:
            res = i.evaluate(self.facts)
            if res:
                self.facts.add(res)

    def query(self, e):
        facts = set([f.expression for f in self.facts])
        i = 1
        print(f'Querying {e}:')
        for f in facts:
            if Fact(f).predicate == Fact(e).predicate:
                print(f'\t{i}. {f}')

```

```

        i += 1

def display(self):
    print("All facts: ")
    for i, f in enumerate(set([f.expression for f in self.facts])):
        print(f'\t{i+1}. {f}')

```

Output:

```

▶ kb = KB()
kb.tell('missile(x)=>weapon(x)')
kb.tell('missile(M1)')
kb.tell('enemy(x,America)=>hostile(x)')
kb.tell('american(West)')
kb.tell('enemy(Nono,America)')
kb.tell('owns(Nono,M1)')
kb.tell('missile(x)&owns(Nono,x)=>sells(West,x,Nono)')
kb.tell('american(x)&weapon(y)&sells(x,y,z)&hostile(z)=>criminal(x)')
kb.query('criminal(x)')
kb.display()

```

```

Querying criminal(x):
  1. criminal(West)
All facts:
  1. hostile(Nono)
  2. sells(West,M1,Nono)
  3. american(West)
  4. owns(Nono,M1)
  5. enemy(Nono,America)
  6. weapon(M1)
  7. criminal(West)
  8. missile(M1)

```