

Basic Structure of HTML5

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
</head>
```

```
<body>
```

```
</body>
```

```
</html>
```

Assignment 1

Create a simple HTML page displaying personal details using text formatting tags.

CODE:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Assignment 1 - Personal Details</title>
</head>
<body bgcolor="#f0f8ff">
  <!-- Header Section -->
  <center>
    <h1 style="color: navy;">STUDENT BIO-DATA</h1>
    <h3>Department of Computer Engineering</h3>
  </center>
  <hr size="3" color="black">

  <!-- Personal Info Section -->
  <h2>1. Personal Information</h2>
  <p>
    <b>Full Name:</b> Rohit S. Sharma<br>
    <b>Date of Birth:</b> 15<sup>th</sup> August 2004<br>
    <b>Email ID:</b> <u>rohit.sharma@example.com</u><br>
    <b>Address:</b> <i>Flat No. 101, Sunshine Society, Pune - 411041.</i>
  </p>
  <!-- Education Section -->
  <h2>2. Educational Qualification</h2>
  <p>
    <strong>Degree:</strong> Bachelor of Engineering (Computer)<br>
    <strong>College:</strong> Savitribai Phule Pune University<br>
    <strong>Current Year:</strong> Second Year (SE)<br>
    <strong>Percentage:</strong> <mark>85.50%</mark>
  </p>
  <!-- Hobbies Section -->
  <h2>3. Hobbies & Interests</h2>
  <p>
    I enjoy:
    <br> &bull; Reading <small>(Science Fiction)</small>
    <br> &bull; Coding in <b>Java</b> and <b>Python</b>
    <br> &bull; Traveling
  </p>
  <hr>
  <center><b>*** End of Profile ***</b></center>
</body>
</html>
```

Assignment 2

Design a web page that includes an image, hyperlink, and a nested table.

```
<!DOCTYPE html>
<html>
<head>
  <title>Profile & Timetable</title>
</head>
<body>

  <!-- Main Layout Table -->
  <table border="1" width="100%" cellpadding="10" cellspacing="0">
    <!-- Header -->
    <tr bgcolor="#2c3e50">
      <th colspan="2" style="color: white; padding: 15px;">
        <h1>STUDENT DASHBOARD</h1>
      </th>
    </tr>

    <tr>
      <!-- Left Column: Profile -->
      <td width="30%" align="center" valign="top" bgcolor="#ecf0f1">
        <h3>Student Profile</h3>
        <!-- Ensure 'student.png' exists in the folder -->
        
        <br><br>
        <p><b>Name:</b> Aryan Patil</p>
        <p><b>Roll No:</b> 24055</p>
        <br>
        <!-- Hyperlink -->
        <a href="http://www.unipune.ac.in/" target="_blank">
          <button style="cursor: pointer; padding: 10px;">Visit SPPU Website</button>
        </a>
      </td>

      <!-- Right Column: Nested Table -->
      <td valign="top">
        <h3 align="center">Weekly Academic Schedule</h3>

        <!-- START NESTED TABLE -->
        <table border="1" width="90%" align="center" cellspacing="0" cellpadding="8">
          <tr bgcolor="#3498db" style="color: white;">
            <th>Time</th>
            <th>Monday</th>
            <th>Tuesday</th>
            <th>Wednesday</th>
          </tr>
```

```

<tr>
  <td align="center">10:00 - 11:00</td>
  <td>Web Development</td>
  <td>Data Structures</td>
  <td>Logic Design</td>
</tr>
<tr>
  <td align="center">11:00 - 12:00</td>
  <td>Database Mgmt</td>
  <td>Web Development</td>
  <td>Mathematics</td>
</tr>
<tr bgcolor="#bdc3c7">
  <td align="center">12:00 - 01:00</td>
  <td colspan="3" align="center"><b>LUNCH BREAK</b></td>
</tr>
<tr>
  <td align="center">01:00 - 03:00</td>
  <td><b>Web Dev Lab</b></td>
  <td>DS Lab</td>
  <td>DBMS Lab</td>
</tr>
</table>
<!-- END NESTED TABLE -->

```

```

</td>
</tr>
</table>
</body>
</html>

```

Assignment 3

Create a form with fields: name, email, gender, date of birth, and submit button.

[illegible]

```
        <input type="reset" value="Clear" style="background-color: red; color:
white; padding: 10px 20px; border: none; cursor: pointer;">
        </center>

    </form>
</td>
</tr>
</table>

</body>
</html>
```

Assignment 4

Apply internal, external, and inline CSS to style a web page with headings and tables.

```
<!DOCTYPE html>
<html>
<head>
  <title>CSS Types Demo</title>

  <!-- 2. INTERNAL CSS -->
  <style>
    body {
      background-color: #f0f8ff; /* AliceBlue */
      font-family: Verdana, sans-serif;
    }

    /* Class Selector for Table */
    .myTable {
      border-collapse: collapse;
      width: 80%;
      margin: auto;
      background-color: white;
      box-shadow: 0 0 10px rgba(0,0,0,0.1);
    }

    .myTable th {
      background-color: #4CAF50;
      color: white;
      padding: 12px;
      text-align: left;
    }

    .myTable td {
      border: 1px solid #ddd;
      padding: 8px;
    }

    /* Hover Effect */
    .myTable tr:hover { background-color: #f5f5f5; }
  </style>
</head>
<body>

  <!-- 1. INLINE CSS -->
  <h1 style="color: navy; text-align: center; border-bottom: 2px solid navy;">
    CSS Implementation Demo
  </h1>
```

```
<p style="text-align: center; color: gray; font-style: italic;">
  This text is styled using Inline CSS.
</p>
```

```
<br>
```

```
<div align="center">
  <h3>Employee Data Table (Styled via Internal CSS)</h3>
```

```
  <table class="myTable">
    <tr>
      <th>ID</th>
      <th>Name</th>
      <th>Department</th>
      <th>Status</th>
    </tr>
    <tr>
      <td>101</td>
      <td>Alice Johnson</td>
      <td>HR</td>
      <td style="color: green; font-weight: bold;">Active</td>
    </tr>
    <tr>
      <td>102</td>
      <td>Bob Smith</td>
      <td>IT</td>
      <td style="color: green; font-weight: bold;">Active</td>
    </tr>
    <tr>
      <td>103</td>
      <td>Charlie Brown</td>
      <td>Finance</td>
      <td style="color: red; font-weight: bold;">Inactive</td>
    </tr>
  </table>
</div>
```

```
</body>
```

```
</html>
```

Assignment 5

Develop a responsive web page using Bootstrap Grid and Components.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Bootstrap Responsive Demo</title>
  <!-- Bootstrap CSS CDN -->
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>

  <!-- Navbar Component -->
  <nav class="navbar navbar-expand-lg navbar-dark bg-dark">
    <div class="container-fluid">
      <a class="navbar-brand" href="#">My Portfolio</a>
    </div>
  </nav>

  <div class="container mt-5">
    <h2 class="text-center mb-4">My Skills (Responsive Grid)</h2>

    <!-- Grid Row -->
    <div class="row">

      <!-- Column 1 -->
      <div class="col-md-4 col-sm-12 mb-3">
        <div class="card shadow">
          <div class="card-header bg-primary text-white">Frontend</div>
          <div class="card-body">
            <h5 class="card-title">HTML & CSS</h5>
            <p class="card-text">Building structure and styling web pages
effectively.</p>
            <a href="#" class="btn btn-outline-primary">Details</a>
          </div>
        </div>
      </div>

      <!-- Column 2 -->
      <div class="col-md-4 col-sm-12 mb-3">
        <div class="card shadow">
          <div class="card-header bg-success text-white">Frameworks</div>
          <div class="card-body">
            <h5 class="card-title">Bootstrap</h5>
```

```

        <p class="card-text">Creating mobile-first responsive layouts quickly.</p>
        <a href="#" class="btn btn-outline-success">Details</a>
    </div>
</div>
</div>

<!-- Column 3 -->
<div class="col-md-4 col-sm-12 mb-3">
    <div class="card shadow">
        <div class="card-header bg-danger text-white">Backend</div>
        <div class="card-body">
            <h5 class="card-title">PHP</h5>
            <p class="card-text">Server-side scripting for dynamic web
applications.</p>
            <a href="#" class="btn btn-outline-danger">Details</a>
        </div>
    </div>
</div>

</div>
</div>

<!-- Bootstrap JS CDN -->
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/js/bootstrap.bundle.min.js"></script>
</body>
</html>

```

Assignment 6

Write a JavaScript program to validate form inputs (e.g., email, empty fields).

```
<!DOCTYPE html>
<html>
<head>
  <title>JS Form Validation</title>
  <style>
    body { font-family: Arial, sans-serif; background: #eee; }
    .login-box { width: 300px; margin: 50px auto; padding: 20px; background: white;
border-radius: 5px; box-shadow: 0 0 10px rgba(0,0,0,0.1); }
    input { width: 100%; padding: 8px; margin: 10px 0; box-sizing: border-box; }
    button { width: 100%; padding: 10px; background: #4CAF50; color: white; border:
none; cursor: pointer; font-size: 16px; }
    button:hover { background: #45a049; }
  </style>

  <script>
    function validateForm() {
      // 1. Retrieve Values
      var email = document.getElementById("u_email").value;
      var pass = document.getElementById("u_pass").value;

      // 2. Check Empty Fields
      if (email == "" || pass == "") {
        alert("Error: Fields cannot be empty!");
        return false; // Stop form submission
      }

      // 3. Check Email Format (Basic Logic)
      // Rule: Must contain '@', must contain '.', and '@' cannot be at the start
      var atPos = email.indexOf("@");
      var dotPos = email.lastIndexOf(".");

      if (atPos < 1 || dotPos < atPos + 2 || dotPos + 2 >= email.length) {
        alert("Error: Please enter a valid email address!");
        return false;
      }

      // 4. Check Password Length
      if (pass.length < 6) {
        alert("Error: Password must be at least 6 characters long.");
        return false;
      }

      // 5. If all checks pass
      alert("Validation Successful! Submitting form...");
      return true; // Allow form submission
    }
  </script>
</head>
</html>
```

```
    }
  </script>
</head>
<body>

  <div class="login-box">
    <h2 style="text-align:center">Login</h2>

    <!-- Form -->
    <form name="myForm" action="dashboard.html" onsubmit="return validateForm()"
method="post">

      <label>Email ID:</label>
      <input type="text" id="u_email" name="email" placeholder="user@example.com">

      <label>Password:</label>
      <input type="password" id="u_pass" name="password" placeholder="*****">

      <button type="submit">Login</button>
    </form>
  </div>

</body>
</html>
```

Assignment 7

Create a web page that uses JavaScript to display dynamic content using DOM.

```
<!DOCTYPE html>
<html>
<head>
  <title>DOM Manipulation</title>
  <style>
    body { text-align: center; font-family: sans-serif; margin-top: 50px; }

    #targetBox {
      width: 300px;
      height: 150px;
      background-color: #e0e0e0;
      border: 2px solid #333;
      padding: 40px 20px;
      box-sizing: border-box; /* Includes padding in width */
      font-size: 20px;
      margin: 20px auto;
      transition: all 0.5s ease; /* Smooth transition */
    }

    .btn {
      padding: 10px 20px;
      margin: 5px;
      cursor: pointer;
      background-color: #007bff;
      color: white;
      border: none;
      border-radius: 5px;
      font-size: 16px;
    }
    .btn:hover { background-color: #0056b3; }
  </style>
</head>
<body>

  <h2>JavaScript DOM Demo</h2>

  <!-- Target Element -->
  <div id="targetBox">Original Text Content</div>

  <br>

  <!-- Interactive Controls -->
  <button class="btn" onclick="changeText()">Change Text</button>
  <button class="btn" onclick="changeStyle()">Change Style</button>
  <button class="btn" onclick="toggleBox()">Show / Hide</button>
```

```
<script>
  // Function 1: Change Content
  function changeText() {
    var box = document.getElementById("targetBox");
    box.innerHTML = "<b>Hello World!</b><br>DOM Manipulation is cool.";
  }

  // Function 2: Change CSS Styles
  function changeStyle() {
    var box = document.getElementById("targetBox");
    box.style.backgroundColor = "#ffeb3b"; // Yellow
    box.style.color = "#d32f2f"; // Red Text
    box.style.border = "5px dashed #d32f2f";
    box.style.borderRadius = "25px";
    box.style.boxShadow = "0px 10px 20px rgba(0,0,0,0.3)";
  }

  // Function 3: Toggle Visibility logic
  function toggleBox() {
    var box = document.getElementById("targetBox");
    // Check computed style or check if inline style is set
    if (box.style.display === "none") {
      box.style.display = "block";
    } else {
      box.style.display = "none";
    }
  }
}
</script>

</body>
</html>
```

Assignment 8

Write a JavaScript program for a simple calculator using functions and switch-case.

```
<!DOCTYPE html>
<html>
<head>
  <title>JS Calculator</title>
  <style>
    .calculator {
      width: 320px;
      margin: 50px auto;
      padding: 20px;
      border: 1px solid #ccc;
      background-color: #f8f9fa;
      border-radius: 10px;
      box-shadow: 0 4px 10px rgba(0,0,0,0.1);
      text-align: center;
    }
    input { width: 90%; padding: 10px; margin: 10px 0; font-size: 16px; }
    .btn-group button { width: 22%; padding: 15px; font-size: 18px; cursor: pointer;
margin: 2px; }
    #result { font-size: 24px; color: navy; font-weight: bold; }
  </style>
</head>
<body>

  <div class="calculator">
    <h2>JS Calculator</h2>

    <input type="number" id="num1" placeholder="Enter Number 1">
    <input type="number" id="num2" placeholder="Enter Number 2">

    <div class="btn-group">
      <button onclick="calculate('+')">+</button>
      <button onclick="calculate('-')">-</button>
      <button onclick="calculate('*')">&times;</button>
      <button onclick="calculate('/')">&divide;</button>
    </div>

    <hr>
    <p>Result: <span id="result">0</span></p>
  </div>

  <script>
    function calculate(operator) {
      // 1. Get Values and Convert to Float
      var n1 = parseFloat(document.getElementById("num1").value);
      var n2 = parseFloat(document.getElementById("num2").value);
      var output = 0;
```

```
// 2. Validation
if (isNaN(n1) || isNaN(n2)) {
    alert("Please enter valid numbers!");
    return;
}

// 3. Logic
switch(operator) {
    case '+':
        output = n1 + n2;
        break;
    case '-':
        output = n1 - n2;
        break;
    case '*':
        output = n1 * n2;
        break;
    case '/':
        if (n2 === 0) {
            alert("Cannot Divide by Zero");
            return;
        }
        output = n1 / n2;
        break;
    default:
        output = "Invalid";
}

// 4. Display
document.getElementById("result").innerHTML = output;
}
</script>

</body>
</html>
```

Assignment 9

Design a PHP script to display "Welcome" message and current date & time.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>PHP Introduction</title>
  <style>
    body {
      font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
      background-color: #f0f2f5;
      display: flex;
      justify-content: center;
      align-items: center;
      height: 100vh;
      margin: 0;
    }
    .server-card {
      background-color: white;
      padding: 40px;
      border-radius: 10px;
      box-shadow: 0 4px 15px rgba(0,0,0,0.1);
      text-align: center;
      border-top: 5px solid #7b1fa2; /* Purple Accent */
    }
    .time-box {
      background-color: #f3e5f5;
      padding: 15px;
      margin-top: 20px;
      border-radius: 5px;
      font-weight: bold;
      color: #4a148c;
      border: 1px dashed #7b1fa2;
    }
  </style>
</head>
<body>

  <div class="server-card">
    <h1 style="color: #4a148c;">Server-Side Scripting</h1>
    <hr>

    <?php
      // --- PHP SCRIPT STARTS HERE ---

      // 1. Configuration: Set Timezone to India
```

```
date_default_timezone_set('Asia/Kolkata');

// 2. Variable Declaration
$greeting = "Welcome to Web Development Lab";
$student_role = "Second Year Engineering Student";

// 3. String Output using Echo
// Note: We can embed HTML tags inside the PHP string
echo "<h2>$greeting</h2>";
echo "<p>You are logged in as: <b>$student_role</b></p>";

// 4. Date Logic
$current_date = date("l, d F Y"); // e.g., Monday, 02 December 2024
$current_time = date("h:i:s A"); // e.g., 03:30:45 PM

echo "<div class='time-box'>";
echo "Server Date: " . $current_date . "<br>";
echo "Server Time: " . $current_time;
echo "</div>";

// --- PHP SCRIPT ENDS HERE ---
?>
```

```
<p><small><i>This page was generated dynamically by
Apache/PHP.</i></small></p>
</div>

</body>
</html>
```

Assignment 10

Write a PHP program to accept form input and display it using the POST method.

```
<!DOCTYPE html>
<html>
<head>
  <title>PHP POST Form Handling</title>
  <style>
    body { font-family: Arial, sans-serif; background-color: #e9ecef; padding: 20px; }
    .container {
      max-width: 400px;
      margin: 0 auto;
      background: white;
      padding: 20px;
      border-radius: 8px;
      box-shadow: 0 2px 10px rgba(0,0,0,0.1);
    }
    input[type="text"], input[type="number"] {
      width: 100%;
      padding: 10px;
      margin: 10px 0;
      border: 1px solid #ccc;
      border-radius: 4px;
      box-sizing: border-box; /* Fix padding issue */
    }
    input[type="submit"] {
      width: 100%;
      background-color: #28a745;
      color: white;
      padding: 10px;
      border: none;
      border-radius: 4px;
      cursor: pointer;
      font-size: 16px;
    }
    input[type="submit"]:hover { background-color: #218838; }
    .result-box {
      margin-top: 20px;
      padding: 15px;
      border-radius: 4px;
      background-color: #d1e7dd;
      border: 1px solid #badbcc;
      color: #0f5132;
    }
    .error { color: red; font-size: 12px; }
  </style>
</head>
<body>
```

```

<div class="container">
  <h2 style="text-align: center; color: #333;">Voting Eligibility Check</h2>
  <!--
    action: PHP_SELF means submit to this same file.
    method: POST ensures data is secure.
  -->
  <form method="POST" action="<?php echo $_SERVER['PHP_SELF'];?>">
    <label>Full Name:</label>
    <input type="text" name="fname" placeholder="Enter your name" required>
    <label>Age:</label>
    <input type="number" name="age" placeholder="Enter your age" required>
    <input type="submit" value="Check Eligibility">
  </form>
  <!-- PHP Processing Logic -->
  <?php
  if ($_SERVER["REQUEST_METHOD"] == "POST") {
    // 1. Retrieve and Sanitize Data
    // htmlspecialchars prevents Cross-Site Scripting (XSS)
    $name = htmlspecialchars($_POST['fname']);
    $age = $_POST['age'];
    // 2. Validation
    if (empty($name) || empty($age)) {
      echo "<p class='error'>Fields cannot be empty!</p>";
    } else {
      // 3. Business Logic
      $status = "";
      if ($age >= 18) {
        $status = "You are <b>Eligible</b> to vote.";
      } else {
        $years_left = 18 - $age;
        $status = "You are <b>Not Eligible</b>. Wait for $years_left more years.";
      }
      // 4. Display Output
      echo "<div class='result-box'>";
      echo "<h4>Result for $name:</h4>";
      echo "Your Age: $age <br>";
      echo "$status";
      echo "</div>";
    }
  }
  ?>
</div>
</body>
</html>

```

Assignment 11

Implement a PHP program for string manipulation (e.g., reverse, length, substring).

```
<!DOCTYPE html>
<html>
<head>
  <title>PHP String Operations</title>
  <style>
    body { font-family: 'Verdana', sans-serif; background-color: #222; color: #fff; padding:
30px; }
    .container { max-width: 600px; margin: 0 auto; background-color: #333; padding:
20px; border-radius: 10px; border-left: 5px solid #ff9800; }
    h2 { color: #ff9800; border-bottom: 1px solid #555; padding-bottom: 10px; }
    .original { background-color: #444; padding: 10px; font-size: 1.2em; border-radius:
5px; margin-bottom: 20px; }
    ul { list-style-type: none; padding: 0; }
    li { background-color: #444; margin: 5px 0; padding: 10px; border-radius: 5px; display:
flex; justify-content: space-between; }
    .label { color: #aaa; font-weight: bold; }
    .value { color: #81c784; font-family: 'Courier New', monospace; font-weight: bold; }
  </style>
</head>
<body>

  <div class="container">
    <h2>PHP String Manipulation</h2>
    <?php
      // 1. Input String
      $str = "Web Development Lab";
      echo "<div class='original'>Original String: <span
style='color:#fff>\"$str\"</span></div>";

      echo "<ul>";

      // 2. Length Calculation
      $len = strlen($str);
      echo "<li><span class='label'>Length (strlen):</span> <span class='value'>$len
characters</span></li>";

      // 3. Word Count
      $words = str_word_count($str);
      echo "<li><span class='label'>Word Count:</span> <span class='value'>$words
words</span></li>";

      // 4. Reverse
      $rev = strrev($str);
      echo "<li><span class='label'>Reverse (strrev):</span> <span
class='value'>$rev</span></li>";
```

```

// 5. Uppercase
$upper = strtoupper($str);
echo "<li><span class='label'>Uppercase:</span> <span
class='value'>$upper</span></li>";

// 6. Search Position (Zero-indexed)
// Searching for 'Dev'
$search_term = "Dev";
$pos = strpos($str, $search_term);
echo "<li><span class='label'>Position of '$search_term':</span> <span
class='value'>Index $pos</span></li>";

// 7. Replace
$replaced = str_replace("Lab", "Course", $str);
echo "<li><span class='label'>Replace 'Lab':</span> <span
class='value'>$replaced</span></li>";

// 8. Substring
// Extract 'Web' (Start at 0, length 3)
$sub = substr($str, 0, 3);
echo "<li><span class='label'>Substring (0, 3):</span> <span
class='value'>$sub</span></li>";
echo "</ul>";
?>
</div>
</body>
</html>

```

Assignment 12

Create a PHP script to store and display values in an array.

```
<!DOCTYPE html>
<html>
<head>
  <title>PHP Arrays</title>
  <style>
    body { font-family: Arial, sans-serif; background-color: #f8f9fa; padding: 40px; }
    .card { background: white; padding: 20px; margin-bottom: 20px; border-radius: 8px;
box-shadow: 0 2px 5px rgba(0,0,0,0.1); }
    h3 { color: #007bff; border-bottom: 2px solid #007bff; display: inline-block;
padding-bottom: 5px; }

    /* List Styling */
    ul { list-style-type: square; color: #555; }
    li { margin: 5px 0; font-size: 18px; }

    /* Table Styling */
    table { border-collapse: collapse; width: 60%; margin-top: 10px; }
    th, td { border: 1px solid #ddd; padding: 12px; text-align: left; }
    th { background-color: #343a40; color: white; }
    tr:nth-child(even) { background-color: #f2f2f2; }
    tr:hover { background-color: #ddd; }
  </style>
</head>
<body>

  <h1 style="text-align:center">PHP Arrays Demonstration</h1>

  <!-- 1. INDEXED ARRAY DEMO -->
  <div class="card">
    <h3>1. Indexed Array (List of Technologies)</h3>
    <p><i>Scenario: Storing a list of skills for a resume.</i></p>

    <?php
      // Declaration
      $tech_stack = array("HTML5", "CSS3", "JavaScript", "PHP 8", "MySQL");

      // Adding a new item dynamically
      $tech_stack[] = "Bootstrap 5";

      echo "<ul>";
      // Loop through indexed array
      foreach ($tech_stack as $tech) {
        echo "<li>$tech</li>";
      }
      echo "</ul>";
```

```
        echo "<b>Total Technologies: " . count($tech_stack) . "</b>";
    ?>
</div>
```

```
<!-- 2. ASSOCIATIVE ARRAY DEMO -->
```

```
<div class="card">
```

```
    <h3>2. Associative Array (Student Marks)</h3>
```

```
    <p><i>Scenario: Storing Key-Value pairs where Key=Subject and
Value=Marks.</i></p>
```

```
<?php
```

```
    // Declaration Key => Value
```

```
    $marks = array(
```

```
        "Web Development" => 90,
```

```
        "Database Mgmt"  => 85,
```

```
        "Data Structures" => 78,
```

```
        "Microprocessors" => 82
```

```
    );
```

```
?>
```

```
<table>
```

```
    <tr>
```

```
        <th>Subject Name</th>
```

```
        <th>Marks Obtained</th>
```

```
    </tr>
```

```
<?php
```

```
    // Loop through associative array
```

```
    // $subject becomes the Key, $score becomes the Value
```

```
    foreach($marks as $subject => $score) {
```

```
        echo "<tr>";
```

```
        echo "<td>" . $subject . "</td>";
```

```
        echo "<td>" . $score . "</td>";
```

```
        echo "</tr>";
```

```
    }
```

```
?>
```

```
</table>
```

```
</div>
```

```
</body>
```

```
</html>
```