

# Click Through CP Manual and AutomationTEST

**PREPARED FOR Netgear** 

### **PREPARED BY**

Candela India Pvt Ltd

# 1. Project Overview

There are total four file which is useful to run Click through captive portal task.

1. portal-bot.pl – This is the main Perl script which is passing to GUI

- 2. botlib.pm This is the standard library where define number of methods which is useful for this test
- 3. bp\_net.pm This is the module which is import from portal-bot.pl file.
- 4. portal-bot.bash-example This file use to execute the portal-bot.pl script

# 2. How to use Script (Two ways to run test manually)?

### 1. First Method.

- a. Copy all the file in /home/lanforge/ directory.
  - i. cp filename /home/lanforge/
- b. Create station in lanforge
- c. open "portal-bot.bash-example" & edit station name(-i) and IP address(--ip4) in file and save it


```
28 source /home/lanforge/lanforge.profile
 29
 30
 31 PBOT DEBUG=1 PBOT NOFORK=1 ./portal-bot.pl \
 32
            sta0008 \
      -b
 33
             bp_net.pm \
 34
      --ip4 192.168.210.196\
 35
      --dns 192.168.200.1 \
 36
     --mgt /dev/null \
 37
     --delays 0,0,0\
             "[BLANK]"
 38
      - U
 39
             "[BLANK]" \
      - p
           "http://192.168.208.18:3001/wifidog/" \
 40
      -a
          "http://www.msftconnecttest.com/redirect" \
 41
      -5
42
             "login/1"
      - n
 43
            'portal/2'
       -0
      -t
            "portal/2" \
 44
45
46
"portal-bot.bash" 47L, 2631C
```

- d. run the script
  - i. ./ portal-bot.bash-example
- e. You can check the event logs for all pass and fail result

### 2. Second Method.

a. Copy all the file in /home/lanforge/ directory.

- i. cp filename /home/lanforge/
- b. create stations in lanforge Gui
- c. run this command (./portal-bot.pl -print)
- d. you will get script detail after giving above command
- e. copy this statement
  - i. ./portal-bot.pl --logout\_url "" --bot "" --ap\_url "" --pass "" --start\_url "" login form "" --login action "" --user ""
- f. Select all the station ->click on batch Modifier->paste above data on Post IF-UP Script>Apply



# 3. How to run script

Some examples are

Go to working directory:

cd Candela-Automation/click\_through\_portal/ and run below test.

- 1. Run all scenarios(2.4 GHz, 5 GHz, 2.4 + 5 GHz): python3 clickthru\_captive\_portal.py -mgr 192.168.200.12 -ssid portal -pwd [Blank] -sec open --radio1 wiphy0 --radio2 wiphy1 -num\_port 40 --mode1 6 --mode2 10 --ip 192.168.215.49 --all test 1
- 2.Run two scenario(2.4 GHz, 5 GHz): python3 clickthru\_captive\_portal.py -mgr 192.168.200.12 -ssid portal -pwd [Blank] -sec open --radio1 wiphy0 --radio2 wiphy1 -num\_port 40 --mode1 6 --mode2 1 --ip 192.168.215.49 --test\_2G 1 --test\_5G 1
- **3. Run one scenario only(2.4 + 5 GHz)**: python3 clickthru\_captive\_portal.py -mgr 192.168.200.12 -ssid portal -pwd [Blank] -sec open --radio1 wiphy0 --radio2 wiphy1 -num\_port 40 --mode1 6 --mode2 10 --ip 192.168.215.49 --test both 1

optional arguments: -h, --help show this help message and exit

- -mgr HOST, --host HOST host name
- -ssid SSID, --ssid SSID ssid for client
- -pwd PASSWD, --passwd PASSWD password to connect to ssid -sec SECURITY,
- --security SECURITY security
- -radio1 RADIO1, --radio1 RADIO1 radio at which client will be connected on 2.4GHz
- -radio2 RADIO2, --radio2 RADIO2 radio at which client will be connected on 5 GHz
- -num\_port NUM\_PORT, --num\_port NUM\_PORT number of client
- --mode1 MODE1 Used to force mode of stations.(enter 6 for 2.4GHz)
- --mode2 MODE2 Used to force mode of stations.(10 for 5GHz)
- --ip IP ip address of AP
- --user USER --Enter the username
- --all\_test ALL\_TEST --run all scenario
- --test 2G TEST 2G --run 2.4 GHz scenario
- --test 5G TEST 5G --run 5 GHz scenario
- --test\_both TEST\_BOTH --run 2+5 GHz scenario

## 4. Contact

Visit - <a href="https://www.candelatech.com/">https://www.candelatech.com/</a>

For any support related help contact - <a href="mailto:support@candelatech.com">support@candelatech.com</a>