ALGORITHMTRIX PVT. LTD. · INTERNAL OPERATIONS

UpsellTrix remaining work and Shopify deployment guide

Product: UpsellTrix (Shopify embedded app) · Version in repo: 0.1.0-private-beta · Date: 3 September 2026

This document is compiled from the repository's own ops and App Store files. It does not invent a production hostname. Fill real HTTPS host, Postgres, and Partner credentials yourself.

> **Verdict:** Spend X → Free Gift and Tiered Free Gifts are code-ready for a *private beta* on a real host. The app is **not** ready to submit to the public Shopify App Store until production URLs, hosting, worker scheduling, listing assets, and a clean-store smoke test are complete.

1. What is already working

Do not treat the following as unfinished product work. These paths exist in the Shopify app repo and have been treated as the stable vertical slice:

Area	Status
Spend X → Free Gift campaigns	Available. Merchant can create, activate, and run them. Gift lines are tagged; Discount Function zeros the price.
Tiered Free Gifts	Available in code (evaluator + sync). Must still be smoke-tested on a clean production-like store.
Admin (embedded)	Overview, Campaigns, Create promotion, Theme setup, Compatibility, Help, Settings.
Theme app embed	Display name UpsellTrix. Required for the progress bar. Draft theme ≠ live theme.
App Proxy	Storefront path `/apps/free-gift/*` → backend `/apps/proxy/*` (widget-state, evaluate-cart).
Discount Function	Extension `fgpb-discount`. Only lines with `_fgpb_free_gift` get 100% off.
Database	PostgreSQL via Prisma. Sessions stored in Postgres (not SQLite in production).
Compliance webhook routes	Implemented in-app (`customers/data_request` , `customers/redact` , `shop/redact`). Must still be *registered on the production app* via deploy.
Legal / support pages	Marketing site has `/privacy` , `/terms` , `/support` . Listing can use them only after that site is on a public HTTPS URL.

2. What is remaining (do this before App Store submit)

A. Production hosting (blocking)

- ☐ Choose a real HTTPS host for the Node app (Fly, Render, Railway, Cloud Run, VM, etc.). Do not use the Shopify CLI tunnel as production.
- ☐ TLS certificate for that host.
- ☐ Dedicated production PostgreSQL (not the staging DB, not SQLite).
- ☐ Automated Postgres backups.
- ☐ Set production env vars in the platform secret store (never commit `.env`).
- ☐ Generate production Shopify TOML from the real host (today `shopify.app.production.upselltrix.toml` still uses `fgpb-ci.myexample.com` — treat as a placeholder until you generate from your host).
- ☐ Local `shopify.app.upselltrix.toml` correctly keeps `example.com` for CLI tunnel rewriting. Do not submit using that file's URLs.

B. Git / release hygiene (blocking)

- ☐ Review and commit the large uncommitted Shopify-app working tree on a clean branch (or discard what should not ship).
- ☐ Review and commit marketing-site screenshot section if that site is part of listing URLs.
- ☐ Do not deploy from mixed local tunnels + uncommitted Discount Function / storefront files unless that is the intended release.
- ☐ Run `npm run check:release` on the commit you will deploy. Fix failures before deploy.

C. Shopify Partner app configuration (blocking)

- ☐ Production `application_url` = your real HTTPS origin.
- ☐ Auth redirect = `https://YOUR_HOST/auth/callback` (must match runtime prefix `/auth`, not `/api/auth`).
- ☐ App proxy URL = `https://YOUR_HOST/apps/proxy`, subpath `free-gift`, prefix `apps`.
- ☐ Embedded app enabled.
- ☐ Scopes stay: `read_discounts,write_discounts,read_publications,read_products` unless product/legal review expands them.
- ☐ Webhooks live on production: `app/uninstalled`, `app/scopes_update`, compliance topics.
- ☐ Theme app extension deployed with merchant-facing name **UpsellTrix**.
- ☐ Discount Function deployed with the same production app.

D. Discount-sync worker (blocking)

Creating the worker code is not enough. Production must **schedule** it.

- ☐ Run `npm run discount-sync:once` every 1–2 minutes as a separate process (recommended), or run `npm run discount-sync:watch` as a dedicated process.
- ☐ Same code version and secrets as the web process.
- ☐ Do not embed the worker inside every web replica.
- ☐ After go-live: `npm run discount-sync:inspect` shows a healthy or empty queue.

E. App Store listing (blocking for public submit)

- ☐ App icon 1200×1200 uploaded (not logo-only feature media).
- ☐ Paste listing copy only from `docs/app-store/listing-copy.md` (FINAL — SAFE TO PASTE).
- ☐ Pricing: Free (private beta). Do not invent paid plans.
- ☐ Privacy policy URL and support URL live (marketing site deployed).
- ☐ Support email: `support@upselltrix.algorithmtrix.com`.
- ☐ Screenshots: unique, 1600×900, real UI, clean demo store (not campaign name “ooo”).
- ☐ Demo screencast linked.
- ☐ Reviewer instructions pasted (fill placeholders in `docs/app-store/reviewer-instructions.md`).
- ☐ Partner Dashboard automated checks actually run (session token, app URL, redirects). Do not tick them from memory.
- ☐ Protected customer data declaration matches real scopes and storage.

F. Functional smoke on a clean store (blocking)

- ☐ Install → Overview loads as UpsellTrix.
- ☐ Enable theme embed on the theme you preview → save.
- ☐ Create Spend X → Free Gift → activate → progress bar + free gift on Add to cart → cart → checkout.
- ☐ Drop below threshold → gift removed.
- ☐ Create a Tiered Free Gifts campaign and smoke it.
- ☐ Mystery Gift is not creatable (coming soon only).
- ☐ Uninstall does not error; reinstall works.
- ☐ Shop A cannot see Shop B campaigns.

G. Intentionally not in this launch (do not list as live)

Item	Rule
Mystery Gift	Coming soon. UI stub. Do not advertise as available.
Buy it now / Shop Pay / accelerated checkout gifts	Not supported. Gifts need Add to cart → cart → checkout.
Paid Shopify Billing plans	Not implemented. Launch is free.
Universal theme / every third-party drawer	Dawn / Online Store 2.0 is the verified path.
Analytics trend charts	Coming soon in admin.
Percentage / fixed discount as new product	Beta / hidden from create. Do not primary-market.

3. Two different “deploys”

	A. Host the Node app	B. Shopify CLI deploy
What it does	Puts your Admin + App Proxy + webhooks on the internet (`npm run start`).	Pushes app config, theme extension, and Discount Function to the Partner app.
When	First. Shopify must call a real HTTPS URL.	After TOML is generated from that URL and validated.
Command	Platform start / Docker `npm run start`	`npm run deploy:production` with production TOML

Local `shopify app dev` is **not** a production deploy. It tunnels to your laptop.

4. What you must have before starting

Input	Used for
HTTPS origin you control, e.g. `https://app.yourdomain.com`	`SHOPIFY_APP_URL` , TOML generate/deploy
PostgreSQL URL (production, dedicated)	`DATABASE_URL` for web, worker, migrate
Shopify API key (client ID) and API secret	Partner app UpsellTrix — from Partner Dashboard
Scopes string matching TOML	`SCOPES=read_discounts,write_discounts,read_publications,read_products`
Secret store on the host	Inject env; never bake into the Docker image
Scheduler (cron / platform job)	`discount-sync:once` every 1–2 minutes
Shopify Partner access to the UpsellTrix app	CLI deploy; listing later

> **Do not guess hostnames.** If you do not have a real host yet, stop after local testing. Do not run `shopify app deploy` with `example.com` as production.

5. Required environment variables (production web + worker)

Variable	Rules
`NODE_ENV`	Must be `production` (enables fail-fast checks)
`PORT`	Optional; default 3000
`DATABASE_URL`	`postgres://` or `postgresql://` only. Not `file:`
`SHOPIFY_API_KEY`	Client ID; required
`SHOPIFY_API_SECRET`	Required; never log or commit
`SHOPIFY_APP_URL`	HTTPS; no localhost; no `example.com` / `*.example.com`
`SCOPES`	Must match TOML access scopes

Worker uses the same Shopify + database variables. Optional: `DISCOUNT_SYNC_WORKER_DISABLED=true` to stop claiming jobs during incidents.

```
NODE_ENV=production npm run validate:env
```

That command must succeed with the real production values before you serve traffic.

6. Detailed deployment steps (in order)

Work from the Shopify app folder:

```
cd C:\Users\Admin\OneDrive\Desktop\UpsellTrix\shopify-app
```

Use the **UpsellTrix** config template, not the legacy Free Gift Progress Bar default, unless you are sure you want the other Partner app:

- Preferred template: `shopify.app.upselltrix.toml`
- Legacy template: `shopify.app.toml`

Step 1 — Freeze the code you will ship

1. Create a release branch from reviewed, committed code.
2. Do not include `.env` files.
3. Run the full gate (this takes a while):

```
npm run check:release
```

This runs deployment-readiness, secret scan, Prisma validate, typecheck, lint, backend/compliance/promotion/discount/storefront tests, and `npm run build`.

If it fails, fix the commit. Do not skip the gate for production.

Step 2 — Provision infrastructure

1. Create the HTTPS host and point DNS at it.

2. Create a **dedicated** production Postgres database and enable backups.
3. Create a staging host + staging database if you will test there first (recommended). Never point staging at production `DATABASE_URL`.
4. Put secrets in the platform secret store.

Step 3 — Validate env against that host

```
NODE_ENV=production ^
SHOPIFY_API_KEY=... ^
SHOPIFY_API_SECRET=... ^
SHOPIFY_APP_URL=https://YOUR_REAL_HOST ^
SCOPES=read_discounts,write_discounts,read_publications,read_products ^
DATABASE_URL=postgresql://... ^
  npm run validate:env

npm run check:deployment-readiness
npm run scan:secrets
npm run db:check
npx prisma migrate status
```

Replace `YOUR_REAL_HOST` and credentials. Do not paste secrets into chat, git, or this PDF.

Optional money-field preflight (report only, safe):

```
npm run money:backfill:dry-run
npm run money:verify
```

Run the actual backfill (`npm run money:backfill`) only if dry-run shows work and you have an approved change window.

Step 4 — Build the application image (or platform build)

```
npm run build:docker
```

Or use the repo `Dockerfile` on your platform. **Do not** run Prisma migrate during image build. **Do not** start the worker inside the web `CMD`. Web command is:

```
npm run start
```

Step 5 — Migrate the database (once, before traffic)

> Web containers do **not** migrate on boot. This is an explicit release step.

1. Backup Postgres first.
2. Optionally pause the worker: `DISCOUNT_SYNC_WORKER_DISABLED=true`.
3. Apply migrations:

```
npm run migrate:deploy
npx prisma migrate status
```

Or the same commands inside a one-shot container with `DATABASE_URL` set. Never run `prisma migrate reset` in production.

Step 6 — Start web and confirm health

1. Deploy the image / start `npm run start`.
2. Confirm:

```
GET https://YOUR_REAL_HOST/health/live
→ 200  { "status": "ok" }

GET https://YOUR_REAL_HOST/health/ready
→ 200  { "status": "ready" }
```

If ready fails, the database is not reachable or not migrated. Do not continue.

Step 7 — Schedule the discount-sync worker

Recommended (cron / scheduled job every 1–2 minutes):

```
npm run discount-sync:once
```

Alternate (always-on process):

```
npm run discount-sync:watch
```

Then inspect:

```
npm run discount-sync:inspect
```

Empty queue is OK. Overlapping run-once jobs are safe (row locks). Platform job timeout should be at least several minutes.

Step 8 — Generate and validate production Shopify TOML

This writes a deploy file. It does **not** overwrite local `shopify.app.toml` / `shopify.app.upselltrix.toml` (those stay as CLI placeholders).

```
set SHOPIFY_APP_URL=https://YOUR_REAL_HOST
set SHOPIFY_TOML_TEMPLATE=shopify.app.upselltrix.toml
set SHOPIFY_TOML_OUT=shopify.app.production.toml
npm run generate:production-toml

set SHOPIFY_TOML_PATH=shopify.app.production.toml
npm run validate:production-toml
```

On PowerShell:

```
$env:SHOPIFY_APP_URL="https://YOUR_REAL_HOST"
$env:SHOPIFY_TOML_TEMPLATE="shopify.app.upselltrix.toml"
$env:SHOPIFY_TOML_OUT="shopify.app.production.toml"
npm run generate:production-toml
$env:SHOPIFY_TOML_PATH="shopify.app.production.toml"
npm run validate:production-toml
```

Validation fails if URLs still contain localhost or `example.com` / `*.example.com`, or if they disagree with `SHOPIFY_APP_URL`.

Expected production TOML fields (example shape only):

```
application_url = "https://YOUR_REAL_HOST"
redirect_urls   = [ "https://YOUR_REAL_HOST/auth/callback" ]

[app_proxy]
url     = "https://YOUR_REAL_HOST/apps/proxy"
subpath = "free-gift"
prefix  = "apps"
```

Step 9 — Deploy to Shopify (config + extensions)

This is an **operator** action. It calls Shopify CLI. CI does not do this for you.

```
$env:SHOPIFY_TOML_PATH="shopify.app.production.toml"
npm run deploy:production
```

Confirm in the CLI that you are deploying the **UpsellTrix** app (not a leftover template app). This publishes:

- App URLs and app proxy
- Webhook subscriptions including compliance
- Theme app extension (progress bar embed)
- Discount Function `fgpb-discount`

> Plain `npm run deploy` does **not** enforce the production TOML gate. Use `deploy:production` for production.

Step 10 — Install on a controlled test store

1. Use a store that is not a real merchant, or a dedicated production-canary store.
2. Install UpsellTrix from the Partner app install link / test store.
3. Approve scopes.
4. Confirm Overview loads inside Shopify Admin (embedded).

Step 11 — Merchant smoke (must pass)

1. Theme setup → enable **UpsellTrix** app embed → **Save** (on the theme you will preview; draft ≠ live).
2. Create a Spend X → Free Gift campaign: threshold, gift product published to Online Store, activate.
3. On the storefront (Dawn recommended): Add to cart until the bar fills.
4. Confirm the gift line appears and is free at checkout (cart path, not Buy it now).
5. Remove items so spend drops below threshold; gift should come off.
6. Create and activate a small Tiered Free Gifts campaign; confirm extra gifts as spend climbs.
7. Reload the cart page; gift state should reconcile (no duplicates).
8. Check App Proxy JSON in the browser network tab: `/apps/free-gift/widget-state` returns JSON, not an HTML error.
9. Restart the web process; session should survive or re-auth cleanly.
10. Uninstall and reinstall once on the test store.

Step 12 — Monitoring

- ☐ Alert if `/health/ready` is not 200.
- ☐ Alert if `discount-sync:inspect` shows a growing failed queue.
- ☐ Confirm logs never print access tokens, cookies, `DATABASE_URL`, or emails.

7. After hosting works: App Store submission steps

Only start this after Step 11 passed on a hosted app (not the CLI tunnel).

1. Deploy the marketing website so `/privacy` and `/support` are public HTTPS.
2. In Partner Dashboard → UpsellTrix → App listing, paste copy from `docs/app-store/listing-copy.md`.
3. Set category, Online Store required, pricing Free.
4. Upload icon (1200×1200) and screenshots (1600×900, unique, real UI).
5. Link demo screencast; paste reviewer instructions with real support email and optional demo store.
6. Declare protected customer data honestly (this app reads products/discounts; it is not a customer-PII product — still complete the form as Shopify asks).
7. Run Partner automated checks. Fix anything red.
8. Submit for review.

> Until those listing assets exist, you can still run a **private beta**: install via Partner "test on development store" / custom distribution. That is not a public App Store submit.

8. Rollback (if production breaks)

Layer	Action
Web	Redeploy the previous image. Do not `prisma migrate reset`.
Shopify config / extensions	Redeploy the previous CLI version from Partner/CLI.
Database	Add a *forward* corrective migration, or approved PITR restore. Never reset.
Worker	`DISCOUNT_SYNC_WORKER_DISABLED=true` then inspect; clear the flag to resume.
Storefront	Merchant turns off the UpsellTrix theme app embed.

9. Local development (not production)

For laptop testing only:

```
cd C:\Users\Admin\OneDrive\Desktop\UpsellTrix\shopify-app
npm run dev -- --config shopify.app.upselltrix.toml --store YOUR-DEV-STORE.myshopify.com
```

CLI rewrites URLs to a tunnel. That is correct for development. It is incorrect as a production URL.

10. Hard rules

- Do not rename cart properties `_fgpb_free_gift`, `_fgpb_campaign_id`, `_fgpb_tier_id`.
- Do not change Discount Function logic as part of "just deploying."
- Do not list Mystery Gift, GoKwik, accelerated checkout gifts, or paid billing as live.

- Do not use “Promotion Engine” or “Free Gift Progress Bar” as the public product name. Public name is **UpsellTrix**.
- Do not guess production hostnames in git.
- Do not run staging fixture scripts against production merchant databases.

11. Suggested next actions (this week)

1. Pick a host and a Postgres provider; write down the real HTTPS URL.
2. Clean the git working tree; run `npm run check:release`.
3. Follow Steps 2–11 on *staging* first if possible.
4. Only then repeat on production and consider App Store listing.

Source of truth in repo: `docs/ops/deployment.md`, `docs/ops/deployment-engineer-handoff.md`, `docs/ops/environment-contract.md`, `docs/app-store/pre-submission-checklist.md`, `docs/release/production-readiness-phase-1.md`, `docs/app-store/feature-inventory.md`. If this PDF and the repo disagree, follow the repo.