Line-by-Line HTML Study Guide

Faculty Feedback & Course Evaluation Portal

Prepared as a personal tutor guide for the CA1 viva. Every line of HTML in every page is shown exactly as it appears in your project, with a short explanation underneath. The last chapters explain the other files: style.css, script.js, README.md, .gitignore and the assets folders.

> **A quick correction before you start.** `<link rel="stylesheet" href="style.css">` is the **link tag**, not an anchor tag. `<link>` connects an external file (here the CSS) to the page and is not clickable. The **anchor tag** is `<a>`: it makes clickable hyperlinks. Being able to say this clearly in the viva will earn you marks.

How to read this guide

What you see	What it means
Grey strip with a small number	One real line of your code. The number is the line number in the file.
Gold-tinted strip	An HTML comment line.
Text under the strip	Plain-English explanation of that line: each tag, each attribute, and any visible text.
Closing: ...	Closing tags, with the line where the matching opening tag was written.
Semantic	A tag whose name describes the meaning of its content (header, nav, main ...).

Anatomy of a tag

Part	Example	Explanation
Opening tag	`<a href="login.html">`	Starts an element. Contains the tag name and its attributes.
Attribute	`href="login.html"`	Extra information about the element, written as name="value".
Content	`Student Login`	What sits between the opening and closing tags.
Closing tag	`</a>`	Ends the element (same name with a slash).
Element	the whole thing	Opening tag + content + closing tag.
Void element	`<img>`, `<input>`, `<meta>`	Has no content and no closing tag.
Nesting	`<ul><li>...</li></ul>`	Elements inside elements. They must close in reverse order.

Project map

File	Purpose
`index.html`	Home page: The landing page and the first thing an evaluator sees.
`login.html`	Student login (demo): A frontend-only login form.
`dashboard.html`	Student dashboard: Shows a student's feedback status for every enrolled course using summary cards and a data table.
`courses.html`	Course and faculty mapping: Shows which faculty teach which course, section and semester in a table, then faculty profile cards and the evaluation criteria list.
`feedback.html`	Feedback form (core page): The main deliverable: a long evaluation form grouped into fieldsets: student information, feedback mode, ratings, written feedback, recommendation and confirmation.
`analytics.html`	Results and analytics: Public results page: summary cards, two bar charts and a rating-distribution table.
`admin.html`	Admin dashboard: Administrator view: five statistic cards, two bar charts, faculty-wise and course-wise comparison tables, recent comments and next-action list.

File	Purpose
about.html	About the portal: Explains the problem and solution, includes the <audio> element, lists the technologies and states the project's limitations honestly.
contact.html	Contact and help: Help page with a support form that uses extra input types: search, tel, number, date.
style.css	All visual design: colours, layout, spacing, responsive rules. Linked from every page.
script.js	All behaviour: mobile menu, login simulation, dynamic dropdown, validation, duplicate check, bar charts.
README.md	Project documentation for GitHub.
.gitignore	Tells Git which files not to upload.
assets/	Folders for local images, video and audio.

How the pieces connect

1. The browser opens an HTML page such as index.html and reads it from top to bottom.
2. At <link rel="stylesheet" href="style.css"> it downloads the CSS and styles the page.
3. At the end of <body>, <script src="script.js"></script> loads the JavaScript, which then finds elements by their id and adds behaviour.
4. Links such as <a href="courses.html"> move the visitor to other pages that repeat the same header, footer, CSS and script.

Contents

How to read this guide 1

Anatomy of a tag . . . 1

Project map . . . 1

How the pieces connect . . . 2

1. index.html - Home page 5

Line-by-line: index.html . . . 5

Viva tips for index.html . . . 21

2. login.html - Student login (demo) 22

Line-by-line: login.html . . . 22

Viva tips for login.html . . . 30

3. dashboard.html - Student dashboard 32

Line-by-line: dashboard.html . . . 32

Viva tips for dashboard.html . . . 43

4. courses.html - Course and faculty mapping 45

Line-by-line: courses.html . . . 45

Viva tips for courses.html . . . 58

5. feedback.html - Feedback form (core page) 59

Line-by-line: feedback.html . . . 59

Viva tips for feedback.html . . . 81

6. analytics.html - Results and analytics 82

Line-by-line: analytics.html . . . 82

Viva tips for analytics.html . . . 91

7. admin.html - Admin dashboard 92

Line-by-line: admin.html . . . 92

Viva tips for admin.html . . . 107

8. about.html - About the portal 108

Line-by-line: about.html . . . 108

Viva tips for about.html . . . 117

9. contact.html - Contact and help 118

Line-by-line: contact.html . . . 118

Viva tips for contact.html . . . 129

10. The other files in your project 130

style.css - the stylesheet . . . 130

script.js - the behaviour . . . 130

README.md - documentation . . . 130

.gitignore - what Git should skip . . . 130

assets/ folders . . . 131

faculty-feedback-portal.zip and the hidden .git folder . . . 131

11. Tag glossary (every tag used in this project) 132

Five viva traps to remember 133

1. index.html - Home page

Purpose	The landing page and the first thing an evaluator sees. It introduces the portal, lists its features, shows the feedback process, plays a demo video and answers common questions.
Size	224 lines in the file, 214 with content (all explained below).
Tags used (count)	a 22, article 4, body 1, button 1, circle 1, dd 4, details 4, div 26, dl 1, dt 4, figcaption 2, figure 2, footer 1, h1 1, h2 5, h3 4, h4 4, head 1, header 1, html 1, img 1, li 23, link 3, main 1, mark 1, meta 3, nav 1, ol 1, p 18, path 2, script 1, section 6, source 1, span 8, strong 8, summary 4, svg 1, title 1, ul 4, video 1

Line-by-line: index.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Faculty Feedback and Course Evaluation Portal — a student-built academic feedback system.">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>Home | Faculty Feedback &amp;amp; Course Evaluation Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

```
11  </head>
```

Closing: </head> ends the head area (opened on line 3).

```
12  <body>
```

<body> Holds everything the visitor actually sees on the page.

```
14    <!-- ============ HEADER / NAVIGATION ============ -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "header / navigation" part of the page.

```
15    <header class="site-header">
```

<header> **Semantic.** Introductory area at the top of the page: branding and navigation.
- class is a label that style.css uses to format the element: site-header (dark-blue sticky top bar with a gold bottom border).

```
16      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
17        <a href="index.html" class="brand">
```

<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="index.html" is a relative path: it opens index.html, which sits in the same folder.
- class is a label that style.css uses to format the element: brand (logo plus site-name link).

```
18          <svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img"
aria-label="Portal crest">
```

<svg> Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- class is a label that style.css uses to format the element: brand-mark (sizes the round logo icon).
- viewBox="0 0 40 40" is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- xmlns identifies the XML namespace that tells the browser this is SVG.
- role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
- aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
19            <circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>
```

<circle> SVG shape: a circle.
- cx is the horizontal position of the circle centre.
- cy is the vertical position of the circle centre.
- r is the circle radius.
- fill="#243B66" sets the shape's fill colour.
- stroke="#B1802F" sets the outline colour.
- stroke-width="2" sets the outline thickness.

```
20            <path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>
```

<path> SVG shape drawn from path commands.
- d holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- fill="#F1E2C3" sets the shape's fill colour.

```
21            <path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>
```

<path> SVG shape drawn from path commands.
- d holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- fill="none" means the shape has no fill: only its outline is drawn.
- stroke="#F1E2C3" sets the outline colour.
- stroke-width="1.6" sets the outline thickness.

```
22          </svg>
```

Closing: </svg> ends the SVG graphic (opened on line 18).

```
23          <span>LPU Feedback Portal<span class="brand-sub">Faculty &amp;amp; Course Evaluation</span></span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another on this line:
- class is a label that style.css uses to format the element: brand-sub (small second line under the site name).

Text content (plain text inside an inline container).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: ends the inline text; ends the inline text.

```
24        </a>
```

Closing: ends the link (opened on line 17).

```
25        <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
26        <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
27          <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
28            <li><a href="index.html" aria-current="page">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29            <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30            <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
31            <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
32            <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33            <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
37        </ul>
```

Closing: ends the bullet list (opened on line 27).

```
38      </nav>
```

Closing: </nav> ends the navigation (opened on line 26).

```
39    </div>
```

Closing: ends the container (opened on line 16).

```
40  </header>
```

Closing: </header> ends the page header (opened on line 15).

```
42  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
43    <!-- ============ HERO SECTION ============ -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "hero section" part of the page.

```
44    <section class="hero">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: hero (big blue banner at the top of the page).

```
45      <div class="container hero-grid">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width); hero-grid (two-column layout (text on the left, picture on the right)).

```
46        <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
47          <p class="eyebrow">CA1 Academic Project &middot; LPU</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
• · displays a middle dot used as a separator
Closing: ends the paragraph.

```
48          <h1>Honest course feedback, organized in one place.</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
Closing: </h1> ends the main heading.

```
49          <p>The Faculty Feedback &amp;amp; Course Evaluation Portal lets students rate courses and faculty using simple forms, and lets administrators read the results as clear, visual summaries — without paper forms or scattered spreadsheets.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the paragraph.

```
50          <div class="btn-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: btn-row (lines buttons up in a row with a gap).

```
51            <a href="feedback.html" class="btn btn-accent">Give Feedback</a>
```

<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-accent (solid gold button).
Text content (visible clickable link text).
Closing: ends the link.

```
52            <a href="courses.html" class="btn btn-outline" style="border-color:#fff;color:#fff;">View Courses</a>
```

<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-outline (button with only an outline).
• style is inline CSS that applies only to this one element. Properties: border-color (border colour), color (text colour).
Text content (visible clickable link text).
Closing: ends the link.

```
53          </div>
```

Closing: ends the container (opened on line 50).

```
54          <div class="hero-stats">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: hero-stats (row of three headline numbers).

```
55            <div><strong>8</strong><span>Courses tracked</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
 Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
56            <div><strong>6</strong><span>Faculty members</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
 Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
57            <div><strong>4.4/5</strong><span>Average rating (demo)</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
 Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
58          </div>
```

Closing: ends the container (opened on line 54).

```
59          </div>
```

Closing: ends the container (opened on line 46).

```
60          <figure>
```

<figure> **Semantic.** Self-contained media (image, video, audio, chart) that may carry a caption.

```
61              <img src="https://images.unsplash.com/photo-1523240795612-9a054b0db644?auto=format&fit=crop&w=900&q
=80"
```

<img> Embeds an image. Void element: no closing tag.
- src is the address of the image file to display.
- This tag continues on the next line (it is not closed with > yet).

```
62                  alt="Students in a lecture hall filling out course evaluation forms on paper and laptops">
```

- Continues the <img> tag from the line above (a long tag is split over lines for readability).
- alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.
- The > here ends the <img> opening tag.

```
63              <figcaption>Feedback season at the end of every semester used to mean stacks of paper forms — this
portal replaces that with a short online form.</figcaption>
```

<figcaption> Caption that describes the <figure> it sits inside.
Text content (caption text shown under the media).
Closing: </figcaption> ends the caption.

```
64          </figure>
```

Closing: </figure> ends the figure (opened on line 60).

```
65        </div>
```

Closing: ends the container (opened on line 45).

```
66      </section>
```

Closing: </section> ends the section (opened on line 44).

```
68      <!-- ============ FEATURES ============ -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "features" part of the page.

```
69      <section class="section" id="features">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
- class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).
- id="features" is a unique name for this element: target for the link index.html#features.

```
70        <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
71          <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
72              <p class="eyebrow">What the portal does</p>
```

 Paragraph of text.
- class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).

Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
73              <h2>Everything needed to collect and read academic feedback</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
74          <p>Built around the four things a feedback system actually needs: a simple form, a way to stay
anonymous, protection against duplicate answers, and a dashboard that turns numbers into a picture.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
75        </div>
```

Closing: ends the container (opened on line 71).

```
76        <div class="card-grid">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: card-grid (responsive grid that lines cards up).

```
77          <article class="card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).

```
78            <h3>Structured rating forms</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
79            <p>Students rate teaching effectiveness, clarity, punctuality and more using stars, sliders and
scales — not a single vague "how was it?" box.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
80          </article>
```

Closing: </article> ends the article (opened on line 77).

```
81          <article class="card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).

```
82            <h3>Anonymous or identified</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
83            <p>Every submission lets the student choose whether their name is attached to their answers,
explained clearly at the point of choice.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
84          </article>
```

Closing: </article> ends the article (opened on line 81).

```
85          <article class="card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).

```
86            <h3>Duplicate-submission checks</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
87            <p>Once feedback is submitted for a course and faculty pairing, the form recognizes it and stops
a second submission for the same pairing.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
88          </article>
```

Closing: </article> ends the article (opened on line 85).

89
```
          <article class="card">
```
<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).

90
```
            <h3>Visual admin dashboard</h3>
```
<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

91
```
            <p>Administrators see average ratings, bar-style comparisons, and course-wise or faculty-wise breakdowns at a glance.</p>
```
 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

92
```
          </article>
```
Closing: </article> ends the article (opened on line 89).

93
```
        </div>
```
Closing: ends the container (opened on line 76).

94
```
      </div>
```
Closing: ends the container (opened on line 70).

95
```
    </section>
```
Closing: </section> ends the section (opened on line 69).

97
```
    <!-- ============ HOW IT WORKS ============ -->
```
HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "how it works" part of the page.

98
```
    <section class="section section-alt" id="how-it-works">
```
<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content); section-alt (gives the block a slightly darker background band).
• id="how-it-works" is a unique name for this element: target for an anchor link to this section.

99
```
      <div class="container">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

100
```
        <div class="section-head">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

101
```
          <p class="eyebrow">Process</p>
```
 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

102
```
          <h2>How feedback moves through the portal</h2>
```
<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

103
```
        </div>
```
Closing: ends the container (opened on line 100).

104
```
        <ol class="feature-list">
```
 Ordered (numbered) list.
• class is a label that style.css uses to format the element: feature-list (styled bullet or numbered list).

105
```
          <li><strong>Log in</strong> — the student signs in with their Student ID (demo login, explained on the About page).</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

106
```
          <li><strong>Select a course</strong> — the course list is mapped to the faculty who actually teach it, using the Course &amp;amp; Faculty Mapping table.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: ends the list item.

107
```
          <li><strong>Rate and write feedback</strong> — the student rates several aspects of the course and can add written comments.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

108
```
          <li><strong>Confirm and submit</strong> — a confirmation checkbox is required before the form can be sent.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

109
```
          <li><strong>Review results</strong> — administrators read summarized averages and charts on the Admin Dashboard.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

110
```
        </ol>
```

Closing: ends the numbered list (opened on line 104).

111
```
      </div>
```

Closing: ends the container (opened on line 99).

112
```
    </section>
```

Closing: </section> ends the section (opened on line 98).

114
```
    <!-- ============ VIDEO SECTION ============ -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "video section" part of the page.

115
```
    <section class="section" id="how-feedback-works-video">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
- class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).
- id="how-feedback-works-video" is a unique name for this element: target for an anchor link to the video section.

116
```
      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

117
```
        <div class="section-head">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

118
```
          <p class="eyebrow">Watch</p>
```
 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

119
```
          <h2>How Feedback Works — a 90-second walkthrough</h2>
```
<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

120
```
          <p>A short explainer video showing a student submitting a course evaluation from start to finish.</p>
```
 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

121
```
        </div>
```
Closing: ends the container (opened on line 117).

122
```
        <figure>
```
<figure> **Semantic.** Self-contained media (image, video, audio, chart) that may carry a caption.

123
```
          <video controls width="100%" height="auto"
```
<video> Embeds a video player; no plugin needed.
• controls shows the built-in play / pause / volume bar.
• width="100%" sets the player width (100% means as wide as its container).
• height="auto" sets the height (auto keeps the video proportions).
• This tag continues on the next line (it is not closed with > yet).

124
```
            poster="https://images.unsplash.com/photo-1611162617213-7d7a39e9b1d7?auto=format&fit=crop&w=1200&q=80">
```
• Continues the <video> tag from the line above (a long tag is split over lines for readability).
• poster is the preview picture shown before the video starts playing.
• The > here ends the <video> opening tag.

125
```
            <source src="https://interactive-examples.mdn.mozilla.net/media/cc0-videos/flower.mp4" type="video/mp4">
```
<source> Gives a media element a file to play together with its format; the browser picks the first one it supports. Void element.
• src is the address of the media file.
• type="video/mp4" names the file format so the browser can skip formats it cannot play.

126
```
            Your browser does not support the video tag. You can
```
Text content (fallback text: shown only by browsers that cannot play video).

127
```
            <a href="https://interactive-examples.mdn.mozilla.net/media/cc0-videos/flower.mp4">download the video</a> instead.
```
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href is an absolute URL pointing to another website.
Text content (visible clickable link text).
Closing: ends the link.
Text content (fallback text: shown only by browsers that cannot play video).

128
```
          </video>
```
Closing: </video> ends the video player (opened on line 123).

129
```
          <figcaption>Demo walkthrough video (sample clip used for CA1 demonstration purposes).</figcaption>
```
<figcaption> Caption that describes the <figure> it sits inside.
Text content (caption text shown under the media).
Closing: </figcaption> ends the caption.

```
130         </figure>
```

Closing: </figure> ends the figure (opened on line 122).

```
131       </div>
```

Closing: ends the container (opened on line 116).

```
132     </section>
```

Closing: </section> ends the section (opened on line 115).

```
134     <!-- ============ GUIDELINES / DEFINITION LIST ============ -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "guidelines / definition list" part of the page.

```
135     <section class="section section-alt" id="guidelines">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content); section-alt (gives the block a slightly darker background band).
• id="guidelines" is a unique name for this element: target for an anchor link to the guidelines.

```
136       <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
137         <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
138           <p class="eyebrow">Before you submit</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
139           <h2>Feedback guidelines</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
140         </div>
```

Closing: ends the container (opened on line 137).

```
141         <dl class="def-list">
```

<dl> Description list: pairs of terms and descriptions.
• class is a label that style.css uses to format the element: def-list (two-column layout for a description list).

```
142           <dt>Be specific</dt>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.

```
143           <dd>Mention what actually helped or didn't — "more solved examples in class" is more useful than "make it better".</dd>
```

<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

```
144           <dt>Be respectful</dt>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.

```
145           <dd>Feedback is read by real people. Describe the teaching, not the person.</dd>
```

<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

146
```
          <dt>One submission per pairing</dt>
```
<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.

147
```
          <dd>Each course-and-faculty combination accepts one feedback submission per student, per
semester.</dd>
```
<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

148
```
          <dt>Anonymous means anonymous</dt>
```
<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.

149
```
          <dd>If you choose anonymous mode, your name and ID are never shown with your ratings.</dd>
```
<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

150
```
        </dl>
```
Closing: </dl> ends the description list (opened on line 141).

151
```
      </div>
```
Closing: ends the container (opened on line 136).

152
```
    </section>
```
Closing: </section> ends the section (opened on line 135).

154
```
    <!-- ============ FAQ ============ -->
```
HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "faq" part of the page.

155
```
    <section class="section" id="faq">
```
<section> **Semantic.** A themed group of content, normally with its own heading.
- class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).
- id="faq" is a unique name for this element: target for the link index.html#faq.

156
```
      <div class="container">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

157
```
        <div class="section-head">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

158
```
          <p class="eyebrow">FAQ</p>
```
 Paragraph of text.
- class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).

Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

159
```
          <h2>Frequently asked questions</h2>
```
<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

160
```
        </div>
```
Closing: ends the container (opened on line 157).

161
```
        <details>
```
<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
162           <summary>Can I edit my feedback after submitting?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
163           <p>Not in this version. This keeps evaluation data consistent for the semester it was submitted
in.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
164         </details>
```

Closing: </details> ends the expandable box (opened on line 161).

```
165         <details>
```

<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
166           <summary>Is my anonymous feedback really untraceable?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
167           <p>In this demo, anonymous submissions are stored without any student identifier attached, so
nothing links the response back to you within the portal.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
168         </details>
```

Closing: </details> ends the expandable box (opened on line 165).

```
169         <details>
```

<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
170           <summary>Who can see the Admin Dashboard?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
171           <p>In a real deployment, only authorized staff. In this CA1 demo, the Admin page is open for
evaluation purposes and clearly marked as sample data.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
172         </details>
```

Closing: </details> ends the expandable box (opened on line 169).

```
173         <details>
```

<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
174           <summary>Does this project use a real database?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
175           <p>No — this is a static frontend project built with HTML, CSS and JavaScript for GitHub Pages.
Login and duplicate-submission checks are simulated with <mark>localStorage</mark>, explained on the About
page.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
<mark> Highlights text like a highlighter pen.
Text content (highlighted text).
Closing: </mark> ends the highlight.
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

176
```
        </details>
```
Closing: </details> ends the expandable box (opened on line 173).

177
```
      </div>
```
Closing: ends the container (opened on line 156).

178
```
    </section>
```
Closing: </section> ends the section (opened on line 155).

179
```
  </main>
```
Closing: </main> ends the main content (opened on line 42).

181
```
  <!-- ============ FOOTER ============ -->
```
HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "footer" part of the page.

182
```
  <footer class="site-footer">
```
<footer> **Semantic.** Closing area of the page: copyright and secondary links.
- class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

183
```
    <div class="container">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

184
```
      <div class="footer-grid">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: footer-grid (four-column footer layout).

185
```
        <div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.

186
```
          <h4>LPU Feedback Portal</h4>
```
<h4> Fourth-level heading: a minor title (used for footer columns).
Text content (minor heading text).
Closing: </h4> ends the minor heading.

187
```
          <p style="color:#cfd5e4; max-width: 32ch;">A CA1 academic project demonstrating HTML fundamentals, semantic HTML and forms.</p>
```
 Paragraph of text.
- style is inline CSS that applies only to this one element. Properties: color (text colour), max-width (maximum width).

Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

188
```
        </div>
```
Closing: ends the container (opened on line 185).

189
```
        <div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.

190
```
          <h4>Navigate</h4>
```
<h4> Fourth-level heading: a minor title (used for footer columns).
Text content (minor heading text).
Closing: </h4> ends the minor heading.

191
```
          <ul>
```
 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

192
```
            <li><a href="courses.html">Courses &amp;amp; Faculty</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.

Text content (visible clickable link text).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: ends the link; ends the list item.

193
```
            <li><a href="feedback.html">Give Feedback</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

194
```
            <li><a href="analytics.html">Analytics</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

195
```
          </ul>
```
Closing: ends the bullet list (opened on line 191).

196
```
        </div>
```
Closing: ends the container (opened on line 189).

197
```
        <div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.

198
```
          <h4>Account</h4>
```
<h4> Fourth-level heading: a minor title (used for footer columns).
Text content (minor heading text).
Closing: </h4> ends the minor heading.

199
```
          <ul>
```
 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

200
```
            <li><a href="login.html">Student Login</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

201
```
            <li><a href="dashboard.html">Student Dashboard</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

202
```
            <li><a href="admin.html">Admin Dashboard</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

203
```
          </ul>
```
Closing: ends the bullet list (opened on line 199).

204
```
        </div>
```
Closing: ends the container (opened on line 197).

205
```
        <div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.

206
```
          <h4>Project</h4>
```
<h4> Fourth-level heading: a minor title (used for footer columns).
Text content (minor heading text).
Closing: </h4> ends the minor heading.

```
207          <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
208            <li><a href="about.html">About Portal</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
209            <li><a href="contact.html">Contact / Help</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
210            <li><a href="about.html#viva">Project Notes</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html#viva" opens that page and jumps to the element whose id is "viva".
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
211          </ul>
```

Closing: ends the bullet list (opened on line 207).

```
212        </div>
```

Closing: ends the container (opened on line 205).

```
213      </div>
```

Closing: ends the container (opened on line 184).

```
214      <div class="footer-bottom">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

```
215        <span>&copy; <span id="current-year"></span> LPU Feedback Portal. Academic demo project — not
affiliated with any official university system.</span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
• © displays the copyright symbol
Another on this line:
• id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.
Closing: ends the inline text.
Text content: Plain text inside an inline container.
Closing: ends the inline text.

```
216        <span>Built with HTML5, CSS3 &amp; JavaScript</span>
```

 Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the inline text.

```
217      </div>
```

Closing: ends the container (opened on line 214).

```
218    </div>
```

Closing: ends the container (opened on line 183).

```
219  </footer>
```

Closing: </footer> ends the page footer (opened on line 182).

221 `  <script src="script.js"></script>`

`<script>` Loads JavaScript into the page.
- `src="script.js"` loads the external JavaScript file script.js.

Closing: `</script>` ends the script.

222 `</body>`

Closing: `</body>` ends the visible page (opened on line 12).

223 `</html>`

Closing: `</html>` ends the whole document (opened on line 2).

Viva tips for index.html

- Full semantic skeleton: header, nav, main, sections, articles, footer.
- `<video controls poster>` with `<source>` and fallback text, wrapped in `<figure>` with `<figcaption>`.
- FAQ built with `<details>` and `<summary>`: it opens and closes with no JavaScript.
- `<ol>` for ordered steps and `<dl>` for term/description pairs.

2. login.html - Student login (demo)

Purpose	A frontend-only login form. It demonstrates form controls (text, email, password, checkbox) and clearly warns that no real authentication happens.
Size	123 lines in the file, 109 with content (all explained below).
Tags used (count)	a 11, aside 1, body 1, button 3, circle 1, code 1, div 12, em 1, fieldset 1, footer 1, form 1, h1 1, h3 1, head 1, header 1, hr 1, html 1, input 4, label 4, legend 1, li 12, link 3, main 1, meta 3, nav 1, p 5, path 2, script 1, section 1, small 3, span 5, strong 2, svg 1, title 1, ul 2

Line-by-line: login.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Student login for the Faculty Feedback and Course Evaluation Portal (frontend demo).">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>Student Login | Faculty Feedback Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: </head> ends the head area (opened on line 3).

12 `<body>`

`<body>` Holds everything the visitor actually sees on the page.

14 `<header class="site-header">`

`<header>` **Semantic.** Introductory area at the top of the page: branding and navigation.
- `class` is a label that style.css uses to format the element: `site-header` (dark-blue sticky top bar with a gold bottom border).

15 `<div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

16 `<a href="index.html" class="brand">`

`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `class` is a label that style.css uses to format the element: `brand` (logo plus site-name link).

17 `<svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img" aria-label="Portal crest">`

`<svg>` Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- `class` is a label that style.css uses to format the element: `brand-mark` (sizes the round logo icon).
- `viewBox="0 0 40 40"` is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- `xmlns` identifies the XML namespace that tells the browser this is SVG.
- `role="img"` tells assistive technology to treat this whole element as one image, described by its aria-label.
- `aria-label` gives an accessible name that screen readers announce (it is not shown on screen).

18 `<circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>`

`<circle>` SVG shape: a circle.
- `cx` is the horizontal position of the circle centre.
- `cy` is the vertical position of the circle centre.
- `r` is the circle radius.
- `fill="#243B66"` sets the shape's fill colour.
- `stroke="#B1802F"` sets the outline colour.
- `stroke-width="2"` sets the outline thickness.

19 `<path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="#F1E2C3"` sets the shape's fill colour.

20 `<path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="none"` means the shape has no fill: only its outline is drawn.
- `stroke="#F1E2C3"` sets the outline colour.
- `stroke-width="1.6"` sets the outline thickness.

21 `</svg>`

Closing: `</svg>` ends the SVG graphic (opened on line 17).

22 `<span>LPU Feedback Portal<span class="brand-sub">Faculty & Course Evaluation</span></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another `<span>` on this line:
- `class` is a label that style.css uses to format the element: `brand-sub` (small second line under the site name).

Text content (plain text inside an inline container).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</span>` ends the inline text; `</span>` ends the inline text.

23 `</a>`

Closing: `</a>` ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html" aria-current="page">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
43      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
44        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
45          <p class="eyebrow">Account</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
46          <h1>Student Login</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
Closing: </h1> ends the main heading.

```
47          <p>Sign in to reach your dashboard and give feedback for your courses.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

48
```
        </div>
```
Closing: ends the container (opened on line 44).

50
```
        <p class="demo-note">
```
 Paragraph of text.
- class is a label that style.css uses to format the element: demo-note (gold notice box explaining this is demo data).

51
```
          <strong>Demo notice:</strong> This is a <em>frontend-only</em> login for a static GitHub Pages
project.
```
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (paragraph text the visitor reads).
 Marks text with emphasis (shown italic). Semantic, unlike <i>.
Text content (emphasised (italic) text).
Closing: ends the emphasised text.
Text content (paragraph text the visitor reads).

52
```
          No password is verified against a real server or database — entering any Student ID and email will
```
Text content: Paragraph text the visitor reads.

53
```
          simulate a successful login using the browser's <code>localStorage</code>. Do not enter a real
password here.
```
Text content (paragraph text the visitor reads).
<code> Shows text in monospace code style.
Text content (text shown in code style).
Closing: </code> ends the code text.
Text content (paragraph text the visitor reads).

54
```
        </p>
```
Closing: ends the paragraph (opened on line 50).

56
```
        <div style="display:grid; grid-template-columns: 1.1fr 0.9fr; gap:2.5rem; align-items:flex-start;">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- style is inline CSS that applies only to this one element. Properties: display (layout mode), grid-template-columns (column sizes), gap (space between items), align-items (vertical alignment).

57
```
          <form id="login-form" novalidate>
```
<form> Groups input controls so they can be validated and submitted together.
- id="login-form" is a unique name for this element: script.js finds this form to run the demo login.
- novalidate switches OFF the browser's built-in validation pop-ups for this form; this project then shows its own messages with JavaScript.

58
```
            <div id="login-msg" class="form-msg" role="status" aria-live="polite"></div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- id="login-msg" is a unique name for this element: empty box where JavaScript shows login success or error messages.
- class is a label that style.css uses to format the element: form-msg (message area for success or error text (hidden until JavaScript shows it)).
- role="status" marks this box as a status message area for screen readers.
- aria-live="polite" makes screen readers announce changes to this box without interrupting the user.

Closing: ends the container.

60
```
            <fieldset>
```
<fieldset> Groups related form controls inside a bordered box.

61
```
              <legend>Sign in</legend>
```
<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

63
```
              <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
64              <label for="login-id">Student ID</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="login-id" links this label to the control whose id is "login-id": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
65              <input type="text" id="login-id" name="studentId" placeholder="e.g. 12312345" required
```

<input> Form control; its type attribute decides what kind. Void element.
- type="text": single-line free text box.
- id="login-id" is a unique name for this element: Student ID field (a label points at it).
- name="studentId" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
- required means the field must be filled in before the browser allows submission (when browser validation is on).
- This tag continues on the next line (it is not closed with > yet).

```
66              minlength="5" maxlength="15" autocomplete="username">
```

- Continues the <input> tag from the line above (a long tag is split over lines for readability).
- minlength="5" sets the minimum number of characters.
- maxlength="15" sets the maximum number of characters the user can type.
- autocomplete="username" tells the browser what kind of data this is so it can suggest saved values.
- The > here ends the <input> opening tag.

```
67              <small class="hint">Your university-issued registration number.</small>
```

<small> Fine print or side-note text.
- class is a label that style.css uses to format the element: hint (small grey helper text under a field).

Text content (fine-print text).
Closing: </small> ends the fine print.

```
68              </div>
```

Closing: ends the container (opened on line 63).

```
70              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
71              <label for="login-email">University Email</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="login-email" links this label to the control whose id is "login-email": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
72              <input type="email" id="login-email" name="email" placeholder="name@university.edu" required
```

<input> Form control; its type attribute decides what kind. Void element.
- type="email": single-line box whose value must look like an e-mail address (the browser checks for an @).
- id="login-email" is a unique name for this element: e-mail field for the demo login.
- name="email" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
- required means the field must be filled in before the browser allows submission (when browser validation is on).
- This tag continues on the next line (it is not closed with > yet).

```
73              autocomplete="email">
```

- Continues the <input> tag from the line above (a long tag is split over lines for readability).
- autocomplete="email" tells the browser what kind of data this is so it can suggest saved values.
- The > here ends the <input> opening tag.

```
74              </div>
```

Closing: ends the container (opened on line 70).

```
76              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
77              <label for="login-password">Password</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="login-password" links this label to the control whose id is "login-password": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
78              <input type="password" id="login-password" name="password" placeholder="Enter your password"
```

<input> Form control; its type attribute decides what kind. Void element.
• type="password": typed characters are hidden as dots.
• id="login-password" is a unique name for this element: password field (demo only, never checked or stored).
• name="password" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
• This tag continues on the next line (it is not closed with > yet).

```
79              minlength="6" autocomplete="current-password">
```

• Continues the <input> tag from the line above (a long tag is split over lines for readability).
• minlength="6" sets the minimum number of characters.
• autocomplete="current-password" tells the browser what kind of data this is so it can suggest saved values.
• The > here ends the <input> opening tag.

```
80              <small class="hint">Demo only — this value is never stored or checked.</small>
```

<small> Fine print or side-note text.
• class is a label that style.css uses to format the element: hint (small grey helper text under a field).
Text content (fine-print text).
Closing: </small> ends the fine print.

```
81              </div>
```

Closing: ends the container (opened on line 76).

```
83              <div class="field checkbox-option">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field); checkbox-option (one checkbox plus its text).

```
84              <input type="checkbox" id="login-remember" name="remember">
```

<input> Form control; its type attribute decides what kind. Void element.
• type="checkbox": square on/off tick box; each one is independent.
• id="login-remember" is a unique name for this element: remember-me checkbox.
• name="remember" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).

```
85              <label for="login-remember" style="font-weight:400; margin-bottom:0;">Remember me on this
device</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="login-remember" links this label to the control whose id is "login-remember": clicking the label focuses that control.
• style is inline CSS that applies only to this one element. Properties: font-weight (boldness), margin-bottom (space below).
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
86              </div>
```

Closing: ends the container (opened on line 83).

```
87            </fieldset>
```

Closing: </fieldset> ends the fieldset group (opened on line 60).

```
89            <div class="btn-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: btn-row (lines buttons up in a row with a gap).

```
90              <button type="submit" class="btn btn-primary">Login</button>
```

<button> Clickable button.
• type="submit": clicking sends the form.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-primary (solid navy button).
Text content (text shown on the button).
Closing: </button> ends the button.

```
91              <button type="reset" class="btn btn-ghost">Clear</button>
```

<button> Clickable button.
- type="reset": clicking clears all fields back to their defaults (built-in, no JavaScript).
- class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-ghost (quiet, low-emphasis button).

Text content (text shown on the button).
Closing: </button> ends the button.

```
92            </div>
```

Closing: ends the container (opened on line 89).

```
93          </form>
```

Closing: </form> ends the form (opened on line 57).

```
95          <aside class="card" aria-label="Login help">
```

<aside> **Semantic.** Side content related to the main content but not essential to it.
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
- aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
96            <h3>Why login?</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
97            <p>Logging in lets the portal:</p>
```

 Paragraph of text.
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
98            <ul class="feature-list">
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.
- class is a label that style.css uses to format the element: feature-list (styled bullet or numbered list).

```
99              <li>Show your dashboard status for each course</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
100             <li>Pre-fill your Student ID for identified feedback</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
101             <li>Apply the duplicate-submission check correctly</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
102           </ul>
```

Closing: ends the bullet list (opened on line 98).

```
103           <hr>
```

<hr> Horizontal rule: a thematic break between pieces of content. Void element.

```
104           <p><small>Choosing <strong>Anonymous</strong> mode later on the feedback form still hides your
identity from displayed results, even if you're logged in.</small></p>
```

 Paragraph of text.
<small> Fine print or side-note text.
Text content (fine-print text).
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (fine-print text).
Closing: </small> ends the fine print; ends the paragraph.

```
105         </aside>
```

Closing: </aside> ends the side box (opened on line 95).

106 `</div>`

Closing: ends the container (opened on line 56).

107 `</div>`

Closing: ends the container (opened on line 43).

108 `</section>`

Closing: </section> ends the section (opened on line 42).

109 `</main>`

Closing: </main> ends the main content (opened on line 41).

111 `<footer class="site-footer">`

<footer> **Semantic.** Closing area of the page: copyright and secondary links.
- class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

112 `<div class="container">`

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

113 `<div class="footer-bottom">`

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

114 `<span>© <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>`

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
- © displays the copyright symbol

Another on this line:
- id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.

Closing: ends the inline text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

115 `<span><a href="about.html" style="color:#cfd5e4;">About this project</a></span>`

 Generic inline container for a piece of text (no meaning of its own).
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="about.html" is a relative path: it opens about.html, which sits in the same folder.
- style is inline CSS that applies only to this one element. Properties: color (text colour).

Text content (visible clickable link text).
Closing: ends the link; ends the inline text.

116 `</div>`

Closing: ends the container (opened on line 113).

117 `</div>`

Closing: ends the container (opened on line 112).

118 `</footer>`

Closing: </footer> ends the page footer (opened on line 111).

120 `<script src="script.js"></script>`

<script> Loads JavaScript into the page.
- src="script.js" loads the external JavaScript file script.js.

Closing: </script> ends the script.

121 `</body>`

Closing: </body> ends the visible page (opened on line 12).

122 `</html>`

Closing: </html> ends the whole document (opened on line 2).

Viva tips for login.html

- Explain every field: `label for` matches `input id`, `type="password"` hides characters, `autocomplete` helps browsers.
- Be honest: this is a demo, a static site cannot verify passwords securely.
- Explain `novalidate`: browser pop-ups are switched off here and JavaScript shows the messages.
- The `<aside>` holds help text that supports the form without being part of it.

3. dashboard.html - Student dashboard

Purpose	Shows a student's feedback status for every enrolled course using summary cards and a data table.
Size	162 lines in the file, 154 with content (all explained below).
Tags used (count)	a 15, aside 1, body 1, button 1, caption 1, circle 1, div 11, footer 1, h1 1, h3 1, head 1, header 1, html 1, li 9, link 3, main 1, meta 3, nav 1, p 3, path 2, script 1, section 1, small 5, span 21, svg 1, table 1, tbody 1, td 40, th 5, thead 1, title 1, tr 9, ul 1

Line-by-line: dashboard.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Student dashboard showing feedback status across enrolled courses.">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>Student Dashboard | Faculty Feedback Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: </head> ends the head area (opened on line 3).

12
```
<body>
```
<body> Holds everything the visitor actually sees on the page.

```
14   <header class="site-header">
```

<header> **Semantic.** Introductory area at the top of the page: branding and navigation.
- class is a label that style.css uses to format the element: site-header (dark-blue sticky top bar with a gold bottom border).

```
15     <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
16       <a href="index.html" class="brand">
```

<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="index.html" is a relative path: it opens index.html, which sits in the same folder.
- class is a label that style.css uses to format the element: brand (logo plus site-name link).

```
17         <svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img"
aria-label="Portal crest">
```

<svg> Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- class is a label that style.css uses to format the element: brand-mark (sizes the round logo icon).
- viewBox="0 0 40 40" is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- xmlns identifies the XML namespace that tells the browser this is SVG.
- role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
- aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
18           <circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>
```

<circle> SVG shape: a circle.
- cx is the horizontal position of the circle centre.
- cy is the vertical position of the circle centre.
- r is the circle radius.
- fill="#243B66" sets the shape's fill colour.
- stroke="#B1802F" sets the outline colour.
- stroke-width="2" sets the outline thickness.

```
19           <path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>
```

<path> SVG shape drawn from path commands.
- d holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- fill="#F1E2C3" sets the shape's fill colour.

```
20           <path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>
```

<path> SVG shape drawn from path commands.
- d holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- fill="none" means the shape has no fill: only its outline is drawn.
- stroke="#F1E2C3" sets the outline colour.
- stroke-width="1.6" sets the outline thickness.

```
21         </svg>
```

Closing: </svg> ends the SVG graphic (opened on line 17).

```
22         <span>LPU Feedback Portal<span class="brand-sub">Faculty &amp; Course Evaluation</span></span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another on this line:
- class is a label that style.css uses to format the element: brand-sub (small second line under the site name).

Text content (plain text inside an inline container).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: ends the inline text; ends the inline text.

```
23       </a>
```

Closing: ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html" aria-current="page">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
43      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
44        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
45          <p class="eyebrow">Student Dashboard</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
46          <h1 id="dashboard-greeting">Welcome, guest.</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
• id="dashboard-greeting" is a unique name for this element: JavaScript replaces this heading text with a personal greeting.
Text content (main heading text of the page).
Closing: </h1> ends the main heading.

```
47          <p>Track which of your courses still need feedback this semester.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
48          </div>
```

Closing: ends the container (opened on line 44).

```
50          <div class="card-grid" style="margin-bottom:2.5rem;">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: card-grid (responsive grid that lines cards up).
- style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

```
51            <div class="stat-card">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

```
52              <span class="stat-value">8</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
53              <span class="stat-label">Enrolled courses</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
54            </div>
```

Closing: ends the container (opened on line 51).

```
55            <div class="stat-card">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

```
56              <span class="stat-value">5</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
57              <span class="stat-label">Feedback completed</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
58            </div>
```

Closing: ends the container (opened on line 55).

```
59            <div class="stat-card">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

```
60              <span class="stat-value">3</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
61              <span class="stat-label">Feedback pending</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
62            </div>
```

Closing: ends the container (opened on line 59).

63 `<div class="stat-card">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `stat-card` (small box showing one big number).

64 `<span class="stat-value">18 Nov</span>`

`<span>` Generic inline container for a piece of text (no meaning of its own).
- `class` is a label that style.css uses to format the element: `stat-value` (the big number).

Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text.

65 `<span class="stat-label">Feedback window closes</span>`

`<span>` Generic inline container for a piece of text (no meaning of its own).
- `class` is a label that style.css uses to format the element: `stat-label` (caption under the big number).

Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text.

66 `</div>`

Closing: `</div>` ends the container (opened on line 63).

67 `</div>`

Closing: `</div>` ends the container (opened on line 50).

69 `<div class="table-wrap">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `table-wrap` (lets a wide table scroll sideways on small screens).

70 `<table>`

`<table>` Table of data (never used for page layout).

71 `<caption>Your course feedback status (demo data)</caption>`

`<caption>` Visible title of the table; also read aloud by screen readers.
Text content (visible title of the table).
Closing: `</caption>` ends the table caption.

72 `<thead>`

`<thead>` Groups the header row of the table.

73 `<tr>`

`<tr>` One table row.

74 `<th scope="col">Course Code</th>`

`<th>` Table header cell: gives meaning to its column or row.
- `scope="col"` tells screen readers this header cell describes the column below it.

Cell content: Course Code
Closing: `</th>` ends the header cell.

75 `<th scope="col">Course Name</th>`

`<th>` Table header cell: gives meaning to its column or row.
- `scope="col"` tells screen readers this header cell describes the column below it.

Cell content: Course Name
Closing: `</th>` ends the header cell.

76 `<th scope="col">Faculty</th>`

`<th>` Table header cell: gives meaning to its column or row.
- `scope="col"` tells screen readers this header cell describes the column below it.

Cell content: Faculty
Closing: `</th>` ends the header cell.

77 `<th scope="col">Status</th>`

`<th>` Table header cell: gives meaning to its column or row.
- `scope="col"` tells screen readers this header cell describes the column below it.

Cell content: Status
Closing: `</th>` ends the header cell.

78 `<th scope="col">Action</th>`

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Action
Closing: `</th>` ends the header cell.

79 `</tr>`

Closing: `</tr>` ends the table row (opened on line 73).

80 `</thead>`

Closing: `</thead>` ends the table header (opened on line 72).

81 `<tbody>`

`<tbody>` Groups the data rows of the table.

82 `<tr>`

`<tr>` One table row.

83 `<td>CSE101</td>`

`<td>` Table data cell.
Cell content: CSE101
Closing: `</td>` ends the data cell.

84 `<td>Programming Fundamentals</td>`

`<td>` Table data cell.
Cell content: Programming Fundamentals
Closing: `</td>` ends the data cell.

85 `<td>Dr. A. Sharma</td>`

`<td>` Table data cell.
Cell content: Dr. A. Sharma
Closing: `</td>` ends the data cell.

86 `<td><span class="badge badge-success">Completed</span></td>`

`<td>` Table data cell.
`<span>` Generic inline container for a piece of text (no meaning of its own).
• `class` is a label that style.css uses to format the element: `badge` (small rounded status pill); `badge-success` (green pill colours).
Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text; `</td>` ends the data cell.

87 `<td><small>Submitted 02 Nov</small></td>`

`<td>` Table data cell.
`<small>` Fine print or side-note text.
Text content (fine-print text).
Closing: `</small>` ends the fine print; `</td>` ends the data cell.

88 `</tr>`

Closing: `</tr>` ends the table row (opened on line 82).

89 `<tr>`

`<tr>` One table row.

90 `<td>CSE102</td>`

`<td>` Table data cell.
Cell content: CSE102
Closing: `</td>` ends the data cell.

91 `<td>Computer Organization</td>`

`<td>` Table data cell.
Cell content: Computer Organization
Closing: `</td>` ends the data cell.

92 `<td>Dr. N. Singh</td>`

`<td>` Table data cell.
Cell content: Dr. N. Singh
Closing: `</td>` ends the data cell.

```
93              <td><span class="badge badge-success">Completed</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
94              <td><small>Submitted 03 Nov</small></td>
```

<td> Table data cell.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; </td> ends the data cell.

```
95              </tr>
```

Closing: </tr> ends the table row (opened on line 89).

```
96              <tr>
```

<tr> One table row.

```
97              <td>MTH101</td>
```

<td> Table data cell.
Cell content: MTH101
Closing: </td> ends the data cell.

```
98              <td>Engineering Mathematics</td>
```

<td> Table data cell.
Cell content: Engineering Mathematics
Closing: </td> ends the data cell.

```
99              <td>Dr. S. Iyer</td>
```

<td> Table data cell.
Cell content: Dr. S. Iyer
Closing: </td> ends the data cell.

```
100             <td><span class="badge badge-pending">Pending</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
101             <td><a href="feedback.html" class="btn btn-sm btn-outline">Give Feedback</a></td>
```

<td> Table data cell.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-sm (smaller button); btn-outline (button with only an outline).
Text content (visible clickable link text).
Closing: ends the link; </td> ends the data cell.

```
102             </tr>
```

Closing: </tr> ends the table row (opened on line 96).

```
103             <tr>
```

<tr> One table row.

```
104             <td>PHY101</td>
```

<td> Table data cell.
Cell content: PHY101
Closing: </td> ends the data cell.

```
105             <td>Engineering Physics</td>
```

<td> Table data cell.
Cell content: Engineering Physics
Closing: </td> ends the data cell.

```
106                 <td>Dr. M. Rao</td>
```

<td> Table data cell.
Cell content: Dr. M. Rao
Closing: </td> ends the data cell.

```
107                 <td><span class="badge badge-pending">Pending</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
108                 <td><a href="feedback.html" class="btn btn-sm btn-outline">Give Feedback</a></td>
```

<td> Table data cell.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-sm (smaller button); btn-outline (button with only an outline).
Text content (visible clickable link text).
Closing: ends the link; </td> ends the data cell.

```
109                 </tr>
```

Closing: </tr> ends the table row (opened on line 103).

```
110                 <tr>
```

<tr> One table row.

```
111                 <td>ENG101</td>
```

<td> Table data cell.
Cell content: ENG101
Closing: </td> ends the data cell.

```
112                 <td>Communication Skills</td>
```

<td> Table data cell.
Cell content: Communication Skills
Closing: </td> ends the data cell.

```
113                 <td>Ms. K. Bhatia</td>
```

<td> Table data cell.
Cell content: Ms. K. Bhatia
Closing: </td> ends the data cell.

```
114                 <td><span class="badge badge-success">Completed</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
115                 <td><small>Submitted 05 Nov</small></td>
```

<td> Table data cell.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; </td> ends the data cell.

```
116                 </tr>
```

Closing: </tr> ends the table row (opened on line 110).

```
117                 <tr>
```

<tr> One table row.

```
118                 <td>CSE103</td>
```

<td> Table data cell.
Cell content: CSE103
Closing: </td> ends the data cell.

```
119                 <td>Data Structures</td>
```

<td> Table data cell.
Cell content: Data Structures
Closing: </td> ends the data cell.

```
120                 <td>Dr. P. Kaur</td>
```

<td> Table data cell.
Cell content: Dr. P. Kaur
Closing: </td> ends the data cell.

```
121                 <td><span class="badge badge-success">Completed</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
122                 <td><small>Submitted 06 Nov</small></td>
```

<td> Table data cell.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; </td> ends the data cell.

```
123                 </tr>
```

Closing: </tr> ends the table row (opened on line 117).

```
124                 <tr>
```

<tr> One table row.

```
125                 <td>CSE104</td>
```

<td> Table data cell.
Cell content: CSE104
Closing: </td> ends the data cell.

```
126                 <td>Web Technologies</td>
```

<td> Table data cell.
Cell content: Web Technologies
Closing: </td> ends the data cell.

```
127                 <td>Dr. R. Verma</td>
```

<td> Table data cell.
Cell content: Dr. R. Verma
Closing: </td> ends the data cell.

```
128                 <td><span class="badge badge-success">Completed</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
129                 <td><small>Submitted 06 Nov</small></td>
```

<td> Table data cell.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; </td> ends the data cell.

```
130                 </tr>
```

Closing: </tr> ends the table row (opened on line 124).

```
131                 <tr>
```

<tr> One table row.

```
132             <td>ECE101</td>
```

<td> Table data cell.
Cell content: ECE101
Closing: </td> ends the data cell.

```
133             <td>Basic Electronics</td>
```

<td> Table data cell.
Cell content: Basic Electronics
Closing: </td> ends the data cell.

```
134             <td>Dr. N. Singh</td>
```

<td> Table data cell.
Cell content: Dr. N. Singh
Closing: </td> ends the data cell.

```
135             <td><span class="badge badge-pending">Pending</span></td>
```

<td> Table data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell.

```
136             <td><a href="feedback.html" class="btn btn-sm btn-outline">Give Feedback</a></td>
```

<td> Table data cell.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-sm (smaller button); btn-outline (button with only an outline).
Text content (visible clickable link text).
Closing: ends the link; </td> ends the data cell.

```
137             </tr>
```

Closing: </tr> ends the table row (opened on line 131).

```
138           </tbody>
```

Closing: </tbody> ends the table body (opened on line 81).

```
139         </table>
```

Closing: </table> ends the table (opened on line 70).

```
140       </div>
```

Closing: ends the container (opened on line 69).

```
142       <aside class="card" style="margin-top:2rem;">
```

<aside> **Semantic.** Side content related to the main content but not essential to it.
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
• style is inline CSS that applies only to this one element. Properties: margin-top (space above).

```
143         <h3>Not logged in yet?</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
144         <p class="mb-0">This dashboard shows the same demo data whether or not you're logged in, so evaluators can view it directly. <a href="login.html">Go to Student Login</a> to see the personalized greeting update above.</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content: Paragraph text the visitor reads.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link.
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
145         </aside>
```

Closing: </aside> ends the side box (opened on line 142).

```
146       </div>
```

Closing: ends the container (opened on line 43).

```
147     </section>
```

Closing: </section> ends the section (opened on line 42).

```
148   </main>
```

Closing: </main> ends the main content (opened on line 41).

```
150   <footer class="site-footer">
```

<footer> **Semantic.** Closing area of the page: copyright and secondary links.
• class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

```
151     <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
152       <div class="footer-bottom">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

```
153         <span>&copy; <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
• © displays the copyright symbol
Another on this line:
• id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.
Closing: ends the inline text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

```
154         <span><a href="feedback.html" style="color:#cfd5e4;">Give feedback now</a></span>
```

 Generic inline container for a piece of text (no meaning of its own).
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• style is inline CSS that applies only to this one element. Properties: color (text colour).
Text content (visible clickable link text).
Closing: ends the link; ends the inline text.

```
155       </div>
```

Closing: ends the container (opened on line 152).

```
156     </div>
```

Closing: ends the container (opened on line 151).

```
157   </footer>
```

Closing: </footer> ends the page footer (opened on line 150).

```
159   <script src="script.js"></script>
```

<script> Loads JavaScript into the page.
• src="script.js" loads the external JavaScript file script.js.
Closing: </script> ends the script.

```
160 </body>
```

Closing: </body> ends the visible page (opened on line 12).

```
161 </html>
```

Closing: </html> ends the whole document (opened on line 2).

Viva tips for dashboard.html

- Point to the table structure: `<caption>`, `<thead>`, `<tbody>`, `<th scope="col">`.
- The `<h1 id="dashboard-greeting">` text is replaced by JavaScript with a greeting.
- Status badges are `<span>` elements; the colour comes from CSS classes.
- Pending rows contain an `<a>` styled as a button linking to feedback.html.

4. courses.html - Course and faculty mapping

Purpose	Shows which faculty teach which course, section and semester in a table, then faculty profile cards and the evaluation criteria list.
Size	168 lines in the file, 160 with content (all explained below).
Tags used (count)	a 12, article 6, body 1, button 1, caption 1, circle 1, div 17, footer 1, h1 1, h2 2, h3 6, head 1, header 1, html 1, img 6, li 17, link 3, main 1, meta 3, nav 1, p 6, path 2, script 1, section 3, small 7, span 13, strong 8, svg 1, table 1, tbody 1, td 48, th 6, thead 1, title 1, tr 9, ul 2

Line-by-line: courses.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Course and faculty mapping for the current semester.">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>Courses &amp;amp; Faculty | Faculty Feedback Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: </head> ends the head area (opened on line 3).

12 `<body>`

`<body>` Holds everything the visitor actually sees on the page.

14 `  <header class="site-header">`

`<header>` **Semantic.** Introductory area at the top of the page: branding and navigation.
- `class` is a label that style.css uses to format the element: `site-header` (dark-blue sticky top bar with a gold bottom border).

15 `    <div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

16 `      <a href="index.html" class="brand">`

`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `class` is a label that style.css uses to format the element: `brand` (logo plus site-name link).

17 `        <svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img" aria-label="Portal crest">`

`<svg>` Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- `class` is a label that style.css uses to format the element: `brand-mark` (sizes the round logo icon).
- `viewBox="0 0 40 40"` is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- `xmlns` identifies the XML namespace that tells the browser this is SVG.
- `role="img"` tells assistive technology to treat this whole element as one image, described by its aria-label.
- `aria-label` gives an accessible name that screen readers announce (it is not shown on screen).

18 `          <circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>`

`<circle>` SVG shape: a circle.
- `cx` is the horizontal position of the circle centre.
- `cy` is the vertical position of the circle centre.
- `r` is the circle radius.
- `fill="#243B66"` sets the shape's fill colour.
- `stroke="#B1802F"` sets the outline colour.
- `stroke-width="2"` sets the outline thickness.

19 `          <path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="#F1E2C3"` sets the shape's fill colour.

20 `          <path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="none"` means the shape has no fill: only its outline is drawn.
- `stroke="#F1E2C3"` sets the outline colour.
- `stroke-width="1.6"` sets the outline thickness.

21 `        </svg>`

Closing: `</svg>` ends the SVG graphic (opened on line 17).

22 `        <span>LPU Feedback Portal<span class="brand-sub">Faculty & Course Evaluation</span></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another `<span>` on this line:
- `class` is a label that style.css uses to format the element: `brand-sub` (small second line under the site name).

Text content (plain text inside an inline container).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</span>` ends the inline text; `</span>` ends the inline text.

23 `      </a>`

Closing: `</a>` ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html" aria-current="page">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <!-- ===== MAPPING TABLE ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "mapping table" part of the page.

```
43    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
44      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
45        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
46          <p class="eyebrow">Semester mapping</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
47          <h1>Courses &amp; Faculty</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: </h1> ends the main heading.

```
48          <p>Which faculty member teaches which course, for which section. Feedback forms are built from this mapping, so a student can only rate faculty who actually taught them.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
49        </div>
```

Closing: ends the container (opened on line 45).

```
51        <div class="table-wrap">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: table-wrap (lets a wide table scroll sideways on small screens).

```
52          <table>
```

<table> Table of data (never used for page layout).

```
53            <caption>Course &amp; Faculty Mapping — Odd Semester (sample data)</caption>
```

<caption> Visible title of the table; also read aloud by screen readers.
Text content (visible title of the table).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: </caption> ends the table caption.

```
54            <thead>
```

<thead> Groups the header row of the table.

```
55              <tr>
```

<tr> One table row.

```
56                <th scope="col">Course Code</th>
```

<th> Table header cell: gives meaning to its column or row.
- scope="col" tells screen readers this header cell describes the column below it.

Cell content: Course Code
Closing: </th> ends the header cell.

```
57                <th scope="col">Course Name</th>
```

<th> Table header cell: gives meaning to its column or row.
- scope="col" tells screen readers this header cell describes the column below it.

Cell content: Course Name
Closing: </th> ends the header cell.

```
58                <th scope="col">Faculty</th>
```

<th> Table header cell: gives meaning to its column or row.
- scope="col" tells screen readers this header cell describes the column below it.

Cell content: Faculty
Closing: </th> ends the header cell.

```
59                <th scope="col">Section</th>
```

<th> Table header cell: gives meaning to its column or row.
- scope="col" tells screen readers this header cell describes the column below it.

Cell content: Section
Closing: </th> ends the header cell.

```
60                <th scope="col">Semester</th>
```

<th> Table header cell: gives meaning to its column or row.
- scope="col" tells screen readers this header cell describes the column below it.

Cell content: Semester
Closing: </th> ends the header cell.

```
61                <th scope="col">Feedback Status</th>
```

<th> Table header cell: gives meaning to its column or row.
- scope="col" tells screen readers this header cell describes the column below it.

Cell content: Feedback Status
Closing: </th> ends the header cell.

```
62              </tr>
```

Closing: </tr> ends the table row (opened on line 55).

63
```
            </thead>
```
Closing: </thead> ends the table header (opened on line 54).

64
```
            <tbody>
```
<tbody> Groups the data rows of the table.

65
```
              <tr><td>CSE101</td><td>Programming Fundamentals</td><td>Dr. A.
Sharma</td><td>K21GG</td><td>Semester 1</td><td><span class="badge badge-success">Open</span></td></tr>
```
<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: CSE101 | Programming Fundamentals | Dr. A. Sharma | K21GG | Semester 1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

66
```
              <tr><td>CSE102</td><td>Computer Organization</td><td>Dr. N.
Singh</td><td>K21GG</td><td>Semester 1</td><td><span class="badge badge-success">Open</span></td></tr>
```
<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: CSE102 | Computer Organization | Dr. N. Singh | K21GG | Semester 1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

67
```
              <tr><td>CSE103</td><td>Data Structures</td><td>Dr. P. Kaur</td><td>K21HH</td><td>Semester
2</td><td><span class="badge badge-pending">Opens 20 Nov</span></td></tr>
```
<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: CSE103 | Data Structures | Dr. P. Kaur | K21HH | Semester 2
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

68
```
              <tr><td>CSE104</td><td>Web Technologies</td><td>Dr. R. Verma</td><td>K21HH</td><td>Semester
2</td><td><span class="badge badge-success">Open</span></td></tr>
```
<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: CSE104 | Web Technologies | Dr. R. Verma | K21HH | Semester 2
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

```
69              <tr><td>MTH101</td><td>Engineering Mathematics</td><td>Dr. S.
Iyer</td><td>K21GG</td><td>Semester 1</td><td><span class="badge badge-success">Open</span></td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: MTH101 | Engineering Mathematics | Dr. S. Iyer | K21GG | Semester 1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

```
70              <tr><td>PHY101</td><td>Engineering Physics</td><td>Dr. M. Rao</td><td>K21GG</td><td>Semester
1</td><td><span class="badge badge-success">Open</span></td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: PHY101 | Engineering Physics | Dr. M. Rao | K21GG | Semester 1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

```
71              <tr><td>ENG101</td><td>Communication Skills</td><td>Ms. K.
Bhatia</td><td>K21JJ</td><td>Semester 1</td><td><span class="badge badge-danger">Closed</span></td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: ENG101 | Communication Skills | Ms. K. Bhatia | K21JJ | Semester 1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-danger (red pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

```
72              <tr><td>ECE101</td><td>Basic Electronics</td><td>Dr. N. Singh</td><td>K21JJ</td><td>Semester
2</td><td><span class="badge badge-success">Open</span></td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 6 times on this line)
Cell contents, in column order: ECE101 | Basic Electronics | Dr. N. Singh | K21JJ | Semester 2
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

```
73            </tbody>
```

Closing: </tbody> ends the table body (opened on line 64).

```
74          </table>
```

Closing: </table> ends the table (opened on line 52).

```
75        </div>
```

Closing: ends the container (opened on line 51).

```
76        <p><small>Sample academic data created for this CA1 demonstration. Faculty names are fictional.</small></p>
```

 Paragraph of text.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; ends the paragraph.

```
77      </div>
```

Closing: ends the container (opened on line 44).

```
78    </section>
```

Closing: </section> ends the section (opened on line 43).

```
80    <!-- ===== FACULTY PROFILES ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "faculty profiles" part of the page.

```
81    <section class="section section-alt">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content); section-alt (gives the block a slightly darker background band).

```
82      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
83        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
84          <p class="eyebrow">Faculty</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
85          <h2>Faculty teaching this semester</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
86        </div>
```

Closing: ends the container (opened on line 83).

```
87        <div class="card-grid">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: card-grid (responsive grid that lines cards up).

```
88          <article class="card faculty-card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge); faculty-card (picture and name side by side).

```
89            <img class="avatar" src="https://ui-avatars.com/api/?name=A+Sharma&background=1c2b4a&color=fff&size=92" alt="Profile photo placeholder for Dr. A. Sharma">
```

<img> Embeds an image. Void element: no closing tag.
• class is a label that style.css uses to format the element: avatar (round profile picture).
• src is the address of the image file to display.
• alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.

```
90            <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
91              <h3 class="mb-0">Dr. A. Sharma</h3>
```

<h3> Third-level heading: a sub-section title.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
92              <small>Programming Fundamentals, Data Structures</small>
```

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print.

```
93            </div>
```

Closing: ends the container (opened on line 90).

```
94          </article>
```

Closing: </article> ends the article (opened on line 88).

```
95          <article class="card faculty-card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge); faculty-card (picture and name side by side).

```
96            <img class="avatar" src="https://ui-avatars.com/api/?name=R+Verma&background=1c2b4a&color=fff&size=92" alt="Profile photo placeholder for Dr. R. Verma">
```

<img> Embeds an image. Void element: no closing tag.
• class is a label that style.css uses to format the element: avatar (round profile picture).
• src is the address of the image file to display.
• alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.

```
97            <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
98              <h3 class="mb-0">Dr. R. Verma</h3>
```

<h3> Third-level heading: a sub-section title.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
99              <small>Web Technologies, Programming Fundamentals</small>
```

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print.

```
100           </div>
```

Closing: ends the container (opened on line 97).

```
101         </article>
```

Closing: </article> ends the article (opened on line 95).

```
102         <article class="card faculty-card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge); faculty-card (picture and name side by side).

```
103           <img class="avatar" src="https://ui-avatars.com/api/?name=N+Singh&background=1c2b4a&color=fff&size=92" alt="Profile photo placeholder for Dr. N. Singh">
```

<img> Embeds an image. Void element: no closing tag.
• class is a label that style.css uses to format the element: avatar (round profile picture).
• src is the address of the image file to display.
• alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.

```
104             <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
105               <h3 class="mb-0">Dr. N. Singh</h3>
```

<h3> Third-level heading: a sub-section title.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
106               <small>Computer Organization, Basic Electronics</small>
```

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print.

```
107             </div>
```

Closing: ends the container (opened on line 104).

```
108           </article>
```

Closing: </article> ends the article (opened on line 102).

```
109           <article class="card faculty-card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge); faculty-card (picture and name side by side).

```
110             <img class="avatar" src="https://ui-avatars.com/api/?name=P+Kaur&background=1c2b4a&color=fff&size
=92" alt="Profile photo placeholder for Dr. P. Kaur">
```

<img> Embeds an image. Void element: no closing tag.
• class is a label that style.css uses to format the element: avatar (round profile picture).
• src is the address of the image file to display.
• alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.

```
111             <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
112               <h3 class="mb-0">Dr. P. Kaur</h3>
```

<h3> Third-level heading: a sub-section title.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
113               <small>Data Structures, Web Technologies</small>
```

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print.

```
114             </div>
```

Closing: ends the container (opened on line 111).

```
115           </article>
```

Closing: </article> ends the article (opened on line 109).

```
116           <article class="card faculty-card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge); faculty-card (picture and name side by side).

```
117             <img class="avatar" src="https://ui-avatars.com/api/?name=S+Iyer&background=1c2b4a&color=fff&size
=92" alt="Profile photo placeholder for Dr. S. Iyer">
```

<img> Embeds an image. Void element: no closing tag.
• class is a label that style.css uses to format the element: avatar (round profile picture).
• src is the address of the image file to display.
• alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.

```
118            <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
119              <h3 class="mb-0">Dr. S. Iyer</h3>
```

<h3> Third-level heading: a sub-section title.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
120              <small>Engineering Mathematics</small>
```

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print.

```
121            </div>
```

Closing: ends the container (opened on line 118).

```
122          </article>
```

Closing: </article> ends the article (opened on line 116).

```
123          <article class="card faculty-card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge); faculty-card (picture and name side by side).

```
124            <img class="avatar" src="https://ui-avatars.com/api/?name=K+Bhatia&background=1c2b4a&color=fff&size=92" alt="Profile photo placeholder for Ms. K. Bhatia">
```

<img> Embeds an image. Void element: no closing tag.
• class is a label that style.css uses to format the element: avatar (round profile picture).
• src is the address of the image file to display.
• alt is the text alternative: read aloud by screen readers and shown if the image fails to load. Required for meaningful images.

```
125            <div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.

```
126              <h3 class="mb-0">Ms. K. Bhatia</h3>
```

<h3> Third-level heading: a sub-section title.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
127              <small>Communication Skills</small>
```

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print.

```
128            </div>
```

Closing: ends the container (opened on line 125).

```
129          </article>
```

Closing: </article> ends the article (opened on line 123).

```
130        </div>
```

Closing: ends the container (opened on line 87).

```
131      </div>
```

Closing: ends the container (opened on line 82).

```
132    </section>
```

Closing: </section> ends the section (opened on line 81).

```
134    <!-- ===== EVALUATION CRITERIA ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "evaluation criteria" part of the page.

```
135     <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
136       <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
137         <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
138           <p class="eyebrow">Criteria</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
139           <h2>What students are asked to rate</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
140         </div>
```

Closing: ends the container (opened on line 137).

```
141         <ul class="feature-list">
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.
• class is a label that style.css uses to format the element: feature-list (styled bullet or numbered list).

```
142           <li><strong>Teaching effectiveness</strong> — did the sessions help you understand the subject?</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
143           <li><strong>Explanation clarity</strong> — were concepts explained in an understandable way?</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
144           <li><strong>Subject knowledge</strong> — depth and accuracy of the faculty's command of the topic.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
145           <li><strong>Interaction</strong> — approachability and willingness to engage with students.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
146          <li><strong>Use of examples</strong> — practical illustrations that connect theory to
application.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

```
147          <li><strong>Course material</strong> — quality of slides, notes and practice resources.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
148          <li><strong>Punctuality</strong> — classes starting and ending as scheduled.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
149          <li><strong>Doubt clarification</strong> — responsiveness to questions inside and outside
class.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
Closing: ends the list item.

```
150        </ul>
```

Closing: ends the bullet list (opened on line 141).

```
151        <p><a href="feedback.html" class="btn btn-primary">Give Feedback</a></p>
```

 Paragraph of text.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-primary (solid navy button).
Text content (visible clickable link text).
Closing: ends the link; ends the paragraph.

```
152      </div>
```

Closing: ends the container (opened on line 136).

```
153    </section>
```

Closing: </section> ends the section (opened on line 135).

```
154  </main>
```

Closing: </main> ends the main content (opened on line 41).

```
156  <footer class="site-footer">
```

<footer> **Semantic.** Closing area of the page: copyright and secondary links.
• class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

```
157    <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
158      <div class="footer-bottom">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

```
159         <span>&copy; <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
- © displays the copyright symbol

Another on this line:
- id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.

Closing: ends the inline text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

```
160         <span><a href="admin.html" style="color:#cfd5e4;">Admin dashboard</a></span>
```

 Generic inline container for a piece of text (no meaning of its own).
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
- style is inline CSS that applies only to this one element. Properties: color (text colour).

Text content (visible clickable link text).
Closing: ends the link; ends the inline text.

```
161       </div>
```

Closing: ends the container (opened on line 158).

```
162     </div>
```

Closing: ends the container (opened on line 157).

```
163   </footer>
```

Closing: </footer> ends the page footer (opened on line 156).

```
165   <script src="script.js"></script>
```

<script> Loads JavaScript into the page.
- src="script.js" loads the external JavaScript file script.js.

Closing: </script> ends the script.

```
166 </body>
```

Closing: </body> ends the visible page (opened on line 12).

```
167 </html>
```

Closing: </html> ends the whole document (opened on line 2).

Viva tips for courses.html

- The mapping table: course code, name, faculty, section, semester, status.
- Faculty profile pictures are <img> with meaningful alt text; each profile is an <article>.
- A table is for data only, never for page layout.
- The criteria are a <ul> of <li> items with for the criterion name.

5. feedback.html - Feedback form (core page)

Purpose	The main deliverable: a long evaluation form grouped into fieldsets: student information, feedback mode, ratings, written feedback, recommendation and confirmation.
Size	298 lines in the file, 270 with content (all explained below).
Tags used (count)	a 11, aside 1, body 1, button 3, circle 1, code 1, dd 5, div 39, dl 1, dt 5, fieldset 5, footer 1, form 1, h1 1, h3 2, head 1, header 1, hr 1, html 1, input 18, label 26, legend 5, li 12, link 3, main 1, meta 3, nav 1, option 25, p 5, path 2, script 1, section 1, select 5, small 4, span 20, strong 3, svg 1, textarea 3, title 1, ul 2

Line-by-line: feedback.html

```
1  <!DOCTYPE html>
```

<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

```
2  <html lang="en">
```

<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

```
3  <head>
```

<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

```
4    <meta charset="UTF-8">
```

<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

```
5    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

```
6    <meta name="description" content="Submit structured course and faculty feedback.">
```

<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

```
7    <title>Give Feedback | Faculty Feedback Portal</title>
```

<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
Closing: </title> ends the page title.

```
8    <link rel="preconnect" href="https://fonts.googleapis.com">
```

<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

```
9    <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```

<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

```
10   <link rel="stylesheet" href="style.css">
```

<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

```
11 </head>
```

Closing: </head> ends the head area (opened on line 3).

12 `<body>`

`<body>` Holds everything the visitor actually sees on the page.

14 `<header class="site-header">`

`<header>` **Semantic.** Introductory area at the top of the page: branding and navigation.
- `class` is a label that style.css uses to format the element: `site-header` (dark-blue sticky top bar with a gold bottom border).

15 `<div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

16 `<a href="index.html" class="brand">`

`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `class` is a label that style.css uses to format the element: `brand` (logo plus site-name link).

17 `<svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img" aria-label="Portal crest">`

`<svg>` Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- `class` is a label that style.css uses to format the element: `brand-mark` (sizes the round logo icon).
- `viewBox="0 0 40 40"` is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- `xmlns` identifies the XML namespace that tells the browser this is SVG.
- `role="img"` tells assistive technology to treat this whole element as one image, described by its aria-label.
- `aria-label` gives an accessible name that screen readers announce (it is not shown on screen).

18 `<circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>`

`<circle>` SVG shape: a circle.
- `cx` is the horizontal position of the circle centre.
- `cy` is the vertical position of the circle centre.
- `r` is the circle radius.
- `fill="#243B66"` sets the shape's fill colour.
- `stroke="#B1802F"` sets the outline colour.
- `stroke-width="2"` sets the outline thickness.

19 `<path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="#F1E2C3"` sets the shape's fill colour.

20 `<path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="none"` means the shape has no fill: only its outline is drawn.
- `stroke="#F1E2C3"` sets the outline colour.
- `stroke-width="1.6"` sets the outline thickness.

21 `</svg>`

Closing: `</svg>` ends the SVG graphic (opened on line 17).

22 `<span>LPU Feedback Portal<span class="brand-sub">Faculty & Course Evaluation</span></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another `<span>` on this line:
- `class` is a label that style.css uses to format the element: `brand-sub` (small second line under the site name).

Text content (plain text inside an inline container).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</span>` ends the inline text; `</span>` ends the inline text.

23 `</a>`

Closing: `</a>` ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html" aria-current="page">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

33
```
          <li><a href="admin.html">Admin</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

34
```
          <li><a href="about.html">About</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

35
```
          <li><a href="contact.html">Contact</a></li>
```
 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

36
```
        </ul>
```
Closing: ends the bullet list (opened on line 26).

37
```
      </nav>
```
Closing: </nav> ends the navigation (opened on line 25).

38
```
    </div>
```
Closing: ends the container (opened on line 15).

39
```
  </header>
```
Closing: </header> ends the page header (opened on line 14).

41
```
  <main>
```
<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

42
```
    <section class="section">
```
<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

43
```
      <div class="container">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

44
```
        <div class="section-head">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

45
```
          <p class="eyebrow">Course Evaluation</p>
```
 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

46
```
          <h1>Give Feedback</h1>
```
<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
Closing: </h1> ends the main heading.

47
```
          <p>Rate your course and faculty on the criteria below. Fields marked required must be completed before submitting.</p>
```
 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

48 `</div>`

Closing: ends the container (opened on line 44).

50 `<p class="demo-note">`

 Paragraph of text.
- class is a label that style.css uses to format the element: demo-note (gold notice box explaining this is demo data).

51 `<strong>Demo notice:</strong> Submissions are stored only in this browser's <code>localStorage</code>, not on a`

 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (paragraph text the visitor reads).
<code> Shows text in monospace code style.
Text content (text shown in code style).
Closing: </code> ends the code text.
Text content (paragraph text the visitor reads).

52 `real server. Submitting feedback twice for the same course-and-faculty pairing will be blocked, demonstrating`

Text content: Paragraph text the visitor reads.

53 `duplicate-submission prevention.`

Text content (paragraph text the visitor reads).

54 `</p>`

Closing: ends the paragraph (opened on line 50).

56 `<div style="display:grid; grid-template-columns: 1.15fr 0.85fr; gap:2.5rem; align-items:flex-start;">`

 Generic block container with no meaning of its own; used only to group elements for layout.
- style is inline CSS that applies only to this one element. Properties: display (layout mode), grid-template-columns (column sizes), gap (space between items), align-items (vertical alignment).

58 `<form id="feedback-form" novalidate>`

<form> Groups input controls so they can be validated and submitted together.
- id="feedback-form" is a unique name for this element: script.js finds this form to run validation and the duplicate-submission check.
- novalidate switches OFF the browser's built-in validation pop-ups for this form; this project then shows its own messages with JavaScript.

59 `<div id="feedback-msg" class="form-msg" role="status" aria-live="polite"></div>`

 Generic block container with no meaning of its own; used only to group elements for layout.
- id="feedback-msg" is a unique name for this element: empty box where JavaScript shows feedback success or error messages.
- class is a label that style.css uses to format the element: form-msg (message area for success or error text (hidden until JavaScript shows it)).
- role="status" marks this box as a status message area for screen readers.
- aria-live="polite" makes screen readers announce changes to this box without interrupting the user.

Closing: ends the container.

61 `<!-- STUDENT INFORMATION -->`

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "student information" part of the page.

62 `<fieldset>`

<fieldset> Groups related form controls inside a bordered box.

63 `<legend>Student Information</legend>`

<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

65 `<div class="field-row">`

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field-row (two form fields side by side (one column on phones)).

```
66              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
67              <label for="fb-student-id">Student ID</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="fb-student-id" links this label to the control whose id is "fb-student-id": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
68              <input type="text" id="fb-student-id" name="studentId" placeholder="e.g. 12312345"
```

<input> Form control; its type attribute decides what kind. Void element.
- type="text": single-line free text box.
- id="fb-student-id" is a unique name for this element: Student ID field of the feedback form.
- name="studentId" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
- This tag continues on the next line (it is not closed with > yet).

```
69              maxlength="15" autocomplete="username">
```

- Continues the <input> tag from the line above (a long tag is split over lines for readability).
- maxlength="15" sets the maximum number of characters the user can type.
- autocomplete="username" tells the browser what kind of data this is so it can suggest saved values.
- The > here ends the <input> opening tag.

```
70              <small class="hint">Optional if submitting anonymously.</small>
```

<small> Fine print or side-note text.
- class is a label that style.css uses to format the element: hint (small grey helper text under a field).

Text content (fine-print text).
Closing: </small> ends the fine print.

```
71              </div>
```

Closing: ends the container (opened on line 66).

```
72              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
73              <label for="fb-email">Email</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="fb-email" links this label to the control whose id is "fb-email": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
74              <input type="email" id="fb-email" name="email" placeholder="name@university.edu"
autocomplete="email">
```

<input> Form control; its type attribute decides what kind. Void element.
- type="email": single-line box whose value must look like an e-mail address (the browser checks for an @).
- id="fb-email" is a unique name for this element: e-mail field of the feedback form.
- name="email" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
- autocomplete="email" tells the browser what kind of data this is so it can suggest saved values.

```
75              </div>
```

Closing: ends the container (opened on line 72).

```
76              </div>
```

Closing: ends the container (opened on line 65).

```
78              <div class="field-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field-row (two form fields side by side (one column on phones)).

```
79              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
80              <label for="fb-course">Course</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="fb-course" links this label to the control whose id is "fb-course": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
81              <select id="fb-course" name="course" required>
```

<select> Dropdown list.
- id="fb-course" is a unique name for this element: course dropdown; JavaScript listens for changes here.
- name="course" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- required means the field must be filled in before the browser allows submission (when browser validation is on).

```
82                  <option value="">Select a course</option>
```

<option> One choice inside a <select>.
- value="" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
83                  <option value="CSE101">CSE101 — Programming Fundamentals</option>
```

<option> One choice inside a <select>.
- value="CSE101" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
84                  <option value="CSE102">CSE102 — Computer Organization</option>
```

<option> One choice inside a <select>.
- value="CSE102" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
85                  <option value="CSE103">CSE103 — Data Structures</option>
```

<option> One choice inside a <select>.
- value="CSE103" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
86                  <option value="CSE104">CSE104 — Web Technologies</option>
```

<option> One choice inside a <select>.
- value="CSE104" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
87                  <option value="MTH101">MTH101 — Engineering Mathematics</option>
```

<option> One choice inside a <select>.
- value="MTH101" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
88                  <option value="PHY101">PHY101 — Engineering Physics</option>
```

<option> One choice inside a <select>.
- value="PHY101" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
89                  <option value="ENG101">ENG101 — Communication Skills</option>
```

<option> One choice inside a <select>.
- value="ENG101" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
90                  <option value="ECE101">ECE101 — Basic Electronics</option>
```

<option> One choice inside a <select>.
- value="ECE101" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
91              </select>
```

Closing: </select> ends the dropdown (opened on line 81).

92
```
            </div>
```
Closing: ends the container (opened on line 79).

93
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

94
```
            <label for="fb-faculty">Faculty</label>
```
<label> Text label for a form control; clicking it focuses the control.
- for="fb-faculty" links this label to the control whose id is "fb-faculty": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

95
```
            <select id="fb-faculty" name="faculty" required>
```
<select> Dropdown list.
- id="fb-faculty" is a unique name for this element: faculty dropdown; JavaScript refills it when the course changes.
- name="faculty" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- required means the field must be filled in before the browser allows submission (when browser validation is on).

96
```
            <option value="">Select course first</option>
```
<option> One choice inside a <select>.
- value="" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

97
```
            </select>
```
Closing: </select> ends the dropdown (opened on line 95).

98
```
            <small class="hint">Updates automatically based on the course chosen.</small>
```
<small> Fine print or side-note text.
- class is a label that style.css uses to format the element: hint (small grey helper text under a field).

Text content (fine-print text).
Closing: </small> ends the fine print.

99
```
            </div>
```
Closing: ends the container (opened on line 93).

100
```
            </div>
```
Closing: ends the container (opened on line 78).

102
```
            <div class="field-row">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field-row (two form fields side by side (one column on phones)).

103
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

104
```
            <label for="fb-section">Section</label>
```
<label> Text label for a form control; clicking it focuses the control.
- for="fb-section" links this label to the control whose id is "fb-section": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

105
```
            <input type="text" id="fb-section" name="section" placeholder="e.g. K21GG" maxlength="10">
```
<input> Form control; its type attribute decides what kind. Void element.
- type="text": single-line free text box.
- id="fb-section" is a unique name for this element: section field.
- name="section" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
- maxlength="10" sets the maximum number of characters the user can type.

106
```
            </div>
```
Closing: ends the container (opened on line 103).

```
107             <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
108             <label for="fb-semester">Semester</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="fb-semester" links this label to the control whose id is "fb-semester": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
109             <select id="fb-semester" name="semester">
```

<select> Dropdown list.
• id="fb-semester" is a unique name for this element: semester dropdown.
• name="semester" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).

```
110             <option value="">Select semester</option>
```

<option> One choice inside a <select>.
• value="" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
111             <option>Semester 1</option>
```

<option> One choice inside a <select>.
• No value attribute, so the visible text itself is what gets submitted.
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
112             <option>Semester 2</option>
```

<option> One choice inside a <select>.
• No value attribute, so the visible text itself is what gets submitted.
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
113             <option>Semester 3</option>
```

<option> One choice inside a <select>.
• No value attribute, so the visible text itself is what gets submitted.
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
114             <option>Semester 4</option>
```

<option> One choice inside a <select>.
• No value attribute, so the visible text itself is what gets submitted.
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
115             </select>
```

Closing: </select> ends the dropdown (opened on line 109).

```
116             </div>
```

Closing: ends the container (opened on line 107).

```
117             </div>
```

Closing: ends the container (opened on line 102).

```
118           </fieldset>
```

Closing: </fieldset> ends the fieldset group (opened on line 62).

```
120           <!-- FEEDBACK MODE -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "feedback mode" part of the page.

```
121           <fieldset>
```

<fieldset> Groups related form controls inside a bordered box.

122
```
                <legend>Feedback Mode</legend>
```
<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

123
```
                <p style="margin-top:0;"><small>Anonymous mode hides your name and Student ID from anything administrators see. Identified mode keeps your details attached to this submission.</small></p>
```
 Paragraph of text.
- style is inline CSS that applies only to this one element. Properties: margin-top (space above).

<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; ends the paragraph.

124
```
                <div class="radio-group">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: radio-group (stacks radio options vertically).

125
```
                <label class="radio-option">
```
<label> Text label for a form control; clicking it focuses the control.
- class is a label that style.css uses to format the element: radio-option (one radio button plus its text).

126
```
                <input type="radio" name="fb-mode" value="anonymous" required>
```
<input> Form control; its type attribute decides what kind. Void element.
- type="radio": round option button; only one choice per group is possible.
- name="fb-mode": radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
- value="anonymous" is the data sent if this radio option is chosen.
- required means the field must be filled in before the browser allows submission (when browser validation is on).

127
```
                <span><strong>Anonymous</strong> — my identity will not be shown with this feedback</span>
```
 Generic inline container for a piece of text (no meaning of its own).
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

128
```
                </label>
```
Closing: </label> ends the label (opened on line 125).

129
```
                <label class="radio-option">
```
<label> Text label for a form control; clicking it focuses the control.
- class is a label that style.css uses to format the element: radio-option (one radio button plus its text).

130
```
                <input type="radio" name="fb-mode" value="identified" required>
```
<input> Form control; its type attribute decides what kind. Void element.
- type="radio": round option button; only one choice per group is possible.
- name="fb-mode": radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
- value="identified" is the data sent if this radio option is chosen.
- required means the field must be filled in before the browser allows submission (when browser validation is on).

131
```
                <span><strong>Identified</strong> — my Student ID may be shown with this feedback</span>
```
 Generic inline container for a piece of text (no meaning of its own).
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

132
```
                </label>
```
Closing: </label> ends the label (opened on line 129).

133
```
                </div>
```
Closing: ends the container (opened on line 124).

```
134             </fieldset>
```

Closing: </fieldset> ends the fieldset group (opened on line 121).

```
136             <!-- COURSE EVALUATION -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "course evaluation" part of the page.

```
137             <fieldset>
```

<fieldset> Groups related form controls inside a bordered box.

```
138               <legend>Course Evaluation</legend>
```

<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

```
140               <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
141               <label for="rating-overall">Overall course rating</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="rating-overall" links this label to the control whose id is "rating-overall": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
142               <div class="range-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: range-row (slider and its number on one line).

```
143               <input type="range" id="rating-overall" name="ratingOverall" min="1" max="5" step="1"
value="4" data-output="out-overall">
```

<input> Form control; its type attribute decides what kind. Void element.
- type="range": slider between min and max.
- id="rating-overall" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
- name="ratingOverall" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- min="1" sets the smallest allowed value.
- max="5" sets the largest allowed value.
- step="1" sets how much the value changes each time (slider moves in steps of 1).
- value="4" is the slider's starting position.
- data-output="out-overall" is a custom data attribute naming the element JavaScript should update with the slider value.

```
144               <span class="range-output" id="out-overall">4</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
- id="out-overall" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
145               </div>
```

Closing: ends the container (opened on line 142).

```
146               </div>
```

Closing: ends the container (opened on line 140).

```
148               <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
149             <label for="rating-clarity">Faculty explanation clarity</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="rating-clarity" links this label to the control whose id is "rating-clarity": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
150             <div class="range-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: range-row (slider and its number on one line).

```
151             <input type="range" id="rating-clarity" name="ratingClarity" min="1" max="5" step="1"
value="4" data-output="out-clarity">
```

<input> Form control; its type attribute decides what kind. Void element.
• type="range": slider between min and max.
• id="rating-clarity" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
• name="ratingClarity" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• min="1" sets the smallest allowed value.
• max="5" sets the largest allowed value.
• step="1" sets how much the value changes each time (slider moves in steps of 1).
• value="4" is the slider's starting position.
• data-output="out-clarity" is a custom data attribute naming the element JavaScript should update with the slider value.

```
152             <span class="range-output" id="out-clarity">4</span>
```

 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
• id="out-clarity" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.
Text content (plain text inside an inline container).
Closing: ends the inline text.

```
153             </div>
```

Closing: ends the container (opened on line 150).

```
154             </div>
```

Closing: ends the container (opened on line 148).

```
156             <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
157             <label for="rating-effectiveness">Teaching effectiveness</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="rating-effectiveness" links this label to the control whose id is "rating-effectiveness": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
158             <div class="range-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: range-row (slider and its number on one line).

```
159             <input type="range" id="rating-effectiveness" name="ratingEffectiveness" min="1" max="5" step="1" value="4" data-output="out-effectiveness">
```

<input> Form control; its type attribute decides what kind. Void element.
- type="range": slider between min and max.
- id="rating-effectiveness" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
- name="ratingEffectiveness" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- min="1" sets the smallest allowed value.
- max="5" sets the largest allowed value.
- step="1" sets how much the value changes each time (slider moves in steps of 1).
- value="4" is the slider's starting position.
- data-output="out-effectiveness" is a custom data attribute naming the element JavaScript should update with the slider value.

```
160             <span class="range-output" id="out-effectiveness">4</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
- id="out-effectiveness" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.

Text content (plain text inside an inline container).
Closing: ends the inline text.

```
161             </div>
```

Closing: ends the container (opened on line 158).

```
162             </div>
```

Closing: ends the container (opened on line 156).

```
164             <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
165             <label for="rating-knowledge">Subject knowledge</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="rating-knowledge" links this label to the control whose id is "rating-knowledge": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
166             <div class="range-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: range-row (slider and its number on one line).

```
167             <input type="range" id="rating-knowledge" name="ratingKnowledge" min="1" max="5" step="1" value="5" data-output="out-knowledge">
```

<input> Form control; its type attribute decides what kind. Void element.
- type="range": slider between min and max.
- id="rating-knowledge" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
- name="ratingKnowledge" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- min="1" sets the smallest allowed value.
- max="5" sets the largest allowed value.
- step="1" sets how much the value changes each time (slider moves in steps of 1).
- value="5" is the slider's starting position.
- data-output="out-knowledge" is a custom data attribute naming the element JavaScript should update with the slider value.

```
168             <span class="range-output" id="out-knowledge">5</span>
```

 Generic inline container for a piece of text (no meaning of its own).
- class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
- id="out-knowledge" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.

Text content (plain text inside an inline container).
Closing: ends the inline text.

169
```
            </div>
```
Closing: ends the container (opened on line 166).

170
```
            </div>
```
Closing: ends the container (opened on line 164).

172
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

173
```
            <label for="rating-interaction">Interaction with students</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="rating-interaction" links this label to the control whose id is "rating-interaction": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

174
```
            <div class="range-row">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: range-row (slider and its number on one line).

175
```
            <input type="range" id="rating-interaction" name="ratingInteraction" min="1" max="5" step="1" value="3" data-output="out-interaction">
```
<input> Form control; its type attribute decides what kind. Void element.
• type="range": slider between min and max.
• id="rating-interaction" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
• name="ratingInteraction" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• min="1" sets the smallest allowed value.
• max="5" sets the largest allowed value.
• step="1" sets how much the value changes each time (slider moves in steps of 1).
• value="3" is the slider's starting position.
• data-output="out-interaction" is a custom data attribute naming the element JavaScript should update with the slider value.

176
```
            <span class="range-output" id="out-interaction">3</span>
```
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
• id="out-interaction" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.
Text content (plain text inside an inline container).
Closing: ends the inline text.

177
```
            </div>
```
Closing: ends the container (opened on line 174).

178
```
            </div>
```
Closing: ends the container (opened on line 172).

180
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

181
```
            <label for="rating-examples">Use of examples</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="rating-examples" links this label to the control whose id is "rating-examples": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

182
```
            <div class="range-row">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: range-row (slider and its number on one line).

183
```
            <input type="range" id="rating-examples" name="ratingExamples" min="1" max="5" step="1" value="4" data-output="out-examples">
```

<input> Form control; its type attribute decides what kind. Void element.
• type="range": slider between min and max.
• id="rating-examples" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
• name="ratingExamples" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• min="1" sets the smallest allowed value.
• max="5" sets the largest allowed value.
• step="1" sets how much the value changes each time (slider moves in steps of 1).
• value="4" is the slider's starting position.
• data-output="out-examples" is a custom data attribute naming the element JavaScript should update with the slider value.

184
```
            <span class="range-output" id="out-examples">4</span>
```

 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
• id="out-examples" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.
Text content (plain text inside an inline container).
Closing: ends the inline text.

185
```
            </div>
```

Closing: ends the container (opened on line 182).

186
```
            </div>
```

Closing: ends the container (opened on line 180).

188
```
            <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

189
```
            <label for="rating-material">Course material quality</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="rating-material" links this label to the control whose id is "rating-material": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

190
```
            <select id="rating-material" name="ratingMaterial">
```

<select> Dropdown list.
• id="rating-material" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
• name="ratingMaterial" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).

191
```
            <option value="5">Excellent</option>
```

<option> One choice inside a <select>.
• value="5" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

192
```
            <option value="4" selected>Good</option>
```

<option> One choice inside a <select>.
• value="4" is the data sent when this option is chosen (the visible text may differ).
• selected makes this option the pre-selected choice in the dropdown.
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

193
```
            <option value="3">Average</option>
```

<option> One choice inside a <select>.
• value="3" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
194                 <option value="2">Below average</option>
```

<option> One choice inside a <select>.
• value="2" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
195                 <option value="1">Poor</option>
```

<option> One choice inside a <select>.
• value="1" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
196             </select>
```

Closing: </select> ends the dropdown (opened on line 190).

```
197             </div>
```

Closing: ends the container (opened on line 188).

```
199             <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
200             <label for="rating-punctuality">Punctuality</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="rating-punctuality" links this label to the control whose id is "rating-punctuality": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
201             <select id="rating-punctuality" name="ratingPunctuality">
```

<select> Dropdown list.
• id="rating-punctuality" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
• name="ratingPunctuality" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).

```
202                 <option value="5">Always on time</option>
```

<option> One choice inside a <select>.
• value="5" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
203                 <option value="4" selected>Usually on time</option>
```

<option> One choice inside a <select>.
• value="4" is the data sent when this option is chosen (the visible text may differ).
• selected makes this option the pre-selected choice in the dropdown.
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
204                 <option value="3">Sometimes late</option>
```

<option> One choice inside a <select>.
• value="3" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
205                 <option value="2">Often late</option>
```

<option> One choice inside a <select>.
• value="2" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
206                 <option value="1">Rarely on time</option>
```

<option> One choice inside a <select>.
• value="1" is the data sent when this option is chosen (the visible text may differ).
Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

207
```
            </select>
```
Closing: </select> ends the dropdown (opened on line 201).

208
```
            </div>
```
Closing: ends the container (opened on line 199).

210
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

211
```
            <label for="rating-doubts">Doubt clarification</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="rating-doubts" links this label to the control whose id is "rating-doubts": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

212
```
            <div class="range-row">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: range-row (slider and its number on one line).

213
```
            <input type="range" id="rating-doubts" name="ratingDoubts" min="1" max="5" step="1" value="4" data-output="out-doubts">
```
<input> Form control; its type attribute decides what kind. Void element.
• type="range": slider between min and max.
• id="rating-doubts" is a unique name for this element: rating control (slider or dropdown) for one evaluation criterion.
• name="ratingDoubts" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• min="1" sets the smallest allowed value.
• max="5" sets the largest allowed value.
• step="1" sets how much the value changes each time (slider moves in steps of 1).
• value="4" is the slider's starting position.
• data-output="out-doubts" is a custom data attribute naming the element JavaScript should update with the slider value.

214
```
            <span class="range-output" id="out-doubts">4</span>
```
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: range-output (small gold box showing the slider value).
• id="out-doubts" is a unique name for this element: live number shown beside a slider; JavaScript updates it as the slider moves.
Text content (plain text inside an inline container).
Closing: ends the inline text.

215
```
            </div>
```
Closing: ends the container (opened on line 212).

216
```
            </div>
```
Closing: ends the container (opened on line 210).

217
```
          </fieldset>
```
Closing: </fieldset> ends the fieldset group (opened on line 137).

219
```
          <!-- WRITTEN FEEDBACK -->
```
HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "written feedback" part of the page.

220
```
          <fieldset>
```
<fieldset> Groups related form controls inside a bordered box.

221
```
            <legend>Written Feedback</legend>
```
<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

222
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

223
```
            <label for="fb-liked">What did you like about the course?</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="fb-liked" links this label to the control whose id is "fb-liked": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

224
```
            <textarea id="fb-liked" name="liked" maxlength="600" placeholder="e.g. Clear explanations, useful in-class examples..."></textarea>
```
<textarea> Multi-line text box.
• id="fb-liked" is a unique name for this element: text box: what the student liked.
• name="liked" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• maxlength="600" sets the maximum number of characters the user can type.
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
Closing: </textarea> ends the text box.

225
```
            </div>
```
Closing: ends the container (opened on line 222).

226
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

227
```
            <label for="fb-improve">What can be improved?</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="fb-improve" links this label to the control whose id is "fb-improve": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

228
```
            <textarea id="fb-improve" name="improve" maxlength="600" placeholder="e.g. More practice problems before the quiz..."></textarea>
```
<textarea> Multi-line text box.
• id="fb-improve" is a unique name for this element: text box: what can be improved.
• name="improve" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• maxlength="600" sets the maximum number of characters the user can type.
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
Closing: </textarea> ends the text box.

229
```
            </div>
```
Closing: ends the container (opened on line 226).

230
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

231
```
            <label for="fb-suggestions">Additional suggestions</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="fb-suggestions" links this label to the control whose id is "fb-suggestions": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

232
```
            <textarea id="fb-suggestions" name="suggestions" maxlength="600" placeholder="Optional"></textarea>
```
<textarea> Multi-line text box.
• id="fb-suggestions" is a unique name for this element: text box: extra suggestions.
• name="suggestions" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• maxlength="600" sets the maximum number of characters the user can type.
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
Closing: </textarea> ends the text box.

233
```
            </div>
```
Closing: ends the container (opened on line 230).

234
```
          </fieldset>
```
Closing: </fieldset> ends the fieldset group (opened on line 220).

```
236             <!-- RECOMMENDATION -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "recommendation" part of the page.

```
237             <fieldset>
```

`<fieldset>` Groups related form controls inside a bordered box.

```
238               <legend>Recommendation</legend>
```

`<legend>` Title of the `<fieldset>` it sits inside.
Text content (title of the fieldset group).
Closing: `</legend>` ends the legend.

```
239               <p style="margin-top:0;"><small>Would you recommend this course/faculty to a junior?</small></p>
```

`<p>` Paragraph of text.
- `style` is inline CSS that applies only to this one element. Properties: margin-top (space above).

`<small>` Fine print or side-note text.
Text content (fine-print text).
Closing: `</small>` ends the fine print; `</p>` ends the paragraph.

```
240               <div class="radio-group">
```

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `radio-group` (stacks radio options vertically).

```
241               <label class="radio-option"><input type="radio" name="fb-recommend" value="definitely"><span>Definitely recommend</span></label>
```

`<label>` Text label for a form control; clicking it focuses the control.
- `class` is a label that style.css uses to format the element: `radio-option` (one radio button plus its text).

`<input>` Form control; its `type` attribute decides what kind. Void element.
- `type="radio"`: round option button; only one choice per group is possible.
- `name="fb-recommend"`: radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
- `value="definitely"` is the data sent if this radio option is chosen.

`<span>` Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text; `</label>` ends the label.

```
242               <label class="radio-option"><input type="radio" name="fb-recommend" value="probably" checked><span>Probably recommend</span></label>
```

`<label>` Text label for a form control; clicking it focuses the control.
- `class` is a label that style.css uses to format the element: `radio-option` (one radio button plus its text).

`<input>` Form control; its `type` attribute decides what kind. Void element.
- `type="radio"`: round option button; only one choice per group is possible.
- `name="fb-recommend"`: radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
- `value="probably"` is the data sent if this radio option is chosen.
- `checked` pre-selects this option when the page loads.

`<span>` Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text; `</label>` ends the label.

```
243               <label class="radio-option"><input type="radio" name="fb-recommend" value="not-sure"><span>Not sure</span></label>
```

`<label>` Text label for a form control; clicking it focuses the control.
- `class` is a label that style.css uses to format the element: `radio-option` (one radio button plus its text).

`<input>` Form control; its `type` attribute decides what kind. Void element.
- `type="radio"`: round option button; only one choice per group is possible.
- `name="fb-recommend"`: radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
- `value="not-sure"` is the data sent if this radio option is chosen.

`<span>` Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text; `</label>` ends the label.

244
```
            <label class="radio-option"><input type="radio" name="fb-recommend"
value="probably-not"><span>Probably not</span></label>
```

<label> Text label for a form control; clicking it focuses the control.
• class is a label that style.css uses to format the element: radio-option (one radio button plus its text).
<input> Form control; its type attribute decides what kind. Void element.
• type="radio": round option button; only one choice per group is possible.
• name="fb-recommend": radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
• value="probably-not" is the data sent if this radio option is chosen.
 Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: ends the inline text; </label> ends the label.

245
```
            <label class="radio-option"><input type="radio" name="fb-recommend"
value="definitely-not"><span>Definitely not</span></label>
```

<label> Text label for a form control; clicking it focuses the control.
• class is a label that style.css uses to format the element: radio-option (one radio button plus its text).
<input> Form control; its type attribute decides what kind. Void element.
• type="radio": round option button; only one choice per group is possible.
• name="fb-recommend": radios sharing the same name form one group, so only one can be chosen; the chosen value is submitted under this name.
• value="definitely-not" is the data sent if this radio option is chosen.
 Generic inline container for a piece of text (no meaning of its own).
Text content (plain text inside an inline container).
Closing: ends the inline text; </label> ends the label.

246
```
            </div>
```

Closing: ends the container (opened on line 240).

247
```
          </fieldset>
```

Closing: </fieldset> ends the fieldset group (opened on line 237).

249
```
          <!-- CONFIRMATION -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "confirmation" part of the page.

250
```
          <div class="confirm-box field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: confirm-box (grey box around the confirmation checkbox); field (spacing wrapper for one form field).

251
```
            <label class="checkbox-option" style="font-weight:400;">
```

<label> Text label for a form control; clicking it focuses the control.
• class is a label that style.css uses to format the element: checkbox-option (one checkbox plus its text).
• style is inline CSS that applies only to this one element. Properties: font-weight (boldness).

252
```
            <input type="checkbox" id="fb-confirm" name="confirm" required>
```

<input> Form control; its type attribute decides what kind. Void element.
• type="checkbox": square on/off tick box; each one is independent.
• id="fb-confirm" is a unique name for this element: confirmation checkbox that must be ticked before submitting.
• name="confirm" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• required means the field must be filled in before the browser allows submission (when browser validation is on).

253
```
            <span>I confirm that this feedback is genuine and submitted for academic evaluation.</span>
```

 Generic inline container for a piece of text (no meaning of its own).
Text content: Plain text inside an inline container.
Closing: ends the inline text.

254
```
            </label>
```

Closing: </label> ends the label (opened on line 251).

255
```
          </div>
```

Closing: ends the container (opened on line 250).

257
```
          <div class="btn-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: btn-row (lines buttons up in a row with a gap).

```
258             <button type="submit" class="btn btn-primary">Submit Feedback</button>
```

<button> Clickable button.
• type="submit": clicking sends the form.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-primary (solid navy button).
Text content (text shown on the button).
Closing: </button> ends the button.

```
259             <button type="reset" class="btn btn-ghost">Reset Form</button>
```

<button> Clickable button.
• type="reset": clicking clears all fields back to their defaults (built-in, no JavaScript).
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-ghost (quiet, low-emphasis button).
Text content (text shown on the button).
Closing: </button> ends the button.

```
260           </div>
```

Closing: ends the container (opened on line 257).

```
261         </form>
```

Closing: </form> ends the form (opened on line 58).

```
263         <!-- FEEDBACK GUIDELINES ASIDE -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "feedback guidelines aside" part of the page.

```
264         <aside class="card" aria-label="Feedback guidelines">
```

<aside> **Semantic.** Side content related to the main content but not essential to it.
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
265           <h3>Rating scale reference</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
266           <dl class="def-list">
```

<dl> Description list: pairs of terms and descriptions.
• class is a label that style.css uses to format the element: def-list (two-column layout for a description list).

```
267             <dt>5</dt><dd>Excellent</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content (the description of the term above).
Closing: </dd> ends the description.

```
268             <dt>4</dt><dd>Good</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content (the description of the term above).
Closing: </dd> ends the description.

```
269             <dt>3</dt><dd>Average</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content (the description of the term above).
Closing: </dd> ends the description.

```
270              <dt>2</dt><dd>Below average</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content (the description of the term above).
Closing: </dd> ends the description.

```
271              <dt>1</dt><dd>Poor</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content (the description of the term above).
Closing: </dd> ends the description.

```
272            </dl>
```

Closing: </dl> ends the description list (opened on line 266).

```
273            <hr>
```

<hr> Horizontal rule: a thematic break between pieces of content. Void element.

```
274            <h3>Quick guidelines</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
275            <ul class="guideline-list">
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.
- class is a label that style.css uses to format the element: guideline-list (styled bullet list in a side box).

```
276              <li>Answer based on this semester only.</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
277              <li>Written feedback should be specific and constructive.</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
278              <li>You can submit once per course-and-faculty pairing.</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
279            </ul>
```

Closing: ends the bullet list (opened on line 275).

```
280          </aside>
```

Closing: </aside> ends the side box (opened on line 264).

```
281        </div>
```

Closing: ends the container (opened on line 56).

```
282      </div>
```

Closing: ends the container (opened on line 43).

```
283    </section>
```

Closing: </section> ends the section (opened on line 42).

```
284  </main>
```

Closing: </main> ends the main content (opened on line 41).

```
286   <footer class="site-footer">
```

<footer> **Semantic.** Closing area of the page: copyright and secondary links.
• class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

```
287     <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
288       <div class="footer-bottom">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

```
289         <span>&copy; <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
• © displays the copyright symbol
Another on this line:
• id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.
Closing: ends the inline text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

```
290         <span><a href="analytics.html" style="color:#cfd5e4;">See results</a></span>
```

 Generic inline container for a piece of text (no meaning of its own).
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
• style is inline CSS that applies only to this one element. Properties: color (text colour).
Text content (visible clickable link text).
Closing: ends the link; ends the inline text.

```
291       </div>
```

Closing: ends the container (opened on line 288).

```
292     </div>
```

Closing: ends the container (opened on line 287).

```
293   </footer>
```

Closing: </footer> ends the page footer (opened on line 286).

```
295   <script src="script.js"></script>
```

<script> Loads JavaScript into the page.
• src="script.js" loads the external JavaScript file script.js.
Closing: </script> ends the script.

```
296 </body>
```

Closing: </body> ends the visible page (opened on line 12).

```
297 </html>
```

Closing: </html> ends the whole document (opened on line 2).

Viva tips for feedback.html

- <fieldset> + <legend> group related controls; mention all five groups.
- Radio buttons share a name so only one can be chosen; the checkbox is independent and required.
- <input type="range"> with min, max, step, value makes each rating slider.
- The faculty dropdown starts empty and JavaScript fills it from the chosen course.
- novalidate is on this form: JavaScript performs the checks and shows friendly messages.

6. analytics.html - Results and analytics

Purpose	Public results page: summary cards, two bar charts and a rating-distribution table. Individual answers are never shown, only averages.
Size	120 lines in the file, 109 with content (all explained below).
Tags used (count)	a 11, article 2, aside 1, body 1, button 1, caption 1, circle 1, code 1, div 15, footer 1, h1 1, h2 3, h3 1, head 1, header 1, html 1, li 9, link 3, main 1, meta 3, nav 1, p 7, path 2, script 1, section 2, span 13, strong 1, svg 1, table 1, tbody 1, td 20, th 4, thead 1, title 1, tr 6, ul 1

Line-by-line: analytics.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Summarized course and faculty evaluation results.">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>Results &amp;amp; Analytics | Faculty Feedback Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
- & displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: </head> ends the head area (opened on line 3).

12 `<body>`

`<body>` Holds everything the visitor actually sees on the page.

14 `  <header class="site-header">`

`<header>` **Semantic.** Introductory area at the top of the page: branding and navigation.
- `class` is a label that style.css uses to format the element: `site-header` (dark-blue sticky top bar with a gold bottom border).

15 `    <div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

16 `      <a href="index.html" class="brand">`

`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `class` is a label that style.css uses to format the element: `brand` (logo plus site-name link).

17 `        <svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img" aria-label="Portal crest">`

`<svg>` Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- `class` is a label that style.css uses to format the element: `brand-mark` (sizes the round logo icon).
- `viewBox="0 0 40 40"` is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- `xmlns` identifies the XML namespace that tells the browser this is SVG.
- `role="img"` tells assistive technology to treat this whole element as one image, described by its aria-label.
- `aria-label` gives an accessible name that screen readers announce (it is not shown on screen).

18 `          <circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>`

`<circle>` SVG shape: a circle.
- `cx` is the horizontal position of the circle centre.
- `cy` is the vertical position of the circle centre.
- `r` is the circle radius.
- `fill="#243B66"` sets the shape's fill colour.
- `stroke="#B1802F"` sets the outline colour.
- `stroke-width="2"` sets the outline thickness.

19 `          <path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="#F1E2C3"` sets the shape's fill colour.

20 `          <path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="none"` means the shape has no fill: only its outline is drawn.
- `stroke="#F1E2C3"` sets the outline colour.
- `stroke-width="1.6"` sets the outline thickness.

21 `        </svg>`

Closing: `</svg>` ends the SVG graphic (opened on line 17).

22 `        <span>LPU Feedback Portal<span class="brand-sub">Faculty & Course Evaluation</span></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another `<span>` on this line:
- `class` is a label that style.css uses to format the element: `brand-sub` (small second line under the site name).

Text content (plain text inside an inline container).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</span>` ends the inline text; `</span>` ends the inline text.

23 `      </a>`

Closing: `</a>` ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html" aria-current="page">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
43      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
44        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
45          <p class="eyebrow">Results</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
46          <h1>Course &amp; Faculty Analytics</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: </h1> ends the main heading.

```
47          <p>Aggregated ratings across all submitted evaluations. Individual responses are never shown here
— only averages.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
48          </div>
```

Closing: ends the container (opened on line 44).

```
50          <p class="demo-note"><strong>Sample data:</strong> the figures on this page are demo values written into <code>script.js</code> for the CA1 demonstration.</p>
```

 Paragraph of text.
- class is a label that style.css uses to format the element: demo-note (gold notice box explaining this is demo data).

 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (paragraph text the visitor reads).
<code> Shows text in monospace code style.
Text content (text shown in code style).
Closing: </code> ends the code text.
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
52          <div class="card-grid" style="margin-bottom:2.5rem;">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: card-grid (responsive grid that lines cards up).
- style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

```
53            <div class="stat-card"><span class="stat-value">412</span><span class="stat-label">Total submissions</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
54            <div class="stat-card"><span class="stat-value">4.42</span><span class="stat-label">Average faculty rating</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
55            <div class="stat-card"><span class="stat-value">4.23</span><span class="stat-label">Average course rating</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
56          <div class="stat-card"><span class="stat-value">68%</span><span class="stat-label">Anonymous submissions</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

```
57      </div>
```

Closing: ends the container (opened on line 52).

```
59      <article style="margin-bottom:2.5rem;">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

```
60          <h2>Faculty performance</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
61          <p>Average rating out of 5, across all courses each faculty member teaches.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
62          <div class="card" id="faculty-bar-chart" role="img" aria-label="Bar chart comparing average faculty ratings out of five"></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
- id="faculty-bar-chart" is a unique name for this element: empty box; JavaScript draws the faculty bar chart inside it.
- role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
- aria-label gives an accessible name that screen readers announce (it is not shown on screen).

Closing: ends the container.

```
63      </article>
```

Closing: </article> ends the article (opened on line 59).

```
65      <article>
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).

```
66          <h2>Course ratings</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
67          <p>Average overall course rating out of 5.</p>
```

 Paragraph of text.
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
68          <div class="card" id="course-bar-chart" role="img" aria-label="Bar chart comparing average course ratings out of five"></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
- id="course-bar-chart" is a unique name for this element: empty box; JavaScript draws the course bar chart inside it.
- role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
- aria-label gives an accessible name that screen readers announce (it is not shown on screen).

Closing: ends the container.

```
69      </article>
```

Closing: </article> ends the article (opened on line 65).

70 `      </div>`

Closing: ends the container (opened on line 43).

71 `    </section>`

Closing: </section> ends the section (opened on line 42).

73 `    <section class="section section-alt">`

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content); section-alt (gives the block a slightly darker background band).

74 `      <div class="container">`

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

75 `        <div class="section-head">`

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

76 `          <p class="eyebrow">Breakdown</p>`

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

77 `          <h2>Rating distribution</h2>`

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

78 `        </div>`

Closing: ends the container (opened on line 75).

79 `        <div class="table-wrap">`

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: table-wrap (lets a wide table scroll sideways on small screens).

80 `          <table>`

<table> Table of data (never used for page layout).

81 `            <caption>How students rated overall course quality (sample data)</caption>`

<caption> Visible title of the table; also read aloud by screen readers.
Text content (visible title of the table).
Closing: </caption> ends the table caption.

82 `            <thead>`

<thead> Groups the header row of the table.

83 `              <tr>`

<tr> One table row.

84 `              <th scope="col">Rating</th>`

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Rating
Closing: </th> ends the header cell.

85 `              <th scope="col">Meaning</th>`

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Meaning
Closing: </th> ends the header cell.

```
86              <th scope="col">Responses</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Responses
Closing: </th> ends the header cell.

```
87              <th scope="col">Share</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Share
Closing: </th> ends the header cell.

```
88            </tr>
```

Closing: </tr> ends the table row (opened on line 83).

```
89          </thead>
```

Closing: </thead> ends the table header (opened on line 82).

```
90          <tbody>
```

<tbody> Groups the data rows of the table.

```
91              <tr><td>5</td><td>Excellent</td><td>186</td><td>45%</td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 4 times on this line)
Cell contents, in column order: 5 | Excellent | 186 | 45%
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell; </tr> ends the table row.

```
92              <tr><td>4</td><td>Good</td><td>142</td><td>34%</td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 4 times on this line)
Cell contents, in column order: 4 | Good | 142 | 34%
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell; </tr> ends the table row.

```
93              <tr><td>3</td><td>Average</td><td>58</td><td>14%</td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 4 times on this line)
Cell contents, in column order: 3 | Average | 58 | 14%
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell; </tr> ends the table row.

```
94              <tr><td>2</td><td>Below average</td><td>19</td><td>5%</td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 4 times on this line)
Cell contents, in column order: 2 | Below average | 19 | 5%
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell; </tr> ends the table row.

```
95              <tr><td>1</td><td>Poor</td><td>7</td><td>2%</td></tr>
```

<tr> One table row.
<td> Table data cell. (appears 4 times on this line)
Cell contents, in column order: 1 | Poor | 7 | 2%
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell; </tr> ends the table row.

```
96          </tbody>
```

Closing: </tbody> ends the table body (opened on line 90).

```
97          </table>
```

Closing: </table> ends the table (opened on line 80).

```
98        </div>
```

Closing: ends the container (opened on line 79).

```
100       <aside class="card" style="margin-top:2rem;">
```

<aside> **Semantic.** Side content related to the main content but not essential to it.
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
- style is inline CSS that applies only to this one element. Properties: margin-top (space above).

```
101         <h3>How to read these numbers</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
102         <p class="mb-0">Averages hide small sample sizes. A course with 12 responses and a 4.8 average is
less reliable than one with 120 responses and a 4.4 average — always check the response count in the Admin
Dashboard before acting on a rating.</p>
```

 Paragraph of text.
- class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).

Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
103       </aside>
```

Closing: </aside> ends the side box (opened on line 100).

```
104     </div>
```

Closing: ends the container (opened on line 74).

```
105   </section>
```

Closing: </section> ends the section (opened on line 73).

```
106 </main>
```

Closing: </main> ends the main content (opened on line 41).

```
108 <footer class="site-footer">
```

<footer> **Semantic.** Closing area of the page: copyright and secondary links.
- class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

```
109   <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
110     <div class="footer-bottom">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

```
111       <span>&copy; <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
- © displays the copyright symbol

Another on this line:
- id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.

Closing: ends the inline text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

```
112       <span><a href="admin.html" style="color:#cfd5e4;">Full admin view</a></span>
```

 Generic inline container for a piece of text (no meaning of its own).
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
- style is inline CSS that applies only to this one element. Properties: color (text colour).

Text content (visible clickable link text).
Closing: ends the link; ends the inline text.

113 `</div>`

Closing: `</div>` ends the container (opened on line 110).

114 `</div>`

Closing: `</div>` ends the container (opened on line 109).

115 `</footer>`

Closing: `</footer>` ends the page footer (opened on line 108).

117 `<script src="script.js"></script>`

`<script>` Loads JavaScript into the page.
- `src="script.js"` loads the external JavaScript file script.js.

Closing: `</script>` ends the script.

118 `</body>`

Closing: `</body>` ends the visible page (opened on line 12).

119 `</html>`

Closing: `</html>` ends the whole document (opened on line 2).

Viva tips for analytics.html

- The two chart `<div>`s are empty in HTML; JavaScript fills them using the ratings arrays.
- `role="img"` and `aria-label` describe each chart for screen-reader users.
- `<article>` wraps each self-contained chart block; `<aside>` holds the reading tip.
- The distribution table shows rating, meaning, responses and share.

7. admin.html - Admin dashboard

Purpose	Administrator view: five statistic cards, two bar charts, faculty-wise and course-wise comparison tables, recent comments and next-action list.
Size	175 lines in the file, 162 with content (all explained below).
Tags used (count)	a 11, article 8, aside 1, body 1, button 1, caption 2, circle 1, div 16, em 3, footer 1, h1 1, h2 5, h3 4, head 1, header 1, html 1, li 12, link 3, main 1, meta 3, nav 1, ol 1, p 10, path 2, script 1, section 1, small 3, span 24, strong 7, svg 1, table 2, tbody 2, td 60, th 24, thead 2, title 1, tr 14, ul 1

Line-by-line: admin.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Administrator dashboard summarizing feedback submissions and ratings.">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>Admin Dashboard | Faculty Feedback Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: </head> ends the head area (opened on line 3).

12 `<body>`

`<body>` Holds everything the visitor actually sees on the page.

14 `<header class="site-header">`

`<header>` **Semantic.** Introductory area at the top of the page: branding and navigation.
- `class` is a label that style.css uses to format the element: `site-header` (dark-blue sticky top bar with a gold bottom border).

15 `<div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

16 `<a href="index.html" class="brand">`

`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `class` is a label that style.css uses to format the element: `brand` (logo plus site-name link).

17 `<svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img" aria-label="Portal crest">`

`<svg>` Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- `class` is a label that style.css uses to format the element: `brand-mark` (sizes the round logo icon).
- `viewBox="0 0 40 40"` is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- `xmlns` identifies the XML namespace that tells the browser this is SVG.
- `role="img"` tells assistive technology to treat this whole element as one image, described by its aria-label.
- `aria-label` gives an accessible name that screen readers announce (it is not shown on screen).

18 `<circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>`

`<circle>` SVG shape: a circle.
- `cx` is the horizontal position of the circle centre.
- `cy` is the vertical position of the circle centre.
- `r` is the circle radius.
- `fill="#243B66"` sets the shape's fill colour.
- `stroke="#B1802F"` sets the outline colour.
- `stroke-width="2"` sets the outline thickness.

19 `<path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="#F1E2C3"` sets the shape's fill colour.

20 `<path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="none"` means the shape has no fill: only its outline is drawn.
- `stroke="#F1E2C3"` sets the outline colour.
- `stroke-width="1.6"` sets the outline thickness.

21 `</svg>`

Closing: `</svg>` ends the SVG graphic (opened on line 17).

22 `<span>LPU Feedback Portal<span class="brand-sub">Faculty & Course Evaluation</span></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another `<span>` on this line:
- `class` is a label that style.css uses to format the element: `brand-sub` (small second line under the site name).

Text content (plain text inside an inline container).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</span>` ends the inline text; `</span>` ends the inline text.

23 `</a>`

Closing: `</a>` ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html" aria-current="page">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• `href="admin.html"` is a relative path: it opens admin.html, which sits in the same folder.
• `aria-current="page"` marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• `href="about.html"` is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• `href="contact.html"` is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• `class` is a label that style.css uses to format the element: `section` (adds vertical spacing around a block of content).

```
43      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

```
44        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• `class` is a label that style.css uses to format the element: `section-head` (limits the width of a heading block so it stays readable).

```
45          <p class="eyebrow">Administration</p>
```

 Paragraph of text.
• `class` is a label that style.css uses to format the element: `eyebrow` (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
46          <h1>Admin Dashboard</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
Closing: </h1> ends the main heading.

```
47          <p>Semester-wide summary of feedback collection and evaluation results.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

48
```
        </div>
```
Closing: ends the container (opened on line 44).

50
```
        <p class="demo-note"><strong>Open for evaluation:</strong> in a real deployment this page would be restricted to authorized staff. This static demo has no server-side access control.</p>
```
 Paragraph of text.
- class is a label that style.css uses to format the element: demo-note (gold notice box explaining this is demo data).

 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

52
```
        <div class="card-grid" style="margin-bottom:2.5rem;">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: card-grid (responsive grid that lines cards up).
- style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

53
```
          <div class="stat-card"><span class="stat-value">412</span><span class="stat-label">Total feedback submissions</span></div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

54
```
          <div class="stat-card"><span class="stat-value">4.42</span><span class="stat-label">Average faculty rating</span></div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

55
```
          <div class="stat-card"><span class="stat-value">4.23</span><span class="stat-label">Average course rating</span></div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

56
```
          <div class="stat-card"><span class="stat-value">96</span><span class="stat-label">Pending evaluations</span></div>
```
 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: stat-card (small box showing one big number).

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
- class is a label that style.css uses to format the element: stat-value (the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
- class is a label that style.css uses to format the element: stat-label (caption under the big number).

Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

57
```
          <div class="stat-card"><span class="stat-value">316</span><span class="stat-label">Completed evaluations</span></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: stat-card (small box showing one big number).
 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
• class is a label that style.css uses to format the element: stat-value (the big number).
Text content (plain text inside an inline container).
Closing: ends the inline text.
Another on this line:
• class is a label that style.css uses to format the element: stat-label (caption under the big number).
Text content (plain text inside an inline container).
Closing: ends the inline text; ends the container.

58
```
        </div>
```

Closing: ends the container (opened on line 52).

60
```
        <!-- ===== FACULTY BAR CHART ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "faculty bar chart" part of the page.

61
```
        <article style="margin-bottom:2.5rem;">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

62
```
          <h2>Faculty performance</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

63
```
          <div class="card" id="faculty-bar-chart" role="img" aria-label="Bar chart of average faculty ratings out of five"></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
• id="faculty-bar-chart" is a unique name for this element: empty box; JavaScript draws the faculty bar chart inside it.
• role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
Closing: ends the container.

64
```
        </article>
```

Closing: </article> ends the article (opened on line 61).

66
```
        <!-- ===== COURSE BAR CHART ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "course bar chart" part of the page.

67
```
        <article style="margin-bottom:2.5rem;">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

68
```
          <h2>Course ratings</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

69
```
          <div class="card" id="course-bar-chart" role="img" aria-label="Bar chart of average course ratings out of five"></div>
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
• id="course-bar-chart" is a unique name for this element: empty box; JavaScript draws the course bar chart inside it.
• role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
Closing: ends the container.

70
```
        </article>
```

Closing: </article> ends the article (opened on line 67).

```
72        <!-- ===== FACULTY COMPARISON TABLE ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "faculty comparison table" part of the page.

```
73        <article style="margin-bottom:2.5rem;">
```

`<article>` **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• `style` is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

```
74          <h2>Faculty-wise analysis</h2>
```

`<h2>` Second-level heading: a major section title.
Text content (section heading text).
Closing: `</h2>` ends the section heading.

```
75          <div class="table-wrap">
```

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
• `class` is a label that style.css uses to format the element: `table-wrap` (lets a wide table scroll sideways on small screens).

```
76            <table>
```

`<table>` Table of data (never used for page layout).

```
77              <caption>Faculty comparison across evaluation criteria (sample data)</caption>
```

`<caption>` Visible title of the table; also read aloud by screen readers.
Text content (visible title of the table).
Closing: `</caption>` ends the table caption.

```
78              <thead>
```

`<thead>` Groups the header row of the table.

```
79                <tr>
```

`<tr>` One table row.

```
80                <th scope="col">Faculty</th>
```

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Faculty
Closing: `</th>` ends the header cell.

```
81                <th scope="col">Responses</th>
```

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Responses
Closing: `</th>` ends the header cell.

```
82                <th scope="col">Clarity</th>
```

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Clarity
Closing: `</th>` ends the header cell.

```
83                <th scope="col">Effectiveness</th>
```

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Effectiveness
Closing: `</th>` ends the header cell.

```
84                <th scope="col">Doubt clarification</th>
```

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Doubt clarification
Closing: `</th>` ends the header cell.

```
85                <th scope="col">Overall</th>
```

`<th>` Table header cell: gives meaning to its column or row.
• `scope="col"` tells screen readers this header cell describes the column below it.
Cell content: Overall
Closing: `</th>` ends the header cell.

```
86                  </tr>
```

Closing: </tr> ends the table row (opened on line 79).

```
87                  </thead>
```

Closing: </thead> ends the table header (opened on line 78).

```
88                  <tbody>
```

<tbody> Groups the data rows of the table.

```
89                  <tr><th scope="row">Dr. P. Kaur</th><td>78</td><td>4.8</td><td>4.7</td><td>4.6</td><td><strong>4.7</strong></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: Dr. P. Kaur
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 78 | 4.8 | 4.7 | 4.6
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text; </td> ends the data cell; </tr> ends the table row.

```
90                  <tr><th scope="row">Dr. A. Sharma</th><td>91</td><td>4.7</td><td>4.6</td><td>4.4</td><td><strong>4.6</strong></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: Dr. A. Sharma
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 91 | 4.7 | 4.6 | 4.4
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text; </td> ends the data cell; </tr> ends the table row.

```
91                  <tr><th scope="row">Dr. N. Singh</th><td>64</td><td>4.4</td><td>4.6</td><td>4.5</td><td><strong>4.5</strong></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: Dr. N. Singh
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 64 | 4.4 | 4.6 | 4.5
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text; </td> ends the data cell; </tr> ends the table row.

92
```
              <tr><th scope="row">Ms. K. Bhatia</th><td>52</td><td>4.5</td><td>4.3</td><td>4.4</td><td><stron
g>4.4</strong></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: Ms. K. Bhatia
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 52 | 4.5 | 4.3 | 4.4
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text; </td> ends the data cell; </tr> ends the table row.

93
```
              <tr><th scope="row">Dr. R. Verma</th><td>70</td><td>4.1</td><td>4.3</td><td>4.2</td><td><strong
>4.2</strong></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: Dr. R. Verma
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 70 | 4.1 | 4.3 | 4.2
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text; </td> ends the data cell; </tr> ends the table row.

94
```
              <tr><th scope="row">Dr. S. Iyer</th><td>57</td><td>4.0</td><td>4.2</td><td>4.1</td><td><strong>
4.1</strong></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: Dr. S. Iyer
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 57 | 4.0 | 4.2 | 4.1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text; </td> ends the data cell; </tr> ends the table row.

95
```
            </tbody>
```

Closing: </tbody> ends the table body (opened on line 88).

96
```
          </table>
```

Closing: </table> ends the table (opened on line 76).

97
```
        </div>
```

Closing: ends the container (opened on line 75).

98
```
      </article>
```

Closing: </article> ends the article (opened on line 73).

100
```
      <!-- ===== COURSE COMPARISON TABLE ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "course comparison table" part of the page.

```
101         <article style="margin-bottom:2.5rem;">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• style is inline CSS that applies only to this one element. Properties: margin-bottom (space below).

```
102           <h2>Course-wise analysis</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
103           <div class="table-wrap">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: table-wrap (lets a wide table scroll sideways on small screens).

```
104             <table>
```

<table> Table of data (never used for page layout).

```
105               <caption>Course comparison with collection status (sample data)</caption>
```

<caption> Visible title of the table; also read aloud by screen readers.
Text content (visible title of the table).
Closing: </caption> ends the table caption.

```
106               <thead>
```

<thead> Groups the header row of the table.

```
107               <tr>
```

<tr> One table row.

```
108                 <th scope="col">Course</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Course
Closing: </th> ends the header cell.

```
109                 <th scope="col">Enrolled</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Enrolled
Closing: </th> ends the header cell.

```
110                 <th scope="col">Responses</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Responses
Closing: </th> ends the header cell.

```
111                 <th scope="col">Response rate</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Response rate
Closing: </th> ends the header cell.

```
112                 <th scope="col">Average rating</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Average rating
Closing: </th> ends the header cell.

```
113                 <th scope="col">Status</th>
```

<th> Table header cell: gives meaning to its column or row.
• scope="col" tells screen readers this header cell describes the column below it.
Cell content: Status
Closing: </th> ends the header cell.

```
114               </tr>
```

Closing: </tr> ends the table row (opened on line 107).

115
```
            </thead>
```
Closing: </thead> ends the table header (opened on line 106).

116
```
            <tbody>
```
<tbody> Groups the data rows of the table.

117
```
            <tr><th scope="row">CSE101</th><td>120</td><td>96</td><td>80%</td><td>4.5</td><td><span class="badge badge-success">Healthy</span></td></tr>
```
<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: CSE101
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 120 | 96 | 80% | 4.5
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

118
```
            <tr><th scope="row">CSE102</th><td>118</td><td>71</td><td>60%</td><td>4.0</td><td><span class="badge badge-pending">Needs reminder</span></td></tr>
```
<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: CSE102
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 118 | 71 | 60% | 4.0
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

119
```
            <tr><th scope="row">CSE103</th><td>110</td><td>88</td><td>80%</td><td>4.6</td><td><span class="badge badge-success">Healthy</span></td></tr>
```
<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: CSE103
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 110 | 88 | 80% | 4.6
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

120
```
            <tr><th scope="row">MTH101</th><td>124</td><td>49</td><td>40%</td><td>3.9</td><td><span class="badge badge-danger">Low response</span></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: MTH101
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 124 | 49 | 40% | 3.9
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-danger (red pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

121
```
            <tr><th scope="row">PHY101</th><td>116</td><td>63</td><td>54%</td><td>4.1</td><td><span class="badge badge-pending">Needs reminder</span></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: PHY101
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 116 | 63 | 54% | 4.1
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

122
```
            <tr><th scope="row">ENG101</th><td>102</td><td>45</td><td>44%</td><td>4.3</td><td><span class="badge badge-danger">Low response</span></td></tr>
```

<tr> One table row.
<th> Table header cell: gives meaning to its column or row.
• scope="row" tells screen readers this header cell describes the whole row.
Cell content: ENG101
Closing: </th> ends the header cell.
<td> Table data cell. (appears 5 times on this line)
Cell contents, in column order: 102 | 45 | 44% | 4.3
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
Closing: </td> ends the data cell.
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-danger (red pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text; </td> ends the data cell; </tr> ends the table row.

123
```
          </tbody>
```

Closing: </tbody> ends the table body (opened on line 116).

124
```
        </table>
```

Closing: </table> ends the table (opened on line 104).

125
```
      </div>
```

Closing: ends the container (opened on line 103).

126
```
    </article>
```

Closing: </article> ends the article (opened on line 101).

```
128         <!-- ===== RECENT WRITTEN FEEDBACK ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "recent written feedback" part of the page.

```
129         <article>
```

`<article>` **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).

```
130           <h2>Recent written feedback</h2>
```

`<h2>` Second-level heading: a major section title.
Text content (section heading text).
Closing: `</h2>` ends the section heading.

```
131           <p>Anonymous submissions are displayed without any student identifier.</p>
```

`<p>` Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: `</p>` ends the paragraph.

```
132           <div class="card-grid">
```

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `card-grid` (responsive grid that lines cards up).

```
133             <article class="card">
```

`<article>` **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- `class` is a label that style.css uses to format the element: `card` (white box with a border and a gold top edge).

```
134               <h3>CSE101 &middot; Dr. A. Sharma</h3>
```

`<h3>` Third-level heading: a sub-section title.
Text content (sub-heading text).
- `·` displays a middle dot used as a separator

Closing: `</h3>` ends the sub-heading.

```
135               <p><em>"The dry-run walkthroughs on the board made loops click for me. More practice sets before the quiz would help."</em></p>
```

`<p>` Paragraph of text.
`<em>` Marks text with emphasis (shown italic). Semantic, unlike `<i>`.
Text content (emphasised (italic) text).
Closing: `</em>` ends the emphasised text; `</p>` ends the paragraph.

```
136               <p class="mb-0"><span class="badge badge-pending">Anonymous</span> <small>06 Nov</small></p>
```

`<p>` Paragraph of text.
- `class` is a label that style.css uses to format the element: `mb-0` (removes the bottom margin).

`<span>` Generic inline container for a piece of text (no meaning of its own).
- `class` is a label that style.css uses to format the element: `badge` (small rounded status pill); `badge-pending` (gold pill colours).

Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text.
`<small>` Fine print or side-note text.
Text content (fine-print text).
Closing: `</small>` ends the fine print; `</p>` ends the paragraph.

```
137             </article>
```

Closing: `</article>` ends the article (opened on line 133).

```
138             <article class="card">
```

`<article>` **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- `class` is a label that style.css uses to format the element: `card` (white box with a border and a gold top edge).

```
139               <h3>MTH101 &middot; Dr. S. Iyer</h3>
```

`<h3>` Third-level heading: a sub-section title.
Text content (sub-heading text).
- `·` displays a middle dot used as a separator

Closing: `</h3>` ends the sub-heading.

```
140             <p><em>"Pace is fast in the last twenty minutes of class. Slides posted a day earlier would let us prepare."</em></p>
```

 Paragraph of text.
 Marks text with emphasis (shown italic). Semantic, unlike <i>.
Text content (emphasised (italic) text).
Closing: ends the emphasised text; ends the paragraph.

```
141             <p class="mb-0"><span class="badge badge-pending">Anonymous</span> <small>05 Nov</small></p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-pending (gold pill colours).
Text content (plain text inside an inline container).
Closing: ends the inline text.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; ends the paragraph.

```
142           </article>
```

Closing: </article> ends the article (opened on line 138).

```
143           <article class="card">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).

```
144             <h3>CSE104 &middot; Dr. R. Verma</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
• · displays a middle dot used as a separator
Closing: </h3> ends the sub-heading.

```
145             <p><em>"Lab sessions are the strongest part of this course. Theory classes could use more live coding."</em></p>
```

 Paragraph of text.
 Marks text with emphasis (shown italic). Semantic, unlike <i>.
Text content (emphasised (italic) text).
Closing: ends the emphasised text; ends the paragraph.

```
146             <p class="mb-0"><span class="badge badge-success">Identified &middot; 123xxxxx</span> <small>04 Nov</small></p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
 Generic inline container for a piece of text (no meaning of its own).
• class is a label that style.css uses to format the element: badge (small rounded status pill); badge-success (green pill colours).
Text content (plain text inside an inline container).
• · displays a middle dot used as a separator
Closing: ends the inline text.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; ends the paragraph.

```
147           </article>
```

Closing: </article> ends the article (opened on line 143).

```
148         </div>
```

Closing: ends the container (opened on line 132).

```
149       </article>
```

Closing: </article> ends the article (opened on line 129).

```
151       <aside class="card" style="margin-top:2.5rem;">
```

<aside> **Semantic.** Side content related to the main content but not essential to it.
• class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
• style is inline CSS that applies only to this one element. Properties: margin-top (space above).

```
152          <h3>Actions an administrator would take next</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
153          <ol class="feature-list">
```

 Ordered (numbered) list.
• class is a label that style.css uses to format the element: feature-list (styled bullet or numbered list).

```
154            <li>Send reminders for courses below a 60% response rate.</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
155            <li>Share faculty-wise summaries with department heads.</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
156            <li>Close the feedback window and freeze the semester's data.</li>
```

 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

```
157          </ol>
```

Closing: ends the numbered list (opened on line 153).

```
158        </aside>
```

Closing: </aside> ends the side box (opened on line 151).

```
159      </div>
```

Closing: ends the container (opened on line 43).

```
160    </section>
```

Closing: </section> ends the section (opened on line 42).

```
161  </main>
```

Closing: </main> ends the main content (opened on line 41).

```
163  <footer class="site-footer">
```

<footer> **Semantic.** Closing area of the page: copyright and secondary links.
• class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

```
164    <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
165      <div class="footer-bottom">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

```
166        <span>&copy; <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
• © displays the copyright symbol
Another on this line:
• id="current-year" is a unique name for this element: JavaScript writes the current year into this empty span.
Closing: ends the inline text.
Text content (plain text inside an inline container).
Closing: ends the inline text.

```
167         <span><a href="about.html" style="color:#cfd5e4;">Project limitations</a></span>
```

 Generic inline container for a piece of text (no meaning of its own).
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="about.html"` is a relative path: it opens about.html, which sits in the same folder.
- `style` is inline CSS that applies only to this one element. Properties: color (text colour).

Text content (visible clickable link text).
Closing: ends the link; ends the inline text.

```
168       </div>
```

Closing: ends the container (opened on line 165).

```
169     </div>
```

Closing: ends the container (opened on line 164).

```
170   </footer>
```

Closing: </footer> ends the page footer (opened on line 163).

```
172   <script src="script.js"></script>
```

<script> Loads JavaScript into the page.
- `src="script.js"` loads the external JavaScript file script.js.

Closing: </script> ends the script.

```
173 </body>
```

Closing: </body> ends the visible page (opened on line 12).

```
174 </html>
```

Closing: </html> ends the whole document (opened on line 2).

Viva tips for admin.html

- `<th scope="row">` marks the first cell of each row as a header for that row.
- Badges show Healthy / Needs reminder / Low response status.
- Anonymous comments display no student identity; identified ones show a masked ID.
- State clearly that all numbers are sample data and the page has no real access control.

8. about.html - About the portal

Purpose	Explains the problem and solution, includes the <audio> element, lists the technologies and states the project's limitations honestly.
Size	141 lines in the file, 125 with content (all explained below).
Tags used (count)	a 12, article 5, audio 1, body 1, button 1, circle 1, code 1, dd 4, details 3, div 5, dl 1, dt 4, figcaption 1, figure 1, footer 1, h1 1, h2 6, h3 1, head 1, header 1, hr 4, html 1, li 18, link 3, main 1, mark 1, meta 3, nav 1, ol 1, p 9, path 2, script 1, section 1, source 1, span 5, strong 4, summary 3, svg 1, title 1, ul 2

Line-by-line: about.html

1
```
<!DOCTYPE html>
```
<!DOCTYPE html> is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
<html> Root element: every other element lives inside it. Its lang attribute names the page language.
- lang="en" declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
<head> Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- charset="UTF-8" sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="viewport" says what kind of information this meta tag carries.
- content makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="About the Faculty Feedback and Course Evaluation Portal project.">
```
<meta> Gives the browser extra information about the page. Void element: it has no closing tag.
- name="description" says what kind of information this meta tag carries.
- content is the short page summary that search engines may show under the title.

7
```
  <title>About the Portal | Faculty Feedback Portal</title>
```
<title> Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
Closing: </title> ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="preconnect" asks the browser to open the connection to that server early so fonts load faster.
- href is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- href is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
<link> Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the <link> tag, not the anchor tag <a>.
- rel="stylesheet" tells the browser the linked file is a CSS stylesheet.
- href="style.css" is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: </head> ends the head area (opened on line 3).

```
12  <body>
```

<body> Holds everything the visitor actually sees on the page.

```
14    <header class="site-header">
```

<header> **Semantic.** Introductory area at the top of the page: branding and navigation.
• class is a label that style.css uses to format the element: site-header (dark-blue sticky top bar with a gold bottom border).

```
15      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
16        <a href="index.html" class="brand">
```

<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
• class is a label that style.css uses to format the element: brand (logo plus site-name link).

```
17          <svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img"
aria-label="Portal crest">
```

<svg> Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
• class is a label that style.css uses to format the element: brand-mark (sizes the round logo icon).
• viewBox="0 0 40 40" is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
• xmlns identifies the XML namespace that tells the browser this is SVG.
• role="img" tells assistive technology to treat this whole element as one image, described by its aria-label.
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
18            <circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>
```

<circle> SVG shape: a circle.
• cx is the horizontal position of the circle centre.
• cy is the vertical position of the circle centre.
• r is the circle radius.
• fill="#243B66" sets the shape's fill colour.
• stroke="#B1802F" sets the outline colour.
• stroke-width="2" sets the outline thickness.

```
19            <path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>
```

<path> SVG shape drawn from path commands.
• d holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
• fill="#F1E2C3" sets the shape's fill colour.

```
20            <path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>
```

<path> SVG shape drawn from path commands.
• d holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
• fill="none" means the shape has no fill: only its outline is drawn.
• stroke="#F1E2C3" sets the outline colour.
• stroke-width="1.6" sets the outline thickness.

```
21          </svg>
```

Closing: </svg> ends the SVG graphic (opened on line 17).

```
22          <span>LPU Feedback Portal<span class="brand-sub">Faculty &amp;amp; Course Evaluation</span></span>
```

 Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another on this line:
• class is a label that style.css uses to format the element: brand-sub (small second line under the site name).
Text content (plain text inside an inline container).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the inline text; ends the inline text.

```
23        </a>
```

Closing: ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html" aria-current="page">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
43      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
44        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
45          <p class="eyebrow">About</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
46          <h1>About this portal</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
Closing: </h1> ends the main heading.

```
47          <p>A CA1 academic project built to demonstrate HTML fundamentals, semantic HTML and HTML forms in
a realistic setting.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
48        </div>
```

Closing: ends the container (opened on line 44).

```
50        <article>
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).

```
51          <h2>The problem</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
52          <p>Course feedback at most institutions is collected on paper at the end of the semester, or
through a generic form tool that wasn't designed for academic evaluation. The result is slow collection,
inconsistent questions across departments, and data that nobody can easily summarize. Students also hesitate
to answer honestly when they aren't sure whether their name is attached.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
54          <h2>The solution</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
55          <p>This portal puts the whole cycle in one place: a structured rating form built around defined
evaluation criteria, an explicit anonymous option, a check that stops the same student submitting twice for
the same course, and an administrator dashboard that shows averages and comparisons as visuals rather than
raw rows.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
56        </article>
```

Closing: </article> ends the article (opened on line 50).

```
58        <hr>
```

<hr> Horizontal rule: a thematic break between pieces of content. Void element.

```
60        <!-- ===== AUDIO: accessibility introduction ===== -->
```

HTML comment: the browser ignores it completely. It is a note for developers; here it labels the "audio: accessibility introduction" part of the page.

```
61        <article>
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).

```
62          <h2>Audio introduction</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
63          <p>A spoken summary of how to use the portal, provided for students who prefer listening or use
screen readers.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
64          <figure>
```

<figure> **Semantic.** Self-contained media (image, video, audio, chart) that may carry a caption.

```
65            <audio controls>
```

<audio> Embeds an audio player.
- controls shows the built-in play / pause / volume bar.

66

```
            <source src="https://interactive-examples.mdn.mozilla.net/media/cc0-audio/t-rex-roar.mp3" type="audio/mpeg">
```

<source> Gives a media element a file to play together with its format; the browser picks the first one it supports. Void element.
- src is the address of the media file.
- type="audio/mpeg" names the file format so the browser can skip formats it cannot play.

67

```
            Your browser does not support the audio element.
```

Text content (fallback text: shown only by browsers that cannot play audio).

68

```
            <a href="https://interactive-examples.mdn.mozilla.net/media/cc0-audio/t-rex-roar.mp3">Download the audio file</a>.
```

<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href is an absolute URL pointing to another website.

Text content (visible clickable link text).
Closing: ends the link.
Text content (fallback text: shown only by browsers that cannot play audio).

69

```
          </audio>
```

Closing: </audio> ends the audio player (opened on line 65).

70

```
          <figcaption>Portal audio introduction (sample clip used for CA1 demonstration purposes).</figcaption>
```

<figcaption> Caption that describes the <figure> it sits inside.
Text content (caption text shown under the media).
Closing: </figcaption> ends the caption.

71

```
        </figure>
```

Closing: </figure> ends the figure (opened on line 64).

72

```
      </article>
```

Closing: </article> ends the article (opened on line 61).

74

```
      <hr>
```

<hr> Horizontal rule: a thematic break between pieces of content. Void element.

76

```
      <article id="tech">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- id="tech" is a unique name for this element: target for an anchor link to the technologies article.

77

```
        <h2>Technologies used</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

78

```
        <dl class="def-list">
```

<dl> Description list: pairs of terms and descriptions.
- class is a label that style.css uses to format the element: def-list (two-column layout for a description list).

79

```
          <dt>HTML5</dt><dd>Page structure, semantic sectioning elements, forms, tables, media elements.</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

80

```
          <dt>CSS3</dt><dd>Custom properties, Grid, Flexbox, media queries, focus and hover states.</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

```
81            <dt>JavaScript</dt><dd>Form validation, dynamic dropdowns, duplicate-submission simulation,
chart rendering.</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content: The description of the term above.
Closing: </dd> ends the description.

```
82            <dt>GitHub Pages</dt><dd>Static hosting — no server, no database, no build step.</dd>
```

<dt> Description term (the word being explained).
Text content (the term being described).
Closing: </dt> ends the term.
<dd> Description details for the term above it.
Text content (the description of the term above).
Closing: </dd> ends the description.

```
83          </dl>
```

Closing: </dl> ends the description list (opened on line 78).

```
84        </article>
```

Closing: </article> ends the article (opened on line 76).

```
86        <hr>
```

<hr> Horizontal rule: a thematic break between pieces of content. Void element.

```
88        <article id="viva">
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
- id="viva" is a unique name for this element: target for the link about.html#viva.

```
89          <h2>What this project honestly is — and isn't</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
90          <p>Being clear about limitations is part of the project, not a weakness in it.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
91          <ul class="feature-list">
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.
- class is a label that style.css uses to format the element: feature-list (styled bullet or numbered list).

```
92            <li><strong>No real authentication.</strong> The login page simulates a session using
<mark>localStorage</mark>. Any Student ID and email will "work". Passwords are never stored or verified.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content (text of a list item).
<mark> Highlights text like a highlighter pen.
Text content (highlighted text).
Closing: </mark> ends the highlight.
Text content: Text of a list item.
Closing: ends the list item.

```
93            <li><strong>No database.</strong> Feedback submissions are not sent anywhere.
Duplicate-submission prevention writes a flag to the browser's own storage, which the student could
clear.</li>
```

 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

94
```
            <li><strong>Analytics are sample data.</strong> The ratings and counts shown on the Analytics and Admin pages are fixed demo values written into <code>script.js</code>.</li>
```
 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
<code> Shows text in monospace code style.
Text content (text shown in code style).
Closing: </code> ends the code text.
Text content (text of a list item).
Closing: ends the list item.

95
```
            <li><strong>No access control.</strong> The Admin Dashboard is reachable by anyone, because static hosting cannot restrict pages.</li>
```
 One item in a list.
 Marks text as important (shown bold). Semantic, unlike <b>.
Text content (important (bold) text).
Closing: ends the important text.
Text content: Text of a list item.
Closing: ends the list item.

96
```
          </ul>
```
Closing: ends the bullet list (opened on line 91).

98
```
          <h3>What a production version would add</h3>
```
<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

99
```
          <ol class="feature-list">
```
 Ordered (numbered) list.
- class is a label that style.css uses to format the element: feature-list (styled bullet or numbered list).

100
```
            <li>A backend server and a real database to store submissions.</li>
```
 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

101
```
            <li>Server-side authentication with hashed passwords and session tokens.</li>
```
 One item in a list.
Text content: Text of a list item.
Closing: ends the list item.

102
```
            <li>Role-based access so only staff reach the admin dashboard.</li>
```
 One item in a list.
Text content (text of a list item).
Closing: ends the list item.

103
```
            <li>A server-enforced uniqueness rule on (student, course, faculty) so duplicates cannot be bypassed.</li>
```
 One item in a list.
Text content: Text of a list item.
Closing: ends the list item.

104
```
            <li>True anonymization, where the identifier is stripped before the response is stored.</li>
```
 One item in a list.
Text content: Text of a list item.
Closing: ends the list item.

105
```
          </ol>
```
Closing: ends the numbered list (opened on line 99).

106
```
        </article>
```
Closing: </article> ends the article (opened on line 88).

108
```
        <hr>
```
<hr> Horizontal rule: a thematic break between pieces of content. Void element.

```
110         <article>
```

<article> **Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).

```
111           <h2>Project FAQ</h2>
```

<h2> Second-level heading: a major section title.
Text content (section heading text).
Closing: </h2> ends the section heading.

```
112           <details>
```

<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
113             <summary>Why no framework?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
114             <p>The CA1 syllabus covers HTML fundamentals and semantic HTML and forms. A framework would hide exactly the concepts being assessed. Everything here is plain HTML, CSS and JavaScript.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
115           </details>
```

Closing: </details> ends the expandable box (opened on line 112).

```
116           <details>
```

<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
117             <summary>Why is localStorage used at all?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
118             <p>Because GitHub Pages serves static files only. localStorage is the simplest way to demonstrate session and duplicate-check behaviour in the browser, and it's clearly labelled as a demonstration everywhere it appears.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
119           </details>
```

Closing: </details> ends the expandable box (opened on line 116).

```
120           <details>
```

<details> Native expandable box: shows only its <summary> until clicked, then reveals the rest. Needs no JavaScript.

```
121             <summary>Are the faculty names real?</summary>
```

<summary> The always-visible, clickable label of a <details> box.
Text content (visible clickable label of the expandable box (here a question)).
Closing: </summary> ends the summary label.

```
122             <p>No. All faculty names, courses, ratings and comments are fictional sample data created for this project.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
123           </details>
```

Closing: </details> ends the expandable box (opened on line 120).

```
124         </article>
```

Closing: </article> ends the article (opened on line 110).

```
125       </div>
```

Closing: ends the container (opened on line 43).

126 `</section>`

Closing: `</section>` ends the section (opened on line 42).

127 `</main>`

Closing: `</main>` ends the main content (opened on line 41).

129 `<footer class="site-footer">`

`<footer>` **Semantic.** Closing area of the page: copyright and secondary links.
- `class` is a label that style.css uses to format the element: `site-footer` (dark-blue footer area).

130 `<div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

131 `<div class="footer-bottom">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `footer-bottom` (bottom strip of the footer with the copyright line).

132 `<span>© <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
- `©` displays the copyright symbol

Another `<span>` on this line:
- `id="current-year"` is a unique name for this element: JavaScript writes the current year into this empty span.

Closing: `</span>` ends the inline text.
Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text.

133 `<span><a href="contact.html" style="color:#cfd5e4;">Contact / Help</a></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own).
`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="contact.html"` is a relative path: it opens contact.html, which sits in the same folder.
- `style` is inline CSS that applies only to this one element. Properties: color (text colour).

Text content (visible clickable link text).
Closing: `</a>` ends the link; `</span>` ends the inline text.

134 `</div>`

Closing: `</div>` ends the container (opened on line 131).

135 `</div>`

Closing: `</div>` ends the container (opened on line 130).

136 `</footer>`

Closing: `</footer>` ends the page footer (opened on line 129).

138 `<script src="script.js"></script>`

`<script>` Loads JavaScript into the page.
- `src="script.js"` loads the external JavaScript file script.js.

Closing: `</script>` ends the script.

139 `</body>`

Closing: `</body>` ends the visible page (opened on line 12).

140 `</html>`

Closing: `</html>` ends the whole document (opened on line 2).

Viva tips for about.html

- `<audio controls>` works like `<video>`: `<source>` plus fallback text, inside a `<figure>`.
- `<dl>` lists technologies as term and description.
- `<mark>` highlights the word localStorage; `<code>` shows file names.
- The honest-limitations list is a strength: it shows you understand what a real system needs.

9. contact.html - Contact and help

Purpose	Help page with a support form that uses extra input types: search, tel, number, date. This form uses plain browser validation (no `novalidate`).
Size	157 lines in the file, 143 with content (all explained below).
Tags used (count)	`a` 17, `address` 1, `aside` 1, `body` 1, `br` 3, `button` 3, `circle` 1, `div` 19, `fieldset` 2, `footer` 1, `form` 1, `h1` 1, `h3` 2, `head` 1, `header` 1, `hr` 1, `html` 1, `input` 7, `label` 9, `legend` 2, `li` 13, `link` 3, `main` 1, `meta` 3, `nav` 1, `option` 6, `p` 4, `path` 2, `script` 1, `section` 1, `select` 1, `small` 3, `span` 5, `svg` 1, `textarea` 1, `title` 1, `ul` 2

Line-by-line: contact.html

1
```
<!DOCTYPE html>
```
`<!DOCTYPE html>` is a declaration, not a tag. It tells the browser this page uses HTML5, so it renders in standards mode instead of old quirks mode. It must be the very first line.

2
```
<html lang="en">
```
`<html>` Root element: every other element lives inside it. Its `lang` attribute names the page language.
- `lang="en"` declares the page language (English) for screen readers, translators and search engines.

3
```
<head>
```
`<head>` Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.

4
```
  <meta charset="UTF-8">
```
`<meta>` Gives the browser extra information about the page. Void element: it has no closing tag.
- `charset="UTF-8"` sets the character encoding so symbols such as the rupee sign, the copyright sign and accented letters display correctly.

5
```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```
`<meta>` Gives the browser extra information about the page. Void element: it has no closing tag.
- `name="viewport"` says what kind of information this meta tag carries.
- `content` makes the page as wide as the device screen at 100% zoom: essential for mobile responsiveness.

6
```
  <meta name="description" content="Help, support requests and contact information for the feedback portal.">
```
`<meta>` Gives the browser extra information about the page. Void element: it has no closing tag.
- `name="description"` says what kind of information this meta tag carries.
- `content` is the short page summary that search engines may show under the title.

7
```
  <title>Contact &amp;amp; Help | Faculty Feedback Portal</title>
```
`<title>` Text shown in the browser tab, in bookmarks and in search results.
Text content (page title text shown in the browser tab).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</title>` ends the page title.

8
```
  <link rel="preconnect" href="https://fonts.googleapis.com">
```
`<link>` Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the `<link>` tag, not the anchor tag `<a>`.
- `rel="preconnect"` asks the browser to open the connection to that server early so fonts load faster.
- `href` is the address of the resource to connect.

9
```
  <link href="https://fonts.googleapis.com/css2?family=Source+Serif+4:wght@500;600;700&family=Inter:wght@400;500;600;700&display=swap" rel="stylesheet">
```
`<link>` Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the `<link>` tag, not the anchor tag `<a>`.
- `href` is the Google Fonts address that supplies the Source Serif 4 and Inter fonts.
- `rel="stylesheet"` tells the browser the linked file is a CSS stylesheet.

10
```
  <link rel="stylesheet" href="style.css">
```
`<link>` Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the `<link>` tag, not the anchor tag `<a>`.
- `rel="stylesheet"` tells the browser the linked file is a CSS stylesheet.
- `href="style.css"` is the path to the CSS file (in the same folder as this page).

11
```
</head>
```
Closing: `</head>` ends the head area (opened on line 3).

12 `<body>`

`<body>` Holds everything the visitor actually sees on the page.

14 `  <header class="site-header">`

`<header>` **Semantic.** Introductory area at the top of the page: branding and navigation.
- `class` is a label that style.css uses to format the element: `site-header` (dark-blue sticky top bar with a gold bottom border).

15 `    <div class="container">`

`<div>` Generic block container with no meaning of its own; used only to group elements for layout.
- `class` is a label that style.css uses to format the element: `container` (centres the content and limits its maximum width).

16 `      <a href="index.html" class="brand">`

`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `class` is a label that style.css uses to format the element: `brand` (logo plus site-name link).

17 `        <svg class="brand-mark" viewBox="0 0 40 40" xmlns="http://www.w3.org/2000/svg" role="img" aria-label="Portal crest">`

`<svg>` Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
- `class` is a label that style.css uses to format the element: `brand-mark` (sizes the round logo icon).
- `viewBox="0 0 40 40"` is the SVG's internal drawing grid (x, y, width, height); the graphic scales to fit.
- `xmlns` identifies the XML namespace that tells the browser this is SVG.
- `role="img"` tells assistive technology to treat this whole element as one image, described by its aria-label.
- `aria-label` gives an accessible name that screen readers announce (it is not shown on screen).

18 `          <circle cx="20" cy="20" r="19" fill="#243B66" stroke="#B1802F" stroke-width="2"/>`

`<circle>` SVG shape: a circle.
- `cx` is the horizontal position of the circle centre.
- `cy` is the vertical position of the circle centre.
- `r` is the circle radius.
- `fill="#243B66"` sets the shape's fill colour.
- `stroke="#B1802F"` sets the outline colour.
- `stroke-width="2"` sets the outline thickness.

19 `          <path d="M20 10 L30 15 L20 20 L10 15 Z" fill="#F1E2C3"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="#F1E2C3"` sets the shape's fill colour.

20 `          <path d="M12 17 V24 C12 27 27 27 28 24 V17" fill="none" stroke="#F1E2C3" stroke-width="1.6"/>`

`<path>` SVG shape drawn from path commands.
- `d` holds the drawing commands (M = move, L = line, C = curve, Z = close) that make the shape.
- `fill="none"` means the shape has no fill: only its outline is drawn.
- `stroke="#F1E2C3"` sets the outline colour.
- `stroke-width="1.6"` sets the outline thickness.

21 `        </svg>`

Closing: `</svg>` ends the SVG graphic (opened on line 17).

22 `        <span>LPU Feedback Portal<span class="brand-sub">Faculty & Course Evaluation</span></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
Another `<span>` on this line:
- `class` is a label that style.css uses to format the element: `brand-sub` (small second line under the site name).

Text content (plain text inside an inline container).
- `&` displays an ampersand (&); writing a bare & could be misread as the start of an entity

Closing: `</span>` ends the inline text; `</span>` ends the inline text.

23 `      </a>`

Closing: `</a>` ends the link (opened on line 16).

```
24      <button class="nav-toggle" aria-label="Toggle navigation menu" aria-expanded="false">&#9776;</button>
```

<button> Clickable button.
• class is a label that style.css uses to format the element: nav-toggle (hamburger button: hidden on big screens, shown on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).
• aria-expanded="false" tells screen readers the menu is currently collapsed; JavaScript switches it to true when opened.
Text content (text shown on the button).
• ☰ is the numeric code for the hamburger menu icon (three bars)
Closing: </button> ends the button.

```
25      <nav class="main-nav" aria-label="Primary">
```

<nav> **Semantic.** A block of major navigation links; screen readers can jump straight to it.
• class is a label that style.css uses to format the element: main-nav (the menu list; collapses behind the hamburger on phones).
• aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
26        <ul>
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.

```
27          <li><a href="index.html">Home</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="index.html" is a relative path: it opens index.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
28          <li><a href="login.html">Student Login</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="login.html" is a relative path: it opens login.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
29          <li><a href="dashboard.html">Dashboard</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="dashboard.html" is a relative path: it opens dashboard.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
30          <li><a href="courses.html">Courses &amp; Faculty</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.
Text content (visible clickable link text).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: ends the link; ends the list item.

```
31          <li><a href="feedback.html">Give Feedback</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
32          <li><a href="analytics.html">Analytics</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="analytics.html" is a relative path: it opens analytics.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
33          <li><a href="admin.html">Admin</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="admin.html" is a relative path: it opens admin.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
34          <li><a href="about.html">About</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="about.html" is a relative path: it opens about.html, which sits in the same folder.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
35          <li><a href="contact.html" aria-current="page">Contact</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href="contact.html" is a relative path: it opens contact.html, which sits in the same folder.
• aria-current="page" marks this link as the page the visitor is on right now.
Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
36        </ul>
```

Closing: ends the bullet list (opened on line 26).

```
37      </nav>
```

Closing: </nav> ends the navigation (opened on line 25).

```
38    </div>
```

Closing: ends the container (opened on line 15).

```
39  </header>
```

Closing: </header> ends the page header (opened on line 14).

```
41  <main>
```

<main> **Semantic.** The unique main content of the page (only one per page; excludes header and footer).

```
42    <section class="section">
```

<section> **Semantic.** A themed group of content, normally with its own heading.
• class is a label that style.css uses to format the element: section (adds vertical spacing around a block of content).

```
43      <div class="container">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

```
44        <div class="section-head">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: section-head (limits the width of a heading block so it stays readable).

```
45          <p class="eyebrow">Support</p>
```

 Paragraph of text.
• class is a label that style.css uses to format the element: eyebrow (small gold label above a heading).
Text content (paragraph text the visitor reads).
Closing: ends the paragraph.

```
46          <h1>Contact &amp; Help</h1>
```

<h1> Top-level heading: the main title of the page (only one per page).
Text content (main heading text of the page).
• & displays an ampersand (&); writing a bare & could be misread as the start of an entity
Closing: </h1> ends the main heading.

```
47          <p>Raise a query about the feedback window, a missing course, or a technical problem with the portal.</p>
```

 Paragraph of text.
Text content: Paragraph text the visitor reads.
Closing: ends the paragraph.

```
48        </div>
```

Closing: ends the container (opened on line 44).

```
50        <div style="display:grid; grid-template-columns: 1.1fr 0.9fr; gap:2.5rem; align-items:flex-start;">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- style is inline CSS that applies only to this one element. Properties: display (layout mode), grid-template-columns (column sizes), gap (space between items), align-items (vertical alignment).

```
51          <form id="support-form">
```

<form> Groups input controls so they can be validated and submitted together.
- id="support-form" is a unique name for this element: the contact / support form.

```
52            <fieldset>
```

<fieldset> Groups related form controls inside a bordered box.

```
53              <legend>Search help topics</legend>
```

<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

```
54              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
55              <label for="help-search">Search</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="help-search" links this label to the control whose id is "help-search": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
56              <input type="search" id="help-search" name="helpSearch" placeholder="e.g. anonymous feedback">
```

<input> Form control; its type attribute decides what kind. Void element.
- type="search": search box (some browsers add a clear button).
- id="help-search" is a unique name for this element: search box on the help form.
- name="helpSearch" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.

```
57              <small class="hint">Searches the help topics listed beside this form.</small>
```

<small> Fine print or side-note text.
- class is a label that style.css uses to format the element: hint (small grey helper text under a field).

Text content (fine-print text).
Closing: </small> ends the fine print.

```
58              </div>
```

Closing: ends the container (opened on line 54).

```
59            </fieldset>
```

Closing: </fieldset> ends the fieldset group (opened on line 52).

```
61            <fieldset>
```

<fieldset> Groups related form controls inside a bordered box.

```
62              <legend>Raise a support request</legend>
```

<legend> Title of the <fieldset> it sits inside.
Text content (title of the fieldset group).
Closing: </legend> ends the legend.

```
64              <div class="field-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
  • class is a label that style.css uses to format the element: field-row (two form fields side by side (one column on phones)).

```
65              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
  • class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
66              <label for="help-name">Full name</label>
```

<label> Text label for a form control; clicking it focuses the control.
  • for="help-name" links this label to the control whose id is "help-name": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
67              <input type="text" id="help-name" name="name" placeholder="Your name" required maxlength="60"
autocomplete="name">
```

<input> Form control; its type attribute decides what kind. Void element.
  • type="text": single-line free text box.
  • id="help-name" is a unique name for this element: name field.
  • name="name" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
  • placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
  • required means the field must be filled in before the browser allows submission (when browser validation is on).
  • maxlength="60" sets the maximum number of characters the user can type.
  • autocomplete="name" tells the browser what kind of data this is so it can suggest saved values.

```
68              </div>
```

Closing: ends the container (opened on line 65).

```
69              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
  • class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
70              <label for="help-email">Email</label>
```

<label> Text label for a form control; clicking it focuses the control.
  • for="help-email" links this label to the control whose id is "help-email": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
71              <input type="email" id="help-email" name="email" placeholder="name@university.edu" required
autocomplete="email">
```

<input> Form control; its type attribute decides what kind. Void element.
  • type="email": single-line box whose value must look like an e-mail address (the browser checks for an @).
  • id="help-email" is a unique name for this element: e-mail field.
  • name="email" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
  • placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
  • required means the field must be filled in before the browser allows submission (when browser validation is on).
  • autocomplete="email" tells the browser what kind of data this is so it can suggest saved values.

```
72              </div>
```

Closing: ends the container (opened on line 69).

```
73              </div>
```

Closing: ends the container (opened on line 64).

```
75              <div class="field-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
  • class is a label that style.css uses to format the element: field-row (two form fields side by side (one column on phones)).

```
76              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
  • class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
77              <label for="help-phone">Phone (optional)</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="help-phone" links this label to the control whose id is "help-phone": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
78              <input type="tel" id="help-phone" name="phone" placeholder="10-digit number"
pattern="[0-9]{10}" maxlength="10" autocomplete="tel">
```

<input> Form control; its type attribute decides what kind. Void element.
• type="tel": telephone number; phones show a number keypad.
• id="help-phone" is a unique name for this element: phone field.
• name="phone" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
• pattern="[0-9]{10}" is a regular expression the value must match (here: exactly 10 digits).
• maxlength="10" sets the maximum number of characters the user can type.
• autocomplete="tel" tells the browser what kind of data this is so it can suggest saved values.

```
79              </div>
```

Closing: ends the container (opened on line 76).

```
80              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
81              <label for="help-reg">Registration number</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="help-reg" links this label to the control whose id is "help-reg": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
82              <input type="number" id="help-reg" name="registration" min="10000000" max="99999999"
placeholder="12312345">
```

<input> Form control; its type attribute decides what kind. Void element.
• type="number": numeric entry; works with min, max and step.
• id="help-reg" is a unique name for this element: registration-number field.
• name="registration" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• min="10000000" sets the smallest allowed value.
• max="99999999" sets the largest allowed value.
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.

```
83              </div>
```

Closing: ends the container (opened on line 80).

```
84              </div>
```

Closing: ends the container (opened on line 75).

```
86              <div class="field-row">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field-row (two form fields side by side (one column on phones)).

```
87              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
88              <label for="help-date">Date the issue occurred</label>
```

<label> Text label for a form control; clicking it focuses the control.
• for="help-date" links this label to the control whose id is "help-date": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
89              <input type="date" id="help-date" name="issueDate">
```

<input> Form control; its type attribute decides what kind. Void element.
• type="date": date picker.
• id="help-date" is a unique name for this element: date field.
• name="issueDate" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).

```
90              </div>
```

Closing: ends the container (opened on line 87).

```
91              <div class="field">
```

 Generic block container with no meaning of its own; used only to group elements for layout.
- class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

```
92              <label for="help-category">Category</label>
```

<label> Text label for a form control; clicking it focuses the control.
- for="help-category" links this label to the control whose id is "help-category": clicking the label focuses that control.

Text content (visible label text tied to a form field).
Closing: </label> ends the label.

```
93              <select id="help-category" name="category" required>
```

<select> Dropdown list.
- id="help-category" is a unique name for this element: category dropdown.
- name="category" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
- required means the field must be filled in before the browser allows submission (when browser validation is on).

```
94              <option value="">Select a category</option>
```

<option> One choice inside a <select>.
- value="" is the data sent when this option is chosen (the visible text may differ).

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
95              <option>Cannot see a course</option>
```

<option> One choice inside a <select>.
- No value attribute, so the visible text itself is what gets submitted.

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
96              <option>Feedback window closed early</option>
```

<option> One choice inside a <select>.
- No value attribute, so the visible text itself is what gets submitted.

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
97              <option>Login problem</option>
```

<option> One choice inside a <select>.
- No value attribute, so the visible text itself is what gets submitted.

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
98              <option>Duplicate submission message</option>
```

<option> One choice inside a <select>.
- No value attribute, so the visible text itself is what gets submitted.

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
99              <option>Other</option>
```

<option> One choice inside a <select>.
- No value attribute, so the visible text itself is what gets submitted.

Text content (text shown for this choice in the dropdown).
Closing: </option> ends the option.

```
100             </select>
```

Closing: </select> ends the dropdown (opened on line 93).

```
101             </div>
```

Closing: ends the container (opened on line 91).

```
102             </div>
```

Closing: ends the container (opened on line 86).

104
```
            <div class="field">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field).

105
```
            <label for="help-message">Describe the issue</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="help-message" links this label to the control whose id is "help-message": clicking the label focuses that control.
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

106
```
            <textarea id="help-message" name="message" required maxlength="800" placeholder="What happened, and what did you expect to happen?"></textarea>
```
<textarea> Multi-line text box.
• id="help-message" is a unique name for this element: issue description box.
• name="message" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).
• required means the field must be filled in before the browser allows submission (when browser validation is on).
• maxlength="800" sets the maximum number of characters the user can type.
• placeholder is faint hint text inside the box that disappears when typing. It does not replace a label.
Closing: </textarea> ends the text box.

107
```
            </div>
```
Closing: ends the container (opened on line 104).

109
```
            <div class="field checkbox-option">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: field (spacing wrapper for one form field); checkbox-option (one checkbox plus its text).

110
```
            <input type="checkbox" id="help-copy" name="sendCopy">
```
<input> Form control; its type attribute decides what kind. Void element.
• type="checkbox": square on/off tick box; each one is independent.
• id="help-copy" is a unique name for this element: send-me-a-copy checkbox.
• name="sendCopy" is the key the value is submitted under (id is for labels and scripts; name is for the submitted data).

111
```
            <label for="help-copy" style="font-weight:400; margin-bottom:0;">Email me a copy of this request</label>
```
<label> Text label for a form control; clicking it focuses the control.
• for="help-copy" links this label to the control whose id is "help-copy": clicking the label focuses that control.
• style is inline CSS that applies only to this one element. Properties: font-weight (boldness), margin-bottom (space below).
Text content (visible label text tied to a form field).
Closing: </label> ends the label.

112
```
            </div>
```
Closing: ends the container (opened on line 109).

113
```
          </fieldset>
```
Closing: </fieldset> ends the fieldset group (opened on line 61).

115
```
          <div class="btn-row">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: btn-row (lines buttons up in a row with a gap).

116
```
            <button type="submit" class="btn btn-primary">Send Request</button>
```
<button> Clickable button.
• type="submit": clicking sends the form.
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-primary (solid navy button).
Text content (text shown on the button).
Closing: </button> ends the button.

117
```
            <button type="reset" class="btn btn-ghost">Reset Form</button>
```
<button> Clickable button.
• type="reset": clicking clears all fields back to their defaults (built-in, no JavaScript).
• class is a label that style.css uses to format the element: btn (basic button look (padding, rounded corners)); btn-ghost (quiet, low-emphasis button).
Text content (text shown on the button).
Closing: </button> ends the button.

```
118             </div>
```

Closing: ends the container (opened on line 115).

```
119             <p><small>This form demonstrates HTML5 validation. Being a static demo, nothing is actually
sent.</small></p>
```

 Paragraph of text.
<small> Fine print or side-note text.
Text content (fine-print text).
Closing: </small> ends the fine print; ends the paragraph.

```
120         </form>
```

Closing: </form> ends the form (opened on line 51).

```
122         <aside class="card" aria-label="Help topics and contact details">
```

<aside> **Semantic.** Side content related to the main content but not essential to it.
- class is a label that style.css uses to format the element: card (white box with a border and a gold top edge).
- aria-label gives an accessible name that screen readers announce (it is not shown on screen).

```
123             <h3>Help topics</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

```
124             <ul class="guideline-list">
```

 Unordered (bulleted) list. Only <li> elements may sit directly inside it.
- class is a label that style.css uses to format the element: guideline-list (styled bullet list in a side box).

```
125               <li><a href="about.html#viva">How anonymous feedback works</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="about.html#viva" opens that page and jumps to the element whose id is "viva".

Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
126               <li><a href="courses.html">Why a course isn't listed</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="courses.html" is a relative path: it opens courses.html, which sits in the same folder.

Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
127               <li><a href="index.html#faq">Can I edit a submission?</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="index.html#faq" opens that page and jumps to the element whose id is "faq".

Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
128               <li><a href="feedback.html">What the rating scale means</a></li>
```

 One item in a list.
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- href="feedback.html" is a relative path: it opens feedback.html, which sits in the same folder.

Text content (visible clickable link text).
Closing: ends the link; ends the list item.

```
129             </ul>
```

Closing: ends the bullet list (opened on line 124).

```
130             <hr>
```

<hr> Horizontal rule: a thematic break between pieces of content. Void element.

```
131             <h3>Reach the office</h3>
```

<h3> Third-level heading: a sub-section title.
Text content (sub-heading text).
Closing: </h3> ends the sub-heading.

132
```
            <address style="font-style:normal;">
```
<address> **Semantic.** Contact information for the page or its owner.
• style is inline CSS that applies only to this one element. Properties: font-style (italic or normal).

133
```
              Academic Evaluation Cell<br>
```
Text content (contact details text).

 Forces a line break. Void element.

134
```
              Block 34, Room 210<br>
```
Text content (contact details text).

 Forces a line break. Void element.

135
```
              <a href="mailto:feedback@university.edu">feedback@university.edu</a><br>
```
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href=mailto:... opens the visitor's e-mail app with this address filled in.
Text content (visible clickable link text).
Closing: ends the link.

 Forces a line break. Void element.

136
```
              <a href="tel:+911800000000">+91 1800 000 000</a>
```
<a> **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
• href=tel:... starts a phone call on devices that support it.
Text content (visible clickable link text).
Closing: ends the link.

137
```
            </address>
```
Closing: </address> ends the address (opened on line 132).

138
```
            <p class="mb-0"><small>Office hours: Monday to Friday, 10:00&ndash;17:00.</small></p>
```
 Paragraph of text.
• class is a label that style.css uses to format the element: mb-0 (removes the bottom margin).
<small> Fine print or side-note text.
Text content (fine-print text).
• – displays a short dash used for ranges
Closing: </small> ends the fine print; ends the paragraph.

139
```
          </aside>
```
Closing: </aside> ends the side box (opened on line 122).

140
```
        </div>
```
Closing: ends the container (opened on line 50).

141
```
      </div>
```
Closing: ends the container (opened on line 43).

142
```
    </section>
```
Closing: </section> ends the section (opened on line 42).

143
```
  </main>
```
Closing: </main> ends the main content (opened on line 41).

145
```
  <footer class="site-footer">
```
<footer> **Semantic.** Closing area of the page: copyright and secondary links.
• class is a label that style.css uses to format the element: site-footer (dark-blue footer area).

146
```
    <div class="container">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: container (centres the content and limits its maximum width).

147
```
      <div class="footer-bottom">
```
 Generic block container with no meaning of its own; used only to group elements for layout.
• class is a label that style.css uses to format the element: footer-bottom (bottom strip of the footer with the copyright line).

148 `<span>© <span id="current-year"></span> LPU Feedback Portal. Academic demo project.</span>`

`<span>` Generic inline container for a piece of text (no meaning of its own). (appears 2 times on this line)
Text content (plain text inside an inline container).
- `©` displays the copyright symbol

Another `<span>` on this line:
- `id="current-year"` is a unique name for this element: JavaScript writes the current year into this empty span.

Closing: `</span>` ends the inline text.
Text content (plain text inside an inline container).
Closing: `</span>` ends the inline text.

149 `<span><a href="index.html" style="color:#cfd5e4;">Back to home</a></span>`

`<span>` Generic inline container for a piece of text (no meaning of its own).
`<a>` **Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
- `href="index.html"` is a relative path: it opens index.html, which sits in the same folder.
- `style` is inline CSS that applies only to this one element. Properties: color (text colour).

Text content (visible clickable link text).
Closing: `</a>` ends the link; `</span>` ends the inline text.

150 `</div>`

Closing: `</div>` ends the container (opened on line 147).

151 `</div>`

Closing: `</div>` ends the container (opened on line 146).

152 `</footer>`

Closing: `</footer>` ends the page footer (opened on line 145).

154 `<script src="script.js"></script>`

`<script>` Loads JavaScript into the page.
- `src="script.js"` loads the external JavaScript file script.js.

Closing: `</script>` ends the script.

155 `</body>`

Closing: `</body>` ends the visible page (opened on line 12).

156 `</html>`

Closing: `</html>` ends the whole document (opened on line 2).

Viva tips for contact.html

- Show `type="tel"` with `pattern="[0-9]{10}"` and `type="number"` with `min`/`max`.
- Submit with empty required fields to show native HTML5 validation messages.
- `<address>` marks the office contact details; `mailto:` and `tel:` links act on click.
- Explain why this form has no `novalidate` while login and feedback forms do.

10. The other files in your project

style.css - the stylesheet

Purpose: controls how every page looks. HTML says what the content is; CSS says how it appears. It is attached to each page by `<link rel="stylesheet" href="style.css">` in the `<head>`.

Section in the file	What it does
1. Design tokens (`:root`)	CSS variables for colours, fonts, widths. Change one value and the whole site updates.
2. Reset	Sets base rules: box-sizing, body font, heading style, focus outline.
3. Layout	`.container`, `.section`: centred content with consistent spacing.
4. Header / nav	Sticky navy bar, brand logo, menu links, hamburger button.
5. Buttons	`.btn` and its colour variants.
6. Cards / badges	White cards, stat boxes, status pills.
7. Forms	Fieldsets, labels, inputs, sliders, radio and checkbox groups, messages.
8. Tables	Table styling and horizontal scrolling wrapper.
9. Dashboard bars	The CSS bar chart: a grey track with a coloured fill.
10. Lists / details / figure	Styling for lists, FAQ boxes and captions.
11. Hero / video	Home banner, video, avatars.
12. Footer	Dark footer grid and bottom strip.
13. Utilities	Small helper classes such as `.demo-note`, `.mb-0`.
14. Responsive	`@media` queries: below 900px and 760px layouts switch to fewer columns and the nav becomes a hamburger menu.

script.js - the behaviour

Purpose: adds interactivity. It is loaded at the end of every page by `<script src="script.js"></script>`. Each function first checks that its element exists, so the same file is safe on every page.

Part	What it does
Sample data objects	Courses, faculty and ratings stored in JavaScript, standing in for a database.
`initMobileNav()`	Hamburger button toggles the `open` class on the nav and flips `aria-expanded`.
`initFooterYear()`	Writes the current year into `#current-year`.
`initRangeOutputs()`	Keeps the number beside each slider in step with the slider position.
`initLoginForm()`	Reads Student ID and e-mail, saves a demo session in localStorage, redirects to dashboard.html.
`initDashboardGreeting()`	Shows `Welcome back, <ID>` on the dashboard.
`initCourseFacultyLink()`	When the course changes, rebuilds the faculty `<option>` list.
`initFeedbackForm()`	Validates choices, checks the confirmation box, blocks duplicates using a localStorage key, shows messages.
`renderBarChart()`	Builds one bar row per rating: width = rating / 5 x 100%.
`DOMContentLoaded` listener	Runs all init functions once the HTML has finished loading.

README.md - documentation

Purpose: the front page of your GitHub repository. It explains the project to anyone who opens it: problem statement, features, technologies, folder structure, how to run and deploy it, limitations, future work and team contribution. Written in Markdown (`#` headings, `|` tables, `-` bullets). Evaluators read it first, so keep it accurate and fill in the team table.

.gitignore - what Git should skip

Purpose: a list of file and folder patterns that Git will not track or upload to GitHub. This keeps the repository clean of personal or automatically generated files. Lines starting with `#` are comments. Here is your file, line by line:

1	`# OS files`
	Comment (Git ignores lines starting with #). Labels the group below.
2	`.DS_Store`
	Hidden file macOS creates in folders to remember view settings. Useless to others, so it is ignored.
3	`Thumbs.db`
	Windows thumbnail cache file: same idea.
5	`# Editor folders`
	Comment labelling the next group.
6	`.vscode/`
	Folder where VS Code keeps your personal editor settings. The trailing slash means it is a directory.
7	`.idea/`
	Same for JetBrains editors such as WebStorm or PyCharm.
9	`# Logs`
	Comment labelling the next group.
10	`*.log`
	Wildcard pattern: ignore every file whose name ends with .log (error and log files).

Note: files that do not match any pattern here (all your HTML, CSS, JS, images) are uploaded normally. A real project might also ignore `node_modules/` or `.env`; yours has neither.

assets/ folders

Purpose: places to keep local media so GitHub Pages does not depend on outside websites. Your project currently uses outside URLs for some images, the video and the audio. Before submission, download them into these folders and update the `src` attributes.

Path	Purpose
`assets/images/`	Local pictures (faculty photos, video poster). Reference as `src="assets/images/name.png"`.
`assets/video/`	Local demo video for the home page `<video>`.
`assets/audio/`	Local audio intro for the About page `<audio>`.
`assets/*/README.md`	Tiny note files explaining what belongs in each folder. They also make Git keep the otherwise empty folders.

faculty-feedback-portal.zip and the hidden .git folder

Item	Purpose
`faculty-feedback-portal.zip`	A compressed copy of the whole project for easy download and sharing. Not needed in the GitHub repository.
`.git/` (appears after `git init`)	Hidden folder where Git stores the full history of your commits. Never edit or delete it by hand.
`index.html` as the home file	GitHub Pages and web servers open `index.html` automatically when someone visits the folder URL, which is why the home page must use exactly that name.

11. Tag glossary (every tag used in this project)

The count shows how many times each tag is written across all nine pages. Learn the **Semantic** ones especially well for the viva.

Tag	Used	Meaning
`<td>`	168	Table data cell.
`<div>`	160	Generic block container with no meaning of its own; used only to group elements for layout.
`<li>`	125	One item in a list.
`<a>`	122	**Anchor / hyperlink.** Makes clickable text or a button that goes to another page, a section, an e-mail or a phone call.
`<span>`	114	Generic inline container for a piece of text (no meaning of its own).
`<p>`	67	Paragraph of text.
`<label>`	39	Text label for a form control; clicking it focuses the control.
`<th>`	39	Table header cell: gives meaning to its column or row.
`<tr>`	38	One table row.
`<strong>`	33	Marks text as important (shown bold). Semantic, unlike `<b>`.
`<option>`	31	One choice inside a `<select>`.
`<input>`	29	Form control; its `type` attribute decides what kind. Void element.
`<link>`	27	Connects an external resource (a stylesheet or a font) to this page. Void element: no closing tag. NOTE: this is the `<link>` tag, not the anchor tag `<a>`.
`<meta>`	27	Gives the browser extra information about the page. Void element: it has no closing tag.
`<article>`	25	**Semantic.** Self-contained content that still makes sense on its own (a card, a post, a comment).
`<small>`	25	Fine print or side-note text.
`<h3>`	22	Third-level heading: a sub-section title.
`<h2>`	21	Second-level heading: a major section title.
`<path>`	18	SVG shape drawn from path commands.
`<section>`	17	**Semantic.** A themed group of content, normally with its own heading.
`<ul>`	17	Unordered (bulleted) list. Only `<li>` elements may sit directly inside it.
`<button>`	15	Clickable button.
`<dd>`	13	Description details for the term above it.
`<dt>`	13	Description term (the word being explained).
`<body>`	9	Holds everything the visitor actually sees on the page.
`<circle>`	9	SVG shape: a circle.
`<footer>`	9	**Semantic.** Closing area of the page: copyright and secondary links.
`<h1>`	9	Top-level heading: the main title of the page (only one per page).
`<head>`	9	Holds information ABOUT the page (title, encoding, linked files). Nothing inside it is displayed on the page.
`<header>`	9	**Semantic.** Introductory area at the top of the page: branding and navigation.
`<html>`	9	Root element: every other element lives inside it. Its `lang` attribute names the page language.
`<main>`	9	**Semantic.** The unique main content of the page (only one per page; excludes header and footer).
`<nav>`	9	**Semantic.** A block of major navigation links; screen readers can jump straight to it.
`<script>`	9	Loads JavaScript into the page.
`<svg>`	9	Inline vector graphic written directly in the HTML: sharp at any size and needs no image file.
`<title>`	9	Text shown in the browser tab, in bookmarks and in search results.
`<fieldset>`	8	Groups related form controls inside a bordered box.

Tag	Used	Meaning
`<legend>`	8	Title of the `<fieldset>` it sits inside.
`<details>`	7	Native expandable box: shows only its `<summary>` until clicked, then reveals the rest. Needs no JavaScript.
`<hr>`	7	Horizontal rule: a thematic break between pieces of content. Void element.
`<img>`	7	Embeds an image. Void element: no closing tag.
`<summary>`	7	The always-visible, clickable label of a `<details>` box.
`<aside>`	6	**Semantic.** Side content related to the main content but not essential to it.
`<select>`	6	Dropdown list.
`<caption>`	5	Visible title of the table; also read aloud by screen readers.
`<table>`	5	Table of data (never used for page layout).
`<tbody>`	5	Groups the data rows of the table.
`<thead>`	5	Groups the header row of the table.
`<code>`	4	Shows text in monospace code style.
`<em>`	4	Marks text with emphasis (shown italic). Semantic, unlike `<i>`.
`<h4>`	4	Fourth-level heading: a minor title (used for footer columns).
`<textarea>`	4	Multi-line text box.
` `	3	Forces a line break. Void element.
`<dl>`	3	Description list: pairs of terms and descriptions.
`<figcaption>`	3	Caption that describes the `<figure>` it sits inside.
`<figure>`	3	**Semantic.** Self-contained media (image, video, audio, chart) that may carry a caption.
`<form>`	3	Groups input controls so they can be validated and submitted together.
`<ol>`	3	Ordered (numbered) list.
`<mark>`	2	Highlights text like a highlighter pen.
`<source>`	2	Gives a media element a file to play together with its format; the browser picks the first one it supports. Void element.
`<address>`	1	**Semantic.** Contact information for the page or its owner.
`<audio>`	1	Embeds an audio player.
`<video>`	1	Embeds a video player; no plugin needed.

Five viva traps to remember

- `<link>` connects CSS; `<a>` makes clickable links. Do not mix them up.
- `id` must be unique on a page; `class` can repeat. `name` is the key for submitted data.
- `placeholder` is a hint, not a label. Every field needs a real `<label for>`.
- `novalidate` on login.html and feedback.html turns off browser pop-ups there; contact.html uses native validation.
- The login and duplicate check are simulated with localStorage. A static site cannot do real security.