

## Data Structure

A mathematical and logical model of data is known as *Data Structure*.

**Primitive data structure:** The data structure, which is available in the compiler, is known as a *primitive data structure*. Example: Array

**Non-primitive data structure:** The data structure, which is not available in the compiler, is known as *non-primitive data structure*. Examples: Stack, Queue, Linked List

**Linear Data Structure:** The data structure in which each element can access maximum one predecessor element and one successor element is known as *linear data structure*. Example: Stack, Queue etc.

**Non-linear Data Structure:** The data structure in which each element can access any number of predecessor elements and any number of successor elements is known as *Non-linear data structure*. Example: Tree, Graphs, etc.

**Static Data Structure:** The data structure in which the number of elements is fixed, is known as *Static Data Structure*. Example: Arrays

**Dynamic Data Structure:** The data structure in which the number of elements is not fixed, is known as *Dynamic Data Structure*. Example: Linked List.

## Array

It is a *static primitive data structure*. It is a homogeneous collection of data. The elements in the array are stored on consecutive memory locations. Array is also known as a subscripted variable, e.g.,  $A[i]$  is  $i^{\text{th}}$  element of the array  $A$  (i.e.,  $i$  is the subscript with variable  $A$ ). As we know that the elements of the array are stored on consecutive memory locations, it becomes convenient to find out the address of memory location of  $i^{\text{th}}$  element, for given base address (address of first element) and  $W$  (i.e. the number of memory locations required by one element).

### One dimensional array

Number of elements  $N = UB - LB + 1$       Where  $LB$ -Lower Bound  $UB$ -Upper Bound

Memory Location of  $A[i]$ ;  $Loc(A[i]) = Base(A) + W * (i - LB)$

$$Loc(A[i]) = Base(A) + W * i$$

Where  $N$  is given as in C++,  $LB$  is assumed as 0

### Two dimensional array

Number of elements =  $ROWS \times COLS = (UBI - LBI + 1) \times (UBJ - LBJ + 1)$

**Row Major:**  $Loc(A[I][J]) = Base(A) + W * (COLS * (I - LBI) + (J - LBJ))$

where  $Base(A)$  is address of first element's memory location

$COLS$  is number of columns =  $UBJ - LBJ + 1$

$W$  is number of memory locations required by one element

$LBI$  is Lower Bound of row

$UBJ$  is upper bound of column

$LBJ$  is Lower bound of column

$$Loc(A[I][J]) = Base(A) + W * (COLS * I + J)$$

where  $COLS$  is the number of columns,  $LBI=0$  and  $LBJ=0$

**Column Major:**  $Loc(A[I][J]) = Base(A) + W * (ROWS * (J - LBJ) + (I - LBI))$

where  $Base(A)$  is address of first element's memory location

$ROWS$  is the number of rows =  $UBI - LBI + 1$

$W$  is number of memory locations required by one element

$LBJ$  is Lower Bound of Column

$UBI$  is upper bound of Row

$LBI$  is Lower bound of Row

$$Loc(A[I][J]) = Base(A) + W * (ROWS * J + I)$$

where  $R$  is number of Rows,  $LBI=0$  and  $LBJ=0$

**Exercise 1** A one-dimensional array P[100] is stored in memory with a base address as 5000. Find out addresses of P[15] and P[40], if each element of this array requires 4 bytes.

Given,	Base (P)	=	5000		
	W	=	4		
	Loc (P[I])	=	Base (P)	+	W*I
	Loc (P[15])	=	5000	+	4*15
		=	5000	+	60
		=	<u>5060</u>		
	Loc (P[40])	=	5000	+	4*40
		=	5000	+	160
		=	<u>5160</u>		

**Exercise 2** A one-dimensional array A[-5..25] is stored in memory with each element requiring 2 bytes. If the base address is 8000, find out the following:

- Address of A[5] and A[-3]
- Total no. of elements present in the array

Given,	Base (A)	=	8000		
	W	=	2		
	LB	=	-5		
	Loc (A[I])	=	Base (A)	+	W*(I-LB)
	Loc (A[5])	=	8000	+	2*(5-(-5))
		=	8000	+	20
		=	<u>8020</u>		
	Loc (A[-3])	=	8000	+	2*(-3-(-5))
		=	8000	+	4
		=	<u>8004</u>		
	Total				
	No. of Elements=	UB-LB+1		=25-(-5)+1	=31

**Exercise 3** A two-dimensional array Q[5][15] is stored in memory along the row with each element requiring 2 bytes. If the base address is 6500, find out the following:

- Addresses of Q[5][10] and Q[3][5]
- Total no. of elements present in the array

Given,	Base (Q)	=	6500		
	W	=	2		
	COLS	=	5		
Row Major,	Loc (Q[I][J])	=	Base (Q)	+	W*(COLS*I+J)
	Loc (Q[5][10])	=	6500	+	2*(15*5+10)
		=	6500	+	170
		=	<u>6670</u>		
	Loc (Q[3][5])	=	6500	+	2*(15*3+5)
		=	6500	+	100
		=	<u>6600</u>		
	Total				
	No. of Elements=	ROWS*COLS		=5*15	=75

**Exercise 4** R[-4..4,7..17] is a two-dimensional array, stored in the memory along the column with each element requiring 4 bytes. If the base address is 5000, find out the following:

- Addresses of R[2][10] and R[3][15]
- Total no. of elements present in the array

Given,	Base (R)	=	5000		
	W	=	4		
	ROWS	=	UBI-LBI+1 = 4-(-4)+1=9		
	COLS	=	UBJ-LBJ+1 = 17-7+1=11		
Column Major,	Loc (R[I][J])	=	Base (R)	+	W*(ROWS*(J-LBJ) + (I-LBI))
	Loc (R[2][10])	=	5000	+	4*(9*(10-7) + (2-(-4)))
		=	5000	+	4*(27+6)
		=	<u>5132</u>		
	Loc (R[3][15])	=	5000	+	4*(9*(15-7) + (3-(-4)))
		=	5000	+	4*(72+7)
		=	<u>5316</u>		
	Total				
	No. of Elements=	ROWS*COLS		=	9*11
		=	99		