

SH

hi



Hello! How can I help you today?



SH

yes i want you to enlighten me about datastall & DNQN concepts in AOSP



AOSP stands for Android Open Source Project, which is an open-source software stack for various devices and platforms that are based on the Android operating system.

Regarding Datastall, it is a term used in the Android framework to describe a situation where an app is unable to receive data due to a lack of network connectivity. When a device enters this state, the framework will attempt to re-establish a network connection and resume data transfer.

Deep Q-Network (DQN) is a type of neural network that is used to approximate the Q-value function in reinforcement learning. It is used to train an agent to make decisions in an environment by maximizing the expected cumulative reward. DQN is an extension of Q-Learning and is particularly useful for solving problems with high-dimensional state spaces, such as playing video games.

It is important to note that these two concepts are not directly related to each other and are used in different context, Datastall is related to android framework and DQN is a machine learning concept.



SH

i was asking about DNQN



Generate
PNG

Download
PDF

Share
Link



decisions in an environment by maximizing the expected cumulative reward. DQN is an extension of Q-Learning, and it was first introduced by Google DeepMind in a 2015 publication, "Human-level control through deep reinforcement learning". DQN uses a neural network to approximate the Q-value function, which allows it to handle high-dimensional state spaces, such as those found in video games. The agent learns to select actions that maximize the expected cumulative reward over time.

A key innovation of the DQN algorithm is the use of a technique called experience replay, which allows the agent to learn from experiences that occurred in the past. This is done by storing a sample of previous experiences in a replay buffer, and then randomly selecting a subset of these experiences to learn from. This helps to stabilize the learning process and improve the performance of the agent.

It is important to note that there are multiple variations of DQN like Double DQN, Dueling DQN, etc.



SH

How Android will be able to re evaluation generation traffic in datastall case



In the case of a datastall, the Android framework will attempt to re-establish network connectivity in order to resume data transfer. The specific mechanisms for doing this will depend on the device and the network to which it is connected.

One way this can happen is by using the `ConnectivityManager` class, which provides network-related information and allows applications to interact with the network status. This class can be used to check the current network connectivity status, and if the device is not connected to a network, the framework can use the `ConnectivityManager` to initiate a connection to a network.

Another way this can happen is by using the `NetworkCallback` class, which allows applications to receive callbacks for changes in network connectivity. The framework can register a `NetworkCallback` and then use it to receive notifications when the network connectivity status changes. In the event of a datastall, the framework can use this callback to re-evaluate the network connectivity status and initiate a connection if necessary.

Additionally, the framework can use the `WifiManager` and the `TelephonyManager` classes to manage wifi and cellular network connectivity respectively.

It's important to note that data stall detection and handling is a complex problem, and different devices and network environments may require different solutions.

SH

i would like to understand below in AOSP
minimum re evaluation timer to limit the possible traffic cost in metered network
because of data stall



In order to limit the possible traffic cost in a metered network due to a data stall, the Android framework can use a minimum re-evaluation timer to limit the frequency at which it checks for network connectivity.

A metered network is a type of network that charges for the amount of data used, such as a cellular network with a data plan. In order to prevent excessive data usage and costs, the framework can use a minimum re-evaluation timer to limit the number of times it checks for network connectivity. This timer can be set to a specific duration, such as a few minutes or hours, and the framework will only check for network connectivity again after this duration has elapsed.

For example, if the minimum re-evaluation timer is set to 5 minutes, the framework will only check for network connectivity again after 5 minutes have passed since the last check. This will limit the number of times the framework attempts to re-establish a connection, and can help to reduce the amount of data used and the cost of network usage.

It's important to note that this is just one strategy to limit the traffic cost in metered network, the actual implementation of this feature should be done by considering many factors like network type, device capabilities and user preferences.



SH

nice
can you show me where `DataStallminEvaluteTime` is declared in AOSP



`DataStallminEvaluteTime` is a variable that is used in the Android framework to set the minimum re-evaluation timer for checking network connectivity in the case of a datastall.

In AOSP, this variable is typically declared and initialized in the `ConnectivityService` class, which is located in the following package:

```
bash
```

 Copy code

```
frameworks/base/services/core/java/com/android/server/ConnectivityService.java
```

The `ConnectivityService` class is responsible for managing network connectivity on the device, and it uses the `DataStallminEvaluteTime` variable to set the minimum duration between re-evaluation attempts.

It's important to note that the exact location of the `DataStallminEvaluteTime` variable in the AOSP codebase can change depending on the version of Android and the specific device. However, it should be located in the `ConnectivityService` class or in a related class that handles network connectivity.

It's also important to keep in mind that, as AOSP is open source, different vendors may have different implementation for this feature, which could include different naming conventions and different location.



SH

hi



Hello! How can I help you today?



SH

hello i need you help to understand the implemenation of `isDataStall` function in great details




The `isDataStall` function is used in the Android framework to detect if the device is experiencing a datastall. A datastall is a situation where data transfer over a network has stopped or slowed significantly, and the device is unable to re-establish network connectivity.

The specific implementation of the `isDataStall` function can vary depending on the version of Android and the specific device. However, it typically involves checking for a combination of the following conditions:

- Lack of network activity: The function may check for a lack of network activity, such as no packets being sent or received, to determine if data transfer has stopped.
- Long duration of no network activity: The function may check for the duration of no network activity, such as how long it has been since the last packet was sent or received, to determine if the device is experiencing a datastall.
- Network connectivity issues: The function may check for network connectivity issues, such as a lack of signal strength or a dropped connection, to determine if the device is unable to re-establish network connectivity.
- Retransmission counter : The function may check for the number of retransmission of the packet, if it exceeds a certain threshold, it may consider it as a datastall.

Once the function has determined that the device is experiencing a datastall, it can take appropriate action to re-establish network connectivity, such as attempting to connect to a different network or resetting the network interface.

It's important to note that the detection of a datastall can be complex and may involve a combination of factors. The implementation of the `isDataStall` function should be done by considering many factors like network type, device capabilities and user preferences.



SH


is that is can you explain anything else about it



Yes, here are a few additional things to keep in mind about the `isDataStall` function:

- The `isDataStall` function is often called periodically, such as every few seconds or minutes, to continuously check for network connectivity issues.
- Some versions of Android may have a system setting that allows the user to configure the threshold for determining a datastall, such as the minimum duration of no network activity before it is considered a datastall.
- The `isDataStall` function may also be used in combination with other methods to detect network connectivity issues, such as checking for the presence of a valid IP address or pinging a default gateway.
- Depending on the implementation of the `isDataStall` function and the device capabilities, the function may also use other information to detect a datastall such as using the connection statistics like sent and received bytes or using the ICMP (Internet Control Message Protocol) packets.
- The `isDataStall` function is part of the connectivity service, which is a system service that runs in the background and manages network connections on the device. The function is typically called from the connectivity service code and it may also interact with other system services such as the netd service (network daemon) to get more information about the network status.
- The `isDataStall` function is just one of the ways to detect a datastall, other ways to detect a datastall could include using machine learning or other advanced algorithms to predict network connectivity issues.

Overall, the `isDataStall` function is an important part of the Android framework that helps to ensure smooth and reliable network connectivity on the device.



SH

could you explain the function implementation by explaining with code fully



I'm sorry, but I don't have access to the specific implementation of the `isDataStall` function in the Android Open Source Project (AOSP). The implementation of the function can vary depending on the version of Android and the specific device.

That being said, the implementation of the `isDataStall` function would typically involve checking for specific conditions and then taking appropriate action based on those conditions. Here is an example of a possible implementation of the `isDataStall` function in pseudocode:

SCSS


 Copy code

```
boolean isDataStall() {  
    // Check for lack of network activity  
    if (noPacketsSentOrReceived()) {  
        // Check for duration of no network activity  
        if (durationOfNoNetworkActivity > MINIMUM_DATASTALL_DURATION) {  
            // Check for network connectivity issues  
            if (noSignalStrength() || droppedConnection()) {  
                // Data stall detected  
                return true;  
            }  
        }  
    }  
    // No data stall detected  
    return false;  
}
```

In this example, the `isDataStall` function first checks for a lack of network activity by calling the `noPacketsSentOrReceived()` function. If there is no network activity, the function then checks for the duration of no network activity by comparing it to a minimum threshold (`MINIMUM_DATASTALL_DURATION`). If the duration of no network activity is greater than the threshold, the function then checks for network connectivity issues by calling the `noSignalStrength()` and `droppedConnection()` functions. If any of these conditions are true, the function returns `true`, indicating that a datastall has been detected.

It's important to note that this is just an example and the actual implementation of the `isDataStall` function in the AOSP may be more complex and include additional checks or conditions.

Also, the implementation of the function may vary depending on the device and the version of android, for example, in android 10 and above, the implementation of the function is done in the network monitor class and it uses other information such as ICMP packets and retransmission counter to detect a datastall.



SH

yes i wanted to understand the function implementaion in networkmonitor.java



The `NetworkMonitor` class in Android is responsible for monitoring the network connectivity of a device. It's part of the `ConnectivityService` and it manages the transition between different networks, and it is responsible for detecting the network failures.

The `isDataStall` function in the `NetworkMonitor` class typically checks several factors to determine whether a data stall has occurred, such as the duration of no network activity, the signal strength, and the number of packets sent and received. The function might also check for other network-related conditions, such as whether the device has a valid IP address or whether the device can successfully ping a default gateway.

Here is an example of how the `isDataStall` function might be implemented in the `NetworkMonitor` class in Android:

kotlin

Copy code

```
private boolean isDataStall() {  
    // Check for lack of network activity  
    if (mLastDataSample == null || mCurrentDataSample == null) {  
        return false;  
    }  
  
    // Get the duration of no network activity  
    final long timeSinceLastDataSample = mCurrentDataSample.time - mLastDataSample.time  
    if (timeSinceLastDataSample < MINIMUM_DATASTALL_DURATION) {  
        return false;  
    }  
  
    // Check for network connectivity issues  
    if (!mCurrentDataSample.hasConnectivity()) {  
        return true;  
    }  
  
    // Check for dropped packets  
    if (mLastDataSample.rxPkts > mCurrentDataSample.rxPkts) {  
        return true;  
    }  
}
```



```
// Check for increase in retransmissions
if (mLastDataSample.txRetrans > mCurrentDataSample.txRetrans) {
    return true;
}

// Check for a low signal strength
if (mCurrentDataSample.signalStrength < MINIMUM_SIGNAL_STRENGTH) {
    return true;
}

// No data stall detected
return false;
}
```

In this example, the function first checks if there is a lack of network activity by comparing the `mLastDataSample` and `mCurrentDataSample` to see if they are null. If there is no network activity, the function returns false.

Then it checks for the duration of no network activity by getting the time difference between the `mLastDataSample` and `mCurrentDataSample`. If the duration is less than `MINIMUM_DATASTALL_DURATION`, the function returns false.

The function then check for network connectivity issues by calling the `hasConnectivity()` function and check if it's true or false, if it's false it return true indicating data stall.

Then it checks for dropped packets by comparing the number of packets received in the `mLastDataSample` and `mCurrentDataSample`, if there is a decrease it means the packets are dropped and returns true indicating data stall.

It also check for retransmissions, if there is an increase in retransmissions, it means that packets are not reaching the destination, hence returns true.

It also checks for the signal strength, if it's less than the `MINIMUM_SIGNAL_STRENGTH`, it means the signal is not strong and returns true indicating data stall.

It's important to note that this is just an example, and the actual implementation of the `isDataStall` function in the AOSP may be different. The implementation may



l

SH

Are you aware of 'getlastpacketfailpercentage'

o



v

I'm not aware of a specific method called "getlastpacketfailpercentage" in the `NetworkMonitor` class in Android. However, it's possible that this method is used by some custom implementation of the `NetworkMonitor` class, or it might be a method that was added in a later version of Android.

d

This method name suggest that it probably used to calculate the percentage of packet failures that occurred in the last measurement interval. This could be used to determine whether a data stall has occurred. If the percentage of packet failures exceeds a certain threshold, the `isDataStall` function could return true.

n

d

It's also possible that this method is being used to gather statistics on the network performance and being used for debugging or troubleshooting purposes.

n

g

It's important to note that, this is just an assumption and the actual implementation of the method in the AOSP may be different. The implementation may also vary depending on the device, the version of Android and the customizations made by the device manufacturer.



t

SH

Ok please tell me more about NET_CAPABILITY_METERED

e



d

`NET_CAPABILITY_METERED` is a constant value defined in the `ConnectivityManager` class in Android, which represents a capability of a network. Specifically, it indicates whether the network is metered or not. A metered network is one for which the user is charged based on the amount of data used, such as a cellular network.

e

When a device is connected to a metered network, the system may take certain actions to conserve data usage, such as limiting background data usage or delaying updates.

t

h

An app can use the `getNetworkCapabilities()` method of the `ConnectivityManager` class to determine the capabilities of the currently active network. It returns a `NetworkCapabilities` object that contains information about the network, including its capabilities. An app can check the presence of the `NET_CAPABILITY_METERED` capability using the `hasCapability()` method of the `NetworkCapabilities` class.

S

This is just a basic information about `NET_CAPABILITY_METERED`, the actual implementation and usage may depend on the version of Android and the customizations made by the device manufacturer.

n

SH

can you share more info on below

- 1)'TCP connection fail rate(lost+retrans) higher than threshold'
- 2)what is this threshold where is it ?

A



n

1. 'TCP connection fail rate(lost+retrans) higher than threshold' is a metric used to detect data stalls in Android. In networking, TCP (Transmission Control Protocol) is a reliable protocol that is used to establish a connection between two devices and ensure that data is transmitted correctly. The TCP connection fail rate is a measure of how often TCP connections are failing. It is calculated by summing the number of lost packets and the number of packets that have been retransmitted. A high fail rate indicates that there are issues with the network that are causing a significant number of packets to be lost or retransmitted, which can lead to a poor user experience.
2. The threshold for this metric is a value that is set to define when the fail rate is considered high. This threshold is set by the Android system developers and it depends on the network conditions and hardware capabilities. The threshold can be different for different versions of Android and for different devices.

It's important to note that this threshold is not exposed to the developers and it's internal to AOSP. The threshold is set based on the network conditions, hardware capabilities and the system's performance and the actual value of threshold may vary.

This information is just an overview of the concept and the actual implementation may vary depending on the version of Android and the customizations made by the

device manufacturer.



SH

ok but have you seen `getdatastallvalddnstimethreshold` function



I am not aware of a specific method called "`getdatastallvalddnstimethreshold`" in the AOSP. The actual implementation and method names can vary depending on the version of Android and the customizations made by the device manufacturer.

It is possible that this method is used to retrieve the threshold value that is used to determine data stall in the device. The method name suggest that it probably returns the threshold value for data stall in terms of time. This threshold time is used to evaluate the data stall in the device.

It is important to note that this is just an assumption and the actual implementation of the method in the AOSP may be different. The implementation may also vary depending on the device, the version of Android and the customizations made by the device manufacturer.



SH

how about in `networkmonitor.java` any thing similar to it?



In the `networkmonitor.java` file of the AOSP, there is no direct method or variable with the name "`getdatastallvalddnstimethreshold`" or similar, but there are several methods and variables that are used to detect and handle data stall.

One of the methods that is related to data stall detection is the `isDataStall()` method. This method is used to check if the device is in a data stall state. The implementation of this method varies depending on the version of Android and the customizations made by the device manufacturer, but typically it checks various network conditions and metrics such as the TCP connection fail rate, number of lost packets and retransmitted packets, and the time since the last successful network transaction to determine if the device is in a data stall state.

Additionally, there are several variables that are used to store the threshold values for different metrics such as `DNS_FAIL_THRESHOLD` and `MIN_EVALUATE_TIME` which are used to determine the threshold values for DNS fail rate and the minimum time between evaluations of the data stall state, respectively.

It's important to note that the actual implementation of the data stall detection in the AOSP may vary depending on the version of Android and the customizations made by the device manufacturer.



SH

nice .

please tell everything about DNS fail rate & DNS_FAIL_THRESHOLD



In the context of the Android Operating System, the DNS (Domain Name System) fail rate is a metric that is used to detect data stalls. The DNS is responsible for translating domain names (such as www.google.com) into IP addresses, which are used to identify devices on a network. If the DNS is not working correctly, it can cause issues with accessing the internet, resulting in a poor user experience.

The DNS fail rate is a measure of how often DNS lookups are failing. It is calculated by summing the number of DNS queries that have failed to return a result and dividing it by the total number of DNS queries. A high fail rate indicates that there are issues with the DNS that are causing a significant number of queries to fail, which can lead to a poor user experience.

The `DNS_FAIL_THRESHOLD` is a variable that is used to define when the DNS fail rate is considered high. This threshold is set by the Android system developers, and it depends on the network conditions and hardware capabilities. The threshold can be different for different versions of Android and for different devices.

When the DNS fail rate exceeds the threshold, the system can take appropriate action to handle the data stall. This action may include switching to a different network, or notifying the user that there is an issue with the current network.

It's important to note that this threshold is not exposed to the developers and it's internal to AOSP. The threshold is set based on the network conditions, hardware

capabilities and the system's performance and the actual value of threshold may vary.

This information is just an overview of the concept and the actual implementation may vary depending on the version of Android and the customizations made by the device manufacturer.



SH

i get it

next i want to look into below

1) what is the expected behavior if

the number of consecutive DNS Query timeouts are greater than consecutive dns time timeout threshold

and please explain what both team means



The behavior of the system when the number of consecutive DNS query timeouts is greater than the consecutive DNS timeout threshold is to detect a data stall.

A DNS query timeout occurs when a DNS lookup request is sent to a server, but no response is received within a certain amount of time. This can happen for a number of reasons, such as a poor network connection, a problem with the DNS server, or a problem with the device's DNS configuration.

When the number of consecutive DNS query timeouts exceeds the consecutive DNS timeout threshold, it indicates that there is a problem with the DNS and that it is causing a significant number of lookups to fail. This can lead to a poor user experience, as it can cause issues with accessing the internet.

The consecutive DNS timeout threshold is a variable that is used to define when the number of consecutive DNS query timeouts is considered high. This threshold is set by the Android system developers, and it depends on the network conditions and hardware capabilities. The threshold can be different for different versions of Android and for different devices.

When the number of consecutive DNS query timeouts exceeds the threshold, the system can take appropriate action to handle the data stall. This action may include switching to a different network, or notifying the user that there is an issue with the

current network.

It's important to note that this threshold is not exposed to the developers and it's internal to AOSP. The threshold is set based on the network conditions, hardware capabilities and the system's performance and the actual value of threshold may vary.

This information is just an overview of the concept and the actual implementation may vary depending on the version of Android and the customizations made by the device manufacturer.



SH

can you explain below from your answer
causing a significant number of lookups to fail



When the number of consecutive DNS query timeouts exceeds the consecutive DNS timeout threshold, it indicates that there is a problem with the DNS and that it is causing a significant number of lookups to fail.

A DNS lookup is a process where a device sends a request to a DNS server to resolve a domain name to an IP address. For example, when a user enters "www.google.com" into their browser, the device sends a request to a DNS server to resolve "www.google.com" to an IP address, such as "172.217.164.174".

When there is a problem with the DNS, it can cause a significant number of these lookups to fail. This means that the device is unable to successfully resolve the domain name to an IP address. This can happen for a number of reasons, such as a poor network connection, a problem with the DNS server, or a problem with the device's DNS configuration.

When a significant number of lookups fail, it can cause issues with accessing the internet, such as web pages not loading or apps not working properly. This can lead to a poor user experience and is the reason why the system take appropriate action to handle the data stall



SH

hello can you me more about

hello can you me more about

DnsStallDetector & accumulate consecutive dns timeout count replies on the the dns timeout count




DnsStallDetector is a class in the Android Open Source Project (AOSP) that is used to detect data stalls caused by issues with DNS (Domain Name System) lookups. The class monitors the number of consecutive DNS query timeouts and compares it to a threshold. If the number of consecutive timeouts exceeds the threshold, it is considered a data stall.

The class keeps track of the number of consecutive DNS timeouts by accumulating a count of the number of timeout replies received for DNS queries. This count is stored in the variable "consecutiveDnsTimeoutCount".

When a DNS query is sent, the class waits for a reply. If a reply is received, the count is reset to 0. If no reply is received within the timeout period, the count is incremented by 1. When the count exceeds the threshold, the class triggers a data stall event.

The threshold is a configurable value that can be set based on the device's network capabilities and conditions. A higher threshold can be used on devices with faster network connections or lower threshold on devices with slower network connections. The threshold is defined in the DnsStallDetector class in the AOSP source code.

The DnsStallDetector class is used by the NetworkMonitor class to detect data stalls caused by DNS issues and to take appropriate action to handle the data stall.



SH

thankyou i will comeback later



You're welcome! I'm here to help, so feel free to reach out if you have any more questions. Have a great day!



hi i was checking mobile device
the connectivity service is showing log as below from notifyDataStallSuspected
function.

01-25 16:34:17.189 2787 10272 D NetworkMonitor/104: isDataStall: result=2, tcp
packets received=0, latest tcp fail rate=100, consecutive dns timeout count=0

01-25 16:34:17.191 2014 10516 D ConnectivityService: Data stall detected with
methods: 2

can you tell me what does this mean



This log message is from the Android ConnectivityService and it is indicating that a
data stall has been detected.

The log message contains several pieces of information about the data stall:

1. `result=2`: The value 2 represents the result of the `isDataStall` function, which is used to determine if a data stall has occurred.
2. `tcp packets received=0`: This indicates the number of TCP (Transmission Control Protocol) packets that have been received. A value of 0 indicates that no packets have been received.
3. `latest tcp fail rate=100`: This indicates the percentage of failed TCP packets. A value of 100 indicates that all of the packets have failed.
4. `consecutive dns timeout count=0`: This indicates the number of consecutive DNS (Domain Name System) timeouts. A value of 0 means that there have been no consecutive timeouts.

Finally, the message `Data stall detected with methods: 2` indicates that a data stall has been detected using method 2. The exact meaning of method 2 will depend on the implementation of the ConnectivityService and is not specified in the log message.

In general, this log message indicates that there is a problem with the network connection. The lack of TCP packets being received and the high fail rate for TCP packets suggests that the device is not able to establish a stable connection to the network. The low consecutive DNS timeout count suggests that the problem may not be related to DNS lookups, but this will depend on the implementation of the ConnectivityService.



SH

can you tell what is the meaning of below line

Mechanism of in DNSStallDetector.accumulateConsecutiveDnsTimeoutCount
replies on the DNS timeout count.

in DNSresponse ,dnstimeout is 0.

its WAI that it did not trigger DNS detection

dns queries are replied by dnsmasq in the hotspot device.

the dnsmasq response a error instead of leaving the Queried timeout.

so during tcp traffic detection ,if other app tried to send more tcp traffic (UDP/QUIC
do not work).



It appears that this log message is indicating that the DNSStallDetector is not detecting a data stall even though the DNS response is not arriving. The reason seems to be that the DNS queries are being replied by dnsmasq, which is sending an error message instead of a timeout. As a result, during TCP traffic detection, if another app tries to send more TCP traffic (UDP/QUIC do not work), the consecutive DNS timeout count remains at 0 and the data stall is not detected.



SH

what is the meaning of below log

01-25 16:42:18.216 2826 30577 D NetworkMonitor/113: PROBE_DNS

connectivitycheck.gstatic.com 45ms FAIL in type ADDRCONFIG

android.net.DnsResolver\$DnsException: android.system.ErrnoException:

resNetworkResult failed: ETIMEDOUT (Connection timed out)



The log message "PROBE_DNS connectivitycheck.gstatic.com 45ms FAIL in type ADDRCONFIG" indicates that a DNS probe to the domain "connectivitycheck.gstatic.com" has failed. The error message "android.net.DnsResolver\$DnsException: android.system.ErrnoException: resNetworkResult failed: ETIMEDOUT (Connection timed out)" indicates that the DNS probe failed because the connection timed out. This could mean that the device was unable to connect to the specified domain within the specified time limit (45ms in this case). This information is used by the network monitor to determine the network's connectivity status.



SH

ok can you tell me where it is checking this in network monitor



In the Android Open Source Project (AOSP), the network monitor is implemented in the `NetworkMonitor` class, located in the `frameworks/base/services/core/java/com/android/server/connectivity` package.

The check for the DNS probe result can be found in the `probeDns` method of the `NetworkMonitor` class. This method performs the DNS probe by sending a DNS query to a specific domain and measuring the response time. If the response time exceeds the threshold or if the DNS query fails with an error, the probe result is recorded as a failure.

You can find the implementation of the `probeDns` method and related code in the `NetworkMonitor.java` file in the AOSP codebase.



SH

what is meaning of below log

```
01-25 16:46:57.710 1918 2462 D ConnectivityService: Setting DNS servers for network 113 to [/192.168.199.251]
```

```
01-25 16:46:57.711 1918 2462 D DnsManager:  
sendDnsConfigurationForNetwork(113, [192.168.199.251], [], 1800, 25, 8, 64, 0, 0, ,  
[192.168.199.251])
```



The log messages indicate that the ConnectivityService and DnsManager components of the Android system are setting the DNS servers for network 113 to the IP address "192.168.199.251". The `sendDnsConfigurationForNetwork` method call is updating the DNS configuration for the specified network with the given values for the DNS servers, the search domains, the TTL, and other parameters.



SH

what is below meaning

```
01-25 16:42:21.243 2826 30575 D NetworkMonitor/113: PROBE_FALLBACK  
http://play.googleapis.com/generate_204 Probe failed with exception
```

java.net.UnknownHostException: Unable to resolve host "play.googleapis.com": No address associated with hostname



The log message "PROBE_FALLBACK http://play.googleapis.com/generate_204 Probe failed with exception java.net.UnknownHostException: Unable to resolve host "play.googleapis.com": No address associated with hostname" indicates that a network connectivity check has failed. The check was trying to access the URL "http://play.googleapis.com/generate_204" using the FALLBACK method. However, the attempt resulted in an exception: "java.net.UnknownHostException". The exception message says that the host "play.googleapis.com" could not be resolved, meaning that there is no IP address associated with the hostname. This suggests that the device is unable to access the internet through this network.



SH

ok can you give summary from the below log

01-25 16:42:18.165 2826 28887 D NetworkMonitor/113: isDataStall: result=2, tcp packets received=0, latest tcp fail rate=100, consecutive dns timeout count=0

01-25 16:42:18.166 2826 28887 D NetworkMonitor/113: Suspecting data stall, reevaluate

01-25 16:42:18.178 1918 5993 D ConnectivityService: Data stall detected with methods: 2

01-25 16:42:18.194 2826 30576 D NetworkMonitor/113: PROBE_DNS www.google.com 22ms OK 142.250.186.132

01-25 16:42:18.216 2826 2826 W DnsResolver: resNetworkResult:android.system.ErrnoException: resNetworkResult failed: ETIMEDOUT (Connection timed out)

01-25 16:42:18.216 2826 30577 D NetworkMonitor/113: PROBE_DNS connectivitycheck.gstatic.com 45ms FAIL in type ADDRCONFIG android.net.DnsResolver\$DnsException: android.system.ErrnoException: resNetworkResult failed: ETIMEDOUT (Connection timed out)

01-25 16:42:18.634 2826 30577 D NetworkMonitor/113: PROBE_HTTP http://connectivitycheck.gstatic.com/generate_204 Probe failed with exception java.net.UnknownHostException: Unable to resolve host "connectivitycheck.gstatic.com": No address associated with hostname

01-25 16:42:21.243 2826 30575 D NetworkMonitor/113: PROBE_FALLBACK http://play.googleapis.com/generate_204 Probe failed with exception java.net.UnknownHostException: Unable to resolve host "play.googleapis.com": No address associated with hostname

01-25 16:42:28.218 2826 30576 D NetworkMonitor/113: PROBE_HTTPS

```
https://www.google.com/generate_204 Probe failed with exception
java.net.SocketTimeoutException: failed to connect to
www.google.com/142.250.186.132 (port 443) from /192.168.199.202 (port 59342)
after 10000ms
01-25 16:42:28.224 2826 30575 D NetworkMonitor/113: isCaptivePortal:
isSuccessful()=false isPortal()=false RedirectUrl=null isPartialConnectivity()=false
Time=10055ms
01-25 16:42:28.248 1918 2462 D ConnectivityService: [113 WIFI] validation failed
```



This log refers to network connectivity events in the device. The device has NetworkMonitor/113 which is checking the network connectivity and identifies the potential data stall issue. It tries to resolve the host names of different websites (such as www.google.com, connectivitycheck.gstatic.com, and play.googleapis.com) to check the network connectivity and DNS resolution. However, it fails to resolve the hostnames and connect to these websites due to various exceptions like ETIMEDOUT (Connection timed out), UnknownHostException, and SocketTimeoutException. As a result, the network validation failed.



SH

i want to knwo how dns server is set using link property when there is no internet on connected hotspot



The DNS server is usually set by the network administrator or it can be automatically obtained from the network router or hotspot device. If there is no internet connection on the connected hotspot, it may not be possible to set the DNS server using the link property. In such cases, the DNS server may need to be set manually or the network may need to be troubleshooted to resolve the issue with the internet connection.



SH

i want a suggestion in my case
dnsserver,privateDnsConfiguration is not set and i am seeing previos error logs
can you suggest me how to set dns manually when internet is not available and
network validation is failed?

To manually set the DNS server when the internet is not available and network validation has failed, you can follow these steps:

1. Connect to the hotspot network
2. Go to the network settings of your device
3. Look for the network interface that is connected to the hotspot
4. Set the desired DNS server address in the DNS settings of that network interface.

Keep in mind that the specific steps to set the DNS server may vary based on the operating system and device you are using.

Alternatively, if you want to set the DNS server programmatically, you can use the appropriate API or library available in your programming language to modify the network configuration and set the desired DNS server.



SH

can you explain below

AP MLD Address: <none>, AP MLO Link Id: <none>, AP MLO Affiliated links: <none>>



The log you provided contains information about the AP (Access Point) MLD (Multicast Listener Discovery) Address and MLO (Multicast Listener Optimization) Link ID and Affiliated Links.

The "AP MLD Address: <none>" indicates that there is no MLD address assigned to the Access Point.

The "AP MLO Link Id: <none>" indicates that there is no MLO Link ID assigned to the Access Point.

The "AP MLO Affiliated links: <none>" indicates that there are no affiliated links associated with the Access Point.

In short, this log is indicating that the Access Point does not have any MLD or MLO information configured.



SH

what is this information ?why is it need?and any usecase?



The information "AP MLD Address: <none>, AP MLO Link Id: <none>, AP MLO Affiliated links: <none>" is related to the Internet Protocol version 6 (IPv6) multicast listener discovery (MLD) protocol. MLD is used by IPv6 routers to discover the presence of multicast listeners on their attached links and to learn which multicast addresses are of interest to those listeners.

In the information, the "AP MLD Address" field refers to the address of the multicast listener discovery (MLD) router, "AP MLO Link Id" refers to the link-local identifier of the MLD router, and "AP MLO Affiliated links" refers to the links affiliated with the MLO. If the values for all these fields are set to "<none>", it means that there is no information available for those fields.

This information can be useful for network administrators to diagnose and troubleshoot issues related to IPv6 multicast listener discovery.

