

## Solving problems by searching

Chapter 3  
(materials from the text and from  
other online presentations)

1

1

## Problem-solving agents

```
function SIMPLE-PROBLEM-SOLVING-AGENT(percept) returns an action
  static: seq, an action sequence, initially empty
          state, some description of the current world state
          goal, a goal, initially null
          problem, a problem formulation

  state ← UPDATE-STATE(state, percept)
  if seq is empty then do
    goal ← FORMULATE-GOAL(state)
    problem ← FORMULATE-PROBLEM(state, goal)
    seq ← SEARCH(problem)
  action ← FIRST(seq)
  seq ← REST(seq)
  return action
```

2

2

## Tree search algorithms

- Basic idea:
  - offline, simulated exploration of state space by generating successors of already-explored states (a.k.a. **expanding** states)

```
function TREE-SEARCH(problem, strategy) returns a solution, or failure
  initialize the search tree using the initial state of problem
  loop do
    if there are no candidates for expansion then return failure
    choose a leaf node for expansion according to strategy
    if the node contains a goal state then return the corresponding solution
    else expand the node and add the resulting nodes to the search tree
```

3

3

## Implementation: general tree search

```
function TREE-SEARCH(problem, fringe) returns a solution, or failure
  fringe ← INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node ← REMOVE-FRONT(fringe)
    if GOAL-TEST[problem](STATE[node]) then return SOLUTION(node)
    fringe ← INSERT-ALL(EXPAND(node, problem), fringe)

  function EXPAND(node, problem) returns a set of nodes
    successors ← the empty set
    for each action, result in SUCCESSOR-FN[problem](STATE[node]) do
      s ← a new NODE
      PARENT-NODE[s] ← node; ACTION[s] ← action; STATE[s] ← result
      PATH-COST[s] ← PATH-COST[node] + STEP-COST(node, action, s)
      DEPTH[s] ← DEPTH[node] + 1
      add s to successors
    return successors
```

4

4

### Uninformed search strategies

- **Uninformed** search strategies use only the information available in the problem definition
- Breadth-first search
- Uniform-cost search
- Depth-first search
- Depth-limited search
- Iterative deepening search

5

5

### Properties of breadth-first search

- **Complete?** Yes (if  $b$  is finite)
- **Time?**  $1+b+b^2+b^3+\dots +b^d + b(b^d-1) = O(b^{d+1})$
- **Space?**  $O(b^{d+1})$  (keeps every node in memory)
- **Optimal?** Yes (if cost = 1 per step)
- **Space** is the bigger problem (more than time)

6

6

### Properties of depth-first search

- **Complete?** No: fails in infinite-depth spaces, spaces with loops
  - Modify to avoid repeated states along path  
→ complete in finite spaces
- **Time?**  $O(b^m)$ : terrible if  $m$  is much larger than  $d$ 
  - but if solutions are dense, may be much faster than breadth-first
- **Space?**  $O(bm)$ , i.e., linear space!
- **Optimal?** No

7

7

### Depth-limited search

= depth-first search with depth limit  $l$ ,  
i.e., nodes at depth  $l$  have no successors

- **Recursive implementation:**

```
function DEPTH-LIMITED-SEARCH( problem, limit) returns soln/fail/cutoff
  RECURSIVE-DLS(MAKE-NODE(INITIAL-STATE[problem]), problem, limit)

function RECURSIVE-DLS(node, problem, limit) returns soln/fail/cutoff
  cutoff-occurred? ← false
  if GOAL-TEST[problem](STATE[node]) then return SOLUTION(node)
  else if DEPTH[node] = limit then return cutoff
  else for each successor in EXPAND(node, problem) do
    result ← RECURSIVE-DLS(successor, problem, limit)
    if result = cutoff then cutoff-occurred? ← true
    else if result ≠ failure then return result
  if cutoff-occurred? then return cutoff else return failure
```

8

8

## Iterative deepening search

```

function ITERATIVE-DEEPENING-SEARCH(problem) returns a solution, or fail-
ure
  inputs: problem, a problem
  for depth ← 0 to ∞ do
    result ← DEPTH-LIMITED-SEARCH(problem, depth)
    if result ≠ cutoff then return result

```

9

9

## Iterative deepening search

- Number of nodes generated in a depth-limited search to depth  $d$  with branching factor  $b$ :

$$N_{DLS} = b^0 + b^1 + b^2 + \dots + b^{d-2} + b^{d-1} + b^d$$

- Number of nodes generated in an iterative deepening search to depth  $d$  with branching factor  $b$ :

$$N_{IDS} = (d+1)b^0 + d b^1 + (d-1)b^2 + \dots + 3b^{d-2} + 2b^{d-1} + 1b^d$$

- For  $b = 10$ ,  $d = 5$ ,

- $N_{DLS} = 1 + 10 + 100 + 1,000 + 10,000 + 100,000 = 111,111$

- $N_{IDS} = 6 + 50 + 400 + 3,000 + 20,000 + 100,000 = 123,456$

- Overhead =  $(123,456 - 111,111)/111,111 = 11\%$

10

10

## Properties of iterative deepening search

- Complete?** Yes
- Time?**  $(d+1)b^0 + d b^1 + (d-1)b^2 + \dots + b^d = O(b^d)$
- Space?**  $O(bd)$
- Optimal?** Yes, if step cost = 1

11

11

## Summary of algorithms

Criterion	Breadth-First	Uniform-Cost	Depth-First	Depth-Limited	Iterative Deepening
Complete?	Yes	Yes	No	No	Yes
Time	$O(b^{d+1})$	$O(b^{\lceil C^*/\epsilon \rceil})$	$O(b^m)$	$O(b^l)$	$O(b^d)$
Space	$O(b^{d+1})$	$O(b^{\lceil C^*/\epsilon \rceil})$	$O(bm)$	$O(bl)$	$O(bd)$
Optimal?	Yes	Yes	No	No	Yes

12

12

## Graph search

```

function GRAPH-SEARCH(problem, fringe) returns a solution, or failure
  closed ← an empty set
  fringe ← INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node ← REMOVE-FRONT(fringe)
    if GOAL-TEST[problem](STATE[node]) then return SOLUTION(node)
    if STATE[node] is not in closed then
      add STATE[node] to closed
      fringe ← INSERTALL(EXPAND(node, problem), fringe)

```

13

13

## Hill-climbing search

- "Like climbing Everest in thick fog with amnesia"

```

function HILL-CLIMBING(problem) returns a state that is a local maximum
  inputs: problem, a problem
  local variables: current, a node
                  neighbor, a node

  current ← MAKE-NODE(INITIAL-STATE[problem])
  loop do
    neighbor ← a highest-valued successor of current
    if VALUE[neighbor] ≤ VALUE[current] then return STATE[current]
    current ← neighbor

```

14

## Simulated annealing search

- Idea: escape local maxima by allowing some "bad" moves but **gradually decrease** their frequency

```

function SIMULATED-ANNEALING(problem, schedule) returns a solution state
  inputs: problem, a problem
         schedule, a mapping from time to "temperature"
  local variables: current, a node
                  next, a node
                  T, a "temperature" controlling prob. of downward steps

  current ← MAKE-NODE(INITIAL-STATE[problem])
  for t ← 1 to ∞ do
    T ← schedule[t]
    if T = 0 then return current
    next ← a randomly selected successor of current
     $\Delta E \leftarrow \text{VALUE}[\text{next}] - \text{VALUE}[\text{current}]$ 
    if  $\Delta E > 0$  then current ← next
    else current ← next only with probability  $e^{\Delta E / T}$ 

```

15

## Simulated Annealing

- Metropolis - 1953:
  - simulation of cooling of material in a heath bath;
    - A solid material is heated past its melting point and then cooled back into a solid state (annealing).
    - The final structure depends on how the cooling is performed
      - slow cooling → large crystal (low energy)
      - fast cooling → imperfections (high energy)
  - According to thermodynamics: at temperature  $T$ , the probability of an increase in energy of  $\Delta E$  is:

$$p(\Delta E) = e^{-\Delta E / kT} \quad k \text{ is the Boltzmann constant}$$

16

16

### Local beam search

- Keep track of  $k$  states rather than just one
- Start with  $k$  randomly generated states
- At each iteration, all the successors of all  $k$  states are generated
- If any one is a goal state, stop; else select the  $k$  best successors from the complete list and repeat.

17

### Summary

- Problem formulation usually requires abstracting away real-world details to define a state space that can feasibly be explored
- Variety of uninformed search strategies
- Iterative deepening search uses only linear space and not much more time than other uninformed algorithms

18

18