

PART 1

1.

```
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$ cc getMostFreqChar.c
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$ ./a.out test.txt
This is a list of courses.
CSC 1010 - COMPUTERS & APPLICATIONS

The Most frequent letter is 's'. It appeared 8 times.
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$
```

PART 2

2.

```
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$ vi addressOfScalar.c
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$ gcc addressOfScalar.c
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$ ./a.out
address of charvar = 0x7fff222dd5af
address of charvar - 1 = 0x7fff222dd5ae
address of charvar + 1 = 0x7fff222dd5b0
address of intvar = 0x7fff222dd5a8
address of intvar - 1 = 0x7fff222dd5a4
address of intvar + 1 = 0x7fff222dd5ac
[sbrahmhatt3@gsuad.gsu.edu@snowball ~]$
```

3.

```
#include <stdio.h>

int main() {
    char charvar = 'a';
    printf("address of charvar = %p\n", (void *)&charvar);
    printf("address of charvar - 1 = %p\n", (void *)&charvar - 1);
    printf("address of charvar + 1 = %p\n", (void *)&charvar + 1);

    int intvar = 1;
    printf("address of intvar = %p\n", (void *)&intvar);
    printf("address of intvar - 1 = %p\n", (void *)&intvar - 1);
    printf("address of intvar + 1 = %p\n", (void *)&intvar + 1);
    return 0;
}
```

PART 3

4.

```
[sbrahmbhatt3@gsuad.gsu.edu@snowball ~]$ gcc addressOfArray.c
[sbrahmbhatt3@gsuad.gsu.edu@snowball ~]$ ./a.out
numbers = 0x7ffedc716830
numbers[0] = 0x7ffedc716830
numbers[1] = 0x7ffedc716834
numbers[2] = 0x7ffedc716838
numbers[3] = 0x7ffedc71683c
numbers[4] = 0x7ffedc716840
sizeof(numbers)= 20
length(numbers)= 5
[sbrahmbhatt3@gsuad.gsu.edu@snowball ~]$
```

5. Yes, both address of the array and address of first element of array are same.