JS & DOM Reference
Overview

JavaScript Objects
JS Array
JS Boolean
JS Date
JS Math
JS Number
JS String
JS RegExp
JS Global

Browser Objects
Window
Navigator
Screen
History
Location

HTML DOM Objects
DOM Document
DOM Events
DOM Elements

DOM Anchor
DOM Area
DOM Base
DOM Body
DOM Button
DOM Form
DOM Frame/IFrame
DOM Frameset
DOM Image
DOM Input Button
DOM Input Checkbox
DOM Input File
DOM Input Hidden
DOM Input Password
DOM Input Radio
DOM Input Reset
DOM Input Submit
DOM Input Text
DOM Link
DOM Meta
DOM Object
DOM Option
DOM Select
DOM Style
DOM Table
DOM td / th
DOM tr
DOM Textarea

JavaScript RegExp g Modifier

🔴 JavaScript RegExp Object

Definition and Usage

The g modifier is used to perform a global match (find all matches rather than stopping after the first match).

Syntax

```
new RegExp("regexp","g")

or simply:

/regexp/g
```

Browser Support

The g modifier is supported in all major browsers.

Examples

Example 1

Do a global search for "is":

```
var str="Is this all there is?";
var patt1=/is/g;
```

The marked text below shows where the expression gets a match:

Is th**is** all there **is**?

[Try it yourself »]

Example 2

Do a global, case-insensitive search for "is":

```
var str="Is this all there is?";
var patt1=/is/gi;
```

The marked text below shows where the expression gets a match:

Is th**is** all there **is**?

[Try it yourself »]

🔴 JavaScript RegExp Object