JS & DOM Reference
Overview

JavaScript Objects
JS Array
JS Boolean
JS Date
JS Math
JS Number
JS String
JS RegExp
JS Global

Browser Objects
Window
Navigator
Screen
History
Location

HTML DOM Objects
DOM Document
DOM Events
DOM Elements

DOM Anchor
DOM Area
DOM Base
DOM Body
DOM Button
DOM Form
DOM Frame/IFrame
DOM Frameset
DOM Image
DOM Input Button
DOM Input Checkbox
DOM Input File
DOM Input Hidden
DOM Input Password
DOM Input Radio
DOM Input Reset
DOM Input Submit
DOM Input Text
DOM Link
DOM Meta
DOM Object
DOM Option
DOM Select
DOM Style
DOM Table
DOM td / th
DOM tr
DOM Textarea

Navigator userAgent Property

🔺 Navigator Object

Definition and Usage

The userAgent property returns the value of the user-agent header sent by the browser to the server.

Syntax

```
navigator.userAgent
```

Browser Support

The userAgent property is supported in all major browsers.

Example

Example

The user-agent header sent by your browser:

```
<script type="text/javascript">

document.write("User-agent header sent: " + navigator.userAgent);

</script>
```

The output of the code above will be:

```
User-agent header sent: Mozilla/5.0 (Windows NT 6.1; rv:9.0.1)
Gecko/20100101 Firefox/9.0.1
```

Try it yourself »

✂ More Examples

All navigator properties in one example

🔺 Navigator Object