JS & DOM Reference
Overview

JavaScript Objects
JS Array
JS Boolean
JS Date
JS Math
JS Number
JS String
JS RegExp
JS Global

Browser Objects
Window
Navigator
Screen
History
Location

HTML DOM Objects
DOM Document
DOM Events
DOM Elements

DOM Anchor
DOM Area
DOM Base
DOM Body
DOM Button
DOM Form
DOM Frame/IFrame
DOM Frameset
DOM Image
DOM Input Button
DOM Input Checkbox
DOM Input File
DOM Input Hidden
DOM Input Password
DOM Input Radio
DOM Input Reset
DOM Input Submit
DOM Input Text
DOM Link
DOM Meta
DOM Object
DOM Option
DOM Select
DOM Style
DOM Table
DOM td / th
DOM tr
DOM Textarea

JavaScript setUTCMilliseconds() Method

🔺 JavaScript Date Object

Definition and Usage

The setUTCMilliseconds() method sets the milliseconds (from 0 to 999), according to universal time.

Note: This method is always used in conjunction with a Date object.

Syntax

```
Date.setUTCMilliseconds(millisec)
```

Parameter	Description
millisec	Required. An integer between 0 and 999 representing the milliseconds

Browser Support

The setUTCMilliseconds() method is supported in all major browsers.

Tips and Notes

Tip: The Universal Coordinated Time (UTC) is the time set by the World Time Standard.

Example

Example

Set the UTC milliseconds to 192:

```
<script type="text/javascript">

var d = new Date();
d.setUTCMilliseconds(192);
document.write(d.getUTCMilliseconds());

</script>
```

The output of the code above will be:

```
192
```

Try it yourself »

🔺 JavaScript Date Object