```cpp
#include <iostream>
using namespace std;

class Complex
{
private:
double real, imaginary;

public:
Complex (double r=0, double i=0)
{
real=r;
imaginary=i;
}

void disp() const
{
cout<<real<< (imaginary>=0? "+" : "-")<< abs(imaginary)<<"i";
}

Complex operator+(const Complex& other)
{
return Complex(real+ other.real,imaginary + other.imaginary);
}

Complex operator*(const Complex& other)
{
double r = real*other.real- imaginary*other.imaginary;
double i = real*other.imaginary+ imaginary*other.real;
return Complex(r,i);
}
};

int main()
{
int r1,r2,i1,i2;

cout<<"Enter the value of first real digit : ";
cin>>r1;
cout<<"Enter the value of first imaginary digit : ";
cin>>i1;

cout<<"Enter the value of second real digit : ";
cin>>r2;
cout<<"Enter the value of second imaginary digit : ";
cin>>i2;

Complex c1(r1,i1);
Complex c2(r2,i2);

cout<<"Complex number 1:";
c1.disp();
cout<<endl;

cout<<"Complex number 2:";
c2.disp();
cout<<endl;

Complex c3=c1+c2;
cout<<"Addition : ";
c3.disp();
cout<<endl;

Complex c4=c1*c2;
cout<<"Multiplication : ";
c4.disp();
```

```
cout<<endl;

return 0;
}
```