```
#include <iostream>
using namespace std;

int volume(int);
float volume1(float);
float volume2(float,float);

int main()
{
int r,r1,r2;
float h;
float pi = 3.14;
char choice;
cout<<"1.The volume of cube:\t"<<endl;
cout<<"2.The volume of sphere:\t"<<endl;
cout<<"3.The volume of cylinder:\t"<<endl;
cout<<"Enter your choice:\t"<<choice<<endl;

switch(choice)
{
case 1:
cout<<"Your selected shape is a cube";
cout<<"Enter the value of radius of the cube:\t"<<r;
cin>>r;
cout<<"The volume of the cube is :\t";
break;

case 2:
cout<<"Your selected shape is a sphere";
cout<<"Enter the value of radius of the sphere:\t"<<r1;
cin>>r1;
cout<<"The volume of the sphere is :\t";
break;

case 3:
cout<<"Your selected shape is a cylinder";
cout<<"Enter the value of radius of the cylinder:\t"<<r2;
cin>>r2;
cout<<"Enter the height of the cylinder:\t:"<<h;
cin>>h;
cout<<"The volume of the cylinder is :\t";
break;

default:
cout<<"Your choice is invalid";
}

int volume(r);
{
return r*r*r;
}

float volume1(r1);
{
return 4/3*pi*r1*r1*r1;
}

float volume2(r2,h);
{
return pi*r2*r2*h;
}
};
```