



30 SQL QUERIES

apostrophe (')

Parentheses ()

1) SQL Query to update DateOfJoining to 15-jul-2012 for empid =1.

```
UPDATE employequery SET joiningdate='15 JULY 2012' WHERE empid=1
UPDATE employequery SET joiningdate=convert(varchar(20),'15 july 2020') WHERE
empid=1 UPDATE employequery SET joiningdate=cast('15 JULY 2013' as varchar (20))
WHERE empid=1
```

2) SQL Query to select all student name where age is greater than 22.

```
Select * from tablename where age>22
```

3) SQL Query to Find all employee with Salary between 40000 and 80000.

```
SELECT * FROM employequery WHERE salary BETWEEN 40000 AND 80000
SELECT * FROM employequery WHERE salary > 40000 AND SALARY <80000
```

4) SQL Query to display full name.

```
SELECT CONCAT(FIRSTNAME, ' ', LASTNAME) FROM employequery
SELECT CONCAT(FIRSTNAME+ ' ', LASTNAME+ ' ',dept) FROM employequery
```

5) SQL Query to find name of employee beginning with S.

```
SELECT * FROM employequery WHERE firstname LIKE 'S%'
```

6) Write a query to fetch details of employees whose firstname ends with an alphabet 'A' and contains exactly five alphabets.

```
SELECT * FROM employequery WHERE firstname LIKE '____A'
```

7) Write a query to fetch details of all employees excluding the employees with first names, "ANUSHKA" and "SOMNATH" from the Employee table.

```
SELECT * FROM employequery WHERE firstname !='SOMNATH' AND
firstname!='ANUSKHA'
```

```
SELECT * FROM employequery WHERE firstname NOT
IN('SOMNATH', 'ANUSKHA')
```

8) SQL query to display the current date?

```
SELECT SYSDATETIME(),CURRENT_TIMESTAMP,getdate()
```

Returns the current system date and time of the operating system on which the SQL Server is running.

9) SQL Query to get day of last day of the previous month?

```
SELECT EOMONTH(DATEADD(MONTH,-1,GETDATE()));
```

--This example returns the number of days of February

```
SELECT
```

```
DAY(EOMONTH('2020-02-09'))
```

--The following example uses the EOMONTH() function with an offset of 2 months:

```
SELECT
```

```
EOMONTH('2019-02-15', 2)
```

10) Write an SQL query to fetch the employee FIRST names and replace the A with '@'.

```
SELECT REPLACE(firstname,'A','@') FROM employequery  
  
REPLACE(string, old_string, new_string)
```

11) Write an SQL query to fetch the domain from an email address

```
SELECT
```

```
SUBSTRING ([EmailID], CHARINDEX( '@', [EmailID]) +0,
```

```
LEN([EmailID])) AS [Domain]
```

```
FROM employequery
```

-- SQL Query to Extract Domain name From Email and Count Number of Records

```
SELECT SUBSTRING (  
[Emailid],
```

```

        CHARINDEX( '@', [Emailid] ) + 1,
        LEN([Emailid]))
    ) AS [Domain Name],
    COUNT(*) AS [Total Records with this Domain]
FROM employequery
WHERE LEN([Emailid]) > 1
GROUP BY SUBSTRING (
    [Emailid],
    CHARINDEX( '@', [Emailid] ) + 1,
    LEN([Emailid]))
)

```

- 12) Write an SQL query to update the employee names by removing leading and trailing spaces.

```

UPDATE employequery SET firstname=RTRIM(LTRIM(FIRSTNAME))

```

- 13) Write an SQL query to fetch all the Employees details from Employee table who joined in the Year 2020

```

SELECT
    [JOININGDATE]
    ,[ModifiedDate]
FROM [AdventureWorks2014].[HumanResources].[EmployeePayHistory] WHERE YEAR(JOININGDATE)=2020

```

```

select * from employequery where joiningdate between '2020-01-01' and '2020-12-31'

```

for the employee who joined after 2020

```

select * from employequery where joiningdate >='2020/01/01'

```

14. Write an SQL query to fetch only odd rows / Even rows from the table.

odd

```

SELECT *
FROM (
    SELECT *, Row_Number() OVER(ORDER BY Firstname,lastname) as rownumber
    --Row_Number() starts with 1.
    FROM [master].[dbo].[employequery]
) t
WHERE t. RowNumber % 2 = 1

```

```
WITH RESULT AS(
select *,ROW_NUMBER() over ( order by empid ) Row_num
FROM [master].[dbo].[employequery]
)
SELECT *FROM RESULT WHERE ROW_NUM % 2 = 1
```

```
EVEN
SELECT *
FROM (
SELECT *, Row_Number() OVER(ORDER BY Firstname,lastname)as rownumber
--Row_Number() starts with 1.
FROM [master].[dbo].[employequery]
) t
WHERE t. RowNumber % 2 = 0
```

```
WITH RESULT AS(
select *,ROW_NUMBER() over ( order by empid ) Row_num
FROM [master].[dbo].[employequery]
)
SELECT *FROM RESULT WHERE ROW_NUM % 2 = 0
```

15. Write an SQL query to create a new table with data and structure copied from another table.

```
select * into newtable from oldtable
```

16. Write an SQL query to create an empty table with the same structure as some other table.

```
select * into newtable from oldtable where 1=0
```

17. Write an SQL query to fetch top 3 HIGHEST salaries?

```
select top 3 * from employequery order by salary desc
select distinct top 3 salary from employequery order by salary desc
```

```
with cte as(
select *,DENSE_RANK() over( order by salary desc) rn FROM
[master].[dbo].[employequery])
select distinct salary from cte where rn<=3
```

18. Find the first employee and last employee from employee table?

```
select top 1 * from employequery order by empid
select top 1 * from employequery order by empid desc
```

```
select * from employequery where empid=(select min(empid) from employequery)
```

```
select * from employequery where empid=(select max(empid) from employequery)
```

for identity last identity created

use @@identity

19. List the ways to get the count of records in a table?

```
select count(*) from employequery
select count(6) from employequery
select count(managerid) from employequery
```

20. Write a query to fetch the department-wise count of employees sorted by department's count in ascending order?

```
select *,row_number() over( partition by dept order by salary desc) rn FROM
[master].[dbo].[employequery]
```

```
select dept,count(*)n from employequery group by dept order by count(*)
FOR PARTICULAR DEPT
select dept,count(*)n from employequery WHERE DEPT='IT'group by dept
```

```
select dept,count(*)n from employequery group by dept order by count(*) desc
```

21. Write a query to retrieve Departments who have less than 4 employees working in it.

```
select dept,count(*)n from employequery group by dept having count(*)<4
```

22. Write a query to retrieve Department wise Maximum salary

```
select dept,max(salary)n from employequery group by dept
```

.

23. Write a query to Employee earning maximum salary in his department.

```
select * from employequery q1 join(select dept,max(salary)salary from employequery
group by dept)q2
on q1.dept=q2.dept and q1.salary=q2.salary
```

```
select * from (
select *,Dense_rank() over ( partition by dept order by Salary desc) as dense
FROM [master].[dbo].[employequery]
) as K
where k.dense =1
```

24. Write an SQL query to fetch the first 50% records from a table

```
select * from employequery where empid<=(select count(*) from employequery)/2
```

25. Query to fetch details of employees not having computer

```
select * from employequery where compyid IS null
```

26. Query to fetch employee details along with the computer details who have been assigned with a computer.

```
select * from employequery where compyid is not null
select * from employequery e inner join comp c on e.compyid=c.compyid
```

27. Fetch all employee details along with the computer name assigned to them.

```
select * from employequery e left outer join comp c on e.compyid=c.compyid
```

28. Fetch all Computer Details along with employee name using it

```
select firstname,c.brand from employequery e left outer join comp c on
e.compyid=c.compyid
```

29. Delete duplicate records from a table

```
example insert into mahindra(id,vehicletype) values(11, 'MAHINDRA')
insert into mahindra(id,vehicletype) values(111, 'MARUTI' )
insert into mahindra(id,vehicletype) values(22, 'bike' )
insert into mahindra(id,vehicletype) values(3333, 'bolero' )
insert into mahindra (id,vehicletype)values(3433, 'kuv' )
insert into mahindra (id,vehicletype)values(3443, 'scorpio')
insert into mahindra(id,vehicletype) values(4343, 'xylo' )
```

using cte

```
with cte as(  
select *, row_number() over(partition by vehicletype order by id desc) rn FROM  
[master].[dbo].[mahindra])  
  
delete from cte where rn>1
```

A) using rank

```
DELETE E  
FROM contacts E  
INNER JOIN  
(  
SELECT *, RANK() OVER(PARTITION BY email ORDER BY id) rank FROM contacts) T ON  
E.ID = t.ID  
WHERE rank > 1;
```

B) Delete duplicate rows with the DELETE JOIN statement

```
DELETE t1 FROM contacts t1  
INNER JOIN contacts t2  
on  
t1.id < t2.id AND  
t1.email = t2.email;  
select * from contacts
```

C) using cte

```
with cte as(  
select *, row_number() over(partition by vehicletype order by id desc) rn FROM  
[master].[dbo].[mahindra])  
  
delete from cte where rn>1
```

D) using group by

```
DELETE FROM contacts  
WHERE ID NOT IN
```

```
(
    SELECT MAX(ID) AS MaxRecordID
    FROM contacts
    GROUP BY email
);
```

30. Find Nth Highest salary

```
WITH RESULT AS(
    select *,dense_RANK() over ( order by SALARY DESC ) Row_num
    FROM [master].[dbo].[employeequery]
)
SELECT *FROM RESULT WHERE ROW_NUM=5
```

31) Write an SQL query to find the count of the total occurrences of a particular character – 'n' in the FullName field.

```
SELECT firstname,
LEN(Firstname) - LEN(REPLACE(firstname, 'n', ''))
FROM employeequery;
```

32) Write an SQL query to fetch records that are present in one table but not in another table.

```
SELECT * FROM EmployeeSalary
```

```
MINUS(except)
```

```
SELECT * FROM ManagerSalary;
```

33) Write an SQL query to fetch common records between two tables.

```
SELECT * FROM EmployeeSalary
```

```
INTERSECT
```

```
SELECT * FROM ManagerSalary;
```

34) Write an SQL query to fetch all the Emplds which are present in either of the tables – 'EmployeeDetails' and 'EmployeeSalary'.

```
SELECT EmpId FROM EmployeeDetails
```

```
UNION
```

```
SELECT EmpId FROM EmployeeSalary;
```

35) **Write an SQL query to display the total salary of each employee adding the Salary with Variable value.**

```
select empid,salary+bonus as total_salary from employequery
```

36) **Write an SQL query to fetch the Empls that are present in both the tables – 'EmployeeDetails' and 'EmployeeSalary.'**

```
SELECT EmpId FROM
```

```
EmployeeDetails
```

```
where EmpId IN
```

```
(SELECT EmpId FROM EmployeeSalary);
```

37) **Write an SQL query to fetch the Empls that are present in EmployeeDetails but not in EmployeeSalary.**

```
SELECT EmpId FROM
```

```
EmployeeDetails
```

```
where EmpId Not IN
```

```
(SELECT EmpId FROM EmployeeSalary);
```

```
DECLARE @dt DATETIME = '2019-12-31 ';
```

```
SELECT
```

```
    CONVERT(VARCHAR(20),@dt,6) s1
```

100 %

Results Messages

	s1
1	31 Dec 19

```
DECLARE @dt DATE = '2019-12-31 ';
```

```
SELECT
```

```
    CONVERT(VARCHAR(20),@dt,0) s1
```

100 %

Results Messages

	s1
1	Dec 31 2019