

# Real World Planning

Shiwali Mohan

Computer Science and Engineering  
University of Michigan

May 25, 2012

# Outline

---

## ① Real World Planning

# Review

---

- Classical Planning
  - fully observable
  - deterministic
  - finite
  - static
  - discrete

# Review

---

- (non) Classical Planning (for uncertainty)
  - ~~fully observable~~ partially observable
  - ~~deterministic~~ non deterministic
  - finite
  - static
  - discrete

# Review

---

- (non) Classical Planning (for uncertainty)
  - ~~fully observable~~ partially observable
  - ~~deterministic~~ non deterministic
  - finite
  - static
  - discrete
- Approaches
  - Sensorless Planning
  - Conditional Planning
  - Execution Monitoring and Replanning
  - Uncertainty Modeling

# Weighty Tower of Hanoi

- Similar to regular Tower of Hanoi
  - disk are to be ordered by their weight
  - `clear()`, `on()`, `smaller()`, `disk()`

Figure: objects: disks - red, green, blue;  
pegs - A, B, C

# Weighty Tower of Hanoi

- Similar to regular Tower of Hanoi
  - disk are to be ordered by their weight
  - `clear()`, `on()`, `smaller()`, `disk()`
  - `clear()`, `on()`, ~~`smaller()`~~ `lighter()`,  
`disk()`

Figure: objects: disks - red, green, blue;  
pegs - A, B, C

# Weighty Tower of Hanoi

- Similar to regular Tower of Hanoi
  - disk are to be ordered by their weight
  - `clear()`, `on()`, `smaller()`, `disk()`
  - `clear()`, `on()`, ~~`smaller()`~~ `lighter()`, `disk()`
- Initial state
 

```
on(Red, Green), on(Green, Blue),
on(Blue, A), clear(Red), disc(Red),
disc(Green), disk(Blue) clear(B),
clear(C), lighter(Red, A),
lighter(Red, B) ...
```

Figure: objects: disks - red, green, blue;  
pegs - A, B, C



# Weighty Tower of Hanoi

- Similar to regular Tower of Hanoi
  - disk are to be ordered by their weight
  - `clear()`, `on()`, `smaller()`, `disk()`
  - `clear()`, `on()`, ~~`smaller()`~~ `lighter()`, `disk()`
- Initial state
 

```
on(Red, Green), on(Green, Blue),
on(Blue, A), clear(Red), disc(Red),
disc(Green), disk(Blue) clear(B),
clear(C), lighter(Red, A),
lighter(Red, B) ...
```

Figure: objects: disks - red, green, blue;  
pegs - A, B, C

- Action
 

```
Action(move(disk, source, destination)
PRECOND: clear(disk) ^ on(disk, source) ^ clear(destination)
^lighter(disk,destination)
EFFECT: on(disk, destination) ^ -on(disk, source) ^
-clear(destination) ^clear(source)
```

# Weighty Tower of Hanoi

---

- Can we do sensorless planning?

# Weighty Tower of Hanoi

---

- Can we do sensorless planning?
- How would the agent do conditional planning?

# Weighty Tower of Hanoi

- Can we do sensorless planning?
- How would the agent do conditional planning?
- Percept Schema

`Percept(lighter(d1,d2)`

`PRECOND: disk(d1) ^ disk(d2) ^ comparing(d1,d2))`

# Weighty Tower of Hanoi

- Can we do sensorless planning?
- How would the agent do conditional planning?

- Percept Schema

`Percept(lighter(d1,d2)`

`PRECOND: disk(d1) ^ disk(d2) ^ comparing(d1,d2))`

- Information-gathering Action

`Action(compare-weight(d1,d2)`

`PRECOND: disk(d1) ^ disk(d2) ^ clear(d1) ^ clear(d2)`

`EFFECT: comparing(d1,d2))`

# Slippery Tower of Hanoi

- Similar to regular Tower of Hanoi
  - `clear()`, `on()`, `smaller()`, `disk()`
  - the gripper is slippery. sometimes the disk is displaced to the destination but at others it remains at the source.




Figure: objects: disks - red, green, blue;  
pegs - A, B, C

# Slippery Tower of Hanoi

- Similar to regular Tower of Hanoi
  - `clear()`, `on()`, `smaller()`, `disk()`
  - the gripper is slippery. sometimes the disk is displaced to the destination but at others it remains at the source.
- Initial state?




Figure: objects: disks - red, green, blue;  
pegs - A, B, C

# Slippery Tower of Hanoi

- Similar to regular Tower of Hanoi
  - `clear()`, `on()`, `smaller()`, `disk()`
  - the gripper is slippery. sometimes the disk is displaced to the destination but at others it remains at the source.
- Initial state?
- Goal State?




Figure: objects: disks - red, green, blue;  
pegs - A, B, C



# Slippery Tower of Hanoi

- Similar to regular Tower of Hanoi
  - `clear()`, `on()`, `smaller()`, `disk()`
  - the gripper is slippery.  
sometimes the disk is displaced to the destination but at others it remains at the source.
- Initial state?
- Goal State?




Figure: objects: disks - red, green, blue;  
pegs - A, B, C

- Action  
`Action(move(disk, source, destination))`  
`PRECOND: clear(disk) ^ on(disk, source) ^ clear(destination)`  
`^smaller(disk,destination)`  
`EFFECT: (on(disk, destination) ^ -on(disk, source) ^`  
`-clear(destination) ^clear(source)) V (on(disk, source))`