

Index

- absorbing sinks
 - surface distribution ρ , 199
 - volume distribution ν , 199
- adhesion tension, 114
- aliphatic, 119
- alkane, 44, 50, 67, 68
- Amott index, 116
- angular momentum, 13–17
- anhydrous manganous sulfate, 141
- API gravity, 45, 47
- apparent T_2 , 58–60
- aromatic, 47, 120
- B*-spline, 188
- baseline offset, 167
- basis function method, 179, 187
- Berea sandstone, 71, 119, 120
- bi-exponential model, 106
- bitumen, 132
- Bloch equation, 21
- Bloch's theorem, 228
- Bloch-Floquet form, 218
- Bohr magneton, 13
- Boltzmann
 - distribution, 18
 - statistics, 17
- Boltzmann's constant, 131
- borehole fluid
 - additive, 6
 - salinity, 9
- borehole signal, 6
- borehole temperature, 133
- boundary condition
 - pore-solid interface, 202
- boundary condition, pore-solid interface, 73
- Bragg planes, 229
- BRD, 184
- Brillouin zone, 229–230
- bulk effective diffusion coefficient, 210, 211
- bulk effective electrical conductivity, 211
- bulk phase
 - oil, 3, 50
 - water, 3, 49
- bulk relaxation
 - crude oils, 51
 - water, 49
- Butler-Reeds-Dawson method, 180
- BVI, 111, 135, 136
- calculus minimum, 183
- capillary curve, 83, 106
- capillary pressure, 84
- carbonates
 - T_2 cutoff, 102
 - T_2 temperature dependence, 76, 88
 - NMR properties, 88
 - permeability plot, 113
 - permeability prediction, 112, 137

- surface relaxivity, 76
 - temperature and pressure effects
 - on $T_{1,2}$, 74
- carrier frequency, 19, 166
- cation-exchange capacity, 90
- chalk, 116
- chelation, 140
- chemical shift anisotropy, 117
- chemical states, 1, 2
- chromium, 72
- chromium lignosulfonate mud, 54
- clastics, 88
- clay, 89, 91, 129, 132
 - flocculation, 141
 - typing, 90
- clay-bound water, 89
- Coates/Timur equation, 111, 135
- coil, *see* tool design
- combustion method, 46
- complex field gradients, 149
- composite-data processing, 192
- constituent diffusion coefficient, 159
- constituent viscosity, 159
- constituent viscosity model, CVM, 158
- contact angle, 114
- copper solenoid, 7
- correctly-posed problem, 176
- CPMG, 23, 26–33, 37, 83, 156, 165, 175
- cross talk, 133
- cumulant calculation
 - numerical examples, 222
- cumulant expansion, 217
- cumulative T_2 distribution, 108
- Curie temperature, 14
- Curie's law, 131
- curvature smoothing, 179, 185
- CVM, constituent viscosity model, 158
- D₂O
 - saturated porous system, 76
 - soak in, 100, 136
- dead oil
 - HI, 44, 47
- dead time, *see* tool design
- decane, 44, 65
- density log, 10
- density of oils, 44
- dephasing, 26, 31, 33, 55, 94, 95, 200, 212
- depth matching, 156, 158
- deuteron relaxation
 - pressure effect, 76
- diagonal matrix, 192
- diamagnetic, 14
- diatomite, 81, 84, 121
- Differential Spectrum Method, 144, 147
- diffraction-like behavior of magnetization, 197
- diffraction-like behavior of PFGSE, 226
- diffusion, 27
 - eigenfunction, 200
 - eigenstate
 - $\rho = 0$, 248
 - $\rho \neq 0$, 250
 - eigenstates, 200, 242
 - eigenvalue, 200
 - fast, *see* fast diffusion
 - in non-uniform fields, 27
 - in porous media, 93
 - restricted, 56, 199
 - slow, *see* slow diffusion

- diffusion coefficient, 28
 - bulk effective, 211
 - gas, 58, 146
 - macroscopic stationary, 210
 - methane, 58, 61
 - methane-decane mixture, 66
 - of water, 78
 - oil, 58, 154
 - time dependent, 212
 - water, 57
- diffusion constant, 61
- diffusion effect, 29, 40, 43, 80, 87
- diffusion of spins, 55
 - porous media, 72
- diffusion propagator, 205, 208–209, 216, 227
- diffusion regime
 - fast, 72, 198, 202, 205
 - intermediate, 72, 205
 - slow, 72, 198, 203, 205
- diffusive motion, 27
 - random walker simulation, 238
- dipole-dipole interaction, 52, 140
- disordered porous medium, 209
- dissolved oxygen, 49, 62
- doping
 - borehole fluid, 49
 - drilling mud, 49
- drilling mud, 44, 52
 - additives, 52
- $D(t)$, short time asymptote, 212
- earth formation, 2
- earth's magnetic field, 4, 6
- echo
 - amplitude, 172
 - phase, 172
- eigenfunction, 200, 201, 218
- eigenvalue, 72, 198, 200, 201, 218
 - diffusion problem, 72
 - low lying, 210, 211
- Einstein relation, 96
- electrical conductivity, 210
 - bulk effective, 211
- electrical membrane measurements, 90
- electron
 - spin angular momentum, 14
- electron spin resonance (ESR), 14
- emulsifier, 54
- energy level, 17
- enhanced T_2 relaxation, 27, 94, 197, 221
- Enhanced Diffusion Analysis, 152
- Enhanced Diffusion Method, 147
- environmental corrections, 130
- fast diffusion, 72–77, 198, 202, 205
- ferrimagnetic, 7
- ferrite, 9
 - manganese-zinc, 7
- ferro-chromium lignosulfonate mud, 54
- ferromagnetic, 14, 49, 130, 155
 - iron or manganese, 49
- FFI, 5, 102, 135
- FGSE, 205
- FID, 22–24, 118, 123–125, 165
- field application, 6
- field gradient, 9
 - pulse, 206
- fixed gradient contribution to $\langle \Phi^2 \rangle$, 220
- fixed gradient spin echo, 205
- flip angles, selection of, 40
- flocculating clays, 141

- folding, 166
- Fontainebleau sandstone, 83
- formation evaluation, 2, 10, 129
- formation factor, 97, 108, 110, 211
- formation fluid, 162
- formation temperature, 7
- Fourier transform, 22, 23, 118, 220
 - of the average diffusion propagator, 226
- Fredholm's equation, 177, 188
- free fluid, 5
- Free Fluid Index, 5, 102
- Free Induction Decay, 22–24
- free precession
 - proton, 4
- gadolinium, 15
- gamma function, 189
- gamma ray, 10
- gas
 - diffusion coefficient, 58, 146
 - dissolved in oil, 132
 - methane, 43, 52
 - saturated, 44
- gas saturation
 - complex field gradients, 149
 - determined by density porosity, 149
 - differential spectrum method, 144
- Gauss, 15
- Gaussian form, 207–208
- Gd⁺⁺, 140
- generalized matrix eigenvalue problem, 249
- geometric mean of T_2 , *see* $T_{2,LM}$
- glass bead, 76
- glauconite, 90
- GOR, 67, 68
 - correction for T_2 vs η , 67, 70
- gyromagnetic ratio, 15, 56, 131, 198, 215
- gyroscope, 15
- H_0 field, inhomogeneity effect, 37
- Hahn's spin echo, 25, 197, 206
- hard pulse, 41
- heavy oil, 132
- heterogeneous field, 23
- hexane, 45, 67
- hexdecane, 67
- HI, 44–48, 132
- Householder transformation, 192
- hydrocarbon typing, 9, 10, 129, 141
- hydrogen
 - atoms, 2, 129
 - density, 3, 131
 - temperature and salinity, 131
 - nuclei, 2, 15, 71, 79, 129
- Hydrogen Index, 44–48
- hydrogen:carbon ratio, 47
- ill-posed, 80, 176–178
- illite, 90
- imbibition of water, spontaneous, 116
- incorrectly-posed problem, 176
- infinite uniform fluid, 201, 207
- inhomogeneous H_0 field, 37
- inhomogeneous field, 6
- inhomogeneous rf field, 36
- initial rate of decay, 204
- inside-out, *see* tool design
- interface absorption, 216
- interfacial tension, 114
- intermediate diffusion, 72, 205
- internal field gradients, 83, 95

- internal gradients, evaluation of, 98
- internuclear dipolar interaction, 117
- intrinsic T_2 , 58–60, 216
- intrinsic relaxation rate, 215
- inverse-Hessian method, 186
- inversion recovery, 23
- inversion symmetry, 228
- iron, 15, 72
- irreducible water estimation
 - T_2 cutoff, 102
 - bi-exponential model, 106
 - spectral representation, 105
- irreducible water saturation, 5, 10, 80, 101, 129, 133
 - factors affecting its estimation, 134
- kaolinite, 90
- kernel, 177
- Kozeny equation, 111
- Langevin type equation, 215
- Larmor frequency, 3, 16, 18, 19, 22, 25, 30, 83, 122, 166, 215
- laser-spin-polarized xenon gas, 212
- lattice, 19
- Levenberg-Marquardt method, 180, 185
- lignosulfonate mud, 54
- linear inversion, 80, 173
- live oil
 - GOR correction of $T_{1,2}$ vs. η , 67
 - HI, 44, 47
- log quality control, 156, 163
- logarithmic mean of T_2
 - definition, 51
- logging guidelines, 161
- long time behavior of $M(t)$, 210
- longitudinal relaxation, 17, 19
- low-pass filter, 166
- macroscopic stationary diffusion coefficient, 210
- Magic Angle Spinning, 100, 117
- magnetic dipole, 52
- magnetic domain, 14
- magnetic field gradient, 27, 55
- magnetic moment, 13, 15, 52, 140
- magnetic resonance fluid characterization, MRF, 158
- magnetic susceptibility, 14, 71, 87, 117, 213
 - diamagnetic, 14
 - paramagnetic, 14
- magnetite, 6
- magnetization, 7, 8, 17–32, 73, 74, 78, 131, 175
 - diffraction-like behavior, 197
- manganese, 15, 72
- MAS, 117
- mean relaxation time, 111, 135
- mercury injection, 81, 84
- methane, 65, 67, 68
 - diffusion coefficient, 61
- microstructural information, 203
- $M(\mathbf{k}, t)$, properties of, 228
- Mn^{++} , 140
- $MnCl_2$, 49
- $MnEDTA$, 49, 50, 139
- monoexponential, 78, 79
- montmorillonite, Ca and Na, 93
- MRF, magnetic resonance fluid characterization, 158
- $M(t)$

- distribution of relaxation rate
 - of, 203
 - long time behavior, 210
 - short time behavior, 209
- mud excluder, 161
- mud filtrate, 52
- mud filtrate, invaded, 162
- multiexponential
 - behavior, 74
 - decay, 72
- Na₄EDTA, 141
- neutron log, 10
- nickel, 72
- NML, 3, 6, 139
- NMR
 - behaviors of different rocks, 87
 - core imaging, 122
 - log interpretation
 - differentiate oil and water, 29, 58
 - logging, 1, 29, 49
 - quadrature detection, 166
 - logging technology
 - modern day, 3
 - logging tool, 1, 3, 29, 129, 139
 - properties
 - carbonates, 88
 - clastics, 88
 - clay, 89
 - porous media, 2
 - pulsed NMR logging, 1, 10
 - relaxation
 - brine in rocks, 43
 - porous media, 1
 - spectroscopy, 1, 2
 - technology, 3
- noise channel, 173
- non-calculus minimum, 181
- non-Gaussian distribution, 217
- non-linear inversion, 173
- non-negativity, 186, 196
- nonlinear fit, 80, 155
- norm smoothing, 179, 180
- nuclear magnetic relaxation, 2
 - porous media, 71
- nuclear magnetic resonance, 1
- Nuclear Magnetism Logging, 3
- nuclear moment, 17
- nuclear polarization, 17
- OBM, 54
- OBMF, 160
- occupation number, 17
- oil
 - dead, 44
 - diffusion coefficient, 58, 154
 - live, 44
 - non-wetting phase, 50
- oil based mud, 54, 136
 - filtrate, 160
- oil exploration, 2
- oil saturation
 - complex field gradients, 150
 - differential spectrum method, 144
- oil viscosity, 10, 61
 - determination, 156
 - estimation, 129, 142, 153, 155
- oil wet, 134
- opal CT, 81
- opposing magnets, *see* tool design
- orthogonal matrix, 192
- orthogonal transformation, 194
- pad-type, *see* tool design
- PAPs, 167

- paramagnetic, 14, 49, 130, 155
 - impurity, 72, 78
 - relaxation rate in solution of, 140
- periodic microstructures, 217
- periodic porous media, 227
 - simple cubic arrays of solid spheres, 212
- permeability, 2
 - prediction, 10, 129, 134
 - for carbonates, 112
- permeability predictor
 - $T_{2,LM}$ equation, 108
 - carbonates, 137
 - Coates/Timur equation, 111
 - summation of echoes, 111, 135
 - table of, 109
- petroleum exploration, 1
- petrophysical properties, 2
- PFGSE, 34, 65, 159, 205–209, 216, 223
 - diffraction-like behavior, 226
 - its applications, 223
- PFGSE amplitude, 242
- Phase Alternate Pairs, PAPs, 167
- phase angle, 172
- phase rotation, 167
- phase sensitive detector, 166
- phase shift, produced by δH , 97, 215
- Planck constant, 131
- polar coordinates, 172
- polarization
 - factor, 132, 142, 150, 157, 175
 - nuclear, 17
 - time, 131
- polarization recovery
 - complete, 87
- incomplete, 132
- polyaromatic, 47
- poorly consolidated clastics, 134
- pore fabric, 1
- pore size distribution, 1, 78, 81
- pore space
 - geometry, 73
 - size and shape, 72, 205
 - surface to volume ratio, 2, 5, 77, 202
 - circular cylinder, 203
 - parallel slab, 203
 - sphere, 203
 - topology, 203
- pore-matrix interface, 71
- porosity, 43
 - density and neutron, 10
 - mineralogy independent, 10, 129, 130
 - NMR, 100, 129
 - total, 3
 - underestimation, 132
- positive definite, 249
- positive semi-definite, 249
- precession of spins, 15, 22
- pressure effect on $T_{1,2}$, 74
- principal coordinates, 193
- principal axes, 193
- proton
 - gyromagnetic ratio, 15
 - relaxation
 - pressure effect, 76
- pseudo inverse, 196
- pulse
 - hard, 41
 - selection of, 40
 - soft, 41

- pulse field gradient spin echo, 33, 205
- pulse sequence
 - CPMG, 27, 29
- pulsed field gradient spin echo, 65, 159
- pulsed NMR, 10
- Q factor, 7
- Q of rf coil, salinity effect, 101, 131
- quadrature channels, 168–171
- quadrature detection, 165
- Quality Factor, Q, 161
- quantized energy level, 17
- quantum mechanical, 11, 13
- quantum phenomena, 11
- radio frequency, 7, 19
- random walk simulation, 88
- random walker simulation, 238
 - mimicking interface absorption, 240
- RD, *see* Repeat Delay
- refocusing, 56, 94, 200
- regularizable, 179
- regularization, 148, 157, 176
 - definition, 179
- regularization parameter, 179
 - optimum value, 183
- relaxation
 - enhancement
 - due to diffusion, 27, 43
- relaxation process, 11
- relaxation rate, 51, 52
 - solution of paramagnetic ions, 140
- relaxation time, 3
 - bulk fluids, 4
 - dependence on
 - pressure, 4
 - temperature, 4
 - distribution, 50, 78, 80
 - longitudinal, 17, 19
 - oil, 3
 - porous media, 4
 - spin-lattice, 19
 - spin-spin, 21
 - transverse, 21
 - water, 3
- renormalized RTOP, 234
- repeat delay time
 - multiple, 142, 154
- Repeat Delay, RD, 27, 132, 142, 162, 175
- Repeat Time, TR, 27, 162
- rephasing, 33
- reservoir fluid, 44
- residual oil determination, 49, 139
- residual oil estimation, 10, 129
- restricted diffusion, 56, 95, 96
 - long time behavior, 97
 - short time behavior, 96
- restricted diffusion coefficient, 83
- restricted geometries, 200, 202, 208
 - random walker simulation, 239
- return to the origin probability, RTOP, 231
- rf coil, 7, 8, 19, 101, 131
- rf field, inhomogeneity effect, 36
- rf pulse, 7
- rf radiation, 206
- ringing, 167
- root mean square distance, 239
- rotating frame, 20, 30, 119
- rotor frequency, 118

- RTOP, *see* return to the origin probability
- RTOP, comparison with $D(t)$, 235
- sandstones
- T_2 cutoff, 102
 - NMR properties, 88
 - permeability prediction, 108
 - surface relaxivity, 85
 - temperature and pressure effects on $T_{1,2}$, 74
- saturating fluids, 43
- saturation recovery, 24
- SBVI, 106
- self diffusion coefficient, 28, 56
- Shift Spectrum Method, 147
- short time asymptote for $D(t)$, 212
- short time asymptotics of the diffusion propagator, 255
- short time behavior of $M(t)$, 209
- signal channel, 173
- signal to noise
- ratio, 100, 161, 183
- signal to noise ratio, 7, 27, 41
- sinc function, 41
- single detection, 165
- singular value decomposition, 178, 189, 192
- Singular Value Decomposition, SVD, 179
- singular values, 192–196
- slope smoothing, 179
- slow diffusion, 72–77, 198, 203, 205
- smectite, 90
- smoothing
- curvature, *see* curvature smoothing
 - norm, *see* norm smoothing
 - slope, *see* slope smoothing
- smoothing parameter, 179
- soft pulse, 41
- solenoid, 7
- spectral representation, 105
- spin
- angular momentum, 14, 15
 - precession, 15, 22
- spin angular momentum, 11
- spin dynamics, 38
- spin echo, 25–27, 33
- described by spin operator, 215
 - restricted geometry, 97
 - spacing, 47
- spin echo train, 27
- spin exchange interaction, 140
- spin quantum number, 131
- spin-lattice relaxation, 19
- spin-rotation, 52
- spin-spin relaxation, 21
- spinning sidebands, 118
- spontaneous imbibition, 116
- stationary measurement, 163
- steepest descent, 186
- stimulated echo, 34
- stock tank oil, 67
- stretched exponential model, 80
- summation of echoes, 111, 135, 155
- surface absorption, 198
- surface effects, 3
- surface relaxation, 43, 49, 71, 87
- mechanism, 71
 - of oil, 75
 - of water, 75
- surface relaxation strength, 73
- surface relaxivity, 2, 73, 81
- clastics, 88
 - independent of temperature, 75

- of porous materials, 85
 - surface to volume ratio, 2, 5, 202
 - surfactant, 54
 - susceptibility difference contribution to $\langle \Phi^2 \rangle$, 218
- SVD, *see* singular value decomposition
- T_1 , 13, 19, 21, 23, 24, 45
 - bulk water, 49
 - clay, 90
 - correlation of
 - diffusion coefficient, 61
 - viscosity, 61
 - crude oils, 51
 - distribution, 75, 76
 - methane, 52
 - temperature and pressure effects, 74
- T_1/T_2 ratio, 83, 132
- T_2 , 13, 21, 23, 25, 45
 - apparent, 58–60
 - bitumen, 132
 - clay, 90, 132
 - correlation of
 - diffusion coefficient, 61
 - viscosity, 61
 - crude oils, 51
 - cutoff, 80, 102
 - carbonate, 104, 133
 - sandstone, 104, 133
 - vuggy pores, 139
 - dependence
 - MnCl₂, 49
 - MnEDTA, 49
 - heavy oil, 132
 - in magnetic field gradient, 55
 - intrinsic, 58–60
 - logarithmic mean, 53, 84
 - OBM filtrate, 55
 - of carbonates, temperature dependence, 76, 88
 - relaxation mechanisms, 87
 - temperature and pressure effects, 74
 - viscosity
 - deviation from linear relationship, 67, 70
- T_2^* , 13, 26
- T_{2B} , 56, 94
- T_{2D} , 56, 94, 147, 151
- T_{2G} , *see* $T_{2,LM}$
- $T_{2,LM}$, 63
 - definition, 51
 - versus viscosity, 158
- $T_{2,LM}$ equation, permeability estimator, 108, 135
- T_{2S} , 94
- TE effect
 - on relaxation rate, 145
 - on viscosity, $T_{2,LM}$, 63
- TE, time between echoes, 56
- temperature effect on $T_{1,2}$, 74
- TEs, multiple, 154
- Tesla, 15
- thermal equilibrium, 17, 19
- thermal motion, 19
- thermally-spin-polarized xenon gas, 212
- thief zone, 10
- three-exponential model, 79
- time dependent diffusion coefficient, 212, 253
- time domain analysis, 144, 154
- tool calibration, 130
- tool characteristics, 161

- tool design
 - coil, 4, 6
 - copper solenoid, 7
 - dead time, 5
 - inside-out, 6
 - opposing magnets, 6
 - pad-type, 9
 - toroidal region, 6
- tool repeatability, 163
- topology, 203
- toroidal region, *see* tool design
- torque, 15
- Torrey's equation, 30, 217
- TR, *see* Repeat Time
- transverse relaxation, 19, 21
- two-exponential model, 79
- uncertainty of solution
 - in SVD inversion, 196
- uniform gradient, 29
- uniform penalty method, 179, 186
- variable echo spacing, 144
- variable RD, 141
- variable TE, 141
- Versene 100 liquid, 141
- viscosity
 - of oil, 46, 51, 53, 61
- viscosity correlation
 - T_1 , 62
 - T_2 , 62
- Wait Time, WT, 27, 132, 162, 175
- water, 43
 - bulk relaxation, 49
 - capillary-bound, 133
 - clay-bound, 133
 - diffusion coefficient, 57
 - irreducible, 5
 - salinity, 43
 - water based mud, 52, 135
 - water cut, 133
 - water wet, 115, 116, 120
 - well bore temperature, 133
 - wettability, 113
 - oil wet, 115, 116, 134
 - water wet, 115, 116, 120
 - wettability index, 116
- WT, *see* Wait Time
- X-ray CAT scan, 122
- xenon gas
 - laser-spin-polarized, 212
 - thermally-spin-polarized, 212