

Sertavance Film-Coated Tablets

Module 3 Quality Documentation — Formulation F-812/B

Regional Information

No excipients of human or animal origin are used in the drug product with the exception of lactose monohydrate, for which a TSE/BSE compliance declaration is provided in Module 3.2.A.2. Certificates of suitability are maintained where applicable.

Data supporting these conclusions are maintained at the manufacturing site and are available for inspection. Comparability of pilot- and commercial-scale batches was demonstrated with respect to dissolution and impurity profiles. Analytical results are trended electronically, and out-of-trend results trigger a documented laboratory investigation. Supplier qualification includes periodic audits, review of certificates of analysis, and trending of incoming material test results. Annual product quality reviews evaluate batch trends, deviations, complaints, and stability data to confirm the continued state of control.

Reference Standards

Primary reference standards for the drug substance and specified impurities are qualified against compendial standards where available. Working standards are qualified against the primary standard under an approved protocol and are stored under controlled conditions.

Supplier qualification includes periodic audits, review of certificates of analysis, and trending of incoming material test results. Training records for personnel involved in manufacturing and testing are maintained under the site quality system. Deviations observed during the campaign were investigated and closed with no impact to product quality. Comparability of pilot- and commercial-scale batches was demonstrated with respect to dissolution and impurity profiles. Environmental monitoring of the manufacturing areas is performed per the site monitoring program, with alert and action limits established from historical data.

Control of Drug Product

The drug product specification includes tests for description, identification, assay, uniformity of dosage units, dissolution, related substances, water content, and microbial limits. Analytical procedures are compendial where available; non-compendial procedures were validated in accordance with ICH Q2(R1).

The control strategy links critical quality attributes to critical process parameters identified during development. Training records for personnel involved in manufacturing and testing are maintained under the site quality system. Risk assessments were performed in accordance with ICH Q9 principles, and residual risks were judged acceptable. Change control procedures ensure that any modification to materials, methods, or equipment is assessed for regulatory impact prior to implementation.

Hold-time studies established acceptable storage durations for intermediate blends and cores under defined conditions. Data supporting these conclusions are maintained at the manufacturing site and are available for inspection. Environmental monitoring of the manufacturing areas is performed per the site monitoring program, with alert and action limits established from historical data. No changes to the approved analytical procedures are proposed in this submission. Comparability of

pilot- and commercial-scale batches was demonstrated with respect to dissolution and impurity profiles.

Control of Excipients (3.2.P.4)

Early clinical formulations F-01 through F-03 employed Kollidon CL. For the commercial formulation F-812/B, Polyplasdone XL-10 (Crospovidone, disintegrant) is used.

Grade selection and control follow the principles of ICH Q6A.

Selection Justification

Polyplasdone XL-10 was selected as the commercial grade of crospovidone on the basis of reduced lot-to-lot variability reported by the qualified supplier.

Approved Drug Product Specification

Component	Function	Grade per current specification
Crospovidone	disintegrant	Polyplasdone XL-10
Reference		SPEC-EX-4902 Rev 04

Note: the superseded specification (pre-2019, withdrawn) listed Kollidon CL; it is retained here for historical traceability only and has no bearing on the current control strategy.

Batch Formula

The representative commercial batch formula is provided for a nominal batch size of 400,000 tablets. Quantities of all components are expressed per tablet and per batch. Purified water is used as granulation fluid and is removed during processing; it does not appear in the final composition.

Annual product quality reviews evaluate batch trends, deviations, complaints, and stability data to confirm the continued state of control. Deviations observed during the campaign were investigated and closed with no impact to product quality. Change control procedures ensure that any modification to materials, methods, or equipment is assessed for regulatory impact prior to implementation. Risk assessments were performed in accordance with ICH Q9 principles, and residual risks were judged acceptable. Environmental monitoring of the manufacturing areas is performed per the site monitoring program, with alert and action limits established from historical data. Training records for personnel involved in manufacturing and testing are maintained under the site quality system.

Stability Summary

Primary stability studies were conducted under ICH long-term (25°C/60% RH) and accelerated (40°C/75% RH) conditions on three registration batches. All quality attributes remained within acceptance criteria through the tested intervals. Photostability testing per ICH Q1B confirmed that the product is not photolabile in the commercial pack.

Hold-time studies established acceptable storage durations for intermediate blends and cores under defined conditions. Analytical results are trended electronically, and out-of-trend results trigger a documented laboratory investigation. Cleaning verification swab results were below the health-based exposure limits derived for the product. Statistical evaluation of batch release data demonstrates process capability well within specification limits. Training records for personnel involved in manufacturing and testing are maintained under the site quality system.

Supplier qualification includes periodic audits, review of certificates of analysis, and trending of incoming material test results. Training records for personnel involved in manufacturing and testing are maintained under the site quality system. Statistical evaluation of batch release data demonstrates process capability well within specification limits. Deviations observed during the campaign were investigated and closed with no impact to product quality.

Process Validation Summary

Process performance qualification was executed on three consecutive commercial-scale batches. All predefined acceptance criteria for critical process parameters and critical quality attributes were met, supporting a conclusion of a validated state of control.

The finished product is stored and distributed under controlled ambient conditions consistent with the approved label storage statement. Supplier qualification includes periodic audits, review of certificates of analysis, and trending of incoming material test results. Data supporting these conclusions are maintained at the manufacturing site and are available for inspection. Annual product quality reviews evaluate batch trends, deviations, complaints, and stability data to confirm the continued state of control. Training records for personnel involved in manufacturing and testing are maintained under the site quality system. Cleaning verification swab results were below the health-based exposure limits derived for the product.

Analytical Method Validation Summary

The assay and related-substances procedures employ reversed-phase high performance liquid chromatography with ultraviolet detection. Validation demonstrated acceptable specificity, linearity, accuracy, precision, and robustness. Forced degradation studies confirmed the stability-indicating capability of the related-substances method.

Analytical results are trended electronically, and out-of-trend results trigger a documented laboratory investigation. Supplier qualification includes periodic audits, review of certificates of analysis, and trending of incoming material test results. Environmental monitoring of the manufacturing areas is performed per the site monitoring program, with alert and action limits established from historical data. Annual product quality reviews evaluate batch trends, deviations, complaints, and stability data to confirm the continued state of control.