

Dintravel — Post-Approval Stability Protocol

Protocol STAB-P-2023-63

Container Closure and Orientation

Samples are stored in the commercial container closure system. Bottles are stored upright; a subset of inverted samples is included at the initial and final timepoints to assess closure-liner interaction. Induction seal integrity is verified at each pull.

Sample Inventory and Pull Windows

Sample inventory per condition and timepoint is defined in the pull schedule appendix. Scheduled pulls are performed within ± 7 days of the nominal date; pull records are maintained in the site stability management system.

Study Storage Conditions

The primary (intermediate/zone IVa condition) storage condition for this protocol is $30^{\circ}\text{C} \pm 2^{\circ}\text{C}$ / 65% RH $\pm 5\%$ RH. Accelerated studies at $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ / 75% RH $\pm 5\%$ RH were completed through six months during development and are not part of this protocol.

Testing Schedule

Long-term samples are tested at 0, 3, 6, 9, 12, 18, 24 and 36 months.

Acceptance Criteria

The stability acceptance criterion applied at each interval is — Total degradation products: not more than 2.0%. All other registered specification tests apply unchanged.

Bracketing and Matrixing

A bracketing design per ICH Q1D tests the extremes of the strength range (5 mg and 50 mg); the 10 mg strength shares identical formulation composition and packaging and is therefore not tested.

Sample Inventory and Pull Windows

Sample inventory per condition and timepoint is defined in the pull schedule appendix. Scheduled pulls are performed within ± 7 days of the nominal date; pull records are maintained in the site stability management system.

Analytical Procedures

Assay and degradation products are determined by the stability-indicating reversed-phase HPLC procedure described in the analytical methods dossier. Dissolution testing uses USP Apparatus II at 50 rpm. All procedures were validated in accordance with ICH Q2(R1) prior to protocol initiation.

Stability Commitments

As a condition of approval, three consecutive production batches of Dintravel will be entered into the stability program, and the retest period will be re-evaluated after 36-month data are available.

Protocol Deviations

The 24-month timepoint for batch 001 was tested 11 days outside the ± 7 -day protocol window; a quality assessment concluded no impact on data validity.

Batch Selection

The protocol covers three primary batches manufactured at commercial scale using the approved process. Batch genealogy, manufacturing dates, and packaging lots are recorded in the batch appendix. All batches were released against the approved specification prior to set-down.

Photostability

Confirmatory photostability testing per ICH Q1B was completed during development and is not repeated in this protocol. The product is labeled for storage in the original container to protect from light.

Analytical Procedures

Assay and degradation products are determined by the stability-indicating reversed-phase HPLC procedure described in the analytical methods dossier. Dissolution testing uses USP Apparatus II at 50 rpm. All procedures were validated in accordance with ICH Q2(R1) prior to protocol initiation.