

Jantreva — Post-Approval Stability Protocol

Protocol STAB-P-2023-44

Batch Selection

The protocol covers three primary batches manufactured at commercial scale using the approved process. Batch genealogy, manufacturing dates, and packaging lots are recorded in the batch appendix. All batches were released against the approved specification prior to set-down.

Storage Conditions

The primary (zone IVb condition) storage condition for this protocol is $30^{\circ}\text{C} \pm 2^{\circ}\text{C}$ / $75\% \text{ RH} \pm 5\% \text{ RH}$. Accelerated studies at $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ / $75\% \text{ RH} \pm 5\% \text{ RH}$ were completed through six months during development and are not part of this protocol.

Timepoints

Interval (months)	0	1	3	6	9	12	18
Long-term testing	X	X	X	X	X	X	X

Bracketing Justification

A bracketing design per ICH Q1D tests the extremes of the strength range (10 mg and 25 mg); the 20 mg strength shares identical formulation composition and packaging and is therefore not tested.

Stability Acceptance Criteria

The stability acceptance criterion applied at each interval is — Dissolution: $Q = 80\%$ in 30 minutes. All other registered specification tests apply unchanged.

Protocol Deviations

The 3-month timepoint for batch 001 was tested 19 days outside the ± 7 -day protocol window; a quality assessment concluded no impact on data validity.

Stability Commitments

The first three commercial-scale batches of Jantreva will be placed on the long-term stability program, with at least one production batch added annually thereafter.

Batch Selection

The protocol covers three primary batches manufactured at commercial scale using the approved process. Batch genealogy, manufacturing dates, and packaging lots are recorded in the batch appendix. All batches were released against the approved specification prior to set-down.

Sample Inventory and Pull Windows

Sample inventory per condition and timepoint is defined in the pull schedule appendix. Scheduled pulls are performed within ± 7 days of the nominal date; pull records are maintained in the site stability management system.