

Rimvastex — Stability Protocol

Protocol STAB-P-2025-56

Analytical Procedures

Assay and degradation products are determined by the stability-indicating reversed-phase HPLC procedure described in the analytical methods dossier. Dissolution testing uses USP Apparatus II at 50 rpm. All procedures were validated in accordance with ICH Q2(R1) prior to protocol initiation.

Container Closure and Orientation

Samples are stored in the commercial container closure system. Bottles are stored upright; a subset of inverted samples is included at the initial and final timepoints to assess closure-liner interaction. Induction seal integrity is verified at each pull.

Storage Conditions

The primary (refrigerated condition) storage condition for this protocol is $5^{\circ}\text{C} \pm 3^{\circ}\text{C}$. Accelerated studies at $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ / 75% RH $\pm$ 5% RH were completed through six months during development and are not part of this protocol.

Testing Schedule

Long-term samples are tested at 0, 3, 6, 12, 18, 24, 36 and 48 months.

Stability Commitments

The first three commercial-scale batches of Rimvastex will be placed on the long-term stability program, with at least one production batch added annually thereafter.

Bracketing Justification

In accordance with ICH Q1D, bracketing is applied: the 5 mg and 50 mg strengths are tested, and the intermediate 25 mg strength is covered because all strengths are direct scale-equivalents of a common blend in the same container closure system.

Stability Acceptance Criteria

The stability acceptance criterion applied at each interval is — Assay: 95.0–105.0% of label claim. All other registered specification tests apply unchanged.

Deviations

The 24-month timepoint for batch 001 was tested 17 days outside the ± 7 -day protocol window; a quality assessment concluded no impact on data validity.

Data Evaluation and Reporting

Stability data are evaluated per ICH Q1E. Regression analysis is applied to quantitative attributes exhibiting change over time; poolability across batches is assessed at the 0.25 significance level. Annual reports summarize all data generated in the reporting interval.

Analytical Procedures

Assay and degradation products are determined by the stability-indicating reversed-phase HPLC procedure described in the analytical methods dossier. Dissolution testing uses USP Apparatus II at 50 rpm. All procedures were validated in accordance with ICH Q2(R1) prior to protocol initiation.

Photostability

Confirmatory photostability testing per ICH Q1B was completed during development and is not repeated in this protocol. The product is labeled for storage in the original container to protect from light.

Container Closure and Orientation

Samples are stored in the commercial container closure system. Bottles are stored upright; a subset of inverted samples is included at the initial and final timepoints to assess closure-liner interaction. Induction seal integrity is verified at each pull.