

The diagram shows a 5V LED driver circuit. A 12V input (J2 VIN) is connected to a 1k resistor (R3) and a diode (D2). The other end of R3 is connected to the +12V input of the AMS1117-5.0 voltage regulator (U2). The regulator's GND pin is connected to the common ground. The +5V output of the regulator is connected to a 5V LED (D4) and a 1k resistor (R4). The other end of R4 is connected to the common ground. A 22uF capacitor (C3) is connected across the +5V output and ground. A second 5V LED (D3) is connected between the +12V input and ground.

The diagram shows a 555 timer (U1, LM555xN) configured as a monostable multivibrator. The circuit components and their connections are as follows:

- Power Supply:** A +5V supply is connected to the VCC pin (pin 4) and the GND pin (pin 1).
- Timing Network:** A 1M resistor (R1) and a 22nF capacitor (C2) are connected to the TRIG pin (pin 2). The TRIG pin is also connected to the THRES pin (pin 6).
- Control Network:** A 1N4148 diode (D1) is connected between the DISCH pin (pin 5) and the TRIG/THRES pins. A 22k resistor (R2) is connected between the DISCH pin and the GND pin.
- Output:** The output of the timer is taken from the OUT pin (pin 3), which is labeled 'SIGNAL'.
- Other Components:** A 100k resistor (RV1) is connected between the +5V supply and the TRIG pin. A 22nF capacitor (C2) is connected between the TRIG pin and the GND pin.

The diagram shows two vertical connections. On the left, a green line with red diamond-shaped terminals at both ends connects the label 'PWR_FLAG' at the top to 'GND' at the bottom. On the right, a green line with red diamond-shaped terminals at both ends connects the label '+12V' at the top to 'PWR_FLAG' at the bottom.

Rev: 1
Id: 1/1