

Infrastructure as a Code

Question:

Explain the concept of Infrastructure as Code (IaC) and how Terraform fits into this paradigm.

Infrastructure as a Code

Managing and provisioning infrastructure using code or config files

Terraform embodies the principles of Infrastructure as Code

HashiCorp Configuration Language(HCL)

Defining resources in configuration files

Creates, Updates, or Deletes resources to align with the desired state

Infrastructure as a Code

Benefits to the organization:

- Consistency, Repeatability and Scalability
- Version Control the infrastructure code
- Enable Collaboration
- Easy Rollback to previous state
- Automation
- Avoid Human Error

Infrastructure as a Code

Define resources like:

- AWS EC2 Instance
- RDS Database
- Security Group
- Instance Type
- Database Engine
- Ingress/Egress Rules

```
terraform apply
```

Infrastructure as a Code

Question:

What are the advantages of using Terraform for infrastructure provisioning compared to other tools?

Infrastructure as a Code

- Declarative Syntax
- Multi Cloud Support
- Consistency and Reproducibility
- Version controlled
- Team Collaboration
- State Management
- Plan and Apply Workflow

Infrastructure as a Code

Question:

Explain the difference between Terraform's apply, plan, and destroy commands?

Infrastructure as a Code

terraform plan

Purpose:

Preview the changes

Functionality:

Analyzes terraform configuration files

Compares with current state of infrastructure

Execution plan

Displays changes to be made

Infrastructure as a Code

terraform apply

Purpose:

Execute the planned changes

Functionality:

Implements the plan generated by terraform plan

Interacts with providers

Prompts to confirm proposed changes

Infrastructure as a Code

terraform destroy

Purpose:

Remove all terraform managed resources

Functionality:

Analyzes terraform state file

Initiates destruction of resources

Prompts for confirmation before deleting


Infrastructure as a Code

Question:

How does Terraform manage and handle dependencies between resources?

Infrastructure as a Code

Dependency Graph



Determines the correct order
Follows the right sequence

Infrastructure as a Code

Terraform config with a dependency

`depends_on`

With changes, dependency graph is auto updated

Evaluates changes and adjusts provisioning plan

Infrastructure as a Code

Terraform config with a dependency

```
# Define a VPC
resource "aws_vpc" "example_vpc" {
  cidr_block = "10.0.0.0/16"
  # Other VPC configurations
  # ...
}

# Define a security group within the VPC
resource "aws_security_group" "example_security_group" {
  vpc_id = aws_vpc.example_vpc.id
  # Other security group configurations
  # ...
}

# Create an EC2 instance requiring the security group
resource "aws_instance" "example_instance" {
  ami           = "ami-xxxxxxx"
  instance_type = "t2.micro"
  subnet_id     = aws_subnet.example_subnet.id
  security_group_ids = [aws_security_group.example_security_group.id]
  # Other instance configurations
  # ...

  # Explicitly define the dependency on the security group
  depends_on = [aws_security_group.example_security_group]
}
```

aws_vpc resource creates a VPC

aws_security_group resource creates a security group

aws_instance resource defines an EC2 instance

depends_on attribute explicitly declares a dependency

Infrastructure as a Code

Question:

How does Terraform handle secrets or sensitive data in its configurations?

Infrastructure as a Code

Sensitive Input Variables

Prevents values from being displayed in logs, outputs, or state file

```
variable "password" {  
  type      = string  
  sensitive = true  
}
```


Infrastructure as a Code

Secret Management Providers

HashiCorp Vault

AWS Secrets Manager

Azure Key Vault

```
data "vault_generic_secret" "example" {  
  path = "secret/data/example"  
}
```

Infrastructure as a Code

Secure File Handling

Passwords Stored in Files

```
resource "aws_instance" "example" {  
  // Other configurations  
  private_key = file("${path.module}/private_key.pem")  
}
```

Infrastructure as a Code

Question:

Describe the difference between Terraform's `null_resource` and `resource` blocks?

Infrastructure as a Code

Resource Blocks

Is used to define and manage resources offered by infrastructure providers

```
resource "aws_instance" "example" {  
    ami           = "ami-0c55b159cbfafa1f0"  
    instance_type = "t2.micro"  
}
```

Infrastructure as a Code

Null Resource Blocks

Allows you to perform arbitrary actions or execute local provisioners

```
null_resource "example" {  
  provisioner "local-exec" {  
    command = "echo Hello, Terraform"  
  }  
}
```

Infrastructure as a Code

Use Case of a `null_resource`

Used for additional post creation tasks

```
resource "aws_s3_bucket" "example_bucket" {
  bucket = "my-unique-bucket-name"
  acl    = "private"
}

null_resource "post_creation_tasks" {
  depends_on = [aws_s3_bucket.example_bucket]

  triggers = {
    bucket_arn = aws_s3_bucket.example_bucket.arn
  }

  provisioner "local-exec" {
    command = "echo Performing post-creation tasks for bucket ${aws_s3_bucket.example_bucket.bucket}"
  }
}
```

Infrastructure as a Code

resource	null_resource
Directly manage infrastructure	Do not create or manage infrastructure
Interacts with Infra API	Execute local actions or provisioners
Has explicit and implicit dependencies	Can act as dependency but doesn't depend on external sources
Tracked by Terraform's state, managed as real resources	Tracked by Terraform's state, represent local actions

Infrastructure as a Code

Question:

Explain the benefits of using Terraform with cloud-agnostic resources and providers?

Infrastructure as a Code

Cloud Agnostic

Independent of any specific cloud provider or platform

Infrastructure as a Code

Key Attributes:

- Independence from Vendor Specific services
- Compatibility Across Cloud Providers
- Flexibility and Portability
- Reduced Vendor Lock-In

Infrastructure as a Code

Non-Cloud-Agnostic Approach

An application might directly utilize AWS S3 for storing data, utilizing specific AWS SDKs and APIs.

Infrastructure as a Code

Cloud-Agnostic Approach

Instead of directly interacting with AWS S3, the application could use generic storage API that can be implemented using different cloud storage services

Infrastructure as a Code

```
# AWS Provider Configuration
provider "aws" {
  region = "us-west-2" # Specify your desired AWS region
  # AWS-specific authentication and settings...
}

# Google Cloud Provider Configuration
provider "google" {
  project = "your-project-id" # Specify your GCP project ID
  region  = "us-central1"     # Specify your desired GCP region
  # GCP-specific authentication and settings...
}

# Azure Provider Configuration
provider "azurerm" {
  features {}
  subscription_id = "your-subscription-id" # Specify your Azure subscription ID
  tenant_id       = "your-tenant-id"      # Specify your Azure tenant ID
  # Azure-specific authentication and settings...
}
```

Infrastructure as a Code

Question:

Explain the Importance of Remote State in Terraform.
How would you configure and manage remote state for a Terraform project?

Infrastructure as a Code

Remote state in Terraform refers to storing the state file, which contains information about the deployed infrastructure's current state, in a centralized and shared location.

Infrastructure as a Code

Benefits of Remote state

- Concurrency and Collaboration
- State Locking
- Security and Access Control
- Disaster Recovery
- Version Control

Infrastructure as a Code

Configuring a Remote State

- Choose a Backend
- Backend Configuration

```
terraform {  
  backend "s3" {  
    bucket      = "your-bucket-name"  
    key         = "path/to/your/statefile.tfstate"  
    region      = "your-aws-region"  
    dynamodb_table = "your-dynamodb-table-name"  
  }  
}
```

Infrastructure as a Code

State Management

- Access Control and Encryption
- Regular Backups
- Locking Mechanism

Infrastructure as a Code

Question:

Imagine a scenario where you need to dynamically create a variable number of AWS EC2 instances based on user input. How would you achieve this using Terraform?

Infrastructure as a Code

- Dynamic Resources
- Input Variables

Infrastructure as a Code

- Input Variables

```
variable "instance_count" {  
  description = "Number of EC2 instances to create"  
  type        = number  
}
```

Infrastructure as a Code

- Dynamic Resource definition

```
resource "aws_instance" "ec2_instance" {  
  count = var.instance_count  
  
  ami          = "ami-xxxxxxx" # Replace with the desired AMI ID  
  instance_type = "t2.micro"    # Replace with the desired instance type  
  
  # Other configuration options for the EC2 instances  
  # ...  
}
```

Infrastructure as a Code

Advantages

- Flexibility and Scaling
- Consistent Configuration
- Dynamic Indexing
- User Interaction

Infrastructure as a Code

Question:

How can Terraform be utilized to achieve a zero-downtime deployment strategy for a web application running on AWS? What resources and techniques would you employ?

Infrastructure as a Code

Web Application Setup

- AWS Load Balancer
- Auto Scaling Group
- Route 53

Infrastructure as a Code

Step 1: Terraform Initialization and Backend Configuration

```
terraform {  
  backend "s3" {  
    bucket = "your-bucket-name"  
    key    = "path/to/your/statefile.tfstate"  
    region = "your-aws-region"  
  }  
}
```

Infrastructure as a Code

Step 2: Resource Definition

Step 2.1: Load Balancer and Listener Configuration

```
resource "aws_lb" "my_load_balancer" {  
  name           = "my-alb"  
  internal       = false  
  load_balancer_type = "application"  
  # Other load balancer configurations  
  # ...  
}  
  
resource "aws_lb_listener" "my_listener" {  
  load_balancer_arn = aws_lb.my_load_balancer.arn  
  port              = 80  
  protocol          = "HTTP"  
  # Other listener configurations  
  # ...  
}
```

Infrastructure as a Code

Step 2: Resource Definition

Step 2.2: Auto Scaling Group and EC2 instances

```
resource "aws_launch_configuration" "my_launch_config" {
  name_prefix      = "my-launch-config-"
  # Instance configurations
  # ...
}

resource "aws_autoscaling_group" "my_auto_scaling_group" {
  launch_configuration = aws_launch_configuration.my_launch_config.id
  desired_capacity     = var.instance_count
  min_size             = 1
  max_size             = 5
  vpc_zone_identifier  = [var.subnet_ids]
  # Other ASG configurations
  # ...
}
```

Infrastructure as a Code

Step 3: Traffic Routing

```
resource "aws_launch_configuration" "my_launch_config" {
  name_prefix      = "my-launch-config-"
  # Instance configurations
  # ...
}

resource "aws_autoscaling_group" "my_auto_scaling_group" {
  launch_configuration = aws_launch_configuration.my_launch_config.id
  desired_capacity     = var.instance_count
  min_size            = 1
  max_size            = 5
  vpc_zone_identifier = [var.subnet_ids]
  # Other ASG configurations
  # ...
}
```