

Discrete Structures

Dr. Syed Faisal Bukhari

Associate Professor

Department of Data Science, Faculty of Computing and Information
Technology, University of the Punjab

Text book

Discrete Mathematics and Its Application, 7th Edition
Kenneth H. Rosen

References

Chapter 1

1. Discrete Mathematics and Its Application, 7th Edition

by

Kenneth H. Rose

2. Discrete Mathematics with Applications

by

Thomas Koshy

Predicates and Quantifiers

- ❑ **Propositional logic**, cannot adequately express the meaning of statements in mathematics and in natural language. For example, suppose that we know that
“Every computer connected to the university network is functioning properly.”
- ❑ **No rules of propositional logic** allow us to conclude the **truth** of the statement.
- ❑ We will introduce a more powerful type of **logic** called **predicate logic**.

Predicates and Quantifiers

- ❑ **Predicate logic** can be used to express the **meaning of a wide range of statements** in **mathematics** and **computer science** in ways that permit us to reason and explore relationships between objects.

Predicates

The statements **involving the variables** such as

$$x > 3$$

$$x + y > 0$$

$$x = y + 3$$

are neither **true nor false** because the values of **variables are not specified**.

Predicates

Statements **involving variables**, such as

“ $x > 3$ ”, “ $x = y + 3$ ”, “ $x + y = z$ ”, “computer x is under attack by an intruder”, and “computer x is functioning properly”

- ❑ These statements are **neither true nor false** when the values of the **variables are not specified**

The statement **“x is greater than 3”** has two parts.

Subject: (variable) x is the subject

Predicate: is greater than 3

- ❑ **Predicate** states the property the object **x has**

Note: Each statement consists of subject and predicate

Propositional Function

- ❑ The **statement $P(x)$** is also said to be the value of **the propositional function P** at **x** .
- ❑ Once a value has been assigned to the variable x , the statement **$P(x)$** becomes a **proposition** and has a **truth value**.

Example Let $P(x)$ denote the statement " $x > 3$." What are the truth values of $P(4)$ and $P(2)$?

Solution:

Let $P(x): x > 3$

$P(4): 4 > 3$

True

$P(2): 2 > 3$

False

Example Let $A(x)$ denote the statement "**Computer x is under attack by an intruder.**" Suppose that of the computers on campus, only **CS2** and **MATH1** are **currently under attack by intruders**. What are truth values of $A(\text{CS1})$, $A(\text{CS2})$, and $A(\text{MATH1})$?

Solution:

$A(x)$ = Computer x is under attack by an intruder

$A(\text{CS1})$ = Computer **CS1 is under attack by an intruder**

False

$A(\text{CS2})$ = Computer **CS2 is under attack by an intruder**

True

$A(\text{MATH1})$ = Computer **MATH1 is under attack by an intruder**

True

Example: Let $Q(x, y)$ denote the statement " $x = y + 3$." What are the truth values of the propositions $Q(1, 2)$ and $Q(3, 0)$?

Solution:

$$Q(x, y): x = y + 3$$

$$Q(1, 2): 1 = 2 + 3$$

$$Q(1, 2): 1 = 5$$

False

$$Q(3, 0): 3 = 0 + 3$$

$$Q(3, 0): 3 = 3$$

True

Predicates

- ❑ In general, a statement involving the **n variables x_1, x_2, \dots, x_n** can be denoted by **$P(x_1, x_2, \dots, x_n)$**
- ❑ A statement of the form $P(x_1, x_2, \dots, x_n)$ is the value of **the propositional function P** at the n -tuple (x_1, x_2, \dots, x_n) , and P is also called a **n -place predicate** or a **n -ary predicate**.

How to create proposition from propositional function?

- ❑ There are two ways:
- ❑ When the **variables in a propositional function** are assigned values, the **resulting statement becomes a proposition** with a certain truth value
- ❑ **Quantification:** is a process to create a **proposition** from a **propositional function**.
- ❑ In English, the words **all, some, many, none**, and **few** are used in **quantifications**.

Universe of discourse (UD) or universe or domain

The **set of all values** x can have is called the **universe of discourse (UD)**.

For example:

Set of all apples is UD

Set of all chalkboards is UD

Quantifiers

- **All** people are mortal.
 - **Every** computer is 16-bit machine.
 - **No** birds are black.
 - **Some** people have blue eyes.
 - **There exists** an even prime number.
-
- ❑ Each contains a word indicating such as **all, every, none, some** and **one**.
 - ❑ Such words, called **quantifiers**, give us an idea about how many **objects have a certain property**.

Note: The area of logic that deals with **predicate and quantifiers** is called **the predicate calculus**

Types of quantifiers

There are two types of quantifiers: **Universal quantifier** and **existential quantifier**

Universal quantification, which tells us that a **predicate** is true for **every element under consideration**.

Universal quantifier

1. **Universal quantifier**: Let $p(x)$ be a **propositional function** with **domain D**. For all x , $p(x)$ is true. Symbolically $\forall x \in D, P(x)$. We read $\forall x P(x)$ as "**for all x P(x)**" or "**for every x P(x)**".

$$\forall x P(x) = P(x_1) \wedge P(x_2) \dots \wedge P(x_n)$$

$$UD = \{x_1, x_2, \dots, x_n\}$$

All elements of UD satisfy $P(x)$.

Signal word or grammar word: all, for all, all of, each, whole, every, given any, for arbitrary, for each, for any

Existential Quantifier

Existential quantification, which tells us that there is **one or more element** under consideration for which the predicate is true

Existential quantifier:

- **Existential quantifier:** Let $P(x)$ be a propositional function with domain D . For **some values** of x such $P(x)$ is true. We read $\exists xP(x)$ as “**There is an x such that $P(x)$** ”, “**There is at least one x such that $P(x)$** ” or “**For some x $P(x)$** ”.

Symbolically $\exists x \in D$ such that $P(x)$

$$\exists xP(x) = P(x_1) \vee P(x_2) \dots \vee P(x_n)$$

$$UD = \{x_1, x_2, \dots, x_n\}$$

Some elements of UD satisfy $P(x)$

Signal word or grammar word: Some, at least, there exist, someone, few, any, exactly one

Quantifiers

Statement	When True ?	When False?
$\forall xP(x)$	$P(x)$ is true for every x .	There is an x for which $P(x)$ is false.
$\exists xP(x)$	There is an x for which $P(x)$ is true.	$P(x)$ is false for every x .

Assumption about the domains of discourse

Generally, an implicit assumption is made that all domains of discourse for **quantifiers are nonempty**.

1. If the **domain is empty**, then **$\forall xP(x)$ is true** for any **propositional function $P(x)$** because there are no elements x in the domain for which **$P(x)$ is false**.
2. If the **domain is empty**, then **$\exists xP(x)$ is false** whenever $Q(x)$ is a propositional function because when the domain is empty, there can be **no element in the domain for which $Q(x)$ is true**.

Example: Let $P(x)$ be the statement " $x + 1 > x$ ". What is the truth value of the quantification $\forall x P(x)$, where the domain consists of all real numbers?

Solution:

UD = set of real numbers

Or

UD = \mathbb{R}

$P(x)$ is a propositional function (pf) and P is predicate and x is a variable

$P(x): x + 1 > x$

$P(-1): -1 + 1 > -1$ (True)

$P(0): 0 + 1 > 0$ (True)

$P(1): 1 + 1 > 1$ (True)

$P(x)$ is true for all real numbers x , the quantification

$\forall x P(x)$, is true

Example: Let $Q(x)$ be the statement " $x < 2$ " What is the truth value of the quantification $\forall x Q(x)$, where the **domain consists of all real numbers**?

Solution:

UD = set of real numbers

Or

$$UD = \mathbb{R}$$

$Q(x)$ is a propositional function (pf) and Q is predicate and x is a variable

$$Q(x): x < 2$$

$$Q(-1): -1 < 2 \text{ (true)}$$

$$Q(0): 0 < 2 \text{ (true)}$$

$$Q(1): 1 < 2 \text{ (true)}$$

$$Q(3): 3 < 2 \text{ (false)}$$

Therefore $\forall x Q(x)$ is false

Example: What is the truth value of $\forall xP(x)$, where $P(x)$ is the statement " $x^2 < 10$ " and the domain consists of the positive integers not exceeding 4?

Solution: $\forall xP(x)$ or $P(1) \wedge P(2) \wedge P(3) \wedge P(4)$

$$UD = \{1, 2, 3, 4\}$$

$P(x)$ is a propositional function (pf) and P is predicate and x is a variable

$$P(x): x^2 < 10$$

$$P(1): 1 < 10 \text{ (true)}$$

$$P(2): 4 < 10 \text{ (true)}$$

$$P(3): 9 < 10 \text{ (true)}$$

$$P(4): 16 < 10 \text{ (false)}$$

Therefore $\forall xP(x)$ is false

Example: Let $P(x)$ denote the statement " $x > 3$ " What is the truth value of the **quantification** $\exists xP(x)$, where the domain consists of all real numbers?

Solution:

$$P(x) = "x > 3"$$

UD = set of real numbers

Or $UD = \mathbb{R}$

$P(x)$ is a propositional function (pf) and P is predicate and x is a variable

$$P(x): x > 3$$

$$P(-1): -1 > 3 \text{ (false)}$$

$$P(0): 0 > 3 \text{ (false)}$$

$$P(1): 1 > 3 \text{ (false)}$$

$$P(4): 4 > 3 \text{ (true)}$$

$P(x)$ is true for some real numbers x , the quantification

$\exists x P(x)$, is true

Example: Let $Q(x)$ denote the statement " $x = x + 1$ ". What is the truth value of the quantification $\exists x P(x)$, where the domain consists of all real numbers?

UD = set of real numbers

$P(x)$ is a propositional function (pf) and P is predicate and x is a variable

$$P(x): x = x + 1$$

$$P(-1): -1 = -1 + 1 \text{ (false)}$$

$$P(0): 0 = 0 + 1 \text{ (false)}$$

$$P(1): 1 = 1 + 1 \text{ (false)}$$

$P(x)$ is false for every real numbers x , the quantification
 $\exists x P(x)$, is false

Example What is the truth value of $\exists xP(x)$, where $P(x)$ is the statement " $x^2 > 10$ " and the universe of discourse consists of the positive integers not exceeding 4?

Solution:

$$\exists xP(x) \text{ or } P(1) \vee P(2) \vee P(3) \vee P(4)$$

$$UD = \{1, 2, 3, 4\}$$

$P(x)$ is a propositional function (pf) and P is predicate and x is a variable

$$P(x): x^2 > 10$$

$$P(1): 1 > 10 \text{ (false)}$$

$$P(2): 4 > 10 \text{ (false)}$$

$$P(3): 9 > 10 \text{ (false)}$$

$$P(4): 16 > 10 \text{ (true)}$$

Therefore $\exists xP(x)$ **is true**

Suggested Readings

1.4 Predicates and Quantifiers