William Stallings
Computer Organization and Architecture
10th Edition

+
Chapter 3

A Top-Level View of Computer Function and Interconnection

+

Computer Components

- Contemporary computer designs are based on concepts developed by John von Neumann at the Institute for Advanced Studies, Princeton

- Referred to as the *von Neumann architecture* and is based on three key concepts:
  - Data and instructions are stored in a single read-write memory
  - The contents of this memory are addressable by location, without regard to the type of data contained there
  - Execution occurs in a sequential fashion (unless explicitly modified) from one instruction to the next

- *Hardwired program*
  - The result of the process of connecting the various components in the desired configuration

+

Hardware and Software Approaches


Data
Sequence of arithmetic and logic functions
Results
(a) Programming in hardware
Instruction codes
Instruction interpreter
Control signals
Data
General-purpose arithmetic and logic functions
Results
(b) Programming in software

Figure 3.1 Hardware and Software Approaches

Software

- A sequence of codes or instructions
- Part of the hardware interprets each instruction and generates control signals
- Provide a new sequence of codes for each new program instead of rewiring the hardware

Major components:

- CPU
  - Instruction interpreter
  - Module of general-purpose arithmetic and logic functions
- I/O Components
  - Input module
    - Contains basic components for accepting data and instructions and converting them into an internal form of signals usable by the system
  - Output module
    - Means of reporting results

Software

I/O Components



Memory address register (MAR)

- Specifies the address in memory for the next read or write

Memory buffer register (MBR)

- Contains the data to be written into memory or receives the data read from memory

I/O address register (I/OAR)

- Specifies a particular I/O device

I/O buffer register (I/OBR)

- Used for the exchange of data between an I/O module and the CPU



PC	=	Program counter
IR	=	Instruction register
MAR	=	Memory address register
MBR	=	Memory buffer register
I/O AR	=	Input/output address register
I/O BR	=	Input/output buffer register

Figure 3.2 Computer Components: Top-Level View



Figure 3.3 Basic Instruction Cycle

+

Fetch Cycle

- At the beginning of each instruction cycle the processor fetches an instruction from memory
- The program counter (PC) holds the address of the instruction to be fetched next
- The processor increments the PC after each instruction fetch so that it will fetch the next instruction in sequence
- The fetched instruction is loaded into the instruction register (IR)
- The processor interprets the instruction and performs the required action

Action Categories



Processor-memory

- Data transferred from processor to memory or from memory to processor

Processor-I/O

- Data transferred to or from a peripheral device by transferring between the processor and an I/O module

Data processing

- The processor may perform some arithmetic or logic operation on data

Control

- An instruction may specify that the sequence of execution be altered



0 3 4 15

Opcode | Address

(a) Instruction format

0 1 15

S | Magnitude

(b) Integer format

Program Counter (PC) = Address of instruction
Instruction Register (IR) = Instruction being executed
Accumulator (AC) = Temporary storage

(c) Internal CPU registers

0001 = Load AC from Memory
0010 = Store AC to Memory
0101 = Add to AC from Memory

(d) Partial list of opcodes

Figure 3.4 Characteristics of a Hypothetical Machine



Figure 3.5 Example of Program Execution (contents of memory and registers in hexadecimal)


Instruction fetch
Operand fetch
Operand store
Multiple operands
Multiple results
Instruction address calculation
Instruction operation decoding
Operand address calculation
Data Operation
Operand address calculation
Return for string or vector data
Instruction complete, fetch next instruction

Figure 3.6 Instruction Cycle State Diagram



Program	Generated by some condition that occurs as a result of an instruction execution, such as arithmetic overflow, division by zero, attempt to execute an illegal machine instruction, or reference outside a user's allowed memory space.
Timer	Generated by a timer within the processor. This allows the operating system to perform certain functions on a regular basis.
I/O	Generated by an I/O controller, to signal normal completion of an operation, request service from the processor, or to signal a variety of error conditions.
Hardware failure	Generated by a failure such as power failure or memory parity error.

Table 3.1

Classes of Interrupts



(a) No interrupts (b) Interrupts; short I/O wait (c) Interrupts; long I/O wait

✖ = interrupt occurs during course of execution of user program

Figure 3.7 Program Flow of Control Without and With Interrupts



Figure 3.8 Transfer of Control via Interrupts



Figure 3.9 Instruction Cycle with Interrupts



Figure 3.10 Program Timing: Short I/O Wait



Figure 3.11 Program Timing: Long I/O Wait


Instruction fetch
Operand fetch
Operand store
Multiple operands
Multiple results
Instruction address calculation
Instruction operation decoding
Operand address calculation
Data Operation
Operand address calculation
Interrupt check
Interrupt
Instruction complete, fetch next instruction
Return for string or vector data
No interrupt

Figure 3.12 Instruction Cycle State Diagram, With Interrupts



Figure 3.13 Transfer of Control with Multiple Interrupts


User program
Printer interrupt service routine
Communication interrupt service routine
Disk interrupt service routine
t = 0
t = 10
t = 15
t = 25
t = 25
t = 35
t = 40

Figure 3.14 Example Time Sequence of Multiple Interrupts

+

I/O Function

- I/O module can exchange data directly with the processor
- Processor can read data from or write data to an I/O module
  - Processor identifies a specific device that is controlled by a particular I/O module
  - I/O instructions rather than memory referencing instructions
- In some cases it is desirable to allow I/O exchanges to occur directly with memory
  - The processor grants to an I/O module the authority to read from or write to memory so that the I/O memory transfer can occur without tying up the processor
  - The I/O module issues read or write commands to memory relieving the processor of responsibility for the exchange
  - This operation is known as direct memory access (DMA)



Figure 3.15 Computer Modules

The interconnection structure must support the following types of transfers:

Memory to processor

Processor reads an instruction or a unit of data from memory

Processor to memory

Processor writes a unit of data to memory

I/O to processor

Processor reads data from an I/O device via an I/O module

Processor to I/O

Processor sends data to the I/O device

I/O to or from memory

An I/O module is allowed to exchange data directly with memory without going through the processor using direct memory access

Bus Interconnection



A communication pathway connecting two or more devices

- Key characteristic is that it is a shared transmission medium

Signals transmitted by any one device are available for reception by all other devices attached to the bus

- If two devices transmit during the same time period their signals will overlap and become garbled

Typically consists of multiple communication lines

- Each line is capable of transmitting signals representing binary 1 and binary 0

Computer systems contain a number of different buses that provide pathways between components at various levels of the computer system hierarchy

System bus

- A bus that connects major computer components (processor, memory, I/O)

The most common computer interconnection structures are based on the use of one or more system buses

Data Bus

- Data lines that provide a path for moving data among system modules
- May consist of 32, 64, 128, or more separate lines
- The number of lines is referred to as the *width* of the data bus
- The number of lines determines how many bits can be transferred at a time
- The width of the data bus is a key factor in determining overall system performance



+

Address Bus



- Used to designate the source or destination of the data on the data bus
  - If the processor wishes to read a word of data from memory it puts the address of the desired word on the address lines
- Width determines the maximum possible memory capacity of the system
- Also used to address I/O ports
  - The higher order bits are used to select a particular module on the bus and the lower order bits select a memory location or I/O port within the module

Control Bus



- Used to control the access and the use of the data and address lines
- Because the data and address lines are shared by all components there must be a means of controlling their use
- Control signals transmit both command and timing information among system modules
- Timing signals indicate the validity of data and address information
- Command signals specify operations to be performed



Figure 3.16 Bus Interconnection Scheme

+ # Summary

Chapter 3

A Top-Level View of Computer Function and Interconnection

- Computer components
- Computer function
  - Instruction fetch and execute
  - Interrupts
  - I/O function
- Interconnection structures
- Bus interconnection