

APPENDIX A: SOURCE CODE STRUCTURE

MYSQL DATABASE

```
CREATE DATABASE IF NOT EXISTS food_ordering_system;
```

```
USE food_ordering_system;
```

```
-- TABLES
```

```
CREATE TABLE IF NOT EXISTS categories (
```

```
    id INT AUTO_INCREMENT PRIMARY KEY,
```

```
    name VARCHAR(100) NOT NULL UNIQUE,
```

```
    description TEXT,
```

```
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
```

```
);
```

```
CREATE TABLE IF NOT EXISTS food_items (
```

```
    id INT AUTO_INCREMENT PRIMARY KEY,
```

```
    category_id INT,
```

```
    name VARCHAR(150) NOT NULL,
```

```
    description TEXT,
```

```
    price DECIMAL(10, 2) NOT NULL,
```

```
    image_url VARCHAR(255),
```

```
    is_available TINYINT(1) DEFAULT 1,
```

```
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
```

```
    FOREIGN KEY (category_id) REFERENCES categories(id) ON DELETE SET  
NULL
```

```
);
```

```
CREATE TABLE IF NOT EXISTS customers (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(150) NOT NULL,  
    email VARCHAR(150) UNIQUE NOT NULL,  
    phone VARCHAR(15),  
    address TEXT,  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);  
  
CREATE TABLE IF NOT EXISTS orders (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    customer_id INT,  
    total_amount DECIMAL(10, 2) NOT NULL,  
    status ENUM('Pending','Confirmed','Preparing','Out for  
Delivery','Delivered','Cancelled') DEFAULT 'Pending',  
    payment_method ENUM('Cash','Card','UPI') DEFAULT 'Cash',  
    notes TEXT,  
    ordered_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (customer_id) REFERENCES customers(id) ON DELETE SET  
NULL  
);  
  
CREATE TABLE IF NOT EXISTS order_items (  
    id INT AUTO_INCREMENT PRIMARY KEY,
```

```
order_id INT NOT NULL,  
  
food_item_id INT NOT NULL,  
  
quantity INT NOT NULL DEFAULT 1,  
  
unit_price DECIMAL(10, 2) NOT NULL,  
  
FOREIGN KEY (order_id) REFERENCES orders(id) ON DELETE CASCADE,  
  
FOREIGN KEY (food_item_id) REFERENCES food_items(id) ON DELETE  
CASCADE  
  
);  
  
CREATE TABLE IF NOT EXISTS admins (  
  
    id INT AUTO_INCREMENT PRIMARY KEY,  
  
    username VARCHAR(100) UNIQUE NOT NULL,  
  
    password VARCHAR(255) NOT NULL,  
  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
  
);  
  
-- SAFE INSERTS (no duplicate errors)  
  
INSERT IGNORE INTO categories (name, description) VALUES  
  
('Starters', 'Delicious appetizers to kick off your meal'),  
  
('Main Course', 'Hearty and satisfying main dishes'),  
  
('Biryani & Rice', 'Flavourful rice dishes'),  
  
('Desserts', 'Sweet treats to end your meal'),  
  
('Beverages', 'Refreshing drinks');  
  
INSERT IGNORE INTO food_items (category_id, name, description, price,  
is_available) VALUES
```

(1, 'Chicken 65', 'Spicy deep-fried chicken with curry leaves', 120.00, 1),
 (1, 'Paneer Tikka', 'Grilled cottage cheese with tandoori spices', 110.00, 1),
 (1, 'Veg Spring Rolls', 'Crispy rolls stuffed with seasoned vegetables', 80.00, 1),
 (2, 'Butter Chicken', 'Creamy tomato-based chicken curry', 180.00, 1),
 (2, 'Paneer Butter Masala', 'Rich paneer in buttery tomato gravy', 160.00, 1),
 (2, 'Fish Curry', 'Traditional South Indian fish curry', 200.00, 1),
 (3, 'Chicken Biryani', 'Aromatic basmati rice with spiced chicken', 180.00, 1),
 (3, 'Veg Biryani', 'Fragrant basmati rice with mixed vegetables', 140.00, 1),
 (3, 'Mutton Biryani', 'Slow-cooked mutton with basmati rice', 220.00, 1),
 (4, 'Gulab Jamun', 'Soft milk dumplings in sugar syrup', 60.00, 1),
 (4, 'Ice Cream', 'Creamy vanilla / chocolate / strawberry', 70.00, 1),
 (5, 'Mango Lassi', 'Thick chilled mango yoghurt drink', 60.00, 1),
 (5, 'Fresh Lime Soda', 'Chilled lime soda, sweet or salted', 40.00, 1);

-- ADMIN FIX

INSERT INTO admins (username, password)

VALUES ('admin', 'admin123')

ON DUPLICATE KEY UPDATE password = 'admin123';

Python code:

"""

Food Ordering System - Flask Backend

Run: python app.py

Then open: http://127.0.0.1:5000

"""

```

from flask import Flask, render_template, request, redirect, url_for, session, jsonify,
flash

import mysql.connector

import json

app = Flask(__name__)

app.secret_key = "food_order_secret_2024"

DB_CONFIG = {
    "host": "localhost",
    "user": "root",
    "password": "shso@30", # ← change this
    "database": "food_ordering_system"
}

def get_db():
    return mysql.connector.connect(**DB_CONFIG)

@app.route("/")
def index():
    db = get_db()
    cur = db.cursor(dictionary=True)
    cur.execute("SELECT * FROM categories")
    categories = cur.fetchall()

    cur.execute("SELECT f.*, c.name AS category_name FROM food_items f JOIN
categories c ON f.category_id = c.id WHERE f.is_available = 1")

```

```

    items = cur.fetchall()

    db.close()

    return render_template("index.html", categories=categories, items=items)

@app.route("/menu")
def menu():
    db = get_db()

    cur = db.cursor(dictionary=True)

    cat_id = request.args.get("category", None)

    cur.execute("SELECT * FROM categories")

    categories = cur.fetchall()

    if cat_id:
        cur.execute("SELECT f.*, c.name AS category_name FROM food_items f JOIN
categories c ON f.category_id = c.id WHERE f.is_available=1 AND
f.category_id=%s", (cat_id,))

    else:
        cur.execute("SELECT f.*, c.name AS category_name FROM food_items f JOIN
categories c ON f.category_id = c.id WHERE f.is_available=1")

    items = cur.fetchall()

    db.close()

    return render_template("menu.html", categories=categories, items=items,
selected_cat=cat_id)

@app.route("/cart")
def cart():

```

```

cart_items = session.get("cart", {})

total = 0

details = []

if cart_items:

    db = get_db()

    cur = db.cursor(dictionary=True)

    for item_id, qty in cart_items.items():

        cur.execute("SELECT * FROM food_items WHERE id=%s", (item_id,))

        food = cur.fetchone()

        if food:

            food["qty"] = qty

            food["subtotal"] = food["price"] * qty

            total += food["subtotal"]

            details.append(food)

    db.close()

    return render_template("cart.html", cart_items=details, total=total)

@app.route("/add_to_cart/<int:item_id>")

def add_to_cart(item_id):

    cart = session.get("cart", {})

    key = str(item_id)

    cart[key] = cart.get(key, 0) + 1

    session["cart"] = cart

    flash("Item added to cart!", "success")

```

```

    return redirect(request.referrer or url_for("menu"))

@app.route("/remove_from_cart/<int:item_id>")
def remove_from_cart(item_id):

    cart = session.get("cart", {})

    key = str(item_id)

    if key in cart:

        del cart[key]

    session["cart"] = cart

    return redirect(url_for("cart"))


@app.route("/update_cart", methods=["POST"])
def update_cart():

    item_id = str(request.form.get("item_id"))

    qty = int(request.form.get("qty", 1))

    cart = session.get("cart", {})

    if qty <= 0:

        cart.pop(item_id, None)

    else:

        cart[item_id] = qty

    session["cart"] = cart

    return redirect(url_for("cart"))


@app.route("/checkout", methods=["GET", "POST"])
def checkout():

```



```

cart_items = session.get("cart", {})

if not cart_items:

    return redirect(url_for("cart"))

db = get_db()

cur = db.cursor(dictionary=True)

details = []

total = 0

for item_id, qty in cart_items.items():

    cur.execute("SELECT * FROM food_items WHERE id=%s", (item_id,))

    food = cur.fetchone()

    if food:

        food["qty"] = qty

        food["subtotal"] = food["price"] * qty

        total += food["subtotal"]

        details.append(food)

if request.method == "POST":

    name = request.form["name"]

    email = request.form["email"]

    phone = request.form["phone"]

    address = request.form["address"]

    payment = request.form.get("payment", "Cash")

    notes = request.form.get("notes", "")

    cur.execute("SELECT id FROM customers WHERE email=%s", (email,))

```

```

existing = cur.fetchone()

if existing:

    customer_id = existing["id"]

else:

    cur.execute("INSERT INTO customers (name, email, phone, address)
VALUES (%s,%s,%s,%s)",

              (name, email, phone, address))

    db.commit()

    customer_id = cur.lastrowid

    cur.execute("INSERT INTO orders (customer_id, total_amount,
payment_method, notes) VALUES (%s,%s,%s,%s)",

              (customer_id, total, payment, notes))

    db.commit()

    order_id = cur.lastrowid

    for item in details:

        cur.execute("INSERT INTO order_items (order_id, food_item_id, quantity,
unit_price) VALUES (%s,%s,%s,%s)",

                  (order_id, item["id"], item["qty"], item["price"]))

        db.commit()

    db.close()

    session.pop("cart", None)

    flash(f'Order #{order_id} placed successfully! 🎉', "success")

    return redirect(url_for("order_confirmation", order_id=order_id))

db.close()

```

```

    return render_template("checkout.html", cart_items=details, total=total)

@app.route("/order_confirmation/<int:order_id>")
def order_confirmation(order_id):

    db = get_db()

    cur = db.cursor(dictionary=True)

    cur.execute("SELECT o.*, c.name AS customer_name, c.email FROM orders o
JOIN customers c ON o.customer_id=c.id WHERE o.id=%s", (order_id,))

    order = cur.fetchone()

    cur.execute("SELECT oi.*, f.name AS food_name FROM order_items oi JOIN
food_items f ON oi.food_item_id=f.id WHERE oi.order_id=%s", (order_id,))

    items = cur.fetchall()

    db.close()

    return render_template("order_confirmation.html", order=order, items=items)

@app.route("/order_history", methods=["GET", "POST"])
def order_history():

    orders = []

    email = ""

    if request.method == "POST":

        email = request.form.get("email", "")

        db = get_db()

        cur = db.cursor(dictionary=True)

        cur.execute("SELECT o.* FROM orders o JOIN customers c ON
o.customer_id=c.id WHERE c.email=%s ORDER BY o.ordered_at DESC", (email,))

        orders = cur.fetchall()

```

```

        db.close()

    return render_template("order_history.html", orders=orders, email=email)

@app.route("/admin/login", methods=["GET", "POST"])
def admin_login():
    if request.method == "POST":
        username = request.form["username"]
        password = request.form["password"]
        db = get_db()
        cur = db.cursor(dictionary=True)
        cur.execute("SELECT * FROM admins WHERE username=%s AND
password=%s", (username, password))
        admin = cur.fetchone()
        db.close()
        if admin:
            session["admin"] = admin["username"]
            return redirect(url_for("admin_dashboard"))
        flash("Invalid credentials!", "danger")
        return render_template("admin_login.html")

@app.route("/admin/logout")
def admin_logout():
    session.pop("admin", None)
    return redirect(url_for("admin_login"))

def admin_required(f):

```

```

from functools import wraps

@wraps(f)
def decorated(*args, **kwargs):
    if "admin" not in session:
        return redirect(url_for("admin_login"))

    return f(*args, **kwargs)

return decorated

@app.route("/admin")
@admin_required
def admin_dashboard():
    db = get_db()

    cur = db.cursor(dictionary=True)

    cur.execute("SELECT COUNT(*) AS cnt FROM orders")

    total_orders = cur.fetchone()["cnt"]

    cur.execute("SELECT SUM(total_amount) AS rev FROM orders WHERE
status='Delivered'")

    revenue = cur.fetchone()["rev"] or 0

    cur.execute("SELECT COUNT(*) AS cnt FROM food_items")

    total_items = cur.fetchone()["cnt"]

    cur.execute("SELECT COUNT(*) AS cnt FROM customers")

    total_customers = cur.fetchone()["cnt"]

    cur.execute("SELECT o.*, c.name AS customer_name FROM orders o JOIN
customers c ON o.customer_id=c.id ORDER BY o.ordered_at DESC LIMIT 10")

```

```

recent_orders = cur.fetchall()

db.close()

return render_template("admin_dashboard.html",

                        total_orders=total_orders, revenue=revenue,

                        total_items=total_items, total_customers=total_customers,

                        recent_orders=recent_orders)

@app.route("/admin/orders")

@admin_required
def admin_orders():

    db = get_db()

    cur = db.cursor(dictionary=True)

    cur.execute("SELECT o.*, c.name AS customer_name FROM orders o JOIN
customers c ON o.customer_id=c.id ORDER BY o.ordered_at DESC")

    orders = cur.fetchall()

    db.close()

    return render_template("admin_orders.html", orders=orders)

@app.route("/admin/orders/update/<int:order_id>", methods=["POST"])

@admin_required
def update_order_status(order_id):

    status = request.form["status"]

    db = get_db()

    cur = db.cursor()

    cur.execute("UPDATE orders SET status=%s WHERE id=%s", (status, order_id))

```

```

db.commit()

db.close()

flash("Order status updated!", "success")

return redirect(url_for("admin_orders"))

@app.route("/admin/food", methods=["GET"])

@admin_required

def admin_food():

    db = get_db()

    cur = db.cursor(dictionary=True)

    cur.execute("SELECT f.*, c.name AS category_name FROM food_items f JOIN
categories c ON f.category_id=c.id ORDER BY c.name, f.name")

    items = cur.fetchall()

    cur.execute("SELECT * FROM categories")

    categories = cur.fetchall()

    db.close()

    return render_template("admin_food.html", items=items, categories=categories)

@app.route("/admin/food/add", methods=["POST"])

@admin_required

def admin_add_food():

    name = request.form["name"]

    category_id = request.form["category_id"]

    description = request.form["description"]

    price = request.form["price"]

```

```

db = get_db()

cur = db.cursor()

cur.execute("INSERT INTO food_items (name, category_id, description, price)
VALUES (%s,%s,%s,%s)",

          (name, category_id, description, price))

db.commit()

db.close()

flash(f'{name}' added successfully!", "success")

return redirect(url_for("admin_food"))

@app.route("/admin/food/delete/<int:item_id>")

@admin_required

def admin_delete_food(item_id):

    db = get_db()

    cur = db.cursor()

    cur.execute("DELETE FROM food_items WHERE id=%s", (item_id,))

    db.commit()

    db.close()

    flash("Food item deleted.", "info")

    return redirect(url_for("admin_food"))

@app.route("/admin/food/toggle/<int:item_id>")

@admin_required

def toggle_availability(item_id):

```



```

db = get_db()

cur = db.cursor()

cur.execute("UPDATE food_items SET is_available = NOT is_available WHERE
id=%s", (item_id,))

db.commit()

db.close()

return redirect(url_for("admin_food"))

if __name__ == "__main__":

    app.run(debug=True)

```

Index.html

```

{% extends "base.html" %}

{% block title %}SpiceBox — Home{% endblock %}

{% block content %}

<section class="hero">

<div class="hero-content">

    <p class="hero-tag">🍲 Madurai's Favourite</p>

    <h1>Fresh Food,<br><span>Fast Delivery</span></h1>

    <p class="hero-sub">Authentic flavours delivered hot to your doorstep.<br>Order
in minutes, eat in joy.</p>

    <a href="{{ url_for('menu') }}" class="btn-primary">Explore Menu →</a>

</div>

<div class="hero-art">🍷</div>

```

```
</section>
```

```
<section class="categories-section">
```

```
<h2 class="section-title">Browse by Category</h2>
```

```
<div class="category-grid">
```

```
{% for cat in categories %}
```

```
<a href="{{ url_for('menu', category=cat.id) }}" class="cat-card">
```

```
<span class="cat-icon">
```

```
{% if 'Starter' in cat.name %} 🥗
```

```
{% elif 'Main' in cat.name %} 🍲
```

```
{% elif 'Biryani' in cat.name %} 🍛
```

```
{% elif 'Dessert' in cat.name %} 🍰
```

```
{% elif 'Beverage' in cat.name %} 🥤
```

```
{% else %} 🍽️ {% endif %}
```

```
</span>
```

```
<p>{{ cat.name }}</p>
```

```
</a>
```

```
{% endfor %}
```

```
</div>
```

```
</section>
```

```
<section class="featured-section">
```

```
<h2 class="section-title">Popular Items</h2>
```

```
<div class="food-grid">
```

```

{% for item in items[:6] %}

<div class="food-card">

  <div class="food-img-placeholder">

    {% if 'Biryani' in item.name %} 🍛

    {% elif 'Chicken' in item.name %} 🍗

    {% elif 'Paneer' in item.name %} 🍕

    {% elif 'Fish' in item.name %} 🐟

    {% elif 'Ice' in item.name %} 🍦

    {% elif 'Lassi' in item.name or 'Lime' in item.name %} 🍹

    {% elif 'Gulab' in item.name %} 🍷

    {% else %} 🍽️ {% endif %}

  </div>

  <div class="food-info">

    <span class="food-cat">{{ item.category_name }}</span>

    <h3>{{ item.name }}</h3>

    <p class="food-desc">{{ item.description }}</p>

    <div class="food-footer">

      <span class="price">₹{{ "%.0f"|format(item.price) }}</span>

      <a href="{{ url_for('add_to_cart', item_id=item.id) }}" class="btn-add">+
Add</a>

    </div>

  </div>

```

```

</div>

{% endfor %}

</div>

<div style="text-align:center;margin-top:2rem">

  <a href="{{ url_for('menu') }}" class="btn-primary">View Full Menu →</a>

</div>

</section>

{% endblock %}

```

Menu.html

```

{% extends "base.html" %}

{% block title %}Menu — SpiceBox{% endblock %}

{% block content %}

<div class="page-header">

  <h1>Our Menu</h1>

  <p>Fresh, authentic, made to order</p>

</div>

<div class="menu-layout">

  <aside class="filter-sidebar">

    <h3>Categories</h3>

    <a href="{{ url_for('menu') }}" class="filter-link {% if not selected_cat
%} active{% endif %}">All Items</a>

    {% for cat in categories %}

      <a href="{{ url_for('menu', category=cat.id) }}"

```

```

class="filter-link {% if selected_cat == cat.id|string %}active{% endif %}">

  {{ cat.name }}

</a>

{% endfor %}

</aside>

<div class="food-grid">

  {% for item in items %}

    <div class="food-card">

      <div class="food-img-placeholder lg">

        {% if 'Biryani' in item.name %} 🍛

        {% elif 'Chicken' in item.name %} 🍗

        {% elif 'Paneer' in item.name %} 🧀

        {% elif 'Fish' in item.name %} 🐟

        {% elif 'Ice' in item.name %} 🍦

        {% elif 'Lassi' in item.name or 'Lime' in item.name %} 🍹

        {% elif 'Gulab' in item.name %} 🌸

        {% elif 'Spring' in item.name %} 🥗

        {% elif 'Mutton' in item.name %} 🍖

        {% else %} 🍲 {% endif %}

      </div>

      <div class="food-info">

        <span class="food-cat">{{ item.category_name }}</span>

```

```

<h3>{{ item.name }}</h3>

<p class="food-desc">{{ item.description }}</p>

<div class="food-footer">

    <span class="price">₹ {{ "%.0f"|format(item.price) }}</span>

    <a href="{{ url_for('add_to_cart', item_id=item.id) }}" class="btn-add">+ Add
to Cart</a>

</div>

</div>

</div>

{% else %}

<div class="empty-state">

    <span>🍲</span>

    <p>No items found in this category.</p>

</div>

{% endfor %}

</div>

{% endblock %}

```

Cart.html

```

{% extends "base.html" %}

{% block title %}Cart — SpiceBox{% endblock %}

{% block content %}

```

```

<div class="page-header">

    <h1>Your Cart</h1>

</div>

{% if cart_items %}

<div class="cart-layout">

    <div class="cart-items">

        {% for item in cart_items %}

            <div class="cart-row">

                <span class="cart-emoji">

                    {% if 'Biryani' in item.name %} 🍛

                    {% elif 'Chicken' in item.name %} 🍗

                    {% elif 'Paneer' in item.name %} 🧀

                    {% elif 'Fish' in item.name %} 🐟

                    {% elif 'Ice' in item.name %} 🍦

                    {% elif 'Lassi' in item.name or 'Lime' in item.name %} 🍹

                    {% else %} 🍲 {% endif %}

                </span>

                <div class="cart-item-info">

                    <h4>{{ item.name }}</h4>

                    <span>₹{{ "%.0f"|format(item.price) }} each</span>

                </div>

                <form method="POST" action="{{ url_for('update_cart') }}" class="qty-form">

```

```

    <input type="hidden" name="item_id" value="{{ item.id }}" />

    <input type="number" name="qty" value="{{ item.qty }}" min="0" max="20"
class="qty-input" />

    <button type="submit" class="btn-qty">Update</button>

</form>

<span class="cart-subtotal">₹ {{ "%.0f"|format(item.subtotal) }}</span>

<a href="{{ url_for('remove_from_cart', item_id=item.id) }}" class="btn-
remove">✕</a>

</div>

{% endfor %}

</div>

<div class="cart-summary">

<h3>Order Summary</h3>

<div class="summary-row"><span>Subtotal</span><span>₹ {{
("%.0f"|format(total) )}}</span></div>

<div class="summary-row"><span>Delivery</span><span
class="free">FREE</span></div>

<div class="summary-row total"><span>Total</span><span>₹ {{
("%.0f"|format(total) )}}</span></div>

<a href="{{ url_for('checkout') }}" class="btn-primary full-width">Proceed to
Checkout →</a>

<a href="{{ url_for('menu') }}" class="btn-secondary full-width">← Continue
Shopping</a>

</div>

</div>

```



```

{% else %}

<div class="empty-state large">

  <span> 🛒 </span>

  <p>Your cart is empty!</p>

  <a href="{{ url_for('menu') }}" class="btn-primary">Browse Menu</a>

</div>

{% endif %}

{% endblock %}

```

Checkout.html

```

{% extends "base.html" %}

{% block title %}Checkout — SpiceBox{% endblock %}

{% block content %}

<div class="page-header">

  <h1>Checkout</h1>

</div>

<div class="checkout-layout">

  <form method="POST" class="checkout-form">

    <h3>Your Details</h3>

    <div class="form-row">

      <div class="form-group">

        <label>Full Name *</label>

        <input type="text" name="name" required placeholder="e.g. Ravi Kumar"/>

      </div>

```

```

<div class="form-group">

  <label>Email *</label>

  <input type="email" name="email" required placeholder="you@example.com"/>

</div>

</div>

<div class="form-row">

  <div class="form-group">

    <label>Phone *</label>

    <input type="tel" name="phone" required placeholder="+91 9876543210"/>

  </div>

  <div class="form-group">

    <label>Payment Method</label>

    <select name="payment">

      <option value="Cash">Cash on Delivery</option>

      <option value="UPI">UPI</option>

      <option value="Card">Card</option>

    </select>

  </div>

</div>

<div class="form-group full">

  <label>Delivery Address *</label>

  <textarea name="address" required rows="3" placeholder="House no, Street, City,
Pincode"></textarea>

```

```

</div>

<div class="form-group full">

  <label>Special Instructions</label>

  <textarea name="notes" rows="2" placeholder="e.g. Extra spicy, no
onions..."></textarea>

</div>

<button type="submit" class="btn-primary full-width">Place Order 🍴</button>

</form>

<div class="cart-summary">

  <h3>Your Order</h3>

  {% for item in cart_items %}

  <div class="summary-row">

    <span>{{ item.name }} × {{ item.qty }}</span>

    <span>₹ {{ "%.0f"|format(item.subtotal) }}</span>

  </div>

  {% endfor %}

  <hr/>

  <div class="summary-row total"><span>Total</span><span>₹ {{
"%.0f"|format(total) }}</span></div>

</div>

</div>

{% endblock %}

```

Orderconfirmation.html

```

{% extends "base.html" %}

{% block title %}Order Confirmed — SpiceBox{% endblock %}

{% block content %}

<div class="confirmation-page">

    <div class="confirm-icon">  </div>

    <h1>Order Placed!</h1>

    <p class="confirm-sub">Thank you, <strong>{{ order.customer_name }}</strong>!
Your order #<strong>{{ order.id }}</strong> has been received.</p>

    <div class="confirm-card">

        <div class="confirm-row"><span>Order ID</span><span>#{{ order.id
}}</span></div>

        <div class="confirm-row"><span>Status</span><span class="badge badge-
pending">{{ order.status }}</span></div>

        <div class="confirm-row"><span>Payment</span><span>{{
order.payment_method }}</span></div>

        <div class="confirm-row"><span>Total</span><span>₹{{
"%0.0f"|format(order.total_amount) }}</span></div>

    <hr/>

    <h4>Items Ordered</h4>

    {% for item in items %}

    <div class="confirm-row">

        <span>{{ item.food_name }} × {{ item.quantity }}</span>

        <span>₹{{ "%0.0f"|format(item.unit_price * item.quantity) }}</span>

    </div>

```

```

    {% endfor %}

</div>

<div class="confirm-actions">

    <a href="{{ url_for('menu') }}" class="btn-primary">Order More →</a>

    <a href="{{ url_for('order_history') }}" class="btn-secondary">View My
Orders</a>

</div>

</div>

{% endblock %}

```

Orderhistory.html

```

{% extends "base.html" %}

{% block title %}My Orders — SpiceBox{% endblock %}

{% block content %}

<div class="page-header">

    <h1>Order History</h1>

    <p>Track all your past orders</p>

</div>

<div class="history-lookup">

    <form method="POST" class="lookup-form">

        <input type="email" name="email" value="{{ email }}" required
placeholder="Enter your email to find orders"/>

        <button type="submit" class="btn-primary">Search Orders</button>

    </form>

```

```

</div>

{% if orders %}

<div class="orders-table-wrap">

  <table class="orders-table">

    <thead>

      <tr>

        <th>Order ID</th><th>Date &
Time</th><th>Total</th><th>Payment</th><th>Status</th>

      </tr>

    </thead>

    <tbody>

      {% for order in orders %}

      <tr>

        <td><strong>#{{ order.id }}</strong></td>

        <td>{{ order.ordered_at.strftime('%d %b %Y, %I:%M %p') }}</td>

        <td>₹{{ "%.0f"|format(order.total_amount) }}</td>

        <td>{{ order.payment_method }}</td>

        <td><span class="badge badge-{{ order.status|lower|replace(' ','_') }}">{{
order.status }}</span></td>

      </tr>

      {% endfor %}

    </tbody>

  </table>

```

```

</div>

{% elif email %}

<div class="empty-state">

  <span> 🍷 </span>

  <p>No orders found for <strong>{{ email }}</strong></p>

</div>

{% endif %}

{% endblock %}

```

Admin.login

```

<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8"/>

  <meta name="viewport" content="width=device-width,initial-scale=1"/>

  <title>Admin Login — SpiceBox</title>

  <link
href="https://fonts.googleapis.com/css2?family=DM+Sans:wght@400;600&display=s
wap" rel="stylesheet">

  <link rel="stylesheet" href="{{ url_for('static', filename='css/style.css') }}" />

</head>

<body class="admin-body">

<div class="admin-login-box">

  <div class="admin-logo"> 🍷 </div>

```

```

<h2>Admin Login</h2>

<p>SpiceBox Management Panel</p>

{% with messages = get_flashed_messages(with_categories=true) %}

    {% for cat, msg in messages %}

        <div class="flash flash-{{ cat }}">{{ msg }}</div>

    {% endfor %}

{% endwith %}

<form method="POST">

    <div class="form-group">

        <label>Username</label>

        <input type="text" name="username" required placeholder="admin" autofocus/>

    </div>

    <div class="form-group">

        <label>Password</label>

        <input type="password" name="password" required placeholder="....."/>

    </div>

    <button type="submit" class="btn-primary full-width">Login →</button>

</form>

<a href="{{ url_for('index') }}" style="display:block;text-align:center;margin-top:1rem;color:var(--accent)">← Back to Site</a>

</div>

</body>

</html>

```


Admin.dashboard

```
{% extends "admin_base.html" %}

{% block title %}Dashboard — Admin{% endblock %}

{% block content %}

<h2 class="admin-page-title">Dashboard</h2>

<div class="stats-grid">

  <div class="stat-card">

    <span class="stat-icon"> 📦 </span>

    <div><p class="stat-label">Total Orders</p><h3>{{ total_orders }}</h3></div>

  </div>

  <div class="stat-card">

    <span class="stat-icon"> 💰 </span>

    <div><p class="stat-label">Revenue (Delivered)</p><h3>₹{{
"%0.0f"|format(revenue) }}</h3></div>

  </div>

  <div class="stat-card">

    <span class="stat-icon"> 🍔 </span>

    <div><p class="stat-label">Food Items</p><h3>{{ total_items }}</h3></div>

  </div>

  <div class="stat-card">

    <span class="stat-icon"> 👤 </span>

    <div><p class="stat-label">Customers</p><h3>{{ total_customers }}</h3></div>

  </div>

</div>
```

```

</div>

<h3 class="admin-section-title">Recent Orders</h3>

<div class="table-wrap">

  <table class="admin-table">

    <thead>

<tr><th>ID</th><th>Customer</th><th>Amount</th><th>Status</th><th>Time</th>
></tr>

    </thead>

    <tbody>

      {% for o in recent_orders %}

        <tr>

          <td>#{{ o.id }}</td>

          <td>{{ o.customer_name }}</td>

          <td>₹{{ "%.0f"|format(o.total_amount) }}</td>

          <td><span class="badge badge-{{ o.status|lower|replace(' ','_') }}">{{ o.status
}}</span></td>

          <td>{{ o.ordered_at.strftime('%d %b, %I:%M %p') }}</td>

        </tr>

      {% endfor %}

    </tbody>

  </table>

</div>

{% endblock %}

```

Admindashboard.html

```
{% extends "admin_base.html" %}
```

```
{% block title %}Dashboard — Admin{% endblock %}
```

```
{% block content %}
```

```
<h2 class="admin-page-title">Dashboard</h2>
```

```
<div class="stats-grid">
```

```
<div class="stat-card">
```

```
<span class="stat-icon"> 📦 </span>
```

```
<div><p class="stat-label">Total Orders</p><h3>{{ total_orders }}</h3></div>
```

```
</div>
```

```
<div class="stat-card">
```

```
<span class="stat-icon"> 💰 </span>
```

```
<div><p class="stat-label">Revenue (Delivered)</p><h3>₹{{
"%0.0f"|format(revenue) }}</h3></div>
```

```
</div>
```

```
<div class="stat-card">
```

```
<span class="stat-icon"> 🍔 </span>
```

```
<div><p class="stat-label">Food Items</p><h3>{{ total_items }}</h3></div>
```

```
</div>
```

```
<div class="stat-card">
```

```
<span class="stat-icon"> 👤 </span>
```

```
<div><p class="stat-label">Customers</p><h3>{{ total_customers }}</h3></div>
```

```
</div>
```

```

</div>

<h3 class="admin-section-title">Recent Orders</h3>

<div class="table-wrap">

  <table class="admin-table">

    <thead>
<tr><th>ID</th><th>Customer</th><th>Amount</th><th>Status</th><th>Time</th>
></tr>

    </thead>

    <tbody>

      {% for o in recent_orders %}

        <tr>

          <td>#{{ o.id }}</td>

          <td>{{ o.customer_name }}</td>

          <td>₹{{ "%.0f"|format(o.total_amount) }}</td>

          <td><span class="badge badge-{{ o.status|lower|replace(' ','_') }}">{{ o.status
}}</span></td>

          <td>{{ o.ordered_at.strftime('%d %b, %I:%M %p') }}</td>

        </tr>

      {% endfor %}

    </tbody>

  </table>

</div>

{% endblock %}

```