TABLE CREATION AND DATA ENTRY

create table if not exists USER(user_id int primary key,first_name varchar(50),last_name varchar(50),adhar_no varchar(20),gender char,age int,mobile_no varchar(50),email varchar(50),city varchar(50),state varchar(50),pincode varchar(20),_password varchar(50),security_ques varchar(50),security_ans varchar(50));

create table if not exsists TRAIN(train_no int primary key,train_name varchar(50),arrival_time time,departure_time time,availability_of seats char,date date);

create table if not exists STATION(no int ,name varchar(50),hault int,arrival_time time,train_noint,primary key(station_no,train_no),constarint foreign key(train_no) references TRAIN(train_no));

create table if not exsists TRAIN_STATUS(train_no int primary key,b_seats1 int,b_seats2 int,a_seats1 int,a_seats2 int,w_seats1 int,w_seats2 int,fare1 float,fare2 float);

create table if not exsists TICKET(id int primary key,user_id int,status char,no_of_passengers int,train_no int,constraint foreign key(user_id) references USER(user_id),constraint foreign key(train_no) references TRAIN(train_no));

create table if not exists PASSENGER(passenger_id int primary key,pnr_no int,age int,gender char,user_id int,reservation_status char,seat_number varchar(5),name varchar(50),ticket_id int,constraint foreign key(user_id) references USER(user_id),constraint foreign key(ticket_id) references TICKET(id));

create table if not exsists STARTS(train_no int primary key,station_no int,constraint foreign key(train_no) references TRAIN(train_no),constraint foreign key(station_no) references STATION(no));

create table if not exsists STOPS_AT(train_no int,station_no int,constraint foreign key(train_no) references TRAIN(train_no),constraint foreign key(station_no) references STATION(no));

create table if not exsists REACHES(train_no int,station _no int,time time,constraint foreign key(train_no) references TRAIN(train_no),constraint foreign key(station _no) references STATION(no));

create table if not exsists BOOKS(user_id int,id int,constraint foreign key(user_id) references USER(user_id),constraint foreign key(id) references TICKET(id));

create table if not exsists CANCEL(user_id int,id int,passenger_id int,constraint foreign key(id) references TICKET(id),constraint foreign key(passenger_id) references PASSENGER(passenger_id),constraint foreign key(user_id) references USER(user_id));

INSERT QUERIES:

insert into

 $USER(user_id,first_name,last_name,aadhar_no,gender,age,mobile_no,email,city,st\\ ate,pincode,_password,security_ques,security_ans)$

values(1701,'vijay','sharma','309887340843','M',34,'9887786655','vijay1@gmail.com','vijayawada','andhrapradesh','520001','12345@#','favouritecolour','red'),(1702,'rohith','kumar','456709871234','M',45,'9809666555','rohith1kumar@gmail.com','guntur','andhrapradesh','522004','12@#345','favouritebike','bmw'),(1703,'manasvi','sre

```
pradesh', '522004', '0987hii', 'favourite flower', 'rose');
insert into TRAIN(train_no,train_name,arrival_time,departure_time,availability_of
seats,date) values(12711, 'pinakini
exp','113000','114000','A',20170410),(12315,'cormandel
exp','124500',125000','NA',20170410);
insert into STATION(no,name,hault,arrival_time,train_no)
values(111,'vijayawada',10,'113000',12711),(222,'tirupathi',5,'114500',12315);
insert into
TRAIN_STATUS(train_no,w_seats1,b_seats1,b_seats2,a_seats1,a_seats2,w_seats
2,fare1,fare2) values(12711,10,4,0,1,1,0,100,450),(12315,10,5,0,0,2,1,300,600);
insert into TICKET(id,user_id,status,no_of_passengers,train_no)
values(4001,1701,'C',1,,12711),(4002,1702,'NC',1,12315);
insert into PASSENGERS(passenger_id,pnr_no,age,gender,user_id,reservation
_status,seat_number,name,ticket_id) values(5001,78965,45,'M',1701,'C','B6-
45', 'ramesh', 4001), (5002, 54523, 54, 'F', 1701, 'W', 'B3-21', 'surekha', 4002);
insert into STARTS(train_no,station_no) values(12711,111),(12315,222);
insert into STOPS_AT(train_no,station_no) values(12711,222),(12315,111);
insert into REACHES(train_no,station_no,time) values(12711,222,'040000'),
(12315,111,'053500');
insert into BOOKS(user_id,id) values(1701,4001),(1702,4002);
insert into CANCEL(user_id,id,passenger_id) values(1701,4001,5001);
```

e','765843210987','F',20,'9995550666','manasvi57@gmail.com','guntur','andhra