Agent chat cheat sheet

Keys for the chat, the compose buffer, the desk sidebar and the details panel. Keys shown are the ones configured in this Emacs setup.

Sending

`RET`	Steer: during a turn it changes course, when idle it sends.
`M-RET`	Queue: sends after the running turn ends.
`C-c C-c`	Send from the compose buffer (viewport).
`C-c C-k`	Cancel the compose buffer.
`C-c C-p`	Peek at the last prompt sent.

When to use it: steer to correct the agent mid-task; queue when the next instruction depends on the current turn finishing.

Model, mode and effort

`C-c C-v`	Pick the model.
`C-c C-m`	Pick the session mode (plan, auto, manual).
`C-c C-t`	Pick the thought level (effort).
`C-<tab>`	Cycle the session mode.

When to use it: switch to plan mode before a risky change; drop effort for quick questions.

History and interrupting

`M-p` / `M-n`	Previous or next prompt in the compose buffer.
`M-r`	Search prompt history.
`C-c C-c`	Interrupt the running turn (viewport).
`C-c C-o`	Jump to the other chat buffer.

When to use it: search history to reuse an earlier prompt instead of retyping it.

Help

`C-c C-h`	The compose buffer's help menu.

When to use it: when a key is forgotten, the help menu lists the compose commands in one place.

Desk sidebar

`RET`	Open the chat at point.
`n` / `N`	New chat in this project / in a chosen project.
`R`	Rename the chat.
`p` / `a`	Pin or unpin; archive.
`c`	Continue the chat with another account.
`i`	Show the details panel for the chat.
`d`	Delete the chat, after asking.

When to use it: pin the chats you return to; archive finished ones so the list stays short.

Details panel

`TAB`	Open or close the section at point.
`g` / `r`	Refresh the details.
`o`	Open the pull request in the browser.
`D`	Show every diff of the chat.

When to use it: check the diffs and the open pull request before asking for a commit.

Terminal and phone

`s-`` ` (macOS) `C-c `` ` in a chat	Open or close the project terminal under the chat. It starts in the chat's folder and is reused for that project.
M-x my/agent-cheatsheet	Open this cheat sheet.
M-x agent-desk-remote-pair	Show a pairing code for the Desk Remote phone app.

When to use it: run a quick command in the project without leaving the chat; pair a new phone when the list stops updating.

Generated from docs/agent-shell-cheatsheet.html in the Doom config.