

1. Which of the following language is the predecessor to C Programming Language?

- a) A
- b) B
- c) BCPL
- d) C++

Ans: c

2. C programming language was developed by

- a) Dennis Ritchie
- b) Ken Thompson
- c) Bill Gates
- d) Peter Norton

Ans: a

3. C was developed in the year ____

- a) 1970
- b) 1972
- c) 1976
- d) 1980

Ans: b

4. C is a ____ language

- a) High Level
- b) Low Level
- c) Middle Level
- d) Machine Level

Ans: c

5. C language is available for which of the following Operating Systems?

- a) DOS
- b) Windows
- c) Unix
- d) All of these

Ans: d

6. Which of the following symbol is used to denote a pre-processor statement?

- a) !
- b) #
- c) ~

d) ;

Ans: b

7. Which of the following is a Scalar Data type

a) Float

b) Union

c) Array

d) Pointer

Ans: a

8. Which of the following are tokens in C?

a) Keywords

b) Variables

c) Constants

d) All of the above

Ans: d

9. What is the valid range of numbers for int type of data?

a) 0 to 256

b) -32768 to +32767

c) -65536 to +65536

d) No specific range

Ans: b

10. Which symbol is used as a statement terminator in C?

a) !

b) #

c) ~

d) ;

Ans: d

11. Which escape character can be used to begin a new line in C?

a) \a

b) \b

c) \m

d) \n

Ans: d

12. Which escape character can be used to beep from speaker in C?

a) \a

- b) \b
- c) \m
- d) \n

Ans: a

13. Character constants should be enclosed between ____

- a) Single quotes
- b) Double quotes
- c) Both a and b
- d) None of these

Ans: a

14. String constants should be enclosed between ____

- a) Single quotes
- b) Double quotes
- c) Both a and b
- d) None of these

Ans: b

15. Which of the following is invalid?

- a) ""
- b) ""
- c) 'a'
- d) 'abc'

Ans: d

16. The maximum length of a variable in C is ____

- a) 8
- b) 16
- c) 32
- d) 64

Ans: a

17. What will be the maximum size of a float variable?

- a) 1 byte
- b) 2 bytes
- c) 4 bytes
- d) 8 bytes

Ans: c

18. What will be the maximum size of a double variable?

- a) 1 byte
- b) 4 bytes
- c) 8 bytes
- d) 16 bytes

Ans: c

19. A declaration float a,b; occupies ___ of memory

- a) 1 byte
- b) 4 bytes
- c) 8 bytes
- d) 16 bytes

Ans: c

20. The size of a String variable is

- a) 1 byte
- b) 8 bytes
- c) 16 bytes
- d) None of these

Ans: d

21. Which of the following is an example of compounded assignment statement?

- a) a=5
- b) a+=5
- c) a=b=c
- d) a=b

Ans: b

22. The operator && is an example for ___ operator.

- a) Assignment
- b) Increment
- c) Logical
- d) Rational

Ans: c

23. The operator & is used for

- a) Bitwise AND
- b) Bitwise OR
- c) Logical AND

d) Logical OR

Ans: a

24. The operator / can be applied to

a) integer values

b) float values

c) double values

d) All of these

Ans: b

25. The equality operator is represented by

a) :=

b) .EQ.

c) =

d) ==

Ans: d

26. Operators have hierarchy. It is useful to know which operator

a) is most important

b) is used first

c) is faster

d) operates on large numbers

Ans: b

27. The bitwise AND operator is used for

a) Masking

b) Comparison

c) Division

d) Shifting bits

Ans: a

28. The bitwise OR operator is used to

a) set the desired bits to 1

b) set the desired bits to 0

c) divide numbers

d) multiply numbers

Ans: a

29. Which of the following operator has the highest precedence?

a) *

b) ==

c) =>

d) +

Ans: d

30. The associativity of ! operator is

a) Right to Left

b) Left to Right

c) (a) for Arithmetic and (b) for Relational

d) (a) for Relational and (b) for Arithmetic

Ans: a

31. Which operator has the lowest priority?

a) ++

b) %

c) +

d) ||

Ans: d

32. Which operator has the highest priority?

a) ++

b) %

c) +

d) ||

Ans: a

33. Operators have precedence. Precedence determines which operator is

a) faster

b) takes less memory

c) evaluated first

d) takes no arguments

Ans: c

34. Integer Division results in

a) Rounding the fractional part

b) Truncating the fractional part

c) Floating value

d) An Error is generated

Ans: b

35. Which of the following is a ternary operator?

- a) `?:`
- b) `*`
- c) `sizeof`
- d) `^`

Ans: a

36. What will be the output of the expression `11 ^ 5`?

- a) 5
- b) 6
- c) 11
- d) None of these

Ans: d

37. The type cast operator is

- a) `(type)`
- b) `cast()`
- c) `::`
- d) `// " "`

Ans: a

38. Explicit type conversion is known as

- a) Casting
- b) Conversion
- c) Disjunction
- d) Separation

Ans: a

39. The operator `+` in `a+=4` means

- a) `a=a+4`
- b) `a+4=a`
- c) `a=4`
- d) `a=4+4`

Ans: a

40. `p++` executes faster than `p+1` because

- a) `p` uses registers
- b) `p++` is a single instruction
- c) `++` is faster than `+`

d) None of these

Ans: b

41. Which of the following statements is true?

a) C Library functions provide I/O facilities

b) C inherent I/O facilities

c) C doesn't have I/O facilities

d) Both (a) and (c)

Ans: a

42. Header files in C contain

a) Compiler commands

b) Library functions

c) Header information of C programs

d) Operators for files

Ans: b

43. Which pair of functions below are used for single character I/O.

a) Getchar() and putchar()

b) Scanf() and printf()

c) Input() and output()

d) None of these

Ans: a

44. The printf() function returns which value when an error occurs?

a) Positive value

b) Zero

c) Negative value

d) None of these

Ans: c

45. Identify the wrong statement

a) putchar(65)

b) putchar('x')

c) putchar("x")

d) putchar('\n')

Ans: c

46. Which of the following is character oriented console I/O function?

a) getchar() and putchar()

- b) gets() and puts()
- c) scanf() and printf()
- d) fgets() and fputs()

Ans: a

47. The output of printf("%u", -1) is

- a) -1
- b) minimum int value
- c) maximum int value
- d) Error message

Ans: c

48. An Ampersand before the name of a variable denotes

- a) Actual Value
- b) Variable Name
- c) Address
- d) Data Type

Ans: c

49. Symbolic constants can be defined using

- a) # define
- b) const
- c) symbols
- d) None of these

Ans: b

50. Null character is represented by

- a) \n
- b) \0
- c) \o
- d) \e

Ans: b

51. Which header file is essential for using strcmp() function?

- a) string.h
- b) strings.h
- c) text.h
- d) strcmp.h

Ans: a

52. malloc() function used in dynamic allocation is available in which header file?

- a) stdio.h
- b) stdlib.h
- c) conio.h
- d) mem.h

Ans: b

53. File manipulation functions in C are available in which header file?

- a) streams.h
- b) stdio.h
- c) stdlib.h
- d) files.h

Ans: d

54. C supports how many basic looping constructs

- a) 2
- b) 3
- c) 4
- d) 6

Ans: b

55. A statement differs from expression by terminating with a

- a) ;
- b) :
- c) NULL
- d) .

Ans: a

56. What should be the expression return value for a do-while to terminate

- a) 1
- b) 0
- c) -1
- d) NULL

Ans: b

57. Which among the following is an unconditional control structure

- a) do-while
- b) if-else
- c) goto

d) for

Ans: c

58. Continue statement is used

a) to go to the next iteration in a loop

b) come out of a loop

c) exit and return to the main function

d) restarts iterations from the beginning of the loop

Ans: a

59. Which operator in C is called a ternary operator

a) if..then

b) ++

c) ?:

d) ()

Ans: c

60. Which of the following header file is required for strcpy() function?

a) string.h

b) strings.h

c) files.h

d) strcsspy()

Ans: a

61. The meaning of conversion character for data input is

a) Data item is a long integer

b) Data item is an unsigned decimal integer

c) Data item is a short integer

d) None of the above

Ans: c

62. The conversion characters for data input means that the data item is

a) An unsigned decimal integer

b) A short integer

c) A hexadecimal integer

d) A string followed by white space

Ans: b

63. An expression contains relational, assign. ment and arithmetic operators. If Parenthesis are not present, the order will be

- a) Assignment, arithmetic, relational
- b) Relational, arithmetic, assignment
- c) Assignment, relational, arithmetic
- d) Arithmetic, relational, assignment

Ans: d

64. Which of the following is a keyword is used for a storage class

- a) printf
- b) external
- c) auto
- d) scanf

Ans: c

65. In the C language 'a' represents

- a) a digit
- b) an integer
- c) a character
- d) a word

Ans: c

66. The number of relational operators in the C language is

- a) Four
- b) Six
- c) Three
- d) One

Ans: b

67. A compound statement is a group of statements included between a pair of

- a) double quote
- b) curly braces
- c) parenthesis
- d) a pair of /'s

Ans: a

68. A Link is

- a) a compiler
- b) an active debugger
- c) a C interpreter
- d) an analyzing tool in C

Ans: d

69. The continue command cannot be used with

- a) for
- b) switch
- c) do
- d) while

Ans: a

70. In C, a Union is

- a) memory location
- b) memory store
- c) memory screen
- d) None of these

Ans: b

71. When the main function is called, it is called with the arguments

- a) argc
- b) argv
- c) None of these
- d) both a & b

Ans: d

72. A multidimensional array can be expressed in terms of

- a) array of pointers rather than as pointers to a group of a contiguous array
- b) array without the group of a contiguous array
- c) data type arrays
- d) None of these

Ans: a

73. C allows arrays of greater than two dimensions, who will determine this

- a) programmer
- b) compiler
- c) parameter
- d) None of these

Ans: b

74. A pointer to a pointer is a form of

- a) multiple indirections
- b) a chain of pointers
- c) both a and b

d) None of these

Ans: c

75. Pointers are of

a) integer data type

b) character data type

c) unsigned integer data types

d) None of these

Ans: d

76. Maximum number of elements in the array declaration `int a[5][8]` is

a) 28

b) 32

c) 35

d) 40

Ans: d

77. If the size of the array is less than the number of initializers then,

a) Extra values are being ignored

b) Generates an error message

c) Size of Array is increased

d) Size is neglected when values are given

Ans: a

78. Array subscripts in C always start at

a) -1

b) 1

c) 0

d) Value provided by the user

Ans: c

79. A Structure

a) can be read as a single entity

b) cannot be read as a single entity

c) can be displayed as a single entity

d) has member variables that cannot be read individually

Ans: b

80. Which is the correct way to declare a pointer?

a) `int_ptr;`

- b) `int *ptr;`
- c) `*int ptr;`
- d) None of these.

Ans: b

81. If you want to exchange two rows in a two-dimensional array, the fastest way is to:

- a) Exchange the elements of the 2rows
- b) Exchange the address of each element in the two-row
- c) Silence the address of the rows in an array of the pointer and exchange the pointer
- d) None of these.

Ans: c

82. A typecast is used to

- a) Define a new data type
- b) Force a value to be a particular variable type
- c) Rename an old type
- d) None of these.

Ans: b

83. Operator precedence determines which operator

- a) Operators on the largest number
- b) Is used first
- c) Is most important
- d) None of these.

Ans:b

84. If you don't initialize a static array, what will be the element set to?

- a) Zero
- b) A floating-point
- c) An undetermined value
- d) None of these.

Ans: a

85. Which is more appropriate for reading in a multi-word string?

- a) `gets( )`
- b) `Printf( )`
- c) `scanf( )`

d) puts ().

Ans: a

86. The process of translating a source program into machine language is a function of:

- a) Compiler
- b) Translator
- c) Assembler
- d) None of these.

Ans: a

87. Function argument can be

- a) A structure member
- b) A pointer variable
- c) A complete structure
- d) All of the above.

Ans: d

88. A "switch" statement is used to:

- a) Switch between user-defined functions in a program
- b) Switch from one variable to another variable
- c) Jump from one place to another in a program.
- d) None of these.

Ans: d

89. Consider the foll statement: "using C language programmers can write their own library functions".

- a) True
- b) False
- c) Maybe
- d) None of these.

Ans: a

90. C is a _____ level programming language?

- a) Low
- b) High
- c) Middle
- d) None of these.

Ans: c

91. A function is a subroutine that may include one or more _____ designed to perform a specific task.

- a) Functions
- b) Statements
- c) Libraries
- d) Datatypes.

Ans:b

92. What is used as a terminator in C?

- a) ?
- b) ;
- c) :
- d) _

Ans: b

93. Which function is necessary to exist in each & every program?

- a) void
- b) sum
- c) main
- d) None of these.

Ans: c

94. What is the answer of: 7%3

- a) 2.5
- b) 1
- c) 2
- d) 3

Ans: b

95. The _____ chars have values from -128 to 127.

- a) signed
- b) unsigned
- c) long
- d) none

Ans: a

96. What is the control character for "a single character".

- a) %c
- b) %d
- c) %i

d) %p

Ans: a

97. What is the control character for "a decimal integer".

a) %c

b) %d

c) %i

d) %p

Ans: b

98. What is the control character for "a floating point number".

a) %c

b) %d

c) %i

d) %f

Ans: d

99. C supports the _____ statement to branch unconditionally from one point to another in the program.

a) continue

b) goto

c) break

d) for

Ans: b

100. The _____ is used to break out of the case statements.

a) continue

b) break

c) default

d) case

Ans: b