

PUTTY:

host name: shrek.unideb.hu

port: 2222

(Neptun)Login name

Login password

Today:

//pwd

Show my location is filesystem

//echo \$HOME

\$HOME - path to your home directory

//cd /

//pwd

Make the root directory your current dir.

pwd - verify

//cd

//pwd

change back to your home dir.

verify

//mkdir - make new directory

//cd <path>

example:

cd exampleDir

mkdir anotherExampleDir

cd .. (step back)

cd /exampleDir/anotherExampleDir

touch <filename>
Make empty file
example: touch example.txt

//nano example.txt
//F3 to save
//Ctrl+x to exit

echo "Hello monday"
//Write "Hello monday" to console

//echo hello > example1.txt
//Write hello to example1 txt file

example:echo blabla > example2.txt
ls
cat example2.txt //Show what contains the file

//>' symbol REWRITE
//>>' symbol adds a new line

//Delete file or folder/directory
rm -r <folder/or_file>
Example:
rm -r example.txt
rm -r folder1

//mv can rename files and folders

```
# mv <old_name> <new_name>
```

Example:

```
# mv folder1 folder2
```

```
//List directories with start "D" character
```

```
# ls D*
```

```
# ls D* -l -d
```

```
//Echo command for list
```

```
# echo D*
```

```
# echo P*
```

```
//List files and directories end with "s"
```

```
# echo *s
```

```
# echo *es
```

```
//List files and directories with start
```

```
//"D", include "n" and end with "s"
```

```
# echo D*n*s
```

```
//List 6 character long files and folders
```

```
# echo ??????
```

```
//List files and directories
```

```
//Start with "D" and 9 character long
```

```
// 9x ? character
```

```
# echo D?????????
```

```
//List files and directories
```

```
//Minimum 4 character long,
```

```
//and more, and ends with "s"
```

```
# echo ?????*s
```

```
//List files and directories
// The name include From "D" to "P"
#echo [DP]*
```

```
//List files and directories
//The name NOT include From "D" to "P"
# echo [!DP]*
```

```
//cp - copy
//Copy <file_name> file to my home folder
//example: cp /etc/hosts hosts
```

```
cp <file_name> <name>
```

```
//ls -a
-la:shows hidden files(begin with a dot character)
```