



Republic of the Philippines
Tarlac State University
COLLEGE OF COMPUTER STUDIES
Tarlac City, Tarlac
Tel. No. (045) 6068173



Step Algo: A Page-Replacement Algorithm Visualizer

github.com/shoichiideologies/page-replacement-algorithm

A Case Study Presented to
The Instructor of the Course
Operating System

In Partial Fulfillment
of the Requirements for the Course
Operating System

Angelo V. Miranda

Instructor:
Jo Anne Cura



Table of Contents

I. Introduction 3

1.1 Page Replacement Algorithms 3

 1.1.1 First-In-First-Out (FIFO) Algorithm 4

 1.1.2 Last Recently Used (LRU) Algorithm] 4

 1.1.3 Optimal Page Replacement 4

1.2 Comparison of Time and Space Complexities of each Algorithms 4

1.3 Analysis 5

II. Documentation 7

 2.1 User Interface..... 7

 2.1.1 Computation Tab 7

 2.1.2 Information Tab 8

 2.2 Source Code..... 13

 2.1.3 Renderer.js..... 13



I. Introduction

In an operating system that uses paging for memory management, a page replacement algorithm is needed to decide which page needs to be replaced when a new page comes in. Page replacement becomes necessary when a page fault occurs and no free page frames are in memory. In this article, we will discuss different types of page replacement algorithms.

1.1 Page Replacement Algorithms

Page replacement algorithms are techniques to manage memory efficiently when the physical memory is full. When a new page needs to be loaded into physical memory, and there is no free space, these algorithms determine which existing page to replace.

If no page frame is free, the virtual memory manager performs a page replacement operation to replace one of the pages existing in memory with the page whose reference caused the page fault. It is performed as follows: The virtual memory manager uses a page replacement algorithm to select one of the pages currently in memory for replacement, accesses the page table entry of the selected page to mark it as “not present” in memory, and initiates a page-out operation for it if the modified bit of its page table entry indicates that it is a dirty page.



1.1.1 First-In-First-Out (FIFO) Algorithm

First-In, First-Out (FIFO) is one of the simplest page replacement algorithms. It works exactly like a queue. The oldest page in memory the one that was loaded first is the first to be removed when space is needed for a new page. Imagine a line of people entering a room; the first person in line is also the first to leave. While FIFO is easy to implement and understand, it doesn't always make the best choices. It may remove pages that are still being used frequently, which can increase the number of page faults. This algorithm is also known to suffer from Belady's anomaly, where adding more memory can unexpectedly lead to worse performance.

1.1.2 Last Recently Used (LRU) Algorithm]

Least Recently Used (LRU) is a smarter page replacement algorithm that tries to guess which pages are no longer needed. It removes the page that has not been used for the longest time, based on the idea that pages used recently are more likely to be used again soon. Think of it like choosing which app to close on your phone you'd probably keep open the one you just used and close the one you haven't touched in hours. LRU is more efficient than FIFO in many real-world situations, especially when programs tend to reuse data shortly after accessing it. However, it requires keeping track of when each page was last used, which may add extra complexity and memory usage depending on the implementation.

1.1.3 Optimal Page Replacement

Optimal Page Replacement (OPT) is a theoretical algorithm that always makes the best possible choice by replacing the page that will not be used for the longest time in the future. It achieves the fewest possible page faults for any given reference string and number of page frames. However, since no real system can predict future memory accesses, OPT can't actually be implemented in practice. It's mainly used as a benchmark to compare the performance of other algorithms like FIFO and LRU.



In cases where two or more pages in memory will not be used again, all of them are equally valid candidates for replacement. In this simulator, the algorithm selects the first-found page among them. This choice is preferred over random selection because it is consistent, predictable, and faster to compute, making it more suitable for simulation and educational purposes.

1.2 Comparison of Time and Space Complexities of each Algorithms

Algorithm	Time Complexity	Space Complexity
First-In-First-Out (FIFO)	$O(n)$ per operation (naïve), $O(1)$ with hash for lookup + queue	$O(n)$
Last Recently Used (LRU)	$O(n)$ naïve, $O(1)$ optimized with HashMap + Doubly Linked List	$O(n)$ frames + $O(n)$ recency metadata
Optimal (OPT)	$O(n)$ per replacement (scan future)	Needs full knowledge of future – only usable for benchmarking

1.3 Analysis

When simulating the FIFO, LRU, and Optimal page replacement algorithms, the most efficient one is identified based on the lowest number of page faults. If a single algorithm produces fewer page faults than the others, it is directly considered the most efficient for the given reference string and memory size. This straightforward case reflects a clear performance advantage and requires no further comparison.

In scenarios where all three algorithms FIFO, LRU, and Optimal, have the same number of page faults, the system applies a tie-breaking preference. Among them, LRU is recommended due to its strong balance between practical efficiency and real-world usability. While FIFO is easy to implement, it may remove frequently used pages and suffers from Belady’s anomaly. Optimal, though theoretically the best with minimal page faults, is impractical for real systems because it requires advance knowledge of future page references.

If two algorithms are tied for the lowest page fault count, the recommendation depends on which algorithms are involved. If LRU is among the tied algorithms, it is



Republic of the Philippines
Tarlac State University
COLLEGE OF COMPUTER STUDIES
Tarlac City, Tarlac
Tel. No. (045) 6068173



preferred because of its consistent and realistic performance. If FIFO is part of the tie but LRU is not, FIFO is chosen for its simplicity. However, if the tie includes Optimal but not LRU, then Optimal is acknowledged for its theoretical excellence, but still considered less practical due to its dependence on future information. These tie-handling rules ensure that algorithm selection is based not only on performance, but also on real-world feasibility.



II. Documentation

2.1 User Interface

2.1.1 Computation Tab

ComputationInformation

Page Replacement Algorithm Visualizer

Enter Page Frames: 3Page String: 20Random Reference Page String: 7,0,1,2,0,3,0,4,2,3,0,3,2,1,2,0,1,7,0,1

Calculate

First-In-First-Out (FIFO) Algorithm

7	0	1	2	0	3	0	4	2	3	0	3	2	1	2	0	1	7	0	:
7	7	7	2		2	2	4	4	4	0			0	0			7	7	:
	0	0	0		3	3	3	2	2	2			1	1			1	0	:
		1	1		1	0	0	0	3	3			3	2			2	2	:

Page Faults: 15

Least Recently Used (LRU) Algorithm

7	0	1	2	0	3	0	4	2	3	0	3	2	1	2	0	1	7	0	:
7	7	7	2		2		4	4	4	0			1	2		1	1		:
	0	0	0		0		0	0	3	3			3			0	0		:
		1	1		3		3	2	2	2			2			2	7		:

Page Faults: 12

Optimal (OPT) Algorithm

7	0	1	2	0	3	0	4	2	3	0	3	2	1	2	0	1	7	0	:
7	7	7	2		2		2			2			2				7		:
	0	0	0		0		4			0			0				0		:
		1	1		3		3			3			1				1		:

Page Faults: 9

Analysis

Algorithm	Page Fault
First-In-First-Out (FIFO)	15
Least Recently Used (LRU)	12
Optimal (OPT)	9

The most efficient algorithm on allocating [3] page frames with a reference page string of length [20] is **Optimal**. It is the most efficient with [9] page faults.



2.1.2 Information Tab

ComputationInformation

Page-Replacement Algorithms

In modern computing, efficient memory management is critical for performance. One important technique is [demand paging](#), where only the necessary parts of a program are loaded into memory as needed. However, when memory becomes full, the operating system must decide which [page](#) to remove to make space for a new one. This decision is made using page-replacement algorithms. Among the various algorithms, three are especially important: First-In, First-Out (FIFO), Optimal Page Replacement (OPT), and Least Recently Used (LRU).

First-In-First-Out (FIFO) Algorithm

First-In, First-Out (FIFO) is one of the simplest page replacement algorithms. It works exactly like a [queue](#): the oldest [page](#) in memory—the one that was loaded first—is the first to be removed when space is needed for a new [page](#). Imagine a line of people entering a room; the first person in line is also the first to leave. While FIFO is easy to implement and understand, it doesn't always make the best choices. It may remove [pages](#) that are still being used frequently, which can increase the number of page faults. This algorithm is also known to suffer from [Belady's anomaly](#), where adding more memory can unexpectedly lead to worse performance.

Time complexity: $O(n)$ per operation (naïve), $O(1)$ with hash for lookup + queue

Space complexity: $O(n)$

Least Recently Used (LRU) Algorithm

Least Recently Used (LRU) is a smarter page replacement algorithm that tries to guess which [pages](#) are no longer needed. It removes the [page](#) that has not been used for the longest time, based on the idea that [pages](#) used recently are more likely to be used again soon. Think of it like choosing which app to close on your phone—you'd probably keep open the one you just used and close the one you haven't touched in hours. LRU is more efficient than FIFO in many real-world situations, especially when programs tend to reuse data shortly after accessing it. However, it requires keeping track of when each [page](#) was last used, which may add extra complexity and memory usage depending on the implementation.

Time complexity: $O(n)$ (naïve), $O(1)$ optimized with [HashMap](#) + [Doubly Linked List](#)

Space complexity: $O(n)$ frames + $O(n)$ recency metadata

Optimal (OPT) Algorithm

Optimal Page Replacement (OPT) is a theoretical algorithm that always makes the best possible choice by replacing the [page](#) that will not be used for the longest time in the future. It achieves the fewest possible page faults for any given [reference string](#) and number of page frames. However, since no real system can predict future memory accesses, OPT can't actually be implemented in practice. It's mainly used as a [benchmark](#) to compare the performance of other algorithms like FIFO and LRU.

In cases where two or more [pages](#) in memory will not be used again, all of them are equally valid candidates for replacement. In this simulator, the algorithm selects the [first-found page](#) among them. This choice is preferred over [random selection](#) because it is consistent, predictable, and faster to compute, making it more suitable for simulation and educational purposes.

Time complexity: $O(n)$ per replacement (scan future)

Space complexity: Requires full future knowledge – only usable for [benchmark](#)

Glossary of Terms

Page: A fixed-size block of memory used in virtual memory systems. Pages are loaded into frames for program execution.

Belady's Anomaly: A situation where adding more memory results in more page faults under certain algorithms like FIFO.

Time Complexity: Describes how the running time of an algorithm scales with input size.

Space Complexity: Describes how much memory an algorithm uses relative to input size.

First-Found: A method that selects the first available option, often for simplicity and consistency.

Random Selection: A method that chooses an option randomly from valid candidates.

Demand Paging: A strategy where pages are loaded into memory only when needed.

Naïve: A basic or unoptimized approach to solving a problem.

Queue: A First-In, First-Out (FIFO) data structure where the first item added is the first removed.

Linked List: A sequence of nodes where each node points to the next, allowing dynamic memory usage.

HashMap: A key-value data structure that allows constant time data access using hashes.

Metadata: Information that describes or gives context to other data.

Frames: Fixed-size memory slots that hold pages during program execution.

Reference String: A sequence showing the order in which memory pages are accessed.

Benchmarking: Evaluating algorithms by comparing performance metrics on standard inputs.

$O(n)$: Linear time complexity, where processing time grows with input size.

$O(1)$: Constant time complexity, where operations take the same time regardless of input size.

Computer Science final project in Operating System by Angelo Miranda
[shoichiideologies/Github](#)



2.2 Example Outputs

2.2.1 3 Page Frames; 10 Page String

Computation

Information

Page Replacement Algorithm Visualizer

Enter Page Frames: 3Page String: 10Random Reference Page String: 3,3,5,7,3,8,3,9,6,9

Calculate

First-In-First-Out (FIFO) Algorithm

3357383969

33338886

555333

7799

Page Faults: 7

Least Recently Used (LRU) Algorithm

3357383969

333333

558866

7799

Page Faults: 6

Optimal (OPT) Algorithm

3357383969

333399

558866

7777

Page Faults: 6

Analysis

Algorithm	Page Fault
First-In-First-Out (FIFO)	7
Least Recently Used (LRU)	6
Optimal (OPT)	6

The most efficient algorithm on allocating [3] page frames with a reference page string of length [10] is LRU and Optimal. They are tied with [6] page faults. LRU. This algorithm is preferred due to better practical efficiency.



2.2.2 4 Page Frame; 17 Page String

Computation

Information

Page Replacement Algorithm Visualizer

Enter Page Frames: 4Page String: 17Random Reference Page String: 6,5,2,9,0,9,2,5,5,5,4,2,3,0,0,6,8

Calculate

First-In-First-Out (FIFO) Algorithm

65290925554230068

66660

5555

2229

042300

68

Page Faults: 9

Least Recently Used (LRU) Algorithm

65290925554230068

66660

5555

2229

4444

5550

2223

99

66

88

Page Faults: 10

Optimal (OPT) Algorithm

65290925554230068

66660

5555

2229

04300

68

Page Faults: 9

Analysis

Algorithm	Page Fault
First-In-First-Out (FIFO)	9
Least Recently Used (LRU)	10
Optimal (OPT)	9

The most efficient algorithm on allocating [4] page frames with a reference page string of length [17] is **FIFO and Optimal**. They are tied with [9] page faults. **FIFO**. This algorithm is preferred for its simplicity.



2.2.3 5 Page Frame; 25 page String

Computation

Information

Page Replacement Algorithm Visualizer

Enter Page Frames: 5Page String: 25Random Reference Page String: 8,5,6,7,4,8,0,1,2,0,0,9,6,9,3,6,1,5,8,0,1,6

Calculate

First-In-First-Out (FIFO) Algorithm

8567480120096936158

888880000000030033

55555511111111555

66666662222222888

77777779999999999

44444444666666666

Page Faults: 15

Least Recently Used (LRU) Algorithm

8567480120096936158

888888888000086066

5555555000000005555

6666666611111113333

7777777722222222111

444444449999999999988

Page Faults: 15

Optimal (OPT) Algorithm

8567480120096936158

888882938856001

55555555555555555

6666666600000000000

7777700000000000000

4441111111111111111

Page Faults: 11

Analysis

Algorithm	Page Fault
First-In-First-Out (FIFO)	15
Least Recently Used (LRU)	15
Optimal (OPT)	11

The most efficient algorithm on allocating [5] page frames with a reference page string of length [25] is **Optimal**. It is the most efficient with [11] page faults.



2.2.3 10 Page Frame; 25 Page String

Computation

Information

Page Replacement Algorithm Visualizer

Enter Page Frames: 10Page String: 25Random Reference Page String: 8,5,6,7,4,8,0,1,2,0,0,9,6,9,3,6,1,5,8,0,1

Calculate

First-In-First-Out (FIFO) Algorithm

8567480120096936158

88888

55555

66666

77777

44444

00000

11111

22222

99999

66666

99999

33333

66666

11111

55555

88888

Page Faults: 10

Least Recently Used (LRU) Algorithm

8567480120096936158

88888

55555

66666

77777

44444

00000

11111

22222

99999

66666

99999

33333

66666

11111

55555

88888

Page Faults: 10

Optimal (OPT) Algorithm

8567480120096936158

88888

55555

66666

77777

44444

00000

11111

22222

99999

66666

99999

33333

66666

11111

55555

88888

Page Faults: 10

Analysis

Algorithm	Page Fault
First-In-First-Out (FIFO)	10
Least Recently Used (LRU)	10
Optimal (OPT)	10

The most efficient algorithm on allocating [10] page frames with a reference page string of length [25] is LRU. Given that all algorithms have [10] page faults. Based on time and space complexity, LRU is preferred because it performs well in practice and does not require future knowledge like Optimal.



2.3 Source Code

2.2.3 Renderer.js

2.2.3.1 Analysis

```
function determineBestAlgorithm() {  
    const results = {  
        FIFO: fifoPageFaults,  
        LRU: lruPageFaults,  
        Optimal: optimalPageFaults,  
    };  
  
    const minFaults = Math.min(...Object.values(results));  
  
    // Find all algorithms that have the minimum fault count  
    const bestAlgorithms = Object.entries(results)  
        .filter(([_, faults]) => faults === minFaults)  
        .map([algo] => algo);  
  
    const outputElement = document.querySelector('#efficient-algo');  
  
    if (bestAlgorithms.length === 1) {  
        outputElement.textContent = `${bestAlgorithms[0]}. It is the most  
efficient with [${minFaults}] page faults.`;  
    } else if (bestAlgorithms.length === 3) {  
        // All tied – compare by complexity  
        outputElement.textContent  
= `LRU. Given that all algorithms have [${minFaults}] page faults. Based on time  
and space complexity,  
+ 'LRU is preferred because it performs well in practice and does not require  
future knowledge like Optimal.';  
    } else {  
        // Tie between 2 algorithms  
        const list = bestAlgorithms.join(' and ');  
        let recommended = ``;  
  
        if (bestAlgorithms.includes('LRU')) {  
            recommended = 'LRU. This algorithm is preferred due to better  
practical efficiency.';  
        } else if (bestAlgorithms.includes('FIFO')) {  
            recommended = 'FIFO. This algorithm is preferred for its  
simplicity.';  
        } else {  
            recommended = 'Optimal. This algorithm is the theoretically best,  
but not practical in real-world systems.';  
        }  
  
        outputElement.textContent  
= `${list}. They are tied with [${minFaults}] page faults. ${recommended}`;  
    }  
}
```

2.2.3.2 Simulate Algorithms

```
function simulateAlgorithms(referenceString, frameCount) {  
    const simulations = document.querySelectorAll('.simulation');  
  
    fifoQueue = [];  
    fifoPageFaults = 0;  
    lruPageFaults = 0;  
    optimalPageFaults = 0;  
  
    for (const simulation of simulations) {  
        const algoId = simulation.id;  
        const pageContainer = simulation.querySelector('.page-container');  
        const pageDivs = pageContainer.querySelectorAll('.page');  
  
        for (const pageDiv of pageDivs) {  
            pageDiv.innerHTML = ``;  
        }  
  
        const frames = [];  
  
        for (const [index, pageNumber] of referenceString.entries()) {  
            let pageFault = false;  
  
            switch (algoId) {  
                case 'fifo': {  
                    pageFault = simulateFIFO(frames, frameCount, pageNumber);  
                    break;  
                }  
  
                case 'lru': {  
                    pageFault = simulateLRU(frames, frameCount, pageNumber,  
referenceString.slice(0, index));  
                    break;  
                }  
  
                case 'optimal': {  
                    pageFault = simulateOptimal(frames, frameCount,  
pageNumber, referenceString.slice(index + 1));  
                    break;  
                }  
            }  
        }  
    }  
}
```



```
        }
        // No default
    }

    const pageDiv = pageDivs[index];
    if (pageFault) {
        for (const framePage of frames) {
            const pageResult = document.createElement('div');
            pageResult.className = 'page-results';
            pageResult.textContent = framePage;
            pageResult.style.width = '100%';
            pageResult.style.height = '30px';
            pageResult.style.borderRadius = 'inherit';
            pageDiv.append(pageResult);
        }
    }
    // Otherwise, leave blank for page hits
}

// After loop, update page fault result
switch (algoId) {
    case 'fifo': {
        document.querySelector('#fifo-page-faults-result').textContent =
        fifoPageFaults;
        document.querySelector('#fifo-page-fault').textContent =
        fifoPageFaults;
        break;
    }
    case 'lru': {
        document.querySelector('#lru-page-faults-result').textContent =
        lruPageFaults;
        document.querySelector('#lru-page-fault').textContent =
        lruPageFaults;
        break;
    }
    case 'optimal': {
        document.querySelector('#optimal-page-faults-result').textContent =
        optimalPageFaults;
        document.querySelector('#optimal-page-fault').textContent =
        optimalPageFaults;
        break;
    }
    // No default
}

// Compare the page faults to find the best algorithm
determineBestAlgorithm();
}
```

2.2.3.2.1 FIFO

```
let lruPageFaults = 0; // Counter for LRU faults (declare global like
fifoPageFaults)

function simulateLRU(frames, frameCount, currentPage, pastPages) {
    let changed = false;

    if (!frames.includes(currentPage)) {
        changed = true; // It is a page fault
        lruPageFaults++;

        if (frames.length < frameCount) {
            frames.push(currentPage);
        } else {
            // Find the least recently used page
            let lruIndex = -1;
            let lruPage = null;
            for (const page of frames) {
                const lastUsed = pastPages.lastIndexOf(page);
                if (lruIndex === -1 || lastUsed < lruIndex) {
                    lruIndex = lastUsed;
                    lruPage = page;
                }
            }

            const replaceIndex = frames.indexOf(lruPage);
            frames[replaceIndex] = currentPage; // Replace LRU page
            in same position
        }
    }

    return changed; // Return true if page fault occurred
}

let optimalPageFaults = 0; // Counter for Optimal faults (global)
```




2.2.3.2.2 LRU

```
function simulateOptimal(frames, frameCount, currentPage, futurePages) {  
    let changed = false;  
  
    if (!frames.includes(currentPage)) {  
        changed = true;  
        optimalPageFaults++;  
  
        if (frames.length < frameCount) {  
            frames.push(currentPage);  
        } else {  
            let farthestIndex = -1;  
            let pageToReplace = null;  
  
            for (const page of frames) {  
                const nextUse = futurePages.indexOf(page);  
  
                if (nextUse === -1) {  
                    // This page is never used again → best to replace  
                    farthestIndex = Infinity;  
                    pageToReplace = page;  
                } else if (nextUse > farthestIndex) {  
                    // Find page used farthest in future  
                    farthestIndex = nextUse;  
                    pageToReplace = page;  
                }  
            }  
  
            const replaceIndex = frames.indexOf(pageToReplace);  
            frames[replaceIndex] = currentPage; // Replace at the same slot  
        }  
    }  
  
    return changed; // Return whether page fault occurred  
}
```

2.2.3.2.3 OPT

```
let fifoQueue = []; // FIFO queue for arrival order  
let fifoPageFaults = 0; // Counter for page faults  
function simulateFIFO(frames, frameCount, currentPage) {  
    let changed = false;  
  
    if (!frames.includes(currentPage)) {  
        changed = true; // It is a page fault  
        fifoPageFaults++;  
  
        if (frames.length < frameCount) {  
            frames.push(currentPage);  
            fifoQueue.push(currentPage);  
        } else {  
            const oldestPage = fifoQueue.shift(); // Remove oldest  
            const oldestIndex = frames.indexOf(oldestPage); // Find  
            frames[oldestIndex] = currentPage; // Replace at same  
            fifoQueue.push(currentPage);  
        }  
    }  
  
    return changed; // Return whether page fault occurred  
}
```



Republic of the Philippines
Tarlac State University
COLLEGE OF COMPUTER STUDIES
Tarlac City, Tarlac
Tel. No. (045) 6068173

