Supplementary Material

Temporal Retiming Attacks on Hybrid Quantum Spiking Classifiers

Authors withheld for review

This supplement preserves completed supporting experiments and the full paired timestamp comparison. Historical studies are not additional final-model N-MNIST robustness evaluations. Every section states the model, partition and evidence boundary needed for interpretation. Numerical values are transcribed from preserved reports; model training, attacks and original independent audits were not rerun during preparation. Source identifiers [R1]–[R10] are mapped to exact repository paths in Section S11.

S1 Development of the hybrid architecture

The selected development configurations are summarized in Table S1 and Figure S1. The earlier eight-dimensional frontend differs from the final 32-dimensional `wide4` frontend. Different training stages, continuation histories and budgets prevent causal attribution of the validation changes to a single circuit component. These are validation-only model-development results, rather than a controlled ablation establishing quantum advantage [R1].

Table S1. Selected quantum-head and frontend development results.

Configuration	Validation accuracy (%)	Parameters	Scope
Quantum v1	86.16	7,026	Earlier 8D frontend
Selected quantum head v2	92.60	7,130	Earlier 8D frontend
`wide4` classical control	97.80	38,122	32D frontend; seed 42
Final QSNN-v3	97.06	40,762	32D frontend; seed 42

Sources: [R1] and companion frontend/quantum-head development reports. Configuration changes and unequal training stages preclude a component-wise causal interpretation.

S1.1 Frozen final-model training details

All five QSNN-v3 runs share one hash-verified seed-42 pretrained frontend and one stratified 55,000/5,000 training/validation partition. The frontend is frozen for the first two epochs and then optimized while its BatchNorm layers remain in evaluation mode. Architecture and hyperparameters are frozen across seeds 42, 123, 777, 2026 and 6543. The official test partition is not instantiated for the final hybrid campaign [R1].

AdamW uses weight decay 10^{-4}, with learning rates 5×10^{-5} for the extractor, 2.5×10^{-4} for latent projection and circuit, and 10^{-3} for the classifier. Training uses batch size 256, a maximum of 40 epochs and gradient clipping at norm 1. The ReduceLROnPlateau schedule uses factor 0.5, patience 2 and minimum learning rate 10^{-5}. Checkpoint selection prioritizes validation accuracy and then validation loss; early stopping has patience 6 after at least eight epochs. The frontend uses float16 autocast, while circuit inputs are float32 and state amplitudes are complex64. These choices describe the simulated implementation and imply no quantum speedup.

The selected epochs are 37, 24, 40, 38 and 40; recorded runtimes are 1,200.00, 938.80, 1,245.30, 1,251.55 and 1,237.35 s, respectively. The seed-42 process was externally terminated during epoch 38, after saving its epoch-37 best checkpoint; that checkpoint was reloaded and evaluated for the reported result. Between-seed variability is conditional on shared pretraining and split, rather than variability across independently pretrained pipelines.




Figure S1. Validation-only development trajectory. Runs differ in frontend dimensions and training stages. The plot documents model development and is not a controlled ablation of quantum advantage [R1].

S2 Earlier binary-grid budget sweep

The historical representation-matched binary custom SNN has 98.73% clean accuracy on the complete 10,000-example official test partition. Its nine-budget attack sweep uses 1,000 clean-correct examples and a different checkpoint, temporal binning and manifest from the controlled four-model study. In particular, its $B_\infty = 1$ ASR is 82.9%, whereas the controlled campaign's custom-model rate is 100.0%. Both values are retained as results of separate experiments [R5].

Table S2. Historical binary-grid attack sweep.

Budget	Successes / N	ASR (%)	Actual B_∞	Actual B_1	Actual B_0
$B_\infty = 1$	829 / 1,000	82.9	1–1	568–2,604	568–2,604
$B_\infty = 2$	1,000 / 1,000	100.0	2–2	840–4,231	573–2,766
$B_\infty = 3$	1,000 / 1,000	100.0	3–3	1,092–5,545	576–2,841
$B_1 = 500$	1,000 / 1,000	100.0	3–9	500–500	268–463
$B_1 = 750$	1,000 / 1,000	100.0	4–9	750–750	364–615
$B_1 = 1{,}000$	1,000 / 1,000	100.0	6–9	1,000–1,000	438–790
$B_0 = 200$	1,000 / 1,000	100.0	8–9	683–955	200–200
$B_0 = 300$	1,000 / 1,000	100.0	8–9	1,051–1,403	300–300
$B_0 = 400$	1,000 / 1,000	100.0	9–9	1,369–1,913	400–400

All realized budget ranges are transcribed from the historical report [R5]; they are not regenerated from attack tensors. Budget families have different units: maximum displacement, total displacement and number of retimed packets.




Figure S2. Historical binary-grid success rates for three budget families. Units differ by family. This sweep is not merged with the controlled four-model results [R5].

The corrected integer-grid campaign separately freezes clean-correct manifests using only strict integer-grid predictions. Its status report lists 8 of 33 attack conditions complete and 25 remaining, with the next condition seed 42 and $B_0 = 300$. The preserved final ASR summary is absent. Historical integer attack values are excluded from the corrected campaign summary because they cannot replace its required corrected artifacts [R5].




Figure S3. Clean confusion matrix of the historical binary custom SNN on 10,000 official-test examples. The diagonal sums to 9,873, giving 98.73% accuracy. This is not a QSNN-v3 confusion matrix [R5].

S3 Clean neuromorphic baselines

Table S3. Three-seed clean classical baseline accuracy.

Dataset	Representation	Mean ± SD (%)	Evaluation scope
N-MNIST	Binary grid	98.5167 ± 0.2203	Official test
N-MNIST	Integer grid	98.3867 ± 0.2146	Official test
DVS-Gesture	Binary grid	81.3131 ± 2.8930	Official test
DVS-Gesture	Legacy integer	83.0808 ± 4.6289	Normalized counts
CIFAR10-DVS	Binary grid	50.4000 ± 2.0075	Frozen 10% test split
CIFAR10-DVS	Legacy integer	46.2000 ± 6.1733	Normalized counts

Seeds 42, 123 and 777. DVS-Gesture and CIFAR10-DVS rows historically labeled "integer" retain legacy normalized-count preprocessing and are **non-comparable** with strict integer grids [R6].




Figure S4. Classical clean accuracy across three seeds. Binary and N-MNIST integer rows are representation-matched. DVS-Gesture and CIFAR10-DVS integer rows retain legacy normalization and do not establish strict-integer performance [R6].

N-MNIST uses all 10,000 official-test examples and DVS-Gesture all 264 official-test examples per seed. CIFAR10-DVS uses a frozen class-stratified 10% split of 1,000 examples because there is no official train/test partition in this protocol. These are clean SNN baselines; they provide no additional QSNN attack or defense results.

S4 Iris attacks and quantum-state diagnostics

Table S4. Historical Iris attack means across five model seeds.

$100\varepsilon/T$	Classical ASR (%)	Adaptive TEMP ASR (%)	Classical $1-F$	Adaptive TEMP $1-F$
2	8.64 ± 6.22	8.64 ± 6.22	0.000987 ± 0.000000	0.000980 ± 0.000006
5	19.18 ± 8.28	19.18 ± 8.28	0.006109 ± 0.000039	0.005766 ± 0.000103
10	32.85 ± 9.67	33.54 ± 10.23	0.024069 ± 0.000276	0.021953 ± 0.000473

Seed-specific clean-correct denominators are 29, 29, 29, 23 and 27. ASR means average seed-specific ratios rather than pooling them. Drift values are reported pure product-state diagnostics [R8].




Figure S5. Earlier Iris ASR and state-drift diagnostics. At 10%, TEMP has one extra attack success, but the classical timing attack has larger mean drift. Error bars show between-model-seed variability on small evaluation subsets [R8].

At 10%, classical successes total 46/137 and adaptive TEMP successes 47/137 across the seed-specific populations. These pooled observations repeat the underlying dataset across model seeds, so they are not 137 independent subjects. The exact paired count table has zero classical-only and one TEMP-only success; it does not support attack superiority. The drift quantity refers to the Iris encoding and must not be substituted for an unmeasured N-MNIST circuit-state distance.

S5 Earlier Iris regularization and mechanism gate

Table S5. Earlier Iris regularization replication.

Measure	Baseline	Regularized model	Interpretation
Clean accuracy (%)	84.00 ± 9.25	84.00 ± 8.63	Mean change 0; one seed improves and one degrades
PGD 10% paired ASR (%)	25.58 ± 10.07	24.09 ± 8.45	Two rescued and zero broken across 125 repeated observations
Reference TEMP 10%	—	One rescued observation	Improvement confined to seed 42
Gradient TEMP	—	One rescued observation per τ	No improvement in the other four seeds

Fixed split seed 42; five paired model seeds; $\lambda_q = 5$ and $\lambda_{\text{pred}} = 0$. This is representation regularization, not tomography detection. Source: `results/phase153_results.md`, under [R9].

The Phase-21 confirmatory mechanism gate subsequently fails two of four criteria. Its split-level confidence interval crosses zero, so Stage B is blocked and no candidate defense is trained. An audit PASS in that report means that the negative gate result was handled according to the protocol; it does not mean that the proposed defense succeeded. No hidden-test defense result is inferred from nonexecution [R9].

S6 MNIST development and SHD classical testing

Table S6. Seed-42 MNIST clean validation screen.

PCA dimensions	Explained variance (%)	Validation accuracy (%)	Macro-F1 (%)
16	87.64	86.80	86.75
24	95.42	85.30	85.24
32	98.42	83.55	83.46

Downsampled 8×8 MNIST and a separate classifier; one development seed. Runs have different continuation and timeout histories. No attack or defense conclusion follows [R7].




Figure S6. MNIST validation accuracy versus PCA dimension. Retaining more variance did not improve validation accuracy in these development runs. This is not a matched-training-budget ablation [R7].

Table S7. SHD classical SNN official-test re-audit.

Seed	Test accuracy (%)	Macro-F1 (%)
42	65.7686	64.6785
123	69.7880	69.1100
777	66.2102	65.6300
2026	64.0018	63.1983
6543	64.1784	63.9006
Mean $\pm$ SD	65.9894 ± 2.3322	65.3035 ± 2.3123

The historical re-audit reports that recomputed values match its previous test values. This is classical SNN testing on a previously accessed test set, not a QSNN robustness study. Source: `results/shd_snn_test_reaudit_report.md`, under [R10].

S7 Quantum-state notation and monitoring bounds

S7.1 State angles, Bloch vector and density-matrix sign

For an individually encoded one-qubit state, the state-amplitude angle $\theta(t)$ and phase $\phi(t)$ define

$$|\psi(t)\rangle = \cos\theta(t)|0\rangle + e^{i\phi(t)}\sin\theta(t)|1\rangle. \tag{S1}$$

With the usual Pauli matrices, its Bloch vector is

$$\mathbf{r} = \big(\sin 2\theta\cos\phi,\ \sin 2\theta\sin\phi,\ \cos 2\theta\big). \tag{S2}$$

The density matrix and its upper-right entry are therefore

$$\rho = \frac{1}{2}\big(I + \mathbf{r}\cdot\boldsymbol{\sigma}\big), \qquad \rho_{01} = \frac{r_x - i r_y}{2}. \tag{S3}$$

This fixes the conjugation/sign ambiguity in the original appendix.

The repository's Iris angle encoder returns $\theta = \pi t/(2T)$, while a conventional R_Y gate uses rotation angle 2θ. Its amplitude option uses $\theta = \arccos\sqrt{1-t/T}$; its phase option uses $\theta = \pi/4$ and $\phi = 2\pi t/T$. State-amplitude angles and rotation-gate angles must therefore be distinguished. The N-MNIST latent circuit has a separate learned angle map and is not an ensemble average of independent per-event qubits.

S7.2 Squared fidelity and the pure-versus-ensemble distinction

We use squared Uhlmann fidelity,

$$F(\rho,\sigma) = \left[\mathrm{Tr}\sqrt{\sqrt{\rho}\,\sigma\sqrt{\rho}}\right]^2. \tag{S4}$$

For pure product states $|\Psi\rangle = \bigotimes_q |\psi_q\rangle$ and $|\Phi\rangle = \bigotimes_q |\phi_q\rangle$, the implemented squared overlap and trace distance are

$$F = |\langle\Psi|\Phi\rangle|^2 = \prod_q |\langle\psi_q|\phi_q\rangle|^2, \qquad D_{\mathrm{tr}} = \sqrt{1-F}. \tag{S5}$$

A mixed event ensemble instead has the form

$$\rho_{\mathrm{ens}} = \frac{1}{N}\sum_{i=1}^{N} |\psi(t_i)\rangle\langle\psi(t_i)| \tag{S6}$$

and requires the mixed-state fidelity in Eq. (S4). The pure product overlap and mixed ensemble fidelity are not interchangeable computational objects.

A one-qubit state is completely determined by its Bloch vector. Identical Bloch vectors imply identical density matrices and zero quantum Jensen–Shannon divergence; there is no additional phase difference hidden from all three Pauli expectations for a single-qubit density matrix. For eight qubits, identical local marginals do not imply identical joint states. A proposed local monitor must recognize this distinction.

S7.3 A simultaneous finite-shot error bound

For N_{basis} independently estimated observables with outcomes ± 1 and n shots per observable, Hoeffding's inequality and a union bound give

$$\Pr\left[\max_j |\widehat{r}_j - r_j| > \delta\right] \le 2N_{\mathrm{basis}}\exp\left(-\frac{n\delta^2}{2}\right). \tag{S7}$$

Thus a simultaneous absolute error at most δ with failure probability at most η is ensured by

$$n \ge \frac{2}{\delta^2}\ln\frac{2N_{\mathrm{basis}}}{\eta}. \tag{S8}$$

For three one-qubit Pauli bases and a balanced total budget $M = 3n$,

$$\delta = \sqrt{\frac{6}{M}\ln\frac{6}{\eta}}. \tag{S9}$$

At $\eta = 0.05$, this continuous balanced-budget expression gives $\delta \approx 0.536$ for $M = 100$ and $\delta \approx 0.059$ for $M = 8{,}192$. Integer shot allocations use $n = \lfloor M/3 \rfloor$ per basis and slightly increase the bound. These are theoretical conservative simultaneous bounds, not measured detector sensitivity, and do not give full-register tomography complexity.

No final N-MNIST tomography threshold, ROC/AUC, false-positive rate, finite-shot sensitivity, detection latency or adaptive-attack result is available. Monitoring remains a proposal, and the Iris regularization results in Section S5 are a different intervention.

S8 Complete paired timestamp comparison and supporting diagnostics

S8.1 Population, duration convention and computation

All conditions use the same 100 seed-42 validation examples, with ten per class, correctly classified by both frozen models before attack. They are not independent repeat samples across conditions. The timestamp protocol preserves event coordinates, polarity, count, labels and identities while enforcing nondecreasing times and the clean recording endpoints. In timestamp units the implemented duration and displacement constraint are

$$D = t_N - t_1 + 1, \qquad \varepsilon = \varepsilon_f D, \qquad |t'_i - t_i| \le \varepsilon, \quad t_1 \le t'_i \le t_N, \quad t'_i \le t'_{i+1}. \tag{S10}$$

The added unit matches the code's inclusive duration convention; it should not be dropped when reproducing budgets. The ten-bin adapter uses the clean recording endpoints and this duration, with hard accumulation in the forward pass and a surrogate backward interpolation [R2].

PGD uses 21 candidate evaluations, 41 attack-internal forwards and 20 backwards. TEMP uses Q candidate/forward evaluations and zero backwards. Candidate matching sets $Q = 21$; forward matching sets $Q = 41$. Elapsed-time calibration chooses $Q = 4{,}000$ for QSNN-v3 and $Q = 1{,}600$ for SNN, yielding median TEMP/PGD runtime ratios 0.978 and 1.083. Two verification forwards per new record are excluded from attack timing. No backward-to-forward conversion factor is assumed [R3].

Table S8. Complete paired timestamp outcomes. Every row has $N = 100$ joint clean-correct validation examples. Success counts are also ASR percentages.

Condition	Victim	$100\varepsilon_f$	PGD	TEMP	b	c	Both	Neither	Exact p
Original fixed budget	SNN	5	0	0	0	0	0	100	1
Original fixed budget	SNN	10	0	1	0	1	0	99	1
Original fixed budget	QSNN-v3	5	3	4	0	1	3	96	1
Original fixed budget	QSNN-v3	10	3	5	0	2	3	95	0.5
21 candidates	SNN	5	0	0	0	0	0	100	1
21 candidates	SNN	10	0	0	0	0	0	100	1
21 candidates	QSNN-v3	5	3	4	0	1	3	96	1
21 candidates	QSNN-v3	10	3	3	0	0	3	97	1
41 forwards	SNN	5	0	0	0	0	0	100	1
41 forwards	SNN	10	0	0	0	0	0	100	1
41 forwards	QSNN-v3	5	3	4	0	1	3	96	1
41 forwards	QSNN-v3	10	3	3	0	0	3	97	1
Elapsed time	SNN	5	0	0	0	0	0	100	1
Elapsed time	SNN	10	0	1	0	1	0	99	1
Elapsed time	QSNN-v3	5	3	4	0	1	3	96	1
Elapsed time	QSNN-v3	10	3	5	0	2	3	95	0.5

b: PGD-only success; c: TEMP-only success. The original fixed-budget condition is distinct from candidate, forward and elapsed-time matching. Identical aggregate counts do not imply additional independent observations. Exact two-sided paired p-values are checked from the preserved discordant counts [R3].

At 5% on QSNN-v3, the three joint successes and one TEMP-only success give exact paired $p = 1$. At 10% under elapsed-time matching, three joint successes and two TEMP-only successes give $p = 0.5$. No matched condition establishes statistically significant TEMP superiority. Failure to detect a difference is not proof of equivalence.

S8.2 Reported bootstrap intervals

The preserved report gives class-stratified paired bootstrap 95% intervals for the TEMP-minus-PGD ASR difference. The QSNN-v3 5% cells have reported intervals $[0,3]$ percentage points. At 10%, the reported intervals are $[0,0]$ under candidate and forward matching and $[0,5]$ under elapsed-time and original fixed-budget conditions. The SNN 10% original and elapsed-time cells have reported intervals $[0,3]$; all other SNN cells have $[0,0]$. These are report-derived summaries, not intervals regenerated without the original per-example records. A degenerate empirical interval from zero observed discordance is not a population equivalence bound [R3].

S8.3 Attributed realized-distortion diagnostic

The final QSNN status section of `readme_jafar.md` explicitly labels the following summary "QSNN, epsilon=10%, wall-clock matched," immediately after its $Q = 4{,}000$ calibration description. The completed comparison report itself does not reproduce the distortion values, and the recovered per-example arrays needed to verify an exact row linkage are absent. Table S9 is therefore retained as a report-specific supporting diagnostic, rather than a newly validated per-example result.

Table S9. Attributed QSNN-v3 realized-distortion summary for the reported 10% wall-clock condition.

Reported measure	PGD	TEMP	Difference	Relative increase (%)
Normalized timestamp shift	0.0667	0.0925	0.0258	38.7
Fraction of events changing bins	0.6463	0.8907	0.2444	37.8
Frame L_2	105.65	137.85	32.20	30.5

Source: `readme_jafar.md`, final QSNN status, Section 6. Differences and relative increases are descriptive arithmetic from rounded summary values. Aggregation details and per-example uncertainty cannot be reconstructed from the available summary.

The reported bin-change difference is 24.44 percentage points. Larger realized perturbation summaries accompany the report's two extra elapsed-time TEMP successes, but the aggregates do not establish that additional distortion causes those failures. Equal maximum displacement budgets need not yield equal realized distortion. Event-count preservation does not imply invariant time-bin histograms or statistical stealth.

S8.4 Scope of report audit claims

The repository reports 2,400 passing canonical timestamp records and 1,600 completed new budget-comparison records, with reused canonical rows where specified. These are record-accounting statements about the timestamp study, not extra independent attacked subjects and not validation of the separate grid campaign. The budget-comparison README still says that no experiment results exist, while its populated report states completion. Numerical results here follow the completed report [R3]. Restoring underlying arrays, logs, manifests and audit outputs is necessary for full independent reproduction.

The controlled grid report separately states that all sixteen of its attack cells passed raw-data reconstruction and prediction audits. It also reports a source/description ambiguity: a B_0 penalty coefficient of 5 in the referenced implementation versus 10 in the paper's general description. The applicable override source is absent from the recovered snapshot, so this discrepancy is attributed to the report rather than claimed as a new inspection of that source [R4].

S9 Positioning, final-model tables and readout analysis

The following material supports the main timestamp-focused presentation. Relocation does not change the evaluation populations or add experiments.

S9.1 Conceptual literature comparison

Table S10. Conceptual positioning of related work. Entries describe research scope, not a common benchmark or an experimental ranking.

Work	Studied interface or construction	Relation to the present study
Yao et al. [1]	Raw-event attacks with discrete-value optimization and sparsity control	Motivates the raw-event interface; not restricted to our identity-preserving retiming.
Du et al. [2]	Raw-event attacks with configurable latencies	Related temporal attack setting; constraints and budgets require separate specification.
Yu et al. [3]	Capacity-one spike-retiming constraints	Protocol reference for the separate classical packet-grid study.
Jha et al. [4]	SNN features followed by quantum kernels for EEG	Hybrid temporal classification; distinct from our variational probability readout.
Gong et al. [5]	Randomized quantum encodings with specified attacker access	Defense assumptions differ from an attack before our classical frontend.
Dowling et al. [6]	Guarantees for specified quantum-classifier scenarios	Motivates assumption-aware interpretation; not a certificate for our timing budgets.
This work	End-to-end timestamp attacks on QSNN-v3; separate classical grid controls	Paired computational controls, explicit populations and report-grounded evidence.

S9.2 Individual final-model validation runs

Table S11. QSNN-v3 validation on the same 5,000 examples.

Seed	**Accuracy (%)**	**Epoch**
42	97.06	37
123	97.28	24
777	97.52	40
2026	97.44	38
6543	97.06	40
Mean $\pm$ SD	97.272 ± 0.212	—

All seeds reuse one pretrained frontend and one split. Reported macro-F1 is $97.2736\% \pm 0.2119\%$ [R1].

S9.3 Complete local packet-grid results

Table S12. Controlled four-model packet-grid results. Clean accuracy and ASR use different stated populations.

Grid	Architecture	Clean test %	ASR B_∞ = 1 %	ASR B_0 = 200 %
Binary	Custom SNN	97.99	100.0	99.5
Binary	ConvNet	96.90	1.9	1.2
Binary	Spiking ResNet18	98.61	0.1	0.0
Binary	VGGSNN	99.21	0.0	0.0
Integer	Custom SNN	98.14	99.9	98.0
Integer	ConvNet	96.58	0.6	1.1
Integer	Spiking ResNet18	98.12	0.2	0.1
Integer	VGGSNN	99.30	0.0	0.0

Clean accuracy uses the complete 10,000-example official test set. ASR uses a separate frozen 1,000-example joint-correct manifest per representation. These are local measurements, not values copied from [3]. Source: [R4].

S9.4 Derivation for the fixed probability readout

For the fixed trained model, let ρ and ρ' denote the clean and retimed quantum states before the fixed readout measurement, and let $q, q' \in \mathbb{R}^{256}$ be the corresponding outcome-probability vectors. Write the logits as $z(q) = Wq + b$, and define the clean pairwise margin against class $k \neq y$ by

$$m_{yk}(q) = (w_y - w_k)^\top q + b_y - b_k. \tag{S11}$$

Here y is the clean predicted class, equal to the label on the attacked clean-correct subset, and w_k is row k of W. Measurement cannot increase trace distance [7, Corollary 3.40], hence

$$\tfrac{1}{2}\|q - q'\|_1 \leq D_{\mathrm{tr}}(\rho, \rho'), \qquad D_{\mathrm{tr}}(\rho, \rho') = \tfrac{1}{2}\|\rho - \rho'\|_1. \tag{S12}$$

The state norm is the trace norm; for probability vectors it is the ordinary ℓ_1 norm. Combining this inequality with Hölder's inequality gives

$$\begin{aligned} m_{yk}(q') &\geq m_{yk}(q) \\ &\quad - 2\|w_y - w_k\|_\infty D_{\mathrm{tr}}(\rho, \rho'). \end{aligned} \tag{S13}$$

Thus a sufficient condition for retaining class y is that the right-hand side remain strictly positive for every $k \neq y$. To see this, subtract the two affine margins and bound the resulting inner product by $\|w_y - w_k\|_\infty \|q' - q\|_1$; positivity of all pairwise margins then preserves the argmax.

This observation separates state displacement from decision failure. A larger state distance need not cause a label change, and a small clean margin can make a smaller displacement consequential. Equation (S13) is a conditional interpretation of the implemented readout, not a certified timestamp radius: no uniform bound from admissible event retiming through the classical frontend to D_{tr} has been established here. The final-model campaign also does not report the per-example states needed to evaluate this condition. Its connection to quantum robustness theory is therefore conceptual rather than an application of an existing certificate [6].

S9.5 Descriptive binomial score intervals

For a reported s successes among n selected examples, let $\widehat{p} = s/n$ and $z = 1.959963984540054$. The plotted 95% Wilson score interval is

$$\frac{\widehat{p} + z^2/(2n) \;\pm\; z\sqrt{\widehat{p}(1-\widehat{p})/n + z^2/(4n^2)}}{1 + z^2/n}. \tag{S14}$$

These intervals are computed from aggregate counts, not recovered per-example outputs. For $n = 100$, the intervals for $s = 0, 1, 3, 4, 5$ are approximately $[0, 3.70]$, $[0.18, 5.45]$, $[1.03, 8.45]$, $[1.57, 9.84]$ and $[2.15, 11.18]$ percent. They summarize a binomial model on the selected subset; deterministic joint-correct selection, repeated conditions and shared examples do not justify coverage claims for the full validation/test population. They neither replace the paired McNemar test nor measure uncertainty of a paired difference.

S10 Static inspection of the preserved attack implementation

This is a source-level audit of the pinned snapshot, not an executed experiment. Code paths are distinguished from proof that particular saved records used them, since most run artifacts are absent.

S10.1 Budget-scaled TEMP schedule

The matched runner explicitly defines the two low-access schedules, rather than truncating the historical 600-candidate initialization. Its candidate evaluator consumes all initialization proposals and all four child batches, with no early stop on success. At each generation it preserves the 12 lowest-margin elites and evaluates only new children. All proposals pass through the timestamp feasibility operator. The final minimum-margin candidate is returned.

Table S13. TEMP schedule defined in the preserved matched runner.

Condition	Initial	Children/generation	Generations	Total Q
Candidate matching	13	2	4	21
Forward matching	13	7	4	41
Elapsed time, QSNN	1,500	625	4	4,000
Elapsed time, SNN	600	250	4	1,600

The source algorithm can be written without implying unmeasured budgets:

1. Read the condition's (n_0, n_g) from the fixed schedule. Draw n_0 uniform perturbations in $[-\varepsilon, \varepsilon]$ per timestamp, apply feasibility, and evaluate their margins.
2. For each $\sigma \in \{0.50, 0.30, 0.18, 0.10\}$, retain 12 lowest-margin candidates. For $j = 0, \ldots, n_g - 1$, use elite j mod 12 as parent, add $0.5(e_a - e_b)$ with independently drawn elite indices a, b, then Gaussian noise of scale $\sigma\varepsilon$ per timestamp. Apply feasibility and evaluate the n_g new children.
3. Replace the pool by the 12 elites plus children; preserve their already computed scores. After the fourth generation return the candidate with minimum margin. Exactly $n_0 + 4n_g$ proposals have been evaluated.

The selected elapsed-time schedules reproduce the stated totals; the generic scaling helper records any rounding adjustment. The report and runner agree on the low-Q definitions, but the saved `budget_definitions.json` and candidate trajectories are unavailable for run-level verification [R3].

S10.2 PGD candidate retention

The preserved `scripts/run_nmnist_common_attack_protocol_seed42.py` scores the clean input and 20 iterates and retains the highest true-label cross-entropy, without a success-priority rule. Cross-entropy ranks true-class probability, while a multiclass decision also depends on competing probabilities; the highest-loss candidate need not be a misclassification even if another iterate is. This establishes a possible retention failure, not its occurrence in the reported records. No success count has been corrected on this basis. A future rerun should record success at every feasible iterate and compare final-selection and any-valid-candidate success under a common documented rule.

S10.3 Timing and inference state

The matched runner requires CUDA and synchronizes immediately before and after `perf_counter` timing. Calibration selects ten joint-clean-correct training examples, one per class, disjoint from evaluation IDs and near each class's median event count among a bounded candidate scan. It uses $\varepsilon_f = 0.10$, two repeats per example, a PGD warm-up and a TEMP warm-up requested at $Q = 400$ (398 actual proposals after rounding). It searches requested budgets

$$Q \in \{800, 1200, 1600, 2000, 2400, 3200, 4000, 4800, 5600, 6400\},$$

recording actual totals after the scaling helper rounds initialization and generation sizes, then choosing the median TEMP/PGD ratio closest to one and accepting a $\pm 10\%$ band. TEMP candidate chunks are at most 64; PGD forwards contain one event example. Evaluation alternates PGD/TEMP order by sample position and excludes two verification forwards from attack

timing. Timestamp tensors use float32 and the quantum backend uses complex64; the attack code does not apply the training loop's float16 autocast. Saved calibration arrays are absent, so absolute times, dispersion and historical device identity cannot be newly verified. The environment note's RTX 4090 observation is a later inspection, not a run-specific timing snapshot.

The timestamp loader calls `eval()` for both victims. The compact SNN and spatial LIF extractor initialize membrane/accumulator tensors inside each forward, with no persistent cross-call neuron state. BatchNorm consequently uses fixed evaluation statistics. This finding does not extend to the missing four-model grid definitions.

S10.4 Unresolved baseline and artifact provenance

The controlled-grid report gives local architecture labels, seed 42, a common recipe, complete counts and manifest hashes. Exact ConvNet, spiking ResNet18 and VGGSNN implementations, training configs and checkpoint files are absent. A name alone does not establish that a published residual or VGG spiking architecture was used; no such reference is assigned without code verification. The reported B_0 coefficient discrepancy (5 versus 10) remains unresolved because the applicable override/configuration is absent. No real clean/retimed event example or state–margin scatter is constructed without its timestamps, probabilities, logits and prediction evidence.

S11 Repository evidence map and reporting boundary

All paths below are repository-relative at commit

`80d02f5733d4cbe7c3e69b828dff66d50ba5c211`.

The package includes corresponding report/source snapshots where available; its `data/evidence_manifest.json` records original snapshot URLs and hashes. Reports and derived CSV transcriptions are the same evidence, not independent replications. Most checkpoints, raw per-example arrays, manifests, original logs and audit outputs referenced by the reports are absent. Internal arithmetic verification during manuscript preparation is distinct from a new execution or full experimental reproduction.

[R1] Final hybrid model and validation. Primary report:
`results/nmnist_hybrid_qsnn_seed42/nmnist_qsnn_v3_multiseed/report.md`.
Companion implementation: `models/nmnist_hybrid_qsnn.py` and `scripts/run_nmnist_qsnn_v3_multiseed.py`. Development reports: `results/nmnist_hybrid_qsnn_seed42/frontend_v3_report.md` and `results/nmnist_hybrid_qsnn_seed42/quantum_head_v2_report.md`. Supports architecture, validation-only results, shared pretraining and development history.

[R2] Timestamp attacks and representation.
`scripts/run_nmnist_temp_drift_v2_seed42.py`,
`scripts/run_nmnist_common_attack_protocol_seed42.py`, and
`scripts/run_nmnist_attack_protocol_v3_auditable_seed42.py`.
Supports native-event retiming, margin-based derivative-free TEMP, timestamp projection, adapter and inclusive duration convention. It does not establish a quantum-drift objective for the final attack.

[R3] Corrected computationally matched comparison.
`results/nmnist_budget_matched_comparison_v2_seed42/report.md`; runner:
`scripts/run_nmnist_budget_matched_comparison_v2_seed42.py`.
Supports original fixed-budget and matched paired outcomes, computational accounting, calibration, exact tests and attributed bootstrap intervals. The contradictory stale README is preserved separately at `results/nmnist_budget_matched_comparison_v2_seed42/README.md`. Supporting distortion and audit-accounting summaries come from the final QSNN section of `readme_jafar.md`.

[R4] Controlled four-model packet-grid study.
`Reports/nmnist_controlled_four_models_lr1e4_comparison.md`.
Supports all eight clean rows, sixteen attack cells, common-recipe controls, separate binary/integer manifests and the report-attributed B_0 coefficient discrepancy. Companion reporting audit: `paper_revision_audit/verified_experimental_results.md`. These are local model results rather than published-reference numbers.

[R5] Historical binary verification and corrected integer status.
`Reports/nmnist_seed42_verification.md` and
`Reports/nmnist_integer_corrected_report.md`.
Supports the historical 98.73% binary test result, nine-budget sweep and non-comparability boundary, and the separately incomplete 8/33 corrected integer campaign.

[R6] Clean neuromorphic baselines.
`Reports/clean_accuracy_report.md`.
Supports full-test or frozen-test-split clean SNN results and identifies the legacy normalized-count rows for DVS-Gesture and CIFAR10-DVS.

[R7] MNIST PCA development.
`results/mnist_8x8_pca_dimension_seed42_report.md`.
Supports the single-seed validation screen with unequal continuation histories, not an attack result or matched-budget ablation.

[R8] Historical Iris attacks.
`results/final_attack_report.md`.
Companion notation/metric sources: `encoding/quantum.py` and `metrics/quantum_drift.py`. Supports frozen-checkpoint attack ratios and pure product-state diagnostics, not final N-MNIST circuit-state measurements.

[R9] Iris mechanism gate and earlier regularization.
`results/iris_phase21_scientific_audit.md`,
`results/phase21_results.md`, and `results/phase153_results.md`.
Supports the negative confirmatory gate, nonexecution of the subsequent defense stage and limited earlier regularization observations. Audit PASS denotes protocol handling, not defense success.

[R10] Environment evidence and SHD re-audit.
`paper_revision_audit/hardware_software_versions.md` and
`results/shd_snn_test_reaudit_report.md`.
The environment observations are a September 2026 snapshot, not a saved runtime record for every experiment. SHD values concern a classical SNN and a previously accessed official test set.

The accompanying main paper cites the research literature separately. The bibliography below is shared with that paper; repository evidence identifiers above are preserved for exact artifact provenance.

References

[1] Yanmeng Yao, Xiaohan Zhao, and Bin Gu. Exploring vulnerabilities in spiking neural networks: Direct adversarial attacks on raw event data. In *Computer Vision – ECCV 2024*, 2024. Official ECCV 2024 conference version, https://www.ecva.net/papers/eccv_2024/papers_ECCV/papers/09164.pdf.

[2] Xiao Du, Wanli Shi, Xiaohan Zhao, Yang Cao, Bin Gu, and Tieru Wu. Raw event-based adversarial attacks for Spiking Neural Networks with configurable latencies. *Neural Networks*, 193:108026, 2026.

[3] Yi Yu, Qixin Zhang, Shuhan Ye, Xun Lin, Qianshan Wei, Kun Wang, Wenhan Yang, Dacheng Tao, and Xudong Jiang. Time is all it takes: Spike-retiming attacks on event-driven spiking neural networks. https://arxiv.org/abs/2602.03284v1, 2026. Frozen protocol reference: v1.

[4] Ravi Kumar Jha, Nikola Kasabov, Saugat Bhattacharyya, Damien Coyle, and Girijesh Prasad. A hybrid spiking neural network - quantum framework for spatio-temporal data classification: a case study on EEG data. *EPJ Quantum Technology*, 12:130, 2025.

[5] Weiyuan Gong, Dong Yuan, Weikang Li, and Dong-Ling Deng. Enhancing quantum adversarial robustness by randomized encodings. *Physical Review Research*, 6:023020, 2024.

[6] Neil Dowling, Maxwell T. West, Angus Southwell, Azar C. Nakhl, Martin Sevior, Muhammad Usman, and Kavan Modi. Adversarial robustness guarantees for quantum classifiers. *npj Quantum Information*, 12:16, 2026.

[7] John Watrous. *The Theory of Quantum Information*. Cambridge University Press, 2018. Author manuscript, https://cs.uwaterloo.ca/~watrous/TQI/.

[8] Emre O. Neftci, Hesham Mostafa, and Friedemann Zenke. Surrogate gradient learning in spiking neural networks. *IEEE Signal Processing Magazine*, 36(6):51–63, 2019.

[9] Daniel Brand and Francesco Petruccione. A quantum leaky integrate-and-fire spiking neuron and network. *npj Quantum Information*, 10:125, 2024.

[10] Nouhaila Innan, Rachmad Vidya Wicaksana Putra, and Muhammad Shafique. SPATE: Spiking-phase adaptive temporal encoding for quantum machine learning. https://arxiv.org/abs/2604.11022, 2026.

[11] Adrián Pérez-Salinas, Alba Cervera-Lierta, Elies Gil-Fuster, and José I. Latorre. Data re-uploading for a universal quantum classifier. *Quantum*, 4:226, 2020.

[12] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

[13] Nicholas Carlini, Anish Athalye, Nicolas Papernot, Wieland Brendel, Jonas Rauber, Dimitris Tsipras, Ian Goodfellow, Aleksander Madry, and Alexey Kurakin. On evaluating adversarial robustness. https://arxiv.org/abs/1902.06705, 2019.

[14] Garrick Orchard, Ajinkya Jayawant, Gregory K. Cohen, and Nitish Thakor. Converting static image datasets to spiking neuromorphic datasets using saccades. *Frontiers in Neuroscience*, 9:437, 2015.

[15] ABC_def1 research implementation. Preserved implementation and experimental reports. https://github.com/shosseinj/ABC_def1, 2026. Snapshot 80d02f5733d4, 28 September 2026.

[16] Maximilian Wendlinger, Kilian Tscharke, and Pascal Debus. A comparative analysis of adversarial robustness for quantum and classical machine learning models, 2024. Preprint, https://arxiv.org/abs/2404.16154.

[17] Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 274–283. PMLR, 2018.

[18] Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 2206–2216. PMLR, 2020.

[19] Julian Büchel, Gregor Lenz, Yalun Hu, Sadique Sheik, and Martino Sorbaro. Adversarial attacks on spiking convolutional neural networks for event-based vision. *Frontiers in Neuroscience*, 16:1068193, 2022.

[20] Amena Khatun and Muhammad Usman. Classical autoencoder distillation of quantum adversarial manipulations. *Physical Review Research*, 7:L042054, 2025.