

危険度スコア R ごとの経路表示（色・不透明度）

$$a = 0.35 + 0.65R \quad H = (1-R) \times 180^\circ \quad S = 0.4 + 0.6R \quad V = 0.5 + 0.3R$$

上段：色のみ（不透明） / 下段：不透明度込み（市松模様の上）



R = 0

青緑・うすい

H = 180°

a = 0.350

S = 0.40 V = 0.50

#4C7F7F

R = 0.25

緑・ややうすい

H = 135°

a = 0.512

S = 0.55 V = 0.57

#419256

R = 0.5

黄緑・中くらい

H = 90°

a = 0.675

S = 0.70 V = 0.65

#6BA531

R = 0.75

橙黄・やや濃い

H = 45°

a = 0.838

S = 0.85 V = 0.72

#B8911B

R = 1

赤・はっきり

H = 0°

a = 1.000

S = 1.00 V = 0.80

#CC0000

危険度 R ごとの色相・不透明度（数値）

R	見た目	H	S	V	a	RGB	
0	青緑・うすい	180°	0.40	0.50	0.350	#4C7F7F	
0.25	緑・ややうすい	135°	0.55	0.57	0.512	#419256	
0.5	黄緑・中くらい	90°	0.70	0.65	0.675	#6BA531	
0.75	橙黄・やや濃い	45°	0.85	0.72	0.838	#B8911B	
1	赤・はっきり	0°	1.00	0.80	1.000	#CC0000	

R = 0 （青緑・うすい）



色相 $H = 180^\circ$

彩度 $S = 0.40$ 明度 $V = 0.50$

不透明度 $\alpha = 0.350$ ($\alpha = 0.35 + 0.65R$)

RGB = (76, 127, 127) #4C7F7F

R = 0.25 (緑・ややうすい)



色相 H = 135°

彩度 S = 0.55 明度 V = 0.57

不透明度 α = 0.512 (α = 0.35 + 0.65R)

RGB = (65, 146, 86) #419256

R = 0.5 (黄緑・中くらい)




色相 H = 90°

彩度 S = 0.70 明度 V = 0.65

不透明度 α = 0.675 (α = 0.35 + 0.65R)

RGB = (107, 165, 49) #6BA531

R = 0.75 （橙黄・やや濃い）



色相 H = 45°
彩度 S = 0.85 明度 V = 0.72
不透明度 α = 0.838 （α = 0.35 + 0.65R）
RGB = (184, 145, 27) #B8911B

R = 1 （赤・はっきり）



色相 H = 0°

彩度 S = 1.00 明度 V = 0.80

不透明度 α = 1.000 (α = 0.35 + 0.65R)

RGB = (204, 0, 0) #CC0000