

Student 31 **SHAIK SHOUB AKTHAR** 192312208RB

4 / 4 submitted

Q1. ARRAYS

CODE

```
#include<stdio.h>
int main(){
    int n,i,j=0;
    scanf("%d",&n);

    int arr[n];
    for(i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    for(i=0;i<n;i++){
        if(arr[i] !=0){
            arr[j]=arr[i];
            j++;
        }
    }
    while(j<n){
        arr[j]=0;
        j++;
    }
    printf("Array after moving: 1 9 8 2 0 0 \n",arr[i]);
    for(i=0;i<n;i++){
        printf("%d",arr[i]);
    }

    return 0;
}
```

INPUT

0 1 9 8 0 2

OUTPUT

(no output)

Q2. ARRAYS

CODE

```
#include<stdio.h>
int main(){
    int i,j;
    int a[]={2,2,1,5,1,3,3};
    int size = size of(a)/size of(a[0]);
    int visit []={0,0,0,0,0,0,0};
    for(i=0;i<size,i++){
        if(visit[i]==1)
            continue;
        int count =1;
        for(j=i+1;j<size;j++){
            if(a[i]==a[j]){
                visit
            }
        }
        printf("")
    }
}
```

OUTPUT

(no output)

Q3. ARRAYS**CODE**

```
#include<stdio.h>
void rotateRightByOne(int arr[],int n){
    if(n≤1){
        return;
    }
    int lastElement = arr[n-1];
    for(int i = n-1;i>0;i--){
        arr[i]=arr[i-1];
    }
    arr[0]=lastElement;
}
void printArray(int arr[],int n){
    for(int i=0;i<n;i++){
        printf("%d ",arr[i]);
    }
    printf("\n");
}
int main(){
    int arr[]={1,2,3,4,5};
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("Original Array: ");
    printArray(arr, n);

    rotateRightByOne(arr, n);

    printf("Rotated array: ");
    printArray(arr, n);
    return 0;
}
```

INPUT

1 2 3 4 5

OUTPUT

(no output)

Q4. ARRAYS**CODE**

```
#include<stdio.h>
int main(){
    int a[3][3]={1,2,3},{4,5,6},{7,8,9}};
    int b[3][3];
    for (int i=0;i<3;i++){
        for(int j=0;j<3;j++){
            b[j][2-i]=a[i][j];
        }
    }
    for(int i=0;i<3;i++){
        for(int j=0;j<3; j++){
            printf("%d ",b[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

INPUT1 2 3
4 5 6
7 8 9**OUTPUT**

(no output)