


## 300PSI NRS Flanged X Grooved End Gate Valve


Model: NRS-FRA

Resilient Wedge NRS Gate Valve – Grooved X Flanged End

Version 1.01 January 2025 release

## 300PSI NRS Flanged X Grooved End Gate Valve Model: NRS-FRA







Technical Features								
Nominal Pressure	300PSI							
Face to Face Standard	ASME B16.10							
Sizes	2½", 3", 4", 5", 6", 8", 10", 12"							
Flange Standard	ASME / ANSI B16.1 Class 125 or ASME / ANSI B16.42 Class 150 or BS EN1092-2 PN16							
Groove Standard	Metric or ANSI / AWWA C606							
Approvals	UL & FM							
Maximum Working Pressure	300PSI (Maximum Testing Pressure: 600 PSI) conforms to UL262 & FM 1120 / 1130							
Maximum Working Temperature	80°C / 176°F							
Coating Details	Epoxy coated interior and exterior by Electrostatic Spray or coating upon request							
NPT plug on body with 2 operating nuts								

Val	Valve Material List							
No	Description	Material						
1	Flat Washer	Steel 1045 or Stainless Steel 304						
2	Hexagon Socket Screw	Steel 1045 or Stainless Steel 304						
3	Sealing Ring	EPDM						
4	O-Ring	EPDM						
5	Sealing Ring	EPDM						
6	O-Ring	EPDM						
7	Bonnet	Ductile Iron						
8	Stem	Stainless Steel 304 or C95400						
9	Plug	Stainless Steel 304 or C95400						
10	Disc	Ductile Iron + EPDM						
11	Body	Ductile Iron						
12	Sealing Ring	EPDM						
13	Retaining Ring	C95400						
14	Gland	Ductile Iron						
15	Post Flange	Ductile Iron						
16	Wrench Nut	Ductile Iron						
17	Bolt	Stainless Steel 304 or Steel 1045						
18	Washer	Stainless Steel 304 or Steel 1045						
19	Hexagon Socket Screw	Steel 1045 or Stainless Steel 304						
20	Stem Nut	CF8 or C95400						

Dimensions												
Part No.	Size	DN	L	D	F	D2	E	G	Н			
NRS-FRA-065	2 ½"	65	190	178	15.9	73	69.1	7.9	292			
NK3-FKA-005						76.1	72.3					
NRS-FRA-080	3″	80	203	191	15.9	88.9	84.9	7.9	322			
NRS-FRA-100	4"	100	229	229	15.9	114.3	110.1	9.5	342			
NRS-FRA-125	5″	125	254	254	15.9	139.7	135.5	9.5	412			
						141.3	137					
NRS-FRA-150	6"	150	267	279	15.9	165.1	160.8	9.5	448			
						168.3	163.9					
NRS-FRA-200	8" 20	200	200 292	343	19	216.3	211.6	11.1	534			
		200				219.1	214.3					
NRS-FRA-250	10"	250	330	406	19	273	268.3	12.7	635			
NRS-FRA-300	12"	300	356	483	19	323.9	318.3	12.7	720			



Gate 2, Aljada Logistics Area, Behind Arada Project Management Office, Near Airport Road, Muweilah, 22436, Sharjah

rhinotek.ae