


## 300PSI OS & Y Flanged X Grooved End Gate Valve


**Model: OSY-FRA** 

Resilient Wedge OS & Y Gate Valve – Flanged X Grooved End

Version 1.01 January 2025 release

## 300PSI OS & Y Flanged X Grooved End Gate Valve Model: OSY-FRA







Technical Features						
Nominal Pressure	300PSI					
Face to Face Standard	ASME B16.10					
Sizes	2½", 3", 4", 5", 6", 8", 10", 12"					
Flange Standard	ASME / ANSI B16.1 Class 125 or ASME / ANSI B16.42 Class 150 or BS EN1092-2 PN16					
Groove Standard	Metric or ANSI / AWWA C606					
Approvals	UL & FM					
Maximum Working Pressure	300PSI (Maximum Testing Pressure: 600 PSI) conforms to UL262 & FM 1120 / 1130					
Maximum Working Temperature	80°C / 176°F					
Coating Details	Epoxy coated interior and exterior by Electrostatic Spray or coating upon request					
NPT plug on body with 2 operating nuts						

Val	Valve Material List							
No	Description	Material						
1	Gasket	Stainless Steel 304 or C95400						
2	Bonnet	Ductile Iron						
3	Packing	Graphite						
4	Disc	Ductile Iron + EPDM						
5	Body	Ductile Iron						
6	Sealing Ring	EPDM						
7	Bolt	Stainless Steel 304 or Steel 1045						
8	Gland	Ductile Iron						
9	Nut	Stainless Steel 304 or Steel 1045						
10	Flat Washer	Stainless Steel 304 or Steel 1045						
11	Bolt	Stainless Steel 304 or Steel 1045						
12	Handwheel	Ductile Iron						
13	Lock Nut	C95400						
14	Locating Screw	Stainless Steel 304 or Steel 1045						
15	Stem	Stainless Steel 304 or C95400						
16	Stem Nut	C95400						
17	Plug	C95400						
18	Lifting Nut	CF8 or C95400						
19	Pin	Stainless Steel 304						
20	Sealing Ring	EPDM						

Dimensions													
Part No.	Size	DN	L	D	F	D2	Е	G	Н				
OSY-FRA-065	2 1/2"	65	190	178	15.9	73	69.1	7.9	370				
US1-FRA-005	Z 72	05	190	1/0	15.9	76.1	72.3						
OSY-FRA-080	3″	80	203	191	15.9	88.9	84.9	7.9	420				
OSY-FRA-100	4"	100	229	229	15.9	114.3	110.1	9.5	447				
OSY-FRA-125	5″	125	254	254	15.9	139.7	135.5	9.5	547				
O31-FRA-125						141.3	137						
OSY-FRA-150	RA-150 6" 150 267 279 15.	15.9	165.1	160.8	9.5	607							
O51-FKA-150	0	150	207	219	15.9	168.3	163.9	9.5	607				
OSY-FRA-200	8"	200	292	343	19	216.3	211.6	11.1	754				
OST-FRA-200						219.1	214.3						
OSY-FRA-250	10"	250	330	406	19	273	268.3	12.7	890				
OSY-FRA-300	12"	300	356	483	19	323.9	318.3	12.7	1031				



Gate 2, Aljada Logistics Area, Behind Arada Project Management Office, Near Airport Road, Muweilah, 22436, Sharjah

rhinotek.ae