


Landing Valve

Model: FIS281 (Female X Female)

Landing Valve

Version 1.01
January 2025 release

Landing Valve
 Model: FIS281
 (Female X Female)



Technical Features	
Used with a Fire Hose Rack Assembly or as a Fire Department outlet connection	
DOUBLE FEMALE	
Standard Equipment	Female NPT inlet and outlet Forged brass valve Red hand wheel
Optional Finishes	PB – Polished Brass RC – Rough Chrome Plated PC – Polished Chrome Plated
NYFD	2 ½" FNPT x FNPT 1 ½" FNPT x FNPT

Valve Material List		
No	Description	Material
1	Body	ASTM B283 C37700
2	Nut	ASTM B283 C37700
3	Washer	304
4	Seat Seal	EPDM (A70)
5	Holder	C37700
6	Set Screw	304
7	Lock Nut	ASTM B283 C37700
8	O-Ring	EPDM (A70)
9	Bonnet	ASTM B283 C37700
10	Stem	ASTM B283 C37700
11	Lock Nut	ASTM B283 C37700
12	O-Ring	EPDM (A70)
13	Handle Wheel	ZL102
14	Wheel Washer	304
15	Wheel Nut	ASTM B283 C37700

Dimensions						
Part No.	Size	A	B	C	D	E
FIS281-040FF	1 ½" x 1 ½"	100	50	66	119	145
FIS281-065FF	2 ½" x 2 ½"	127	68	84	157	200



Gate 2, Aljada Logistics Area,
Behind Arada Project Management
Office, Near Airport Road,
Muweilah, 22436, Sharjah

rhinotek.ae